


Molecular Coding Format manual

Akira Yamaji

November 23, 2021

Located at <http://www.ctan.org/pkg/mcf2graph>

Suggestion or request mail to: mcf2graph@gmail.com



Contents

| | | |
|----------|---------------------------------|-----------|
| 1 | Introduction | 3 |
| 2 | MCF syntax | 3 |
| 2.1 | Make bond | 3 |
| 2.1.1 | Chain | 3 |
| 2.1.2 | Chain use !,ln | 3 |
| 2.1.3 | Jump to atom | 3 |
| 2.1.4 | Branch bond | 3 |
| 2.1.5 | Branch modified bond | 3 |
| 2.1.6 | Connect atom | 3 |
| 2.1.7 | Ring | 3 |
| 2.1.8 | Rotate current angle | 3 |
| 2.2 | Change bond type | 4 |
| 2.2.1 | Double,triple,wedge,vector | 4 |
| 2.2.2 | Over line | 4 |
| 2.2.3 | Steric ring | 4 |
| 2.2.4 | Change multiple bond type | 4 |
| 2.3 | Change bond length | 4 |
| 2.3.1 | Chain length | 4 |
| 2.3.2 | Ring length | 4 |
| 2.4 | Change atom | 4 |
| 2.4.1 | Insert atom | 4 |
| 2.4.2 | Addressed atom | 5 |
| 2.4.3 | Brock address | 5 |
| 2.4.4 | Reset brock address | 5 |
| 2.4.5 | Absolute address | 5 |
| 2.4.6 | Relative address | 5 |
| 2.4.7 | Charged atom | 5 |
| 2.5 | Fuse ring | 5 |
| 2.6 | Spiro ring | 6 |
| 2.7 | Group | 6 |
| 2.7.1 | Insert group | 6 |
| 2.7.2 | Insert modified group | 6 |
| 2.7.3 | Add group | 6 |
| 2.7.4 | Add modified group | 6 |
| 2.8 | Chain environment | 7 |
| 2.8.1 | Horizontal,vertical | 7 |
| 2.8.2 | Left-right,right-left | 7 |
| 2.8.3 | Fixed rotate angle | 7 |
| 2.8.4 | Multi rotate angle | 7 |
| 2.9 | Miscellaneous | 7 |
| 2.9.1 | Abbreviated parts | 7 |
| 2.9.2 | Parts definition | 7 |
| 2.9.3 | Parts inline definition | 7 |
| 2.9.4 | Move position | 7 |
| 2.9.5 | Serial number | 7 |
| 2.9.6 | Change color | 8 |
| 2.9.7 | Change font | 8 |
| 3 | Option parameter | 8 |
| 3.1 | Angle parameter | 8 |
| 3.2 | Size/Ratio parameter | 8 |
| 3.2.1 | Bond length | 8 |
| 3.2.2 | Molecular size | 8 |
| 3.2.3 | Molecular position | 8 |
| 3.3 | Size parameter | 9 |
| 3.3.1 | Font size | 9 |
| 3.3.2 | Font margin | 9 |
| 3.3.3 | Offset thickness of bond | 9 |
| 3.3.4 | Offset of double bond gap | 9 |
| 3.3.5 | Offset of atom width | 9 |
| 3.3.6 | Offset of wedge width | 9 |
| 3.3.7 | Max bond length | 9 |
| 3.4 | Ratio parameter | 9 |
| 3.4.1 | Thickness/bond length | 9 |
| 3.4.2 | Char/bond thickness | 9 |
| 3.4.3 | Bond gap/bond length | 9 |
| 3.4.4 | Atom/bond length | 9 |
| 3.4.5 | Wedge/bond length | 9 |
| 3.4.6 | Font atom gap/atom length | 9 |
| 3.4.7 | Chain/ring length | 9 |
| 3.4.8 | Hash gap/bond length | 9 |
| 3.5 | Drawing mode | 10 |
| 3.5.1 | Numbering atom | 10 |
| 3.5.2 | Numbering bond | 10 |
| 3.5.3 | Trimming mode | 10 |
| 3.5.4 | Expand mode | 10 |
| 3.5.5 | Abbreviate group | 10 |
| 3.5.6 | Abbreviate bond type | 10 |
| 3.6 | Frame | 10 |
| 3.6.1 | Font frame | 10 |
| 3.6.2 | Molecular frame | 10 |
| 3.6.3 | Atom frame | 10 |
| 3.7 | Parameter setting | 11 |
| 3.7.1 | Local parameter setting | 11 |
| 3.7.2 | Global parameter setting | 11 |
| 4 | Function | 11 |
| 4.1 | Function MC() | 11 |
| 4.2 | Function MCat() | 11 |
| 4.3 | Function check() | 11 |
| 4.4 | Function add() | 12 |
| 4.5 | Function ext() | 13 |
| 4.5.1 | Local ext() setting | 13 |
| 4.5.2 | Global ext() setting | 13 |
| 5 | MCF example | 14 |
| 5.1 | Luciferin | 14 |
| 5.2 | Colchicine | 14 |
| 5.3 | Paclitaxel | 14 |
| 5.4 | Maltose | 14 |
| 5.5 | Cellobiose | 14 |
| 6 | Example to use mcf2graph | 15 |
| 6.1 | Metafont/Metapost source file | 15 |
| 6.2 | Molecular data base file | 16 |
| 6.3 | Function query() | 17 |
| 6.4 | Information aux file output | 18 |
| 6.5 | Metafont aux file output | 19 |
| 6.6 | MCF aux file output | 20 |
| 6.7 | Report output | 21 |
| 6.8 | MOL file output | 22 |
| 6.9 | LuaTeX file example | 23 |
| 6.10 | LaTeX file example | 24 |

1 Introduction

Molecular Coding Format(MCF) is new linear notation represent chemical structure diagrams. This Coding is named from programming technique such as operator, array, scope, macro, addressing, etc. mcf2graph convert from MCF to pk font, PNG, SVG, EPS, MOL file. It is also able to calculate molecular weight, exact mass, molecular formula.


2 MCF syntax

2.1 Make bond

2.1.1 Chain

real number plus (+): counterclockwise
 real number minus(-): clockwise
 \$n (0<=n<360): absolute angle


<10,-30,45,-45,60,\$300,\$0



2.1.2 Chain use !,!n

! : take value 60 or -60 depend on current angle and environment
 !6 : !,!,!,!,!,!


<-30,!6



2.1.3 Jump to atom

@n : Jump to An
 ** An: atom number(-999<=n<=4095)


<-30,!6,@3,0,!,@5,-30



2.1.4 Branch bond

\ : 0

<-30,!6,@3,\,!




2.1.5 Branch modified bond

\ : 0
 *\ : 0~wf
 * : 0~zf
 \\ : 0~dm
 ** : 0~wv

<30,!8,

@2,\,!,@4,*\,!,@6,*,!,@8,\\,!,@10,**,!




<30,!6,

\~dr,! : 0~dr,!

\'1.5,-90 : 0'1.5,-90


\^15,-60 : 0^15,-60



2.1.6 Connect atom

&n : Connect to An

<-30,!6,@3,\,!3,&6~bd,@9,&4~bz




2.1.7 Ring

?n : n membered ring(3<=n<=20)

?6 : <-120,60,60,60,60,60,&1


?6



2.1.8 Rotate current angle

<angle : rotate current angle

0,0,<90,0,<-90,0,<\$315,0,<\$90,0,<\$0,0




2.2 Change bond type

2.2.1 Double, triple, wedge, vector


(Double, triple)
a~type : ~type, a
dm : double middle
dl : double left side
dr : double right side
db : double left or right side
tm : triple
!! : !~db / !!! : !~tm

<-30,!~dm,!~dl,!~dr,!~db,!~tm
<-30,!~dm,!~dl,!~dr,!! ,!! ,!,!!!



(Wedge, Vector)
wf: wedge forward
wb: wedge backward
zf: hashed(zebra stripe) wedge forward
zb: hashed(zebra stripe) wedge backward
vf: vector forward
vb: vector backward

<-30,
!~wf,!~wb,!~zf,!~zb,!~vf,!~vb



(Dotted, wave)
Bn=bond type : change bond type at Bn
dt : dotted / wv : wave
bd : broad / bz : broad dotted


<-30,!7,1=dt,3=wv,5=bd,7=bz



2.2.2 Over line

si_ : single over line
wf_ : wedge forward over line
wb_ : wedge backward over line
zf_ : hashed wedge forward over line
zb_ : hashed wedge backward over line
bd_ : broad over line
dl_ : double left over line
dr_ : double right over line
dm_ : double over line


<30,!8,!60,90'18,
{2~si_,4~wf_,6~wb_,8~zf_,10~zb_,
12~bd_,14~dl_,16~dr_,18~dm_}:/_'2



2.2.3 Steric ring

wf_r : wedge forward (half width)
bd_r : broad (half width, rounded)
wb_r : wedge backward (half width)


#1.25,-30~wf_r,30~bd_r'1,30~wb_r,
120,0,30,&1,##,6^\$90:/!OH'-.5,
{1^\$-90,2^\$90,3^\$-90,4^\$90}:/OH'-.5,



2.2.4 Change multiple bond type

{2,4,6}=dr : 2=dr,4=dr,6=dr

<30,!7,{2,4,6}=dr




2.3 Change bond length

2.3.1 Chain length


(!,!n)'length : change length of !,!n

<-30,!2,!4'1.2,!2



#n : bond length=n
: reset bond length


<-30,!2,#1.2,!4,##,!2



2.3.2 Ring length

?n'length : change ring length

?6,@4,\,?6'1.2




2.4 Change atom

2.4.1 Insert atom

Insert hetero atom


<-30,!2,0,!2,N,!2



2.4.2 Addressed atom

2:0 : change A2 C to O
 {3,4}:N : change A3,A4 C to N


<30,!4,2:0,{3,4}:N



2.4.3 Brock address

| : divide brock


?6,@4,\,|,?6,2:0



2.4.4 Reset brock address

|| : reset brock address


?6,@4,\,|,?6,||,2:N



2.4.5 Absolute address

\$2:N : change A\$2 C to N **1<=n<=3095


?6,@4,\,|,?6,\$2:N



2.4.6 Relative address

-2:N : change A(-2) C to N **-999<=n<=-1


?6,@4,\,?6,-2:N



2.4.7 Charged atom

p_ : positive / n_ : negative

<-30,!2,N,??,p_,!2,S,n_^180,
 !6,7:N,7:??,9:S,7:n_,9:n_^180




2.5 Fuse ring

(Attached 1 bond)

?6,3=?6 : fuse ?6 at B3


** Bn(n:-999<=n<=4095): bond number

?6,3=?6



** fused ring size depend on
 attached bond length

?6,@4,\,?6'1.2,5=?6,11=?6




?6,3=?6[13] : fuse ?6[13] at B3

?6[13]: 6 membered ring scaled 13/10


** ?m[n] (5<=m<=8,11<=n<=15)

?6,3=?6[13]



?6,{-3,-4,-4,-2,-2,-4,-4}=?6

?6,{4,8,13,20,25,28,33}=?6



(Attached 2 bond)

(4,11)=?6 : fuse 4/6 ring to B11..B4

(4,11)=?5 : fuse 3/5 ring to B11..B4


(4,11)=?4 : fuse 2/4 ring to B11..B4

** ?m[n] (4<=m<=6,n=m-2)

1:<30,?6,3=?6,(11,4)=?6

2:<30,?6,3=?6,(11,4)=?5


3:<30,?6,3=?6,(11,4)=?4



(Attached 3 bond)

(16,4)=?6[3] : fuse 3/6 ring to B16..B4
(16,4)=?5[2] : fuse 2/5 ring to B16..B4
** ?m[n] (5<=m<=6,n=m-3)


1:?6,{3,10}=?6,(16,4)=?6[3]
2:?6,{3,10}=?6,(16,4)=?5[2]



(Attached 4 bond)

(21,4)=?6[2] : fuse 2/6 ring to B21..B4
MC(<-30,?6,{3,10,15}=?6,(21,4)=?6[2])


** ?m[n] (m=6,n=2)



2.6 Spiro ring

@4,?5 : add ?5 at A4

<30,!6,@4,?5




2.7 Group

2.7.1 Insert group

/ : group start single bond

/_ : methyl
/! : ethyl
/!2 : propyl
/?! : isopropyl
/??? : tert-butyl
/Ph : phenyl


<30,!/_,!2,/!,!2,/!2,!4,/?!,
!4,/???,!2,/Ph^-60,!



2.7.2 Insert modified group


// : double (double middle)
*/ : wedge forward
/* : hashed wedge forward
/ : wave
** : direct

<30,!//0,!2,*H,!2,*H,!2,*H,!2,**?3,!




~ : change type
^ : change angle
' : change length
> : change environment

<-30,'^1,!,
/_'^2^30,!2,/!2>lr,!2,/!2>r1,!)



2.7.3 Add group


<30,!17,2:/_4:/!6:/!2,
10:/?!14:/???16:/Ph^-60



2.7.4 Add modified group


~,^,' : change type,angle,length

<30,!6,{2~wf,4~zf,6^-30,8^\$120}:/_



~,^,'> : change angle,length,environment

<-30,!7^1,3:/_'^2^30,5:/!2>lr,7:/!2>r1




2.8 Chain environment

2.8.1 Horizontal,vertical

>hz : horizontal environment (default)
>vt : vertical environment


```
?4,  
{3^-90,3^-30,3^90}:/'(!3,"{hz}")>hz,  
{1^-60,1,1^60}:/'(!3,"{vt}")>vt
```



2.8.2 Left-right,right-left

>lr : left-right environment
>rl : right-left environment


```
<-30,!6,  
{3^-30,3,3^30}:/'(!3,"{lr}")>lr,  
{5^-30,5,5^30}:/'(!3,"{rl}")>rl
```



2.8.3 Fixed rotate angle

>n : rotate n


```
<30,!4,  
2:/!6>30, % 2:\,30,30,30,30,30,30  
4:/!4>-45 % 4:\,-45,-45,-45,-45
```



2.8.4 Multi rotate angle

>'(90,-90,...) : rotate 90,-90,...

```
<30,!6,6>'(90,-90,90,-90,90):/!5
```




2.9 Miscellaneous

2.9.1 Abbreviated parts


```
NH : N,/H~n1 N! : N,/_ N!2 : N,/  
SO : S,//0 S00 : S,//0^35,/^-35
```

```
<-30,!2,NH,!2,N!,!2,N!2,S0,!2,S00,!
```



```
?! : /_,!  
/?! : isopropyl /??? : tert-butyl  
/N?! : dimethylamino
```


```
<30,!9'1,?!,! ,??,! ,2:??,4:/??,6:/??!,8:/N?!
```



2.9.2 Parts definition


'(..) : user defined parts

```
iBuOH:= '(!,/_,! ,OH);  
MC(<30,?6,{4,6}:/iBuOH)
```



2.9.3 Parts inline definition

```
<30,!8,{2,6}:/'(!,/_,! ,OH)
```




2.9.4 Move position

@(x,y) : Move l*(x,y) from current position

@\$(x,y) : Move l*(x,y) from origin(@)

** l=bond length of ring


```
<30,?6,@3,!4,//0,! ,0,n^60,@$(6,1),H,p^15
```



2.9.5 Serial number

```
6--10 : 6,7,8,9,10
```


```
<30,!14,{2,6--10,14}:/_~bd_r'0.5
```



2.9.6 Change color

(use with metapost only)


```
beginfont()
  MC(<30,Ph,{2,5}:N,3:/NH2,4:/COOH,
    %-----
    2:red,      % red   A2
    5:blue,    % blue  A5
    3:green,   % green B3
    %-----
  )
endfont
```



2.9.7 Change font

(use with metapost only)

```
beginfont()
  %-----
  atomfont:="cmr8";
  %-----
  MC(<30,Ph,{2,5}:N,3:/NH2,4:/COOH)
endfont
```



3 Option parameter


3.1 Angle parameter

mangle=0 ** default

```
MCat(0.2,0.5)(Ph)
```

```
mangle:=30;
```

```
MCat(0.8,0.5)(Ph)
```




3.2 Size/Ratio parameter

3.2.1 Bond length

(fit to font size)


blength=0 ** default



(ratio bond/font width)

blength=0.1 ** (0<blength<=1)


blength=60mm(width)*0.1=6mm



(bond length)


blength=9mm

** (blength>1) ignore msize(w,h)




3.2.2 Molecular size

msize=(1,1) ** default




msize=(0.25,1)

msize=40mm-4mm*0.25=9mm




msize=(11mm,11mm)



3.2.3 Molecular position


mposition=(0.5,0.5) ** default



mposition=(1,0)



mposition=(10mm,4mm)




3.3 Size parameter

3.3.1 Font size

fsize=(font width,font height)

** default: (30mm,20mm)

fsize=(40mm,15mm)




3.3.2 Font margin

fmargin=(margin left right,top bottom)


** default: (0.4mm,0.4mm)

fmargin=(10mm,2mm)




3.3.3 Offset thickness of bond

default: offset_thickness=0.2pt




3.3.4 Offset of double bond gap

default: offset_bond_gap=0.3pt




3.3.5 Offset of atom width

default: offset_atom=0.8pt




3.3.6 Offset of wedge width

default: offset_wedge=0.4pt



3.3.7 Max bond length


default: max_blength=10mm



3.4 Ratio parameter


3.4.1 Thickness/bond length

default: ratio_thickness_bond=0.015




3.4.2 Char/bond thickness

default: ratio_char_bond=1.5




3.4.3 Bond gap/bond length

default: ratio_bondgap_bond= 0.15




3.4.4 Atom/bond length

default: ratio_atom_bond= 0.36




3.4.5 Wedge/bond length

default: ratio_wedge_bond=0.12




3.4.6 Font atom gap/atom length

default: ratio_atomgap_atom= 0.050



3.4.7 Chain/ring length

default: ratio_chain_ring= 0.66



3.4.8 Hash gap/bond length


default: ratio_hashgap_bond=0.12



3.5 Drawing mode


3.5.1 Numbering atom

```
sw_numbering=Atom
numbering_start:=3; numbering_end:=8;
default: sw_numbering=0 :
```




3.5.2 Numbering bond

```
sw_numbering=Bond
numbering_start:=3; numbering_end:=8;
default: sw_numbering=0 :
```




3.5.3 Trimming mode

```
sw_trimming:=0; ** default
msize:=(1,0.7);
MCat(0.2,0.3) (Ph)
MCat(0.8,0.7) (Ph)
```




```
sw_trimming:=1;
MCat(0.2,0.3) (Ph)
MCat(0.8,0.7) (Ph)
```



3.5.4 Expand mode

```
MCat(0, .5) (<30,Ph,4:/COOH,3:/NH2)
sw_expand:=1;
MCat(1, .5) (<30,Ph,4:/COOH,3:/NH2)
** default: sw_expand=0
```



3.5.5 Abbreviate group

```
** default: sw_abbreviate=Group
```



3.5.6 Abbreviate bond type


```
** default: sw_abbreviate=Bond
```




3.6 Frame

3.6.1 Font frame


```
** default:sw_frame=0
(Draw font frame)
fmargin:=(5mm,2mm);
sw_frame=Outside
```



(Frame inside margin)
sw_frame=Inside




(Draw both frame)
sw_frame=Bothside=Inside+Outside



3.6.2 Molecular frame


```
sw_frame=Mol
** default:sw_frame=0
```



3.6.3 Atom frame

```
sw_frame=Atom
** default: sw_frame=0
```


```
MC(<30,COOH,!,COOH)
```



3.7 Parameter setting


3.7.1 Local parameter setting

```
beginfont()
  MC(Ph)
endfont
beginfont()
  %-----
  ratio_thickness_bond:=0.05;
  %-----
  MC(Ph)
endfont
beginfont()
  MC(Ph)
endfont
```



3.7.2 Global parameter setting

```
beginfont()
  MC(Ph)
endfont
%-----
ratio_thickness_bond:=0.05;
%-----
beginfont()
  MC(Ph)
endfont
beginfont()
  MC(Ph)
endfont
```



4 Function


4.1 Function MC()

(Draw molecule)

```
msize=(a,b)      **default (1,1)
mposition=(c,d)  **default (0.5,0.5)
```

a: ratio molecular width/font width
b: ratio molecular height/font height
c: x axis position
d: y axis position

```
beginfont()
  MC(<30,Ph,3:/F,4:/Cl)
endfont
```



4.2 Function MCat()


(Draw molecule at mposition)

```
MCat(c,d)(....) :
```

```
mposition:=(c,d); MC(....)
```

c: x axis position
d: y axis position

```
defaultsize:=5bp;
fsize:=(60mm,40mm); fmargin:=(3mm,3mm);
blength:=0.07; sw_frame:=Outside;
mangle:=0;
for i=1 step -0.5 until 0:
  for j=0 step 0.33 until 1:
    MCat(j,i)(Ph,4:N)
    add(drawarrow((A1+A1up**aw)..A1);
        label(decimal(mangle),
            p0+(0.5w,0.5h));
    )
    mangle:=mangle+30;
  endfor
endfor
```



4.3 Function check()

(immediately compile)

```
beginfont("EN:Pyridine")
  MC(<30,Ph,2:N)
endfont
```

(check mcf and compile)

** check(mc) : error count

```
beginfont("EN:Pyridine",
  ":<30,Ph,}2:N") % ** extra '}'
  if check(mc)=0: MC(scantokens(mc)) fi
endfont
```



check(mc)=0 check(mc)>=1

4.4 Function add()

(Add label to molecule)

w: molecular width
h: molecular height
aw: atom font size
em: label font size
p0: origin of molecular structure
l: bond length

An: atom number
A[m]: atom position
A[m]ang: branch angle of A[m]
A[m]up: dir A[m]ang
A[m]left: dir A[m]ang+90
A[m]right: dir A[m]ang-90
A[m]down: dir A[m]ang+180

Bn: bond number
B[m]: bond(path)
B[m]s: bond start position
B[m]m: bond middle position
B[m]e: bond end position
B[m]ang: bond angle
B[m]up: dir B[m]ang
B[m]left: dir B[m]ang+90
B[m]right: dir B[m]ang-90
B[m]down: dir B[m]ang+180


plus : '+' circled
minus : '-' circled
circlediam = 0.6aw (default)
circlepen = 0.2bp (default)

lonepair r: ':' rotated r
lonepairdiam = 0.3aw (default)
lonepairspace = 0.7aw (default)


** : scaled
<< : rotated
a /* b : point b of a

```
beginfont("EN:add() 1")
fsize:=(70mm,40mm);
sw_frame:=Bothside;
max_blength:=10mm;
msize:=(.91,.9);
MCat(.5,.85)(<30,?6,{2,5}:0)
add(
  defaultscale:=.8;
  labeloffset:=.3aw;
  dotlabel.lft("p0",p0);
  dotlabel.rtl("p0+(w,h)",p0+(w,h));
  dotlabel.ulft("A1",A1);
  drawarrow A1..A1+__*1<<A1ang;
  dotlabel.lrt("B3s",B3s);
  dotlabel.rtl("B3m",B3m);
  drawarrow B3m..B3m+__*1<<(B3ang+90);
  dotlabel.ulft("A6",A6);
```

```
drawarrow A1{A1down}..A6;
dotlabel.urt("B3e",B3e);
label.rtl("An"&decimal(An)&
" Bn"&decimal(Bn)&
" aw"&decimal(aw)&
" em"&decimal(em),
p0+(-9em,-1.5em));
label.rtl("w"&decimal(w)&
" h"&decimal(h)&
" l"&decimal(l),
p0+(-9em,-3em));
)
endfont
```



```
beginfont("EN:add() 2")
fsize:=(60mm,20mm);
msize:=(1,0.85);
%-----
MCat(0,0)(<30,Ph,3=d1,4:/NH2)
%-----
add(
  labeloffset:=.7aw;
  label.top(lonpair 90,A7);
  drawarrow
    (A7+up**1.2aw){A7left}
    ..{B7right}B7/*0.3;
  drawarrow
    B3m..A3+B2up**1.5aw..{A3down}A3;
)
%-----
MCat(1,0)(<30,?6,{1,5}=d1,4://NH2)
%-----
add(
  labeloffset:=.7aw;
  label.top(plus,A7);
  label.urt(minus,A3);
  label(lonpair A3ang,A3+A3up**1.7aw);
)
%-----
ext(drawdblarrow (.4w,.4h)..(.55w,.4h));
%-----
endfont
```




4.5 Function ext()

(Extra label to font)

```
w:   font width
h:   font height
w0:  font width-2xpart(fmarg)
h0:  font height-2ypart(fmarg)
aw:  atom font size
em:  label font size
p0:  fmarg


n:   molecular number
p[m]: molecular origin position
w[m]: molecular width
h[m]: molecular height

ratio_thickness_char:
pen thickness / char width
%-----
beginfont()
  fontsize=(70mm,30mm);
  blength=0.065;
%-----
MCat(0.1,0.5)(
  <-210,60'1,60'1,60'1,{1,3}=d1,
  1:/R1,4:/R2^-60
)
  add(
    defaultscale=0.6;
    label.bot("Diene",p0+(0.5w,0));
  )
MCat(0.4,0.5)(
  <-30,-60'1,1=d1,1:/R3,2:/R4^60
  add(defaultscale=0.6;
    label.bot("Dienophile",p0+(.5w,0));
  )
MCat(0.9,0.5)(
  <30,?6,6=d1,2:/R2,3:/R4,4:/R3,5:/R1
)
%-----
ext(
  drawarrow (.52w,.5h)..(.6w,.5h);
  defaultscale=0.7;
  label("+", (0.25w,0.5h));
  ratio_thickness_char=0.125;
  label.bot("Diels-Alder Reaction",
    (.5w,h));
)
%-----
endfont
```



4.5.1 Local ext() setting


```
beginfont("EN:?3")
  fontsize=(12mm,15mm);
  MCat(0.5,1)(<30,?3)
endfont
beginfont("EN:?4")
  fontsize=(12mm,15mm);
  MCat(0.5,1)(?4)
%-----
ext(label.top(inf_EN,(0.5w,0));)
%-----
endfont
beginfont("EN:?5")
  fontsize=(12mm,15mm);
  MCat(0.5,1)(?5)
endfont
beginfont("EN:?5")
  fontsize=(12mm,15mm);
  MCat(0.5,1)(?6)
endfont
```



4.5.2 Global ext() setting

ext_clear: reset global ext()


```
beginfont("EN:?3")
  fontsize=(12mm,15mm);
  MCat(0.5,1)(<30,?3)
endfont
%-----
ext(label.top(inf_EN,(0.5w,0));)
%-----
beginfont("EN:?4")
  fontsize=(12mm,15mm);
  MCat(0.5,1)(?4)
endfont
beginfont("EN:?5")
  fontsize=(12mm,15mm);
  MCat(0.5,1)(?5)
endfont
%-----
ext_clear;
%-----
beginfont("EN:?6")
  fontsize=(12mm,15mm);
  MCat(0.5,1)(?6)
endfont
```



5 MCF example


5.1 Luciferin

```
(use data base file 'mcf_data_base')
beginfont("f:mcf_data_base",
  "t:EN", "v:Luciferin")
  fsize:=(50mm,15mm);
  if check(mc)=0: MC(scantokens(mc)) fi
endfont
```




5.2 Colchicine

```
beginfont("EN:Colchicine", "MW:385.41",
  %-----
  ": <30,Ph,{1,2,6}:/O!,-4,-5}=?7, ",
  ": {-1,-4,-6}=d1,-2://0,-3:/O!, ",
  ": @9,\,NH,!,//0,! ")
  %-----
  fsize:=(50mm,20mm);
  if check(mc)=0: MC(scantokens(mc)) fi
endfont
```



5.3 Paclitaxel


```
beginfont("EN:Paclitaxel", "MW:853.91",
  %-----
  ": ?6,5=d1,@3,#1,36,45,45,45,45,##, ",
  ": &5",
  ": -4=?6,-4=?4,-1=wb,-3=wf,-1:0,||, ",
  ": 4:??,6:/_{3~-60,15}:*/OH, ",
  ": 8:/*H~-60,",
  ": 9:*/_~60,10://0, ",
  ": @1,\,0,!,//0,!,*OH,!/,Ph,60~wf, ",
  ": NH,-60,//0,60,Ph, ",
  ": @7,\*,0,-45,//0,60,Ph, ",
  ": @11,*\,0,-60,//0,60, ",
  ": @12,*~15,0,60,//0,-60 ")
  %-----
  fsize:=(50mm,25mm);
  if check(mc)=0: MC(scantokens(mc)) fi
endfont
```



5.4 Maltose

```
(bond type for glycan)
arc_lb : arc left > bottom
arc_br : arc bottom right
```


```
beginfont("EN:Maltose", "MW:342.3",
  %-----
  ": #1.25,-30~wf_r,30~bd_r'1,30~wb_r, ",
  ": 120,0,30,&1,##, ",
  ": {1~$-90,2~$90,3~$-90}:/OH'-.5, ",
  ": 6~$90:!/OH'-.5, ",
  ": @4,$-50~arc_lb'1,0,$50~arc_br'1,<$0, ",
  ": |,#1.25,-30~wf_r,30~bd_r'1,30~wb_r, ",
  ": 120,0,30,&1,##, ",
  ": {2~$90,3~$-90,4~$-90}:/OH'-.5, ",
  ": 6~$90:!/OH'-.5 ")
  %-----
  fsize:=(50mm,20mm);
  if check(mc)=0: MC(scantokens(mc)) fi
endfont
```



5.5 Cellobiose

```
(bond type for glycan)
arc_lbr : arc left > bottom > right
arc_ltr : arc left > top > right
```

```
beginfont("EN:Cellobiose", "MW:342.3",
  %-----
  ": #1.25,-30~wf_r,30~bd_r'1,30~wb_r, ",
  ": 120,0,30,&1,##, ",
  ": {1~$-90,2~$90,3~$-90}:/OH'-.5, ",
  ": 6~$90:!/OH'-.5, ",
  ": @4,$0~arc_ltr,0,$0~arc_lbr, ",
  ": |,#1.25,-30~wf_r,30~bd_r'1,30~wb_r, ",
  ": 120,0,30,&1,##, ",
  ": {2~$90,3~$-90,4~$-90}:/OH'-.5, ",
  ": 6~$90:!/OH'-.5 ")
  %-----
  fsize:=(50mm,20mm);
  if check(mc)=0: MC(scantokens(mc)) fi
endfont
```



6 Example to use mcf2graph

6.1 Metafont/Metapost source file

```
%-----
input mcf2graph.mf;                                > input main macro
%-----
sw_output:=Info;      % aux(information) file output on > global setting
%% sw_output:=Report; > report output
%%% sw_output:=MOL2k; > MOL file output
fsize:=(60mm,40mm);  % (font width,font height)        >
tag1:="J";           > jobname
tag2:="C";           > char No
tag3:="mw";          % calculated molecular weight      >
tag4:="fm";          % calculated molecular formula     >
outputformat:="png"; hppp:=vppp:=0.1;                > PNG output
outputtemplate:="%j-%3c.png";                        >
%-----
beginfont("EN:Ampicillin","MW:349.405")              > information
  MC(<45,?4,-3=?5,2:N,7:S,                            > immediately compile
    3^45:/*H,1://O^15,5:/*COOH^-18,6:??,              >
    @4,*\^15,NH,!,//O,!/*NH2,! ,Ph)                  >
endfont                                               >
%-----
beginfont("EN:Cholesterol","MW:386.65",              >information
  %-----
  ": <30,?6,{-4,-2}?6,-4=?5,7=d1,                    ", > mc1
  ": 10:/*H^180,11:/*H^-60,17:/*H^-54,              ", > mc2
  ": {4,12}:*/_^60,                                   ", > mc3
  ": @-1,18,/*_,-60,!3,?!                            ") > mc4
  %-----
  if check(mc)=0: MC(scantokens(mc)) fi               > mc=mc1 - mc4
endfont                                               >
%-----
beginfont("f:mcf_data_base.mcf","t:EN","v:Adenine") > from mcf_data_base.mcf
  if check(mc)=0: MC(scantokens(mc)) fi               > select EN="Adenine"
endfont                                               >
%-----
beginfont("t:EN","v:Guanine")                        > select EN="Guanine"
  if check(mc)=0: MC(scantokens(mc)) fi
endfont
%-----
beginfont("t:EN","v:Cytosine")                      > select EN="Cytosine"
  if check(mc)=0: MC(scantokens(mc)) fi
endfont                                               >
%-----
beginfont("t:n","v+:4")                              > v+:4 = select No.4
  if check(mc)=0: MC(scantokens(mc)) fi               > keep file open
endfont                                               >
%-----
forever:
%%%%%%%%%% beginfont("f:mcf_data_base","v+:*")      > select all
  beginfont("f:mcf_data_base","t:EXA","v+:1")        > 'v+:1'= select EXA=1
    if f_EOF=0: if check(mc)=0: MC(scantokens(mc)) fi fi > keep file open
  endfont                                             >
  exitif f_EOF=1;                                     > exit if file end
endfor
%-----
bye
```

6.2 Molecular data base file

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% molecular data base file   mcf_data_base.mcf   by Akira Yamaji   2021.11.14
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% tag1:var1;tag2:var2;tag3:var3   ....
% first character of line "%" comment out
% first character of line "+" begin MCF
% first string of line "+-" end MCF
% first string of line "%-" end header
% Cat = Category
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%-----
Cat:biological;EN:Adenine;MW:135.13
+
<30,?6,3=?5,{1,3,5,9}=d1,{2,6,9}:N,5:/NH2,7:NH
+-----
Cat:biological;EN:Guanine;MW:151.13
+
<30,?6,3=?5,{1,3,9}=d1,{2,9}:N,{6,7}:NH,5://0,1:/NH2
+-----
Cat:biological;EN:Cytosine;MW:111.10
+
<30,?6,{4,6}=d1,4:N,3://0,2:NH,5:/NH2
+-----
Cat:biological;EN:Thymine;MW:126.11
+
<30,?6,3=d1,{2,6}:NH,{1,5}://0,4:/_
+-----
Cat:biological;EN:Uracil;MW:112.09
+
<30,?6,6=d1,{3,5}://0,{2,4}:NH
+-----
Cat:biological;EN:Geraniol;MW:154.25
+
<30,!8,OH,{2,6}=dr,{2,6}:/_
+-----
Cat:biological;EN:Limonene;MW:136.24
+
<30,?6,2=d1,2:/_,@5,*\,/_,!!
+-----
Cat:biological;EN:l-Menthol;MW:156.27
+
<30,?6,2:/*?!,5:*/_ ,3:*/OH
+-----
Cat:biological;EN:Vanillin;MW:152.15
+
<30,Ph,2:/OH,3:/O!,5:/CHO
+-----
Cat:biological;EN:Allicin;MW:162.28
+
<-30,!! ,!2,S0,! ,S,!2,!!
+-----
Cat:biological;EN:Stearic acid;MW:284.48
+
<30,!17,COOH
+-----
```


6.3 Function query()

(Example)

```
%-----  
% query()  
%  
% "f:filename" : input file name (default "mcf_data_base.mcf")  
% "o:filename" : output file name (default "temp.mcf")  
% "s:sort-key" : sort by sort-key  
%  
% operator : = , <> , <= , >= , < , >  
%  
% filter 1 : Cat=biological  
% filter 2 : MW>=285  
% filter 3 : MW<=295  
%-----  
query("s:EN",  
      "f:mcf_data_base.mcf","o:temp.mcf","s:EN",  
      "Cat=biological","MW>=285","MW<=295");  
%-----  
forever:  
  beginfont("f:temp","v+:*") % use file temp.mcf / select all  
    if f_EOF=0: if check(mc)=0: MC(scantokens(mc)) fi fi  
  endfont  
  exitif f_EOF=1;  
endfor  
%-----
```

(output)

```
Cat:biological;EN:Atoropin;MW:289.375;EXA:1  
+  
<30,0,!,//0,!,!,Ph,@$1,\~zb^-60,|,?7'1.1,@6,*\^190'1.25,N!,&3~wb,$3:/!OH~wv  
+-----  
Cat:biological;EN:Cianidanol;MW:290.27;EXA:1  
+  
<30,Ph,3=?6,@8,*\,Ph,7:0,{1,5,13,14}:/OH,9:/*OH  
+-----  
Cat:biological;EN:Lycorine;MW:287.315;EXA:1  
+  
<30,Ph,{-4,-2}=?6,{6,(9,12)}=?5,13=dl,8:N,{15,17}:0,  
9:/*H^180,10:*/H^60,13:*/OH,14:/*OH  
+-----  
Cat:biological;EN:Morphine;MW:285.343;EXA:1  
+  
<30,Ph,{2,-4}=?6,(1,12)=?5[2],-1:0,-1=zb,  
@7,60~wf'0.75,70~si_'1.3,45,N!,&9~wb,15=dl,6:/OH,8^180:*/H,12:/*OH  
+-----  
Cat:biological;EN:Piperine;MW:285.343;EXA:1  
+  
<30,Ph,|,-1=?5,{1,3}:0,@$4,\,!,!,!,!,//0,!,|,?6,1:N  
+-----
```

6.4 Information aux file output

(Insert option parameter setting)

```
sw_output:=Info;           %% tag1:var1;tag2:var2
sw_output:=Info+Table;    %% tag1;tag2 var1;var2
sw_output:=Info+Temp;     %% tag1:var1;tag2:var2 / output 'temp-info.aux'
sw_output:=Info+Mcode;    %% output jobname&'.aux'
sw_output:=Info+Mcode+Temp; %% output 'temp-info.aux','temp-mc.aux'
sw_output:=Font+Info+Temp; %% output font,'temp-info.aux','temp-mc.aux'
```

(Command line)

```
>mpost -s ahlenght=1 FILENAME (sw_output=Info)
>mpost -s ahlenght=2 FILENAME (sw_output=Info+Table)
```

(Source)

```
beginfont("EN:Ampicillin")    .... endfont
beginfont("EN:Cholesterol")   .... endfont
beginfont("EN:Limonin")       .... endfont
beginfont("EN:beta-Carotene") .... endfont
```

(Setting)

```
tag1:="J"; tag2:="C"; tag3:="mw"; tag4:="fm"; tag5:="EN";
```

(Output)

(sw_output=Info)

```
F:mcf_man_soc;C:1;mw:349.40462;fm:C16H19N3O4S;EN:Ampicillin
F:mcf_man_soc;C:2;mw:386.6532;fm:C27H46O;EN:Cholesterol
F:mcf_exa_soc;C:3;mw:470.5113;fm:C26H30O8;EN:Limonin
F:mcf_exa_soc;C:4;mw:536.8722;fm:C40H56;EN:beta-Carotene
```

(sw_output=Info+Table)

```
F;C;mw;fm
mcf_man_soc;1;349.40462;C16H19N3O4S;Ampicillin
mcf_man_soc;2;386.6532;C27H46O;Cholesterol
mcf_exa_soc;3;470.5113;C26H30O8;Limonin
mcf_exa_soc;4;536.8722;C40H56;beta-Carotene
```

(aux_delimiter="/")

```
F:mcf_man_soc/C:1/mw:349.40462/fm:C16H19N3O4S/EN:Ampicillin
F:mcf_man_soc/C:2/mw:386.6532/fm:C27H46O/EN:Cholesterol
F:mcf_exa_soc/C:3/mw:470.5113/fm:C26H30O8/EN:Limonin
F:mcf_exa_soc/C:4/mw:536.8722/fm:C40H56/EN:beta-Carotene
```

(Tag)

```
J : jobname
C : char number
NO : serial number
EN : english name
JN : japanese name
FM : formula from literature data
MW : molecular weight from literature data
MI : monoisotopic mass from literature data
USE : the use
mw : molecular weight calculated
mi : monoisotopic mass calculated
fm : molecular formula calculated
w : font width
h : font height
```

6.5 Metafont aux file output

(Insert option parameter setting)

```
sw_output:=Mfont;
```

(Command line)

```
>mpost -s ahlengh=7 FILENAME (sw_output=Mfont)
```

(Output)

```
beginfont("Cat:biological","EN:Adenine","MW:135.13",
": <30,?6,3=?5,{1,3,5,9}=d1,{2,6,9}:N,5:/NH2,7:NH")
if check(mc)=0: MC(scantokens(mc)) fi
endfont
beginfont("Cat:biological","EN:Guanine","MW:151.13",
": <30,?6,3=?5,{1,3,9}=d1,{2,9}:N,{6,7}:NH,5://0,1:/NH2")
if check(mc)=0: MC(scantokens(mc)) fi
endfont
beginfont("Cat:biological","EN:Cytosine","MW:111.10",
": <30,?6,{4,6}=d1,4:N,3://0,2:NH,5:/NH2")
if check(mc)=0: MC(scantokens(mc)) fi
endfont
beginfont("Cat:biological","EN:Thymine","MW:126.11",
": <30,?6,3=d1,{2,6}:NH,{1,5}://0,4:/_")
if check(mc)=0: MC(scantokens(mc)) fi
endfont
beginfont("Cat:biological","EN:Adenine","MW:135.13",
": <30,?6,3=?5,{1,3,5,9}=d1,{2,6,9}:N,5:/NH2,7:NH")
if check(mc)=0: MC(scantokens(mc)) fi
endfont
beginfont("Cat:biological","EN:Guanine","MW:151.13",
": <30,?6,3=?5,{1,3,9}=d1,{2,9}:N,{6,7}:NH,5://0,1:/NH2")
if check(mc)=0: MC(scantokens(mc)) fi
endfont
beginfont("Cat:biological","EN:Cytosine","MW:111.10",
": <30,?6,{4,6}=d1,4:N,3://0,2:NH,5:/NH2")
if check(mc)=0: MC(scantokens(mc)) fi
endfont
beginfont("Cat:biological","EN:Thymine","MW:126.11",
": <30,?6,3=d1,{2,6}:NH,{1,5}://0,4:/_")
if check(mc)=0: MC(scantokens(mc)) fi
endfont
beginfont("Cat:biological","EN:Uracil","MW:112.09",
": <30,?6,6=d1,{3,5}://0,{2,4}:NH")
if check(mc)=0: MC(scantokens(mc)) fi
endfont
beginfont("Cat:biological","EN:Geraniol","MW:154.25",
": <30,!8,OH,{2,6}=dr,{2,6}:/_")
if check(mc)=0: MC(scantokens(mc)) fi
endfont
beginfont("Cat:biological","EN:Limonene","MW:136.24",
": <30,?6,2=d1,2:/_@5,*\,/_,!!")
if check(mc)=0: MC(scantokens(mc)) fi
endfont
beginfont("Cat:biological","EN:l-Menthol","MW:156.27",
": <30,?6,2/*?!5:*/_3:*/OH")
if check(mc)=0: MC(scantokens(mc)) fi
endfont
```

6.6 MCF aux file output

(Insert option parameter setting)

```
sw_output:=Mcode;           %% output 'jobname-nnn-EN-mc.aux'
sw_output:=Mcode+Temp;      %% output 'temp-mc.aux'
sw_output:=Info+Mcode;      %% output 'jobname-data.aux'
sw_output:=Info+Mcode+Temp; %% output 'temp-info.aux','temp-mc.aux'
sw_output:=Font+Mcode+Temp; %% output font,'temp-mc.aux'
sw_output:=Font+Info+Mcode+Temp; %% output font,'temp-info.aux','temp-mc.aux'
```

(Command line)

```
>mpost -s ahlength=8 FILENAME (sw_output=Info+Mcode)
```

(Output temporary file)

```
sw_output=Mcode      ** file name = 'jobname-nnn-EN-mc.aux'
sw_output=Mcode+Temp ** file name = 'temp-mc.aux'
```

(result)

```
<30,?6,3=?5,{1,3,5,9}=d1,{2,6,9}:N,5:/NH2,7:NH
```

(Output data-base file)

```
sw_output=Mcode+Info ** file name = 'jobname-data.aux'
```

(result)

```
Cat:biological;EN:Adenine;MW:135.13;EXA:1
+
<30,?6,3=?5,{1,3,5,9}=d1,{2,6,9}:N,5:/NH2,7:NH
+-----
```

(Lualatex example)

```
beginfont("t:EN","v:Adenine")
  sw_output:=Mcode+Temp;
endfont

%-----
\begin{mplibcode}
  beginfont("t:EN","v:Vancomycin")
    sw_output:=Mcode+Temp;      %%% output temp-mc.aux %%%
  endfont;
\end{mplibcode}
%-----
\verbatiminput{temp-mc.aux}
%-----
```

(result)

```
file name = 'temp-mc.aux'

<30,?6,@4,?6,@-4,\,!3,<-12,?5,@-3,<-12,?6,-3=?6,@-3,*\,!3,
?6,@-4,?6,@6,\,!/*Me^-40,*OH^20,!//0,!1,OH,
3=wb,11=d1,15=dr,17=wf,19=wf,38=wb,{5,7,16,24,25,33,42}:0,
32:*/H^60,10:/Me,{12,31}:*/_,27://_,37:/*_,28:/OH,{3,29}:/*OH
```

6.7 Report output

(Insert option parameter setting)

```
sw_output:=Report;      ** file name = 'jobname-report.aux'  
sw_output:=Report+Temp; ** file name = 'temp-report.aux'
```

(Command line)

```
>mpost -s ahlength=3 FILENAME
```

(Output)

```
=====
```

| | | | | |
|-----|---|---|--------|----------|
| No. | 3 | / | Name = | Cytosine |
|-----|---|---|--------|----------|

```
-----
```

<30,?6,{4,6}=d1,4:N,3://0,2:NH,5:/NH2

```
-----
```

row= 1 / length= 37 / commands= 7
{}=X = 1 / {}:X = 0 / '() = 0 / @ = 0 / & = 0 / < = 1

```
-----
```

Warnings = 0 / Code= 60
Width * Height = 34.68852 * 47.4036
Shift width * height = 0 * -14.46167
Bond length = 12.75589 Atom size = 5.38914
Atom count= 9 Bond count= 9 Ring count= 1 Hide H count= 2

```
-----
```

| < NO. | ><atom(s) | >(x axis | , | y axis |)<bond><hideH><chg> |
|-------|-----------|-----------|-------|--------|---------------------|
| A1 | C | (| 0 | , | 0) 3 1 |
| A2 | N | (| 0.866 | , | -0.5) 3 |
| A3 | C | (| 1.732 | , | 0) 4 |
| A4 | N | (| 1.732 | , | 1) 3 |
| A5 | C | (| 0.866 | , | 1.5) 4 |
| A6 | C | (| 0 | , | 1) 3 1 |
| A7 | O | (| 2.508 | , | -0.448) 2 |
| A8 | H | (| 0.866 | , | -0.922) 1 |
| A9 | NH2 | (| 0.866 | , | 2.371) 1 |

```
-----
```

| < NO. | >< bond | (sdt)><angle +(| + -)><length (| pt)> |
|-------|---------|-----------------|-----------------|--------------|
| B1 | 1 -> | 2 (1) | 330 (-30) | 1 (12.76) |
| B2 | 2 -> | 3 (1) | 30 (30) | 1 (12.76) |
| B3 | 3 -> | 4 (1) | 90 (90) | 1 (12.76) |
| B4 | 4 -> | 5 (2) | 150 (150) | 1 (12.76) |
| B5 | 5 -> | 6 (1) | 210 (-150) | 1 (12.76) |
| B6 | 6 -> | 1 (2) | 270 (-90) | 1 (12.76) |
| B7 | 3 -> | 7 (2) | 330 (-30) | 0.66 (8.42) |
| B8 | 2 -> | 8 (1) | 270 (-90) | 0.36 (4.59) |
| B9 | 5 -> | 9 (1) | 90 (90) | 0.66 (8.42) |

```
-----
```

| <atom> | (atom wt) | [mi wt] | < cnt > | < sum wt > | [sum mi wt] |
|------------------|-------------------|--------------|---------|------------|---------------|
| C | (12.0107) | [12] | * 4 | 48.04279 | [48] |
| H | (1.00793) | [1.00783] | * 5 | 5.03967 | [5.03914] |
| N | (14.0067) | [14.00307] | * 3 | 42.0201 | [42.0092] |
| O | (15.9994) | [15.99492] | * 1 | 15.9994 | [15.99492] |
| Molecular Weight | [Mono Isotopic] | = | | 111.1019 | [111.04326] |

```
-----
```

Weight Calc: 111.1019 / Input: 111.10 / weight gap= 0.00195
Fomula Calc: C4H5N3O / Input:

```
=====
```

6.8 MOL file output

(Insert option parameter setting)

```
sw_output:=MOL2k;    % MOL(V2000)
sw_output:=MOL3k;    % MOL(V3000)
```

(Command line)

```
>mpost -s ahlength=5 FILENAME    % MOL(V2000)
>mpost -s ahlength=6 FILENAME    % MOL(V3000)
```

(Output)

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
```

```
-MCFtoMOL- EN:Caffeine
```

```
14 15 0 0 0 0 0 0 0 0999 V2000
      0      0      0 C  0 0 0 0
  0.86603    -0.5      0 N  0 0 0 0
  1.73206      0      0 C  0 0 0 0
  1.73206      1      0 C  0 0 0 0
  0.86603     1.5      0 C  0 0 0 0
      0      1      0 N  0 0 0 0
  2.6831   -0.30902    0 N  0 0 0 0
  3.27089      0.5      0 C  0 0 0 0
  2.6831    1.30902    0 N  0 0 0 0
  0.86603   -1.36383    0 C  0 0 0 0
 -0.76894    1.44394    0 C  0 0 0 0
 -0.76894   -0.44394    0 D  0 0 0 0
  0.86603    2.36383    0 D  0 0 0 0
  2.95299    2.1396    0 C  0 0 0 0
  1  2  1  0      0  0
  2  3  1  0      0  0
  3  4  2  0      0  0
  4  5  1  0      0  0
  5  6  1  0      0  0
  6  1  1  0      0  0
  3  7  1  0      0  0
  7  8  2  0      0  0
  8  9  1  0      0  0
  9  4  1  0      0  0
  2 10  1  0      0  0
  6 11  1  0      0  0
  1 12  2  0      0  0
  5 13  2  0      0  0
  9 14  1  0      0  0
```

```
M  END
```

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
```

6.9 LuaTeX file example

```

\documentclass{article}
\usepackage{luamplib}%
\usepackage[T1]{fontenc}%
\usepackage{textcomp}%
\mplibcodeinherit{enable}%
\mplibverbatim{enable}%
\mplibnumbersystem{double}%
\everymplib{%
  if unknown Ph1: input mcf2graph.mf; fi
  sw_output:=Font; max_blength:=4.5mm;
  defaultfont:="uhvr8r"; defaultsize:=8bp; defaultscale:=1;
}%
\begin{document}
\noindent%
%-----
\begin{mplibcode}
  fsize:=(50mm,50mm);
  beginfont("NO:1","EN:Limonin","MW:470.51",
    %-----
    ": <30,?6,{-3,-4}=?6,           ",
    ": -5=?3,-2=wf,-1=wb,6=?5,-4=?6,-5=wf, ",
    ": {13,15,17,20}:0,{3,12,21}://0,      ",
    ": {4~wf^60,8~zf^60,18^35,18^-35}:/_,   ",
    ": {1^60,5^180,16^60}:/*H,           ",
    ": @14,\*,|,?5,{1,4}=d1,3:0         ")
    %-----
  if check(mc)=0: MC(scantokens(mc)) fi
  endfont
\end{mplibcode}\\
%-----
\begin{mplibcode}
  fsize:=(80mm,50mm);
  beginfont("NO:2","EN:beta-carotene","MW:536.87",
    %-----
    ": <30,?6,3=d1,{3,5^35,5^-35}:/_,      ",
    ": @4,\,|,!18,{1,3,5,7,9,11,13,15,17}=dr, ",
    ": {3,7,12,16}:/_,                      ",
    ": |,?6,6=d1,{6,2^35,2^-35}:/_         ")
    %-----
  if check(mc)=0: MC(scantokens(mc)) fi
  endfont
\end{mplibcode}\\
%-----
\begin{mplibcode}
  fsize:=(50mm,50mm);
  beginfont("NO:3","EN:Gibberellin A3","MW:346.37",
    %-----
    ": <18,?5,3=?7,5=?6[12],              ",
    ": @8,160'1.3,&3,13=d1,6=wf,8=wb,      ",
    ": @5,40~zf'1,0,60,//0^180,&14~zb,    ",
    ": 2:/COOH,7://_,13:*/OH,8:/*OH,      ",
    ": 14:*/_,{1^60,4^60}:*/H             ")
    %-----
  if check(mc)=0: MC(scantokens(mc)) fi
  endfont;
%-----
\end{mplibcode}\\
\end{document}

```

6.10 LaTeX file example


```

%-----
\documentclass[a4paper]{article}
\usepackage{graphicx}
\makeatletter%
%-----
\usepackage{mcf_setup}
%-----
\pagestyle{empty}
%-----
\def\put@char{%
  \begin{picture}(84,42)%
    \put(0,38){\bf [MOLnum]\EN{ }\small\tt/FM:\fm/MW:\mw}%
    \put(10,0){\font\@strufont=\File\relax%
      \hbox{\@strufont\char\Char}}%
  \end{picture}%
}%
\def\INFO#1{\@for\@temp:=#1\do{\tag@var\@temp}\put@char}%
\makeatother
%-----
\begin{document}
\unitlength=1mm%
\INFO{J:mcf_man_soc,C:141,NO:1,mw:349.40462,fm:C16H19N3O4S,EN:Ampicillin}%
\INFO{J:mcf_man_soc,C:142,NO:2,mw:386.6532,fm:C27H46O,EN:Cholesterol}%
\end{document}
%-----

```


[1]Ampicillin

FM:C16H19N3O4S MW:349.40462



[2]Cholesterol

FM:C27H46O MW:386.6532



Index

!, 3
!!, 4
!!!, 4
, 7
**, 6, 12
*/, 6
/, 6
*\, 3
**, 3
/, 6
/*, 6, 12
//, 6
:, 5
?, 3
?!, 7
??, 7
??!, 7
@, 3
@(), 7
#, 4
##, 4
\$, 5
&, 3
, 7
~, 3, 6
~, 3, 4, 6
~~, 4
\, 3
*, 3
\|, 3
|, 5
||, 5
>, 3, 7
>>, 12
<, 6
' , 3, 4, 6

A[], 12
A[]ang, 12
A[]down, 12
A[]left, 12
A[]right, 12
A[]up, 12
add(), 12
An, 12
arc_br, 14
arc_lb, 14
arc_lbr, 14
arc_ltr, 14
Atom, 10
atomfont, 8
aux_delimiter, 18
aw, 12, 13

B[], 12
B[]ang, 12
B[]down, 12
B[]e, 12
B[]left, 12
B[]m, 12
B[]right, 12
B[]s, 12
B[]up, 12
bd, 4
bd_, 4
bd_r, 4
beginfont(), 11
blength, 8
blue, 8
Bn, 12
Bond, 10
Bothside, 10
Brock, 10
bz, 4

C, 18
check(), 11, 14
circlediam, 12
circlepen, 12

db, 4
defaultscale, 12, 13
dl, 4
dl_, 4
dm, 4
dm_, 4
dr, 4
dr_, 4
dt, 4

em, 12, 13
EN, 18
endfont, 11
ext(), 13
ext_clear, 13

FM, 18
fm, 18
fmargin, 9
Font, 23
fsize, 9

green, 8
Group, 10

h, 12, 18
h0, 13
hz, 7

Info, 18
Inside, 10
Inverse, 10

J, 18
JN, 18

l, 12

labeloffset, 12
 lonenpair, 12
 lonenpairdiam, 12
 lonenpairspace, 12
 lr, 7

 mangle, 8
 max_blength, 9
 MC(), 11
 MCat(), 11
 mcf2graph.mf, 15
 mcf_setup.sty, 24
 Mcode, 20
 Mfont, 19
 MI, 18
 mi, 18
 minus, 12
 Mol, 10
 MOL2k, 22
 MOL3k, 22
 mposition, 8
 msize, 8
 MW, 18
 mw, 18

 n, 13
 N!, 7
 N!2, 7
 N?!, 7
 NH, 7
 NO, 18
 numbering_end, 10
 numbering_start, 10

 offset_atom, 9
 offset_bond_gap, 9
 offset_thickness, 9
 offset_wedge, 9
 Outside, 10

 p0, 12
 Ph, 6
 plus, 12

 query(), 17

 ratio_atom_bond, 9
 ratio_atomgap_atom, 9
 ratio_bondgap_bond, 9
 ratio_chain_ring, 9
 ratio_char_bond, 9
 ratio_hashgap_bond, 9
 ratio_thickness_bond, 9
 ratio_thickness_char, 13
 ratio_wedge_bond, 9
 red, 8
 Report, 21
 rl, 7

 si_, 4
 SO, 7

 S00, 7
 sw_abbreviate, 10
 sw_expand, 10
 sw_frame, 10
 sw_numbering, 10
 sw_output, 15, 21, 22
 sw_trimming, 10

 Table, 18
 tag, 15
 Temp, 18, 20
 tm, 4

 USE, 18

 var, 15
 vb, 4
 vf, 4
 vt, 7

 w, 12, 18
 w0, 13
 wb, 4
 wb_, 4
 wb_r, 4
 wf, 4
 wf_, 4
 wf_r, 4
 wv, 4

 zb, 4
 zb_, 4
 zf, 4
 zf_, 4