

# The cooking-units package\*

Ben Vitecek  
b.vitecek@gmx.at

2022/06/06

## Abstract

This package enables user to globally format units, to switch between them and change your recipes to a given number of persons.  
For not implemented units or differences between Imperial and U.S. unit you may have a look at appendix [B](#).  
It should be used for light-hearted things like cookery books (and not e.g. scientific texts; use e.g. `siunitx` for those).

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
1.1	Supported languages . . . . .	2
<b>2</b>	<b>The Commands</b>	<b>3</b>
<b>3</b>	<b>Label &amp; refs: Changing the amount of the recipe</b>	<b>5</b>
<b>4</b>	<b>Good to know stuff</b>	<b>6</b>
4.1	Rounding temperatures . . . . .	6
4.2	At which point is the plural used? . . . . .	6
<b>5</b>	<b>Predefined units &amp; some notes</b>	<b>7</b>
<b>6</b>	<b>Defining units</b>	<b>7</b>
<b>7</b>	<b>Defining options to change units</b>	<b>9</b>
7.1	Obsolete Commands . . . . .	13
<b>8</b>	<b>Language support</b>	<b>14</b>
8.1	Phrases . . . . .	16

---

\*This document corresponds to Benedikt Vitecek v2.01, dated 2022/06/06.

<b>9</b>	<b>Options</b>	<b>17</b>
9.1	Load time options . . . . .	18
9.2	Normal options . . . . .	18
9.2.1	Unit Specific options . . . . .	18
9.2.2	Command behavior . . . . .	20
9.2.3	Hooks . . . . .	21
9.2.4	Input and Outputs . . . . .	22
9.2.5	Rounding options . . . . .	25
9.2.6	Fractions . . . . .	26
9.2.7	Spaces . . . . .	28
9.2.8	label & refs . . . . .	29
9.3	Weird options . . . . .	32
<b>10</b>	<b>Public Commands</b>	<b>34</b>
<b>11</b>	<b>Bugs &amp; Feedback</b>	<b>34</b>
<b>12</b>	<b>Bens Einheitsammelsurium (Bens unit Almanac)</b>	<b>35</b>
<b>A</b>	<b>Translations</b>	<b>36</b>
A.1	English . . . . .	37
A.2	american . . . . .	38
A.3	German . . . . .	39
A.4	French . . . . .	41
<b>B</b>	<b>US, Imperial and Other units</b>	<b>42</b>
	<b>Change History</b>	<b>43</b>
	<b>Index</b>	<b>45</b>

## 1 Introduction

While writing on a cookery book I used – for some reasons whatsoever – three different units for weight: kilogram (kg), gram (g) and decagram (dag, or older: dkg). Later my mother told me that she doesn't like it if a cookery book uses more than two different units (for weight in this case). Happily I hardly used Decagram and therefore didn't have many problems changing the units. But, well . . . I am using  $\text{\LaTeX}$  and changing those units by hand seemed not very  $\text{\LaTeX}$ -like, so I started writing some code to convert units. I expanded the code, rewrote it in  $\text{\LaTeX}3$  (which is much more pleasant than  $\text{\LaTeX}2\epsilon$ ) and here it is.

## 1.1 Supported languages

- German
- English
- French

Want to contribute a new language or make a correction to an existing one? See section 11 for more details. Wanna just check the existing translations? See appendix A.

## 2 The Commands

This package offers the following commands for number/unit printing (and converting):

- `\cunum<label>[<options>]{<amount>}[<space>]{<unit-key>}`
- `\cutext<label>>[<options>]{<amount>}{<unit-key>}`
- `\Cutext<label>>[<options>]{<amount>}{<unit-key>}`
- `\cuam<label>>[<options>] {<amount>}`
- `\cusetup{<options>}`

Numbers and units are printed using `\cunum`. The numerical part can interpret `_` and `/` as (mixed) fractions and `--` as a separator for ranges; to convert units use the option `<old-unit>=<new-unit>`<sup>1</sup>. It furthermore allows the sign `?` to be used as a placeholder for not known amounts and raises a warning to remind you that this amount needs a check-up<sup>2</sup>. `[<space>]` adds a space between the number and the unit using `\phantom`.

For a list of predefined units have a look at table 1.

`<label>` is explained in section 3.

1 kg	<code>\cunum{1}{kg}\</code>
2.3 kg	<code>\cunum{2.3}{kg}\</code>
2.3 kg	<code>\cunum{2,3}{kg}\</code>
2–3 kg	<code>\cunum{2--3}{kg}\</code>
2.5–3.5 kg	<code>\cunum{2.5--3.5}{kg}\</code>
2500–3500 g	<code>\cunum[kg=g]{2.5--3,5}{kg}\</code>
392 °F	<code>\cunum[C=F]{200}{C}\</code>
356–392 °F	<code>\cunum[C=F]{180--200}{C}\</code>
$\frac{1}{2}$ m	<code>\cunum{1/2}{m}\</code>
$1\frac{1}{2}$ m	<code>\cunum{1_1/2}{m}\</code>
$1\frac{1}{2}$ m	<code>\cunum[m=cm]{1_1/2}{m}\</code>
? ℓ	<code>\cunum{?}{l}\</code>
50 dag	<code>\cunum{50}{dag}\</code>
5 dag	<code>\cunum{5}[0]{dag}\</code>
1.12 m	<code>\cunum{1.1234}{m}</code>

<sup>1</sup>New keys can be added and defined, see section 5 and section 6 for further information.

<sup>2</sup>You can customize this behavior, see section 9

Decimal numbers are automatically rounded to 2 digits after the colon, temperatures (C, F, K and Re) are automatically rounded to integers.<sup>3</sup>

`\cutext` and `\Cutext` print the number and the written name of the unit. Since v1.10 it works similar<sup>4</sup> to `\cunum`: it allows the conversion between units and interprets the numerical part (again `_` and `/` are used for (mixed) fractions and `--` for ranges). Furthermore, `\cutext` and `\Cutext` allow the usages of numerals (see section 9.1 for more information).

1 litre	<code>\cutext{1}{1}\</code>
1 litre	<code>\Cutext{1}{1}\</code>
1 to 2 litres	<code>\Cutext{1--2}{1}\</code>
12 litres	<code>\cutext{12}{1}\</code>
13 litres	<code>\Cutext{13}{1}</code>

and using (e.g.) package option `use-fmtcount-numerals=true`

one litre	<code>\cutext{1}{1}\</code>
One litre	<code>\Cutext{1}{1}\</code>
one to two litres	<code>\cutext{1--2}{1}\</code>
One to two litres	<code>\Cutext{1--2}{1}\</code>
twelve litres	<code>\cutext{12}{1}\</code>
13 litres	<code>\Cutext{13}{1}</code>

You can customize the numeral functions used with `numeral-function` and `Numeral-function`.

Furthermore, since v1.10 `\cutext` and `\Cutext` also allow their units to be changed (this behavior can be altered using `cutext-change-unit`):

	<code>\cusetup{1=ml}</code>
1000 millilitres	<code>\cutext{1}{1}\</code>
1000 millilitres	<code>\Cutext{1}{1}\</code>
1000 to 2000 millilitres	<code>\cutext{1--2}{1}\</code>
12000 millilitres	<code>\cutext{12}{1}\</code>
13000 millilitres	<code>\Cutext{13}{1}\</code>
? litres	<code>\Cutext{?}{1}\</code>
1/2 litre	<code>\Cutext{1/2}{1}\</code>

`\cuam` works like `\cunum`, but without a unit, so changing units doesn't affect it. Like `\cunum` `_` and `/` are used to imply a (mixed) fraction and `--` is used for ranges.

3	<code>\cuam{3}\</code>
2-3	<code>\cuam{2--3}\</code>
2/3	<code>\cuam{2/3}\</code>
1 2/3	<code>\cuam{1_2/3}</code>

Furthermore it allows the concept of “phrases” (replacing a positive integer by a word; such as “12” becoming “dozen”<sup>5</sup>) which can be activated by the option `use-phrases` (as I don't know any english phrases, I switched the language to german for the following examples)

<sup>3</sup>You can – of course – change this behavior, see section 9.

<sup>4</sup>One could also say “exactly like”.

<sup>5</sup>At least I think

	<code>\selectlanguage{ngerman}</code>
	<code>\cusetup{use-phrases=true}</code>
11	<code>\cuam{11}\</code>
1 Dutzend	<code>\cuam{12}\</code>
13	<code>\cuam{13}\</code>
2 Dutzend	<code>\cuam{24}\</code>
1–2 Dutzend	<code>\cuam{12--24}\</code>
12–13	<code>\cuam{12--13}\</code>
18	<code>\cuam{18}\</code>
5 Dutzend	<code>\cuam{60}</code>

### 3 Label & refs: Changing the amount of the recipe

What if you don't want to change units, but the amounts of the recipe because you cook not for 4 persons, but for 2 and don't like to do the math? Simple, use the following commands:

- `\culabel{<label>}{<number of persons>}`
- `\curef{<label>}`

The first one is the important one: It defines a `<label>` for a recipe which is initially for `<number of persons>`. Afterwards `<label>` can be used to tell the commands from section 2 that the given amounts are for `<number of persons>`. Each `<label>` must be unique and an error is raised if a `<label>` is already defined.

If you would like to print the number of persons this recipe is for, use `\curef`, which is fully expandable.

The following example uses `\culabel` to specify that the recipe is initially intended for 2 persons:

	<code>\culabel{recipe}{2}</code>
recipe for 2 persons:	recipe for <code>\curef{recipe}</code> persons:\
10–20 dag flour,	<code>\cunum&lt;recipe&gt;{10--20}{dag}</code> flour,\
½ ℓ water,	<code>\cunum&lt;recipe&gt;{1/2}{1}</code> water,\
10 gramme nuts,	<code>\cutext[ref=recipe]{10}{g}</code> nuts,\
2–3 eggs,	<code>\cuam&lt;recipe&gt;{2--3}</code> eggs,\
180 °C (356 °F) open fire	<code>\cunum{180}{C}</code> ( <code>\cunum[C=F]{180}{C}</code> ) open fire

In combination with the option `set-number-of-persons` and `recalculate-amount` you can have this recipe changed to four persons:

	<code>\culabel{recipe}{2}</code>
	<code>%% adding options:</code>
	<code>\cusetup{set-number-of-persons=4,recalculate-amount=true}</code>
recipe for 4 persons:	recipe for <code>\curef{recipe}</code> persons:\
20–40 dag flour,	<code>\cunum&lt;recipe&gt;{10--20}{dag}</code> flour,\
1 ℓ water,	<code>\cunum&lt;recipe&gt;{1/2}{1}</code> water,\
20 gramme nuts,	<code>\cutext[ref=recipe]{10}{g}</code> nuts,\
4–6 eggs,	<code>\cuam&lt;recipe&gt;{2--3}</code> eggs,\
180 °C (356 °F) open fire	<code>\cunum{180}{C}</code> ( <code>\cunum[C=F]{180}{C}</code> ) open fire

Note that fractions are automatically evaluated and that only values with a *label* are changed (`\cunum{180}{C}` for example stays the same which also makes sense as the heat should be the same).

## 4 Good to know stuff

### 4.1 Rounding temperatures

By default temperatures are rounded to integers (using `round-precision=0`). Since v1.30 it is possible to round amounts to a negative precision. If you want to round temperatures to the tens see the following example (`\cusetoptionfor` is described in section 9.2.1).

182 °C	<code>\cunum{182}{C}\</code>
356 °F	<code>\cunum[C=F]{180}{C}\</code>
144 °Ré	<code>\cunum[C=Re]{180}{C}\</code>
453 K	<code>\cunum[C=K]{180}{C}\</code>
	<code>\cusetoptionfor{C,F,K,Re}{round-precision=-1}</code>
180 °C	<code>\cunum{180}{C}\</code>
360 °F	<code>\cunum[C=F]{180}{C}\</code>
140 °Ré	<code>\cunum[C=Re]{180}{C}\</code>
450 K	<code>\cunum[C=K]{180}{C}\</code>

### 4.2 At which point is the plural used?

While using `\cutext` and `\Cutext` one may wonder which rules are used in order to determine if the printed unit is singular or plural. If rules for a specific language are not found the default ruleset is used. There are currently two rule sets: One default and one if you are using french.

Each set has three separate rules: one for “normal” numbers, one for ranges and one for fractions.

#### French

Use singular if:

**normal** The absolute value of the number is smaller 2

**fraction** The absolute value of the evaluated fraction is smaller 2. (e.g.  $1\frac{1}{2} = 1.5$  uses singular,  $2\frac{3}{4} = 2.75$  uses plural).

**range** The absolute value of the second number is smaller 2. (e.g. 1-2: Take 2.)

For sources see [7], [8] & [9]<sup>6</sup>.

---

<sup>6</sup>Thanks a lot to Alexis Jeandea! I never would have imagined that the french language uses the singular for everything smaller 2.

## Default (all other languages)

Use singular if:

**normal** The number is equal to 1.

**fraction** There is no mixed fraction part and the nominator is equal to 1.

**range** The second number is equal to 1. (e.g. 1-2: Take 2.)

## 5 Predefined units & some notes

In table 1 and you can find all predefined units which can be transformed into each other (sorted by group). Other predefined units (which cannot be used for transformations) are shown in table 2. Table 3 pretty much exists just for fun.

Table 1: This table shows all units which can be transformed into each other, sorted by group. The columns “default” show the abbreviations used if no translation is defined for the given language. The translations used for `\cutext` and `\Cutext` are shown in appendix A. Note that “electron volt” exists just for fun.

description	key	default	description	key	default
kilogramme	<b>kg</b>	kg	metre	<b>m</b>	m
decagramme	<b>dag</b>	dag	decimetre	<b>dm</b>	dm
gramme	<b>g</b>	g	centimetre	<b>cm</b>	cm
ounce	<b>oz</b>	oz	millimetre	<b>mm</b>	mm
pound	<b>lb</b>	lb	inch	<b>in</b>	in
stick (of butter)	<b>stick</b>	stick			
day	<b>d</b>	d	litre	<b>l</b>	l
hour	<b>h</b>	h	decilitre	<b>dl</b>	dl
minute	<b>min</b>	min	centilitre	<b>cl</b>	cl
second	<b>s</b>	s	millilitre	<b>ml</b>	ml
calorie	<b>cal</b>	cal	degree Celsius	<b>C</b>	°C
kilocalorie	<b>kcal</b>	kcal	degree Fahrenheit	<b>F</b>	°F
joule	<b>J</b>	J	degree Réaumur	<b>Re</b>	°Ré
kilojoule	<b>kJ</b>	kJ	kelvin	<b>K</b>	K
electron volt	<b>eV</b>	eV			

## 6 Defining units

New units can be defined using

- `\declarecookingunit` [*⟨symbol/key-val-list⟩*] {*⟨unit-key⟩*}
- `\newcookingunit` [*⟨symbol/key-val-list⟩*] {*⟨unit-key⟩*}
- `\providecookingunit` [*⟨symbol/key-val-list⟩*] {*⟨unit-key⟩*}

Table 2: A (not only) spoonful of (more or less) country and language dependent units. Please note that sometimes a translation is nearly impossible as a unit (e.g. “saltspoonful”) may not exist in another language (like german; at least I never heard of it). So please only use units known to you. For “tablespoon” and “teaspoon” I used the german abbreviations “EL” and “TL” (because I forgot to change them initially).

description	key	symbol
pinch	pn	pinch
tablespoon	EL	EL
teaspoon	TL	TL
dessertspoonful	dsp	dsp.
coffeespoonful	csp	csp.
saltspoonful	ssp	ssp.
Messerspitze (point of a knife)	Msp	Msp.

Table 3: List of (not really) nonsense units (exist just for fun, there will be no support for those units; unless – of course – you really want it).

unit-key	symbol
eVc-2	$eV/c^2$
hbareV-1	$\hbar/eV$
chbareV-1	$ch/eV$
(chbareV-1)3	$c^3\hbar^3/eV^3$

<u><code>\declarecookingunit</code></u>	<code>\declarecookingunit</code> [ <i>symbol/key-val-list</i> ] { <i>unit-key</i> }
<code>\newcookingunit</code>	<code>\newcookingunit</code> [ <i>symbol/key-val-list</i> ] { <i>unit-key</i> }
<u><code>\providecookingunit</code></u>	<code>\providecookingunit</code> [ <i>symbol/key-val-list</i> ] { <i>unit-key</i> }

These commands define the unit  $\langle unit-key \rangle$ . Note that  $\langle unit-key \rangle$  can neither contain / nor , ; but it is allowed to be a command since v2.00 (see examples below).

If the key is not the same as the printed symbol use the optional argument. It can either contain the symbol you want printed or a key-value list (see below) for more advanced adjustments.

`\newcookingunit` raises an error if the unit is already defined, `\declarecookingunit` creates or (if given) overwrites  $\langle symbol \rangle$  and `\providecookingunit` does nothing if the unit is already defined.

All units have male gender m by default (unless you change it using a key below).

Some examples:

```

\declarecookingunit{kg}
\declarecookingunit{g}
\declarecookingunit[Msp.] {Msp}
\declarecookingunit[\ensuremath{\{\}^{\{\circ\}}\kern-\scriptspace C}]{C}
\declarecookingunit{\%} % can use commands now

```

**Note:** The definition of the printed degree Celsius is copied and pasted from (a maybe



older version of) `siunitx`.

---

<code>symbol</code>	<code>symbol = {\langle symbol \rangle}</code>
<code>gender</code>	<code>gender = {\langle m/f/n \rangle}</code>
<code>set-option</code>	<code>set-option = {\langle key-val-list \rangle}</code>
<code>add-to-group</code>	<code>add-to-group = {\langle group \rangle}</code>
<code>natural-unit</code>	<code>natural-unit = {\langle true/false \rangle}</code>

---

Those keys can only be used in the optional argument of `\declarecookingunit`, `\newcookingunit` or `\providecookingunit`. They can be used to define some properties of the unit during its initialization.

`symbol` allows you to set the printed symbol of the unit. A similar effect can be achieved by just using the optional argument. Use this option if you want to use other keys during the definition. This symbol is used as a fallback for all languages, if no explicit symbol is found for said language.

`gender` sets the gender of the unit (default is `m`). Allowed is `m`, `f` or `n`. Note that this sets the default gender for all languages.

`set-option` allows to add some key-vals to the specific unit which are activated once the unit is used. See page 17.

`add-to-group` adds the unit defined to `\langle group \rangle`. See section 9.2.1 for more information.

`natural-unit` is a simple true/false switch. If `true` the unit will be specified to be a “natural-unit”. This is more or less a joke option.

---

## `\declarecookingderivatives`

---

`\declarecookingderivatives` `{\langle unit-list \rangle}` `{\langle unit-key \rangle}`  
`{\langle mathematical-relation \rangle}` `{\langle unit-symbol \rangle}`

*This function is experimental.* Defines new units which are a combination of the units given in `\langle unit-list \rangle` and their key-chain. `\langle unit-key \rangle`, `\langle mathematical-relation \rangle` and `\langle unit-symbol \rangle` accept `\#1` to `\#n` as arguments with `n` being the number of units given in `\langle unit-list \rangle`. `n` cannot be greater than 8 (and it will probably compile for quite a while). Also note that this command doesn’t work/isn’t tested for single keys.

Also note that it is quite possible that an “overflow-error” will occur if there are too many units.

**Example:** Your homework is to change the unit of energy  $\text{kg m}^2 \text{s}^{-2}$  into  $\text{oz in}^2 \text{min}^{-2}$ . To check if you are correct you use `\declarecookingderivatives`:

```
\declarecookingderivatives{kg,m,s}{\#1*\#2:\#3}
{ (\#1)*(\#2)^2/(\#3)^2 } {\sfrac{\#1\,#2$}{^2$}{\#3$}{^2$}}
```

Using `\cunum[kg*m:s=oz*in:min]{1}{kg*m:s}` shows that  $1 \text{ kg m}^2/\text{s}^2$  is equal to  $196829101.34 \text{ oz in}^2/\text{min}^2$ .

**Note:** As this is a bit more experimental and can easily lead to overflow-errors, no actual L<sup>A</sup>T<sub>E</sub>X keys are created with `\declarecookingderivatives`. Internally the keys and possible values are stored in a *huge* property list. If an unknown key is encountered, it checks if said key can be found in the property list.

## 7 Defining options to change units

Options (to change units) can be newly defined or added to already existing ones using

- `\cdefinekeychain`
- `\cdefinesinglekey`
- `\cuaddtokeychain`
- `\cuaddsinglekeys`

<code>\cdefinekeychain</code>	<code>\cdefinekeychain</code>
<code>\cdefinesinglekey</code>	<pre> {   {⟨unit-key-1⟩} {⟨value⟩}   {⟨unit-key-2⟩} {⟨... unit-key-2 are ⟨value⟩ unit-key-1⟩}   {⟨unit-key-3⟩} {⟨... unit-key-3 are ⟨value⟩ unit-key-1⟩}   ... } \cdefinesinglekey{⟨unit-key-1⟩} {   {⟨unit-key-2⟩} {⟨1 unit-key-2 are ... unit-key-1⟩}   {⟨unit-key-3⟩} {⟨1 unit-key-3 are ... unit-key-1⟩}   ... } </pre>

If you define new units (see section 6) and cannot add them to already existing keys you may use `\cdefinekeychain` or `\cdefinesinglekey` respectively to define new key-chains or single keys.

`\cdefinekeychain` collects the unit-key's given and defines a key-chain. This allows you to change every unit into every other unit given in the list. So  $\langle unit-key-1 \rangle$  can take  $\langle unit-key-1 \rangle$ ,  $\langle unit-key-2 \rangle$ ,  $\langle unit-key-3 \rangle$ , ... as values;  $\langle unit-key-2 \rangle$  can take  $\langle unit-key-1 \rangle$ ,  $\langle unit-key-2 \rangle$ ,  $\langle unit-key-3 \rangle$ , ... as values, etc. Please note that  $\langle \dots \rangle$  has to be a number.

Sometimes it is not that easy and the conversion of one unit into another needs are more complicated formula (see for example temperatures). If that is the case use `\cdefinesinglekey`. As the name says it defines *only* a single key  $\langle unit-key-1 \rangle$  with the values  $\langle unit-key-1 \rangle$ ,  $\langle unit-key-2 \rangle$ , etc. The advantage of this command is that now  $\langle \dots \rangle$  can be a formula and the numerical input of `\cunum`, etc. can be placed explicitly using #1.

**Example:** This example defines following keys with their respective value:

- the key `kg` with the values `kg`, `dag`, `g` and `oz`
- the key `dag` with the values `kg`, `dag`, `g` and `oz`
- the key `g` with the values `kg`, `dag`, `g` and `oz`
- the key `oz` with the values `kg`, `dag`, `g` and `oz`
- ...

1 kg = 1 kg	1 kg = 100 dag	1 kg = 1000 g
1 kg = 35.273 99 oz	1 kg = 2.204 622 6 lb	

```
\cdefinekeychain
{
  {kg} { 1 }
  {dag}{ 100 } %% 1 kg are 100 dag
  {g} { 1000 } %% 1 kg are 1000 g
  {oz} { 35.27399 } %% 1 kg are 35.27399 oz
  {lb} { 2.204 622 6 } %% 1 kg are 2.204 622 6 lb
}
```

```
\cdefinekeychain
{
  {d} { 1 }
  {h} { 24 } %% 1 day are 24 hours
  {min}{ 1440 } %% 1 day are 1440 minutes
  {s} { 86400 } %% 1 day are 86400 seconds
}
```

**Note:** The value of the first item can be something different from 1. So something like this is also possible:

```
\cdefinekeychain
{
  {kg} { 0.4535924 }
  {dag}{ 45.35924 }
  {g} { 453,5924 }
  {oz} { 16 }
  {lb} { 1 }
}
```

**Example:** To convert degree Fahrenheit to degree Celsius, kelvin and degree Réamur one needs the formulas<sup>7</sup>

$$T_C = (T_F - 32) \cdot \frac{5}{9}$$

$$T_K = (T_F - 459.67) \cdot \frac{5}{9}$$

$$T_{Re} = (T_F - 32) \cdot \frac{4}{9}$$

with  $T_F$  being the input temperature in degree Fahrenheit and  $T_C$  being the same temperature in degree Celsius, etc. Using `\cdefinesinglekey` the key F with values C, K and Re is defined by:

```
\cdefinesinglekey {F}
{
  {C} { ( #1 - 32 ) * 5/9 } %% see formulas above
  {K} { ( #1 + 459.67 ) * 5/9 }
  {Re} { ( #1 - 32 ) * 4/9 }
}
```

---

<sup>7</sup>See Wikipedia.

This defines the key F with the values F, C, K and Re.

```

\cuaddtokeychain
\cuaddsinglekeys
\cuaddtokeychain
{
  {\langle unit-key-1 \rangle} {\langle value \rangle}
  {\langle unit-key-2 \rangle} {\langle \dots unit-key-2 are \langle value \rangle unit-key-1 \rangle}
  {\langle unit-key-3 \rangle} {\langle \dots unit-key-3 are \langle value \rangle unit-key-1 \rangle}
  \dots
}
\cuaddsinglekeys{\langle unit-key-1 \rangle}
{
  {\langle unit-key-2 \rangle} {\langle 1 unit-key-2 are \dots unit-key-1 \rangle}
  {\langle unit-key-3 \rangle} {\langle 1 unit-key-3 are \dots unit-key-1 \rangle}
  \dots
}

```

`\cuaddtokeychain` first parses through its unit-list and searches for a base unit key which is already in a key-chain (aka. was defined by `\cudefinekeychain`). The other units, not yet part of a key-chain, are added to the same key-chain as the base unit. So the newly added units are available as a key and a value for the other units in the same key-chain. Note that  $\langle \dots \rangle$  must be a number.

If the conversion is more complicated use `\cuaddsinglekeys`. It adds  $\langle unit-key-2 \rangle$ , etc. as values to  $\langle unit-key-1 \rangle$ . The numerical input can be placed using `#1` (see `\cudefinesinglekey`). This command neither defines new keys nor does it add values to keys other than  $\langle unit-key-1 \rangle$ .

**Example:** Suppose you are British (I am sorry, I can't think of another reason to use those units) and you want to implement 'stone' (yes, I was surprised myself that such a unit exists, but it even appears in a Sherlock Holmes story). You exactly know that 1st equals 14lb, well ... now you have two choices. `\cuaddkeys` or `\cuaddtokeys` (use the one best fitting). This example uses the first, the next the latter one.

```

\newcookingunit{st} %% defining new unit 'stone'
\cuaddtokeychain
{
  {1b} { 14 } %% unit already in a key-chain.
  {st} { 1 } %% new unit. 1st = 14lb
}

0.07st \cunum[1b=st]{1}{1b}\
14lb \cunum[st=1b]{1}{st}\
6350.29g \cunum[st=g]{1}{st}\
6.35kg \cunum[st=kg]{1}{st}\
0.16st \cunum[kg=st]{1}{kg}\
101.6kg \cunum[st=kg]{16}{st}

```

**Note:** Of course using

```

\cuaddtokeychain
{
  {st} { 1/14 } %% 1lb = 1/14st
  {1b} { 1 } %% unit already in a key-chain.
}

```

is also possible

**Example:** Now you want to add degree Rømer and convert Celsius to degree Rømer:

$$T_{R\o} = T_C * \frac{21}{40} + 7.5$$

```

%% defining new unit 'degree R{\o}mer'
\newcookingunit [\ensuremath{ {} ^ { \circ } } \kern-\scriptspace R{\o}] {Ro}
\cuaddsinglekeys {C} %% adds value 'Ro' to key 'C'.
{
  {Ro} { #1 * 21/40 + 7.5 }
}
\cusetoptionfor{Ro}{ round-precision = 0 } %% round to integer automatically

10°C \cunum{10}{C}\
13°Rø \cunum[C=Ro]{10}{C}

```

## 7.1 Obsolete Commands

---

`cdefinekeys`

```

\cdefinekeys{⟨unit-key-1⟩}
{
  {⟨unit-key-2⟩} {⟨1 unit-key-1 are ... unit-key-2⟩}
  {⟨unit-key-3⟩} {⟨1 unit-key-1 are ... unit-key-3⟩}
  {⟨unit-key-4⟩} {⟨1 unit-key-1 are ... unit-key-4⟩}
  ...
}

```

*This command is going to be obsolete at one point. It is advised to use `\cdefinekeychain` instead.*

`\cdefinekeys` takes  $\langle unit-key-1 \rangle$  as a “basis”, defines a key with the name  $\langle unit-key-1 \rangle$  and adds the values  $\langle unit-key-1 \rangle$ ,  $\langle unit-key-2 \rangle$ ,  $\langle unit-key-3 \rangle$ , etc. Furthermore this command also defines the keys  $\langle unit-key-2 \rangle$ ,  $\langle unit-key-3 \rangle$ , etc. with the same values as  $\langle unit-key-1 \rangle$ . Please note that  $\langle \dots \rangle$  has to be a number.

---

`\cuaddkeys`  
`\cuaddtokeys`

```

\cuaddkeys{⟨unit-key-1⟩}
{
  {⟨unit-key-2⟩} {⟨1 unit-key-1 are ... unit-key-2⟩}
  {⟨unit-key-3⟩} {⟨1 unit-key-1 are ... unit-key-3⟩}
  {⟨unit-key-4⟩} {⟨1 unit-key-1 are ... unit-key-4⟩}
  ...
}
\cuaddtokeys {⟨unit-key-1⟩} {⟨unit-key-2⟩} {⟨1 unit-key-2 are ... unit-key-1⟩}

```

*Those commands are going to be obsolete at one point. It is advised to use `\cuaddtokeychain` instead.*

`\cuaddkeys` takes the already defined key  $\langle unit-key-1 \rangle$  as a “basis”, and adds  $\langle unit-key-2 \rangle$ ,  $\langle unit-key-3 \rangle$ , etc. to its values. Furthermore it adds those new values to other keys linked to  $\langle unit-key-1 \rangle$  and defines the new keys  $\langle unit-key-2 \rangle$ , etc. with the same values as  $\langle unit-key-1 \rangle$ .

Works similar to `\cuaddkeys` regarding the definition of keys.

## 8 Language support

Unit names and symbols depend on the language. To change the name and symbol for given language you can use `\cudefinename`; to only change symbols use `\cudefinesymbol`.

---

```
decimal-mark
cutext-range-sign
one(m)
one(f)
one(n)
```

---

Those are special keys (as they cannot be used as units). Not only are printed units language depending, but as is the decimal mark ( . or , ) and the text which substitutes the range-sign. To set the decimal mark use `decimal-mark` (see examples below), to set the range-sign for `\cutext` and `\Cutext` use `cutext-range-sign`.

Note that `cutext-range-sign` is “overwritten” by the *option* `cutext-range-sign`. If the *option* is set, then the language symbol will be ignored.

Furthermore if you are using numerals you may also use the keys `one(m)`, `one(f)` and `one(n)`. Integers below a certain value (see option `use-numerals-below`) are written-out. The problem is that the written-out “1” depends on the gender of the word following (e.g. “ein Baum” (m), “eine Pflanze” (f) and “ein Auto” (n)). Use those keys to set the specific gender of “1” (see also examples below).

---

```
\cudefinename
```

---

```
\cudefinename{<Language>}
{
  {<unit-key-1>} [<symbol-1>] {<singular-1>} [<plural-1>] <<gender>>
  {<unit-key-2>} [<symbol-2>] {<singular-2>} [<plural-2>] <<gender>>
  ...
}
```

This command defines the names (and optionally the symbol) of the units printed in `\cutext` and `\Cutext` (and `\cunum` regarding the symbol) for the specific `<Language>`. For details regarding `<language>` see the translations documentation.

If the plural form of the name differs from the singular form use `[<plural>]` to specify the plural form, else it will be equal to its singular form. The singular form is only used if the number in `\cutext` and `\Cutext` is equal to 1.

`<gender>` can be `m` (maskulin), `f` (feminin) or `n` (neutrum). If not given, `m` is used as default.

```
\cudefinename {English}
{
  {kg} {kilogramme}
  {oz} {ounce}
  {h} {hour} [hours]
  {C} {degree\space Celsius} [degrees\space Celsius]
  {decimal-marker} {.}
  {cutext-range-sign} {~to~}
  {one(m)} {one}
  {one(f)} {one}
  {one(n)} {one}
}

\cudefinename {German}
{
  {kg} {Kilogramm} <n>
```

```

{oz} {Unze} <f>
{d} {Tag} [Tage]
{h} {Stunde} [Stunden] <f>
{C} {Grad\space Celsius}
{decimal-marker} {,}
{cutext-range-sign} {~bis~}
{one(m)} {ein}
{one(f)} {eine}
{one(n)} {ein}
}

```

---

```

\cundefinesymbol \cundefinesymbol{<Language>}
{
  {<unit-key-1>} {<symbol-1>}
  {<unit-key-2>} {<symbol-2>}
  ...
}

```

This command defines the symbols of the units printed in `\cunum` for the specific *<Language>*. It works similar as `\cundefinename`, but only the symbols (and no names) can be set. For details regarding *<Language>* see the `translations` documentation.

```

\cundefinesymbol {English}
{
  {decimal-mark} {\.}
  {cutext-range-sign} {~to~}
  {one(m)} {one}
  {one(f)} {one}
  {one(n)} {one}
}
\cundefinesymbol {German}
{
  {decimal-mark} {,}
  {cutext-range-sign} {~bis~}
  {one(m)} {ein}
  {one(f)} {eine}
  {one(n)} {ein}
}
\cundefinesymbol {French}
{
  {l} {L}
  {dl} {dL}
  {cl} {cL}
  {ml} {mL}
  {cutext-range-sign} {~\{a}~}
  {decimal-mark} {,}
  {one(m)} {un}
  {one(f)} {une}
  {one(n)} {un}
}

```

**Example:** Imagine that instead of the abbreviation “dag” for “decagramme” you want to use “ducks” (because ... I don’t know). You can easily do this via

```
\cudesymbolsymbol {English}
{
  {dag} {ducks}
}
```

As you can see it may be a bit suboptimal as there is no plural version allowed. You do it anyway and end up with:

12 ducks weed	<code>\cunum{12}{dag} weed\\</code>
3 ducks nuts	<code>\cunum{3}[0]{dag} nuts\\</code>
10 ducks duckmeat	<code>\cunum{10}{dag} duckmeat</code>

## 8.1 Phrases

Each language has synonyms for certain (integer) numbers. This package supports those phrases and they can be implemented with the following command to be used by `\cuam`:

---

```
\cudfinephrase {<Language>}
{
  {<integer-1>} {<phrase-1>} [<phrase-1-plural>] <<gender-1>>
  {<integer-2>} * {<phrase-2>} [<phrase-2-plural>] <<gender-2>>
  ...
}
```

This command pairs for a given `{<Language>}` (see package translations) the number `{<integer-1>}` with `{<phrase-1>}` (& `<phrase-1-plural>` and `<gender-1>`). Afterwards the package can check if an amount given in `\cuam` is either this number or a *multiple* of it.

If the behavior of checking for a multiple is not wanted, you can use the optional star `*`.

`<gender>` can be `m`, `f` or `n`. It is `m` by default.

Afterwards the numbers are ordered from highest to lowest so that the phrase with the highest number is used (if used at all).

Furthermore, it chooses star (`*`) phrases over non-star phrases.

**Example:** The following example creates some phrases for the language “German”:

```
\cudfinephrase {German}
{
  { 12 } {Dutzend} <n> %% implemented by default
  { 60 } {Schock} <n>
  { 6 } * {halbes\ Dutzend} <n>
}
```

Let’s just use them (german language activated!):



	<code>\selectlanguage{ngerman}</code>
	<code>\cusetup{use-phrases=true}</code>
1 Dutzend	<code>\cuam{12}\</code>
2 Dutzend	<code>\cuam{24}\</code>
25	<code>\cuam{25}\</code>
1 Schock	<code>\cuam{60}\</code>
2 Schock	<code>\cuam{120}\</code>
121	<code>\cuam{121}\</code>
1 halbes Dutzend	<code>\cuam{6}\</code>
18	<code>\cuam{18}</code>

As you can see, “Schock” (60) is preferred over “Dutzend” (12) as it linked to the higher number. Furthermore, for 6 the phrase “halbes Dutzend” (half a dozen) is used, but because it is a star version it is *not* used for 18.

## 9 Options

Options in cooking-units can mostly be set globally using `\cusetup` or locally using the optional argument of the respective command (but *not* as a package option). The only exception is the option given in section 9.1 which needs to be used as a package option.

---

`\cusetup`    `\cusetup{<options>}`

Options can be set using `\cusetup{<options>}`.

---

<code>\cusetoptionfor</code>	<code>\cusetoptionfor{&lt;unit-list&gt;}{&lt;options&gt;}</code>
<code>\cuaddoptionfor</code>	<code>\cuaddoptionfor{&lt;unit-list&gt;}{&lt;options&gt;}</code>
<code>\cuclearoptionfor</code>	<code>\cuclearoptionfor{&lt;unit-list&gt;}</code>

---

cooking-units allows you to attach options to units. Those options are activated if (and only if) the specific unit is used *or* if another unit is converted into it. Those options allow you to e.g. round temperatures to integers automatically. Furthermore, those added options are overwritten by local options.

`\cusetoptionfor` sets *<options>* to each unit in *<unit-list>* overwriting the old ones.

`\cuaddoptionfor` adds *<options>* to each unit in *<unit-list>*.

`\cuclearoptionfor` clears all options given to each unit in *<unit-list>*.

**Example:** Temperatures C, F, K and Re are by default rounded to integers.

75 °C	<code>\cunum{75.23}{C}\</code>
75 °F	<code>\cunum{75.23}{F}\</code>
75 K	<code>\cunum{75.23}{K}\</code>
75 °Ré	<code>\cunum{75.23}{Re}\</code>
	<code>\cusetoptionfor{C,F,K,Re}{round-precision=-1}</code>
80 °C	<code>\cunum{75.23}{C}\</code>
80 °F	<code>\cunum{75.23}{F}\</code>
80 K	<code>\cunum{75.23}{K}\</code>
80 °Ré	<code>\cunum{75.23}{Re}\</code>
	<code>\cuclearoptionfor{C,F,K,Re}</code>
75.23 °C	<code>\cunum{75.23}{C}\</code>
75.23 °F	<code>\cunum{75.23}{F}\</code>
75.23 K	<code>\cunum{75.23}{K}\</code>
75.23 °Ré	<code>\cunum{75.23}{Re}</code>

## 9.1 Load time options

---

`use-fmtcount-numerals` `\usepackage[use-fmtcount-numerals=<true/false>]{cooking-units}`

If set to `true` loads package `fmtcount` and uses `\numberstringnum` for `\cutext` and `\Numberstringnum` for `\Cutext` to write-out numbers below `use-numerals-below` (13 by default), integers above are printed as numbers. You can decide to not print any numerals by setting `print-numerals` to `false`.

Note: You don't need to use this function to use numerals. Using `print-numerals` and setting `numeral-function` and `Numeral-function` also works.

one kilogramme	<code>\cutext{1}{kg}\</code>
One kilogramme	<code>\Cutext{1}{kg}\</code>
two kilogramme	<code>\cutext{2}{kg}\</code>
Two kilogramme	<code>\Cutext{2}{kg}\</code>
twelve kilogramme	<code>\cutext{12}{kg}\</code>
Twelve kilogramme	<code>\Cutext{12}{kg}\</code>
13 kilogramme	<code>\cutext{13}{kg}\</code>
13 kilogramme	<code>\cutext{13}{kg}\</code>
14 kilogramme	<code>\Cutext{14}{kg}</code>

**Note:** `use-fmtcount-numerals` is a package option as it needs to load `fmtcount` which is not loaded by default.

**Note:** Please note the keys `one(m)`, `one(f)` and `one(n)` to change the printed “one” (as “one” is in many languages dependent on the gender of the following word. E.g in German: Masculine: ein Baum, Feminin: eine Pflanze, Neutrum: ein Auto).

**Note:** You can always change the functions used to print numerals with `numeral-function` and `Numeral-function`.

## 9.2 Normal options

Options in this subsection can only be set as local options or using `\cusetup`, but *not* as load time options.

### 9.2.1 Unit Specific options

---

`<unit>` `<unit-key-1> = <unit-key-2>`

Change `<unit-key-1>` to `<unit-key-2>` (see section 7 to define new options).

---

`<group>` `<group>` = `<unit-key>`

Changes each unit contained in `<group>` to `<unit-key>` (`<unit-key>` must be part of `<group>`).

---

<code>&lt;group&gt;</code>	default <code>&lt;unit-key&gt;</code> s
weight	kg, dag, g, oz, lb, stick
length	m, dm, cm, mm, in
volume	l, dl, cl, ml
temperature	C, F, K, Re
energy	cal, kcal, J, kJ, eV
time	d, h, min, s

---

```
1000 g          \cusetup{weight=g}
                \cunum{1}{kg}\\
10 g            \cunum{1}{dag}\\
1 g             \cunum{1}{g}\\
28.35 g         \cunum{1}{oz}\\
453.59 g        \cunum{1}{lb}\\
113.4 g         \cunum{1}{stick}\\
```

You can define new groups using `\cudeclareunitgroup`:

---

`\cudeclareunitgroup` `\cudeclareunitgroup` `{<group-name>}` `{<unit-list>}`

Defines the group `<group-name>` containing the list `<unit-list>`. This allows the usage of `<group-name>=<unit-key>` to change all units in the group `<group-name>` to `<unit-key>` (which has to be part of `<unit-list>`).

**Example:** Define the group “weight”:

```
\cudeclareunitgroup {weight} { kg , dag, g, oz, lb, stick }
```

Now `\cusetup{weight=dag}` can be used to change all units contained in `weight` to `dag`.

---

`\cuaddtounitgroup` `\cuaddtounitgroup``{<group>}``{<unit-list>}`

Adds `<unit-list>` to an already existing `<group>` (both need to exist).

**Example:** Adding `st` to the group `weight`

```
1000 g          \cuaddtounitgroup{weight}{st}
                \cusetup{weight=g}
                \cunum{1}{kg}\\
10 g            \cunum{1}{dag}\\
1 g             \cunum{1}{g}\\
28.35 g         \cunum{1}{oz}\\
453.59 g        \cunum{1}{lb}\\
113.4 g         \cunum{1}{stick}\\
6350.29 g       \cunum{1}{st}
```

---

---

`add-unit-to-group`

```
add-unit-to-group =
{
  <group1> = {<unit-key-list>},
  <group2> = {<unit-key-list>},
  ...
}
```

*This option is going to be obsolete at one point.* Adds each `<unit-key>` in `<unit-keys-list>` to `<group>`. The key-val equivalent of `\cuaddtounitgroup`.

---

---

`set-option-for-<unit-key>`  
`add-option-for-<unit-key>`

```
set-option-for-<unit-key> = {< key1 = value1, ... >}
add-option-for-<unit-key> = {< key1 = value1, ... >}
```

*This option is going to be obsolete at one point.* Sets and adds `<key1=value1,...>` to a specific `<unit-key>`, `erase-all-options` (see below) is used to erase all options for all `<unit-key>`s.

The less flexible key-value version of `\cusetoptionfor` and `\cuaddoptionfor`.

---

---

`set-option-for`  
`add-option-for`

```
set-option-for =
{
  <unit-key1> = {<keys=vals>},
  <unit-key2> = {<keys=vals>},
  ...
}
add-option-for =
{
  <unit-key1> = {<keys=vals>},
  <unit-key2> = {<keys=vals>},
  ...
}
```

*This option is going to be obsolete at one point.* Sets/adds each `<keys=vals>` to the specific `<unit-key>`. Works pretty much the same way their `set-option-for-<unit-key>` and `add-option-for-<unit-key>` counterparts.

The less flexible versions of the commands `\cusetoptionfor` and `\cuaddoptionfor`.

---

---

`erase-all-options`  
`erase-all-options-for`

```
erase-all-options
erase-all-options-for = {<unit-key1, unit-key2, ...>}
```

*This option is going to be obsolete at one point.* Erase options added to units. `erase-all-options` erases all options for *all* `<unit-key>`s.

`erase-all-options-for` is used to remove added options from the specified `<unit-key>`s (key-value version of `\cuclearoptionfor`).

## 9.2.2 Command behavior

---

---

`cutext-to-cunum`

```
cutext-to-cunum = <true/false>
```

Want to get rid of all `\cutext` and `\Cutext`? Set this option to `true` and all `\cutext` and `\Cutext` are changed into `\cunum`.

1 kilogramme	<code>\cutext{1}{kg}\</code>
2 kilogramme	<code>\Cutext{2}{kg}\</code>
½ kilogramme	<code>\cutext{1/2}{kg}\</code>
? kilogramme	<code>\cutext{?}{kg}\</code>
1000 to 2000 gramme	<code>\cutext[kg=g]{1--2}{kg}\</code>
	<code>\cusetup{cutext-to-cunum=true}</code>
1 kg	<code>\cutext{1}{kg}\</code>
2 kg	<code>\Cutext{2}{kg}\</code>
½ kg	<code>\cutext{1/2}{kg}\</code>
? kg	<code>\cutext{?}{kg}\</code>
1000-2000 g	<code>\cutext[kg=g]{1--2}{kg}</code>

---

`cutext-change-unit`    `cutext-change-unit = <true/false>`

Set this option to `false` if you do *not* want the units of `\cutext` and `\Cutext` to be changed. Set to `true` by default

1000 gramme	<code>\cutext[kg=g]{1}{kg}\</code>
½ kilogramme	<code>\cutext[kg=g]{1/2}{kg}\</code>
1000 to 2000 gramme	<code>\cutext[kg=g]{1--2}{kg}\</code>
	<code>\cusetup{cutext-change-unit=false}</code>
1 kilogramme	<code>\cutext[kg=g]{1}{kg}\</code>
½ kilogramme	<code>\cutext[kg=g]{1/2}{kg}\</code>
1 to 2 kilogramme	<code>\cutext[kg=g]{1--2}{kg}</code>

---

`cuam-version`    `cuam-version = <old/new>`  
`cutext-version`    `cutext-version = <old/new>`

Since v1.10 this package also parses and checks the input of `\cutext` and `\Cutext` and `\cuam`. If you want to restore the old behavior, set this option to `old`, but note that then you can neither change the amounts for a given number of persons nor change the unit of `\cutext` and `\Cutext`. Both of them are set to `new` by default.

### 9.2.3 Hooks

---

<code>commands-add-hook</code>	<code>commands-add-hook = {&lt;code&gt;}</code>
<code>cunum-add-hook</code>	<code>cunum-add-hook = {&lt;code&gt;}</code>
<code>cutext-add-hook</code>	<code>cutext-add-hook = {&lt;code&gt;}</code>
<code>Cutext-add-hook</code>	<code>Cutext-add-hook = {&lt;code&gt;}</code>
<code>cuam-add-hook</code>	<code>cuam-add-hook = {&lt;code&gt;}</code>

Adds `<code>` to the respective command (or in case of the first key: to *all* commands). The hook is executed *after* setting the keys, but *before* parsing and processing the input. Please be careful with spaces, they will be printed.

**Example:** You would like to count how often all commands of this package are used. Simply add:

```
\newcounter{CookingUnitsCounter} %% or however you like it
\cusetup{commands-add-hook={\stepcounter{CookingUnitsCounter}}}
%% beware of spaces inside the add-hook keys.
```

to your preamble. The following table lists how often each command is used in this documentation (with help of `totalcount`):

command	times
<code>\cunum</code>	206
<code>\cutext</code>	62
<code>\Cutext</code>	27
<code>\cuam</code>	63
total	358

## 9.2.4 Input and Outputs

<code>expand-both</code>	<code>expand-both = &lt;n/o/f/x&gt;</code>
<code>expand-amount</code>	<code>expand-amount = &lt;n/o/f/x&gt;</code>
<code>expand-unit</code>	<code>expand-unit = &lt;n/o/f/x&gt;</code>

By default the commands `\cunum`, `\cutext` and `\Cutext` and `\cuam` do *not* expand their input. You can change the expansion behavior of `<amount>` and/or `<unit-key>` using the options specified above. The meaning of the available values are the same as specified in the L<sup>A</sup>T<sub>E</sub>X3 document “interface3”.

It is set to `n` (no expansion) by default.

<code>set-special-sign</code>	<code>set-special-sign = {&lt;character(s)&gt;}</code>
<code>add-special-sign</code>	<code>add-special-sign = {&lt;character(s)&gt;}</code>

Allows `<character(s)>` to be used in the first mandatory argument of `\cunum`, `\cuam`, `\cutext` and `\Cutext` without raising an error (you can customize this behavior, see `set-unknown-message`). By default it is set to `?`. Please note that the sign `<` is not allowed as a special sign.

<code>? kg</code>	<code>\cunum{?}{kg}\</code>
<code>10?–20? kg</code>	<code>\cunum[g=kg]{10?--20?}{kg}\</code>
	<code>\cusetup{add-special-sign={xX}}</code>
<code>x kg</code>	<code>\cunum{x}{kg}\</code>
<code>X–? kg</code>	<code>\cunum{X--?}{kg}\</code>
	<code>\cusetup{set-special-sign={}}</code>
<code>1 kg</code>	<code>\cunum{1}{kg}\</code>
<code>1–2 kg</code>	<code>\cunum{1--2}{kg}</code>

<code>set-unknown-message</code>	<code>set-unknown-message = &lt;error/warning/none&gt;</code>
----------------------------------	---

Using a special sign (`?` by default) causes a warning to be raised. Set this option to **error** if you want an error (as an extra emphasis), **warning** if you want a warning (default) and **none** if you don't want to know anything about it.

<code>set-cutext-translation-message</code>	<code>set-cutext-translation-message = &lt;error/warning/none&gt;</code>
---	--

If a translation for `\cutext` and `\Cutext` is not available for the language, the commands are replaced by `\cunum`. Currently – if this is happening – a warning is shown, you may change the behavior of the message (error, warning or not showing at all) using this option.

---

**print-numerals**

`print-numerals = <true/false>`

Prints numerals for integers smaller than `use-numerals-below` if set to `true`. If set to `false` no numerals are printed.

If you use the package option `use-fmtcount-numerals` this option is automatically set to `true`.

If you want to use another package, just set this option to `true` and use `numeral-function` and `Numeral-function`).

**Example:** (Using the package option `use-fmtcount-numerals`:

```
one kilogramme      \cutext{1}{kg}\\
two kilogramme      \cutext{2}{kg}\\
twelve kilogramme   \cutext{12}{kg}\\
13 kilogramme       \cutext{13}{kg}\\
                    \cusetup{print-numerals=false}
1 kilogramme        \cutext{1}{kg}\\
2 kilogramme        \cutext{2}{kg}\\
12 kilogramme       \cutext{12}{kg}\\
13 kilogramme       \cutext{13}{kg}
```

---

**use-numerals-below**

`use-numerals-below = <integer>`

If `print-numerals` is `true`, prints the numerals in `\cutext` and `\Cutext` for integers smaller than `<integer>`. `<integer>` is by default 13. You can deactivate the printing of numerals by `print-numerals=false`.

```
one kilogramme      \cutext{1}{kg}\\
two kilogramme      \cutext{2}{kg}\\
twelve kilogramme   \cutext{12}{kg}\\
13 kilogramme       \cutext{13}{kg}\\
                    \cusetup{use-numerals-below=10}
one kilogramme      \cutext{1}{kg}\\
two kilogramme      \cutext{2}{kg}\\
12 kilogramme       \cutext{12}{kg}\\
13 kilogramme       \cutext{13}{kg}\\
                    \cusetup{use-numerals-below=0}
1 kilogramme        \cutext{1}{kg}\\
2 kilogramme        \cutext{2}{kg}\\
12 kilogramme       \cutext{12}{kg}\\
13 kilogramme       \cutext{13}{kg}\\
                    \cusetup{use-numerals-below=12001}
one thousand gramme \cutext[kg=g]{1}{kg}\\
two thousand gramme \cutext[kg=g]{2}{kg}\\
twelve thousand gramme \cutext[kg=g]{12}{kg}\\
13000 gramme        \cutext[kg=g]{13}{kg}
```

---

<code>numeral-function</code>	<code>numeral-function = &lt;function&gt;</code>
<code>Numeral-function</code>	<code>Numeral-function = &lt;function&gt;</code>

---

Sets the functions used for printing numerals. `numeral-function` is used for lowercase, `Numeral-function` for capitalized cases.

**Example:** Using the commands from `fmtcount` you can set the numeral function equal to

```
\cusetup{
  numeral-function = \numberstringnum ,
  Numeral-function = \Numberstringnum
}
```

(this happens if you use the package option `use-fmtcount-numerals`)

---

<code>parse-number</code>	<code>parse-number = &lt;true/false&gt;</code>
---------------------------	--

---

If set to `false` prints the number of `\cunum`, `\cutext`, `\Cutext` and `\cuam` as they are (after some ... well ... parsing due to “\_”). Is set to `true` by default.

	<code>\cusetup{parse-number=false}</code>
1 kg	<code>\cunum[kg=g]{1}{kg}\</code>
1-2 kg	<code>\cunum{1--2}{kg}\</code>
1-----2 kg	<code>\cunum{1-----2}{kg}\</code>
1.2 kg	<code>\cunum{1.2}{kg}\</code>
1,2 kg	<code>\cunum[kg=g]{1,2}{kg}\</code>
1/2 kg	<code>\cunum{1/2}{kg}\</code>
1_2/3 kg	<code>\cunum{1_2/3}{kg}\</code>
1/2_3 kg	<code>\cunum{1/2_3}{kg}\</code>
someweirdstuff kg	<code>\cunum{someweirdstuff}{kg}\</code>
1 kg	<code>\cutext{1}{kg}\</code>
100 kg	<code>\cutext{100}{kg}\</code>
gjfak kg	<code>\cutext{gjfak}{kg}\</code>
12 kg	<code>\cutext[kg=g]{12}{kg}\</code>
1-----2	<code>\cuam{1-----2}\</code>
1,2	<code>\cuam{1,2}\</code>
1_1/2	<code>\cuam{1_1/2}\</code>
kwflk	<code>\cuam{kwflk}\</code>

---

<code>range-sign</code>	<code>range-sign = {&lt;string&gt;}</code>
<code>cunum-range-sign</code>	<code>cunum-range-sign = {&lt;string&gt;}</code>
<code>cutext-range-sign</code>	<code>cutext-range-sign = {&lt;string&gt;}</code>

---

`cunum-range-sign` sets the *printed* range sign used in `\cunum` (and `\cuam`) to `<string>`, `cutext-range-sign` sets the printed range sign used in `\cutext` and `\Cutext` to `<string>`. Using `range-sign` sets the range signs for both `\cunum` (and `\cuam`) and `\cutext`/`\Cutext` to `<string>`.

The default for `<string>` is `--` (for both).

Since version 1.45 there also exists the language symbol `cutext-range-sign` (see section 8). If the *option* `cutext-range-sign` is set the language symbol will be ignored.



1–2 kg	<code>\cunum{1--2}{kg}\</code>
1–2	<code>\cuam{1--2}\</code>
1 to 2 kilogramme	<code>\cutext{1--2}{kg}\</code>
1 to 2 kilogramme	<code>\Cutext{1--2}{kg}</code>
	<code>\cusetup{cunum-range-sign={~to~}}</code>
1 to 2 kg	<code>\cunum{1--2}{kg}\</code>
1 to 2	<code>\cuam{1--2}\</code>
1 to 2 kilogramme	<code>\cutext{1--2}{kg}\</code>
1 to 2 kilogramme	<code>\Cutext{1--2}{kg}</code>
	<code>\cusetup{cutext-range-sign={--}}</code>
1–2 kg	<code>\cunum{1--2}{kg}\</code>
1–2	<code>\cuam{1--2}\</code>
1–2 kilogramme	<code>\cutext{1--2}{kg}\</code>
1–2 kilogramme	<code>\Cutext{1--2}{kg}</code>
	<code>\cusetup{range-sign={-to-}}</code>
1-to-2 kg	<code>\cunum{1--2}{kg}\</code>
1-to-2	<code>\cuam{1--2}\</code>
1-to-2 kilogramme	<code>\cutext{1--2}{kg}\</code>
1-to-2 kilogramme	<code>\Cutext{1--2}{kg}</code>

---

**use-phrases**    `use-phrases = <true/false>`

Setting this option to **true** replaces certain integers (see section 8.1 for more information) with their phrase counterpart. This option is set to **false** by default.

**Example:** For the German language:

	<code>\selectlanguage{ngerman}</code>
12	<code>\cuam{12}\</code>
12–24	<code>\cuam{12--24}\</code>
36	<code>\cuam{36}\</code>
	<code>\cusetup{use-phrases=true}</code>
1 Dutzend	<code>\cuam{12}\</code>
1–2 Dutzend	<code>\cuam{12--24}\</code>
3 Dutzend	<code>\cuam{36}\</code>
	<code>\cusetup{use-phrases=true,print-numerals=true}</code>
ein Dutzend	<code>\cuam{12}\</code>
ein bis zwei Dutzend	<code>\cuam{12--24}\</code>
drei Dutzend	<code>\cuam{36}\</code>

### 9.2.5 Rounding options

---

**round-precision**    `round-precision = <integer>`

Rounds the amount automatically to *<integer>* digits after the colon. Note that units like C, F, K and Re are still rounded to integers due to `\cusetoptionfor`.

1.23457 kg	<code>\cusetup{round-precision=5}</code>
0.01259 kg	<code>\cunum{1.23456789}{kg}\</code>
194 kg	<code>\cunum[g=kg]{12.587}{g}\</code>
392–410 °F	<code>\cunum{194}{kg}\</code>
–273 °C	<code>\cunum[C=F]{200--210}{C}\</code>
	<code>\cunum[K=C]{0.0012}{K}\</code>
	<code>\cusetup{round-precision=1}</code>
1.2 kg	<code>\cunum{1.23456789}{kg}\</code>
12.6 kg	<code>\cunum{12.58}{kg}\</code>
0.2 kg	<code>\cunum[g=kg]{194}{g}\</code>
392–410 °F	<code>\cunum[C=F]{200--210}{C}\</code>
–273 °C	<code>\cunum[K=C]{0.0012}{K}</code>

**Note:** Negative numbers are also allowed.

–270 °C	<code>\cusetoptionfor{C,F}{round-precision=-1}</code>
–270 °C	<code>\cunum{-271,2}{C}\</code>
180 °C	<code>\cunum[K=C]{0.0012}{K}\</code>
360–390 °F	<code>\cunum{185}{C}\</code>
	<code>\cunum[C=F]{180--200}{C}\</code>

---

**round-to-int** `round-to-int = <true/false>`

*This option is deprecated.* Rounds the amount to an integer if set `true`. Use `round-precision=0` instead.

---

**round-half** `round-half = <default/commercial>`

This option is only important for half-way numbers (e.g. 0.005). By setting it to `default` the value will be rounded to the nearest even number. Setting it to `commercial` rounds the value away from zero.

It is set to `default` by ... default.

**Note:** `default` actually refers to the fact that it is the default rounding algorithm used by `\fp_eval:n { round( ) }` without a third argument.

0 kg	<code>\cusetup{round-half=default}</code>
–0 kg	<code>\cunum{0.005}{kg}\</code>
1.24 kg	<code>\cunum{-0.005}{kg}\</code>
	<code>\cunum{1.245}{kg}\</code>
	<code>\cusetup{round-half=commercial}</code>
0.01 kg	<code>\cunum{0.005}{kg}\</code>
–0.01 kg	<code>\cunum{-0.005}{kg}\</code>
1.25 kg	<code>\cunum{1.245}{kg}</code>

## 9.2.6 Fractions

---

**eval-fraction** `eval-fraction = <true/false>`

This option takes `true` or `false` as values. If set to `true` all fractions are evaluated. Please note that divisions through zero are not allowed.

0.33 kg	<code>\cusetup{eval-fraction=true}</code>
0.5 kg	<code>\cunum{1/3}{kg}\</code>
500 g	<code>\cunum{1/2}{kg}\</code>
1.5 kg	<code>\cunum[kg=g]{1/2}{kg}\</code>
1500 g	<code>\cunum{1_1/2}{kg}\</code>
-1500 g	<code>\cunum[kg=g]{1_1/2}{kg}\</code>
1 <sup>2</sup> / <sub>3</sub> kg	<code>\cunum[kg=g]{-1_1/2}{kg}\</code>
	<code>\cunum[kg=g]{1_2/?}{kg}\</code>

---

**convert-fraction**    `convert-fraction = <true/false>`

By default units of fractions are not converted into another unit. Setting this option to `true` allows fractions to be evaluated when a change of units is requested (and *only* if a change of unit is requested).

$\frac{1}{3}$ kg	<code>\cusetup{convert-fraction=true}</code>
333.33 g	<code>\cunum{1/3}{kg}\</code>
1 <sup>1</sup> / <sub>2</sub> kg	<code>\cunum[kg=g]{1/3}{kg}\</code>
1500 g	<code>\cunum{1_1/2}{kg}\</code>
1 <sup>2</sup> / <sub>3</sub> kg	<code>\cunum[kg=g]{1_1/2}{kg}\</code>
	<code>\cunum[kg=g]{1_?/3}{kg}\</code>

---

**fraction-command**    `fraction-command = \command`

Sets the command used for printing fractions equal to `\command`. `\command` has to take two arguments. By default it is equal to `\sfrac` from `xfrac`.

Please note that the amount is *not* printed inside a math environment by default.

$\frac{1}{8}$	<code>\newcommand\myfrac[2]{#1/#2}</code>
$\frac{1}{2}$ kg	<code>\cusetup{fraction-command=\myfrac}</code>
$\frac{4}{5}$ °C	<code>\cuam{1/8}\</code>
$\frac{12}{3}$ kg	<code>\cunum{1/2}{kg}\</code>
	<code>\cunum{4/5}{C}\</code>
	<code>\cunum{1_2/3}{kg}\</code>
$\frac{1}{8}$	<code>\cusetup{fraction-command=\nicefrac}</code>
$\frac{1}{2}$ kg	<code>\cuam{1/8}\</code>
$\frac{4}{5}$ °C	<code>\cunum{1/2}{kg}\</code>
$\frac{12}{3}$ kg	<code>\cunum{4/5}{C}\</code>
	<code>\cunum{1_2/3}{kg}</code>

---

**fraction-inline**    `fraction-inline = {<input containing #1 and #2>}`

Similar to `fraction-command` only that you don't have to define a command to alter the output of the fraction.

$1/8$	<code>\csetup{fraction-inline={#1/#2}}</code>
$1/2$ kg	<code>\cuam{1/8}\</code>
$4/5$ °C	<code>\cunum{1/2}{kg}\</code>
$12/3$ kg	<code>\cunum{4/5}{C}\</code>
	<code>\cunum{1_2/3}{kg}\</code>
	<code>\csetup{fraction-inline={\nicefrac{#2}{#1}}}</code>
$8/1$	<code>\cuam{1/8}\</code>
$2/1$ kg	<code>\cunum{1/2}{kg}\</code>
$5/4$ °C	<code>\cunum{4/5}{C}\</code>
$1^{3/2}$ kg	<code>\cunum{1_2/3}{kg}</code>

### 9.2.7 Spaces

---

**mixed-fraction-space**    `mixed-fraction-space = <length>`

---

Sets the length between the fraction and the number in a mixed-fraction, default is 0.1em (because I said so; if someone has some literature or sources to look up the space, please let me know).

$1^{2/3}$	<code>\cuam{1_2/3}\</code>
$1^{2/3}$ kg	<code>\cunum{1_2/3}{kg}\</code>
$10^{2/3}$ kg	<code>\cunum{10_2/3}{kg}\</code>
	<code>\csetup{mixed-fraction-space=1em}</code>
1 $^{2/3}$	<code>\cuam{1_2/3}\</code>
1 $^{2/3}$ kg	<code>\cunum{1_2/3}{kg}\</code>
10 $^{2/3}$ kg	<code>\cunum{10_2/3}{kg}\</code>
	<code>\csetup{mixed-fraction-space=0em}</code>
$1^{2/3}$	<code>\cuam{1_2/3}\</code>
$1^{2/3}$ kg	<code>\cunum{1_2/3}{kg}\</code>
$10^{2/3}$ kg	<code>\cunum{10_2/3}{kg}</code>

---

**cutext-space**    `cutext-space = {<string>}`

---

<string> is inserted between the numeral part and the unit part when using `\cutext` and `\Cutext`. By default it is set an unbreakable space ~.

1 kilogramme	<code>\cutext{1}{kg}\</code>
10 kilogramme	<code>\Cutext{10}{kg}\</code>
	<code>\csetup{cutext-space=\space}</code>
1 kilogramme	<code>\cutext{1}{kg}\</code>
10 kilogramme	<code>\Cutext{10}{kg}\</code>
	<code>\csetup{cutext-space={}}</code>
1kilogramme	<code>\cutext{1}{kg}\</code>
10kilogramme	<code>\Cutext{10}{kg}\</code>
	<code>\csetup{cutext-space={qwe}}</code>
1qwekilogramme	<code>\cutext{1}{kg}\</code>
10qwekilogramme	<code>\Cutext{10}{kg}\</code>

---

**phrase-space** `phrase-space = {<string>}`

*<string>* is inserted between the numeral part and the phrase part while using `\cuam`. By default it is set to the unbreakable space `~`. Use this option if you want to e.g. insert a normal space.

(Switching to german)

	<code>\selectlanguage{ngerman}</code>
1 Dutzend	<code>\cuam{12}\</code>
12 Dutzend	<code>\cuam{144}\</code>
	<code>\cusetup{phrase-space=\space}</code>
1 Dutzend	<code>\cuam{12}\</code>
12 Dutzend	<code>\cuam{144}\</code>
	<code>\cusetup{phrase-space={}}</code>
1Dutzend	<code>\cuam{12}\</code>
12Dutzend	<code>\cuam{144}\</code>
	<code>\cusetup{phrase-space={qwe}}</code>
1qweDutzend	<code>\cuam{12}\</code>
12qweDutzend	<code>\cuam{144}\</code>

---

**amount-unit-space** `amount-unit-space = {<string>}`

Change the spacing for `\cunum` between the printed amount(s) and the unit. The default value is `\thinspace`.

1 kg	<code>\cunum{1}{kg}\</code>
1/2 kg	<code>\cunum{1/2}{kg}\</code>
1-2 kg	<code>\cunum{1--2}{kg}\</code>
	<code>\cusetup{amount-unit-space={\hspace{1em}}}</code>
1 kg	<code>\cunum{1}{kg}\</code>
1/2 kg	<code>\cunum{1/2}{kg}\</code>
1-2 kg	<code>\cunum{1--2}{kg}\</code>
	<code>\cusetup{amount-unit-space={}}</code>
1kg	<code>\cunum{1}{kg}\</code>
1/2kg	<code>\cunum{1/2}{kg}\</code>
1-2kg	<code>\cunum{1--2}{kg}\</code>
	<code>\cusetup{amount-unit-space={qwe}}</code>
1qwekg	<code>\cunum{1}{kg}\</code>
1/2qwekg	<code>\cunum{1/2}{kg}\</code>
1-2qwekg	<code>\cunum{1--2}{kg}\</code>

### 9.2.8 label & refs

---

**recalculate-amount** `recalculate-amount = {true/false}`

Set this option to `true` if you want to change your recipes to the given number of people set by `set-number-of-persons`. Note that only those values who have a label are changed.

---

**set-number-of-persons** `set-number-of-persons =  $\langle integer \rangle$`

With this option you can determine the number of people your recipes are for. Note that this option only has an effect on those who have a  $\langle label \rangle$  given. It is set to 4 by default. Please also note the use of `recalculate-amount`.

2 persons	<code>\culabel{anotherrecipe}{2}</code>
1 kg	<code>\curef{anotherrecipe}~persons\\</code>
1	<code>\cunum&lt;anotherrecipe&gt;{1}{kg}\\</code>
10 kilogramme	<code>\cuam&lt;anotherrecipe&gt;{1}\\</code>
	<code>\Cutext[ref=anotherrecipe]{10}{kg}\\</code>
	<code>\cusetup{recalculate-amount=true}</code>
4 persons	<code>\curef{anotherrecipe}~persons\\</code>
2 kg	<code>\cunum&lt;anotherrecipe&gt;{1}{kg}\\</code>
2	<code>\cuam&lt;anotherrecipe&gt;{1}\\</code>
20 kilogramme	<code>\Cutext[ref=anotherrecipe]{10}{kg}\\</code>
	<code>\cusetup{set-number-of-persons=3}</code>
3 persons	<code>\curef{anotherrecipe}~persons\\</code>
1.5 kg	<code>\cunum&lt;anotherrecipe&gt;{1}{kg}\\</code>
1.5	<code>\cuam&lt;anotherrecipe&gt;{1}\\</code>
15 kilogramme	<code>\Cutext[ref=anotherrecipe]{10}{kg}\\</code>
	<code>\cusetup{set-number-of-persons=2}</code>
2 persons	<code>\curef{anotherrecipe}~persons\\</code>
1 kg	<code>\cunum&lt;anotherrecipe&gt;{1}{kg}\\</code>
1	<code>\cuam&lt;anotherrecipe&gt;{1}\\</code>
10 kilogramme	<code>\cutext&lt;anotherrecipe&gt;{10}{kg}\\</code>
	<code>\cusetup{set-number-of-persons=1}</code>
1 persons	<code>\curef{anotherrecipe}~persons\\</code>
0.5 kg	<code>\cunum&lt;anotherrecipe&gt;{1}{kg}\\</code>
0.5	<code>\cuam&lt;anotherrecipe&gt;{1}\\</code>
5 kilogramme	<code>\Cutext[ref=anotherrecipe]{10}{kg}\\</code>

---

**label** `label =  $\{ \langle string \rangle * \langle integer \rangle \}$`

The key-value version of `\culabel`. It defines the label  $\langle string \rangle$  which is originally for  $\langle integer \rangle$  people. Please note that the `*` is mandatory as it separates the string from the integer. Each label is defined globally and must be unique.

1 person	<code>\cusetup{label=Toast*1}</code>
2	<code>\curef{Toast}~person\\</code>
2 dag	<code>\cuam&lt;Toast&gt;{2}\\</code>
	<code>\cunum&lt;Toast&gt;{2}{dag}\\</code>
	<code>\cusetup{recalculate-amount=true}</code>
4 persons	<code>\curef{Toast}~persons\\</code>
8	<code>\cuam&lt;Toast&gt;{2}\\</code>
8 dag	<code>\cunum&lt;Toast&gt;{2}{dag}</code>

---

**get-label** `get-label =  $\{ \langle label \rangle \}$`

The key-value version of `\curef`. Note that this key doesn't save the value inside a macro but rather prints it directly into the document.

```

3          \culabel{Schinken}{3}
3          \cusetup{get-label=Schinken}\\
3          \curef{Schinken}\\
4          \cusetup{recalculate-amount=true}
4          \cusetup{get-label=Schinken}\\
4          \curef{Schinken}

```

**Note:** `\curef` is expendable.

---

**ref** `ref = {⟨label⟩}`

---

Instead of using the first optional arguments of the commands in section 2 you may use this option. It requires a valid value and throws an error if `⟨label⟩` is not defined.

```

10 dm      \culabel{Kaese}{3}
10 dm      \cunum<Kaese>[m=dm]{1}{m}\\
10 dm      \cunum[ref=Kaese,m=dm]{1}{m}\\
13.33 dm   \cusetup{recalculate-amount=true}
13.33 dm   \cunum<Kaese>[m=dm]{1}{m}\\
13.33 dm   \cunum[ref=Kaese,m=dm]{1}{m}

```

---

<code>curef-add-forbidden-unit</code>	<code>curef-add-forbidden-unit</code>	<code>= {⟨unit list⟩}</code>
<code>curef-remove-forbidden-unit</code>	<code>curef-remove-forbidden-unit</code>	<code>= {⟨unit list⟩}</code>
<code>curef-clear-forbidden-units</code>	<code>curef-clear-forbidden-units</code>	<code>= ⟨true/false⟩</code>

---

There are units which do not depend on the number of folks you are cooking for, units measuring the temperature are an example. Changing those units with the label & ref system would be accidental and in the best case throw an error. With the following options you can add units to the “forbidden unit list”, remove them and clear the whole list entirely.

By default the list contains C, F, K and Re.

```

2 m        \culabel{check}{2}
2 kg       \cusetup{recalculate-amount=true}
1 °C      \cunum<check>{1}{m}\\
           \cunum<check>{1}{kg}\\
           \cunum[ref=check]{1}{C}\\
           \cusetup{curef-add-forbidden-unit={m,kg}}
1 m        \cunum<check>[m]{1}{m}\\
1 kg       \cunum<check>[m]{1}{kg}\\
1 °C      \cunum[ref=check]{1}{C}\\
           \cusetup{curef-remove-forbidden-unit={C}}
1 m        \cunum<check>[m]{1}{m}\\
1 kg       \cunum<check>[m]{1}{kg}\\
2 °C      \cunum[ref=check]{1}{C}\\
           \cusetup{curef-clear-forbidden-units=true}
2 m        \cunum<check>[m]{1}{m}\\
2 kg       \cunum<check>[m]{1}{kg}\\
2 °C      \cunum[ref=check]{1}{C}

```

### 9.3 Weird options

---

`check-temperature` `check-temperature =  $\langle true/false \rangle$`

Checks if the used temperature is below absolute zero. Currently C, F, K and Re are supported. While `\cunum{0}{K}` is ok, `\cunum{-1}{K}` raises an error, same for the others. Is set to `false` by default. To add new units see `add-temperature-to-check`.

---

`add-temperature-to-check` `add-temperature-to-check =`  
`{`  
`$\langle unit-key-1 \rangle = \langle minimum-value-1 \rangle$  ,`  
`$\langle unit-key-2 \rangle = \langle minimum-value-2 \rangle$  ,`  
`...`  
`}`

This option adds  $\langle unit-key-1 \rangle$  and so on to the list of units to be checked if `check-temperature` is active. The argument can be a comma-separated list of  $\langle unit-key \rangle = \langle minimum-value \rangle$ . This sets the allowed minimum value of  $\langle unit-key \rangle$  to  $\langle minimum-value \rangle$ .

**Example:** This package implements the allowed minimum values for the temperatures C, F, K and Re to be checked if `check-temperature` is active using:

```
\cusetup
{
  add-temperature-to-check =
  {
    K = 0,
    C = -273.15 ,
    F = -459.67 ,
    Re = -218.52
  }
}
```

If you want to add a new value, for example degree Rømer (which has been defined in another example) you can write:

```
\cusetup
{
  add-temperature-to-check = { Ro = -135.90375 }
}
```

---

`convert-to-eV` `convert-to-eV =  $\langle true/false \rangle$`

Converts (nearly) every unit in table 1 to electron volt or the respective derivative (if possible). Note that this option is: a) experimental and probably will forever be and (b) just a joke, you are not supposed to use these units in a cookery book (and as you see this package doesn't support the arrangement of such huge numbers). Also you may want to check the values if you really want to use them, just to be sure (I've checked them several times and hope they are finally correct, but mistakes happen).





## 10 Public Commands

This section describes some public functions, Their main usage is the printing of stuff. They are primitives used between an `\ExplSyntaxOn` and `\ExplSyntaxOff`; for usage in a document you may do the following:

```
\ExplSyntaxOn
\NewDocumentCommand \cuprintfrac { 0{ } m m }
{
  \cookingunits_print_fraction:nnn {#1} {#2} {#3}
}
\NewDocumentCommand \cuprinrange { m m }
{
  \cookingunits_print_range:nn {#1} {#2}
}
\ExplSyntaxOff
```

---

<code>\cookingunits_print_fraction:nnn</code>	<code>\cookingunits_print_fraction:nnn</code>
	<code>{\mixed-part}}{\numerator}}{\denominator}}</code>

*Note:* There is no parsing and processing done in this command, it just prints the input. Uses the internal fraction printing command to print a fraction. `{\mixed-part}}` can be empty if no mixed part is needed.

---

<code>\cookingunits_print_range:nn</code>	<code>\cookingunits_print_range:nn</code>
	<code>{\left-part}}{\right-part}}</code>

*Note:* There is no parsing and processing done in this command, it just prints the input. Uses the internal range printing command to print a range (using the same range sign as `\cunum` would use)

## 11 Bugs & Feedback

Bug reports are always welcome. If you are sending a bug report please include a minimal working example showing the bug and a short description. If you use mail please add `cooking-units` to the e-mail header. GMX has the habit of putting e-mails into the spam account and adding `cooking-units` to the header makes it easier to recognize those e-mails. It can also take longer of GitHub, but I hope I figured out how to get a mail if a new issue is created (by not me).

Feedback and requests (commands, units, etc.) are also welcome. Please also add (if possible) an example of the desired output into the minimal example (and – if by mail – add `cooking-units` to the header).

Furthermore, as you can see I am not able to speak too many languages (german and english to be precise) so if you are able to speak a language not yet implemented and would like to help you can send me the translations known to you. A list of all units (and their current translations) is given in appendix [A](#).

## 12 Bens Einheitsammelsurium (Bens unit Almanac)

Units are a fascinating mess. There are so many different ones which are different and the few ones which are the same (in name at least) are *also* different, depending on geographical position, time period and probably pure spite. We can be glad that SI-units exist.

So for those units which didn't make it into table 1 and table 2, this section exists. Please note that this list is intended to be a just-for-fun list and not a compilation of every unit in existence with its exact value ordered by geographical and chronological position. I am sadly neither a historian nor very good in regards to languages. It would sound like fun, but ultimately, I wouldn't have the time. Therefore I am only taking units into account which I either found in literature (stone, canna, etc.), are well known (foot) or have some other experience with them (ell) (exception: Batman). The reason I am not including units which I found in the internet is that I would like to see those units in their "natural environment".

**unit (translation) [abbreviation]** Description, containing a quote or not. *Please note that most of the units are country dependent! So the translation may not have the same amount as the word it is translated to.*

**Batman** So ... You wanna be Batman? Be like Bruce Wayne? Having a secret identity? Then congratulations! You *are* Batman! How much Batman depends on the location, but Wikipedia is your friend in this matter.

**Rotolo<sup>sicilian</sup> (Rottel<sup>de</sup>)** Around 0.850 kg

*Auf den Fußboden lagen vier ungeriefte Käse zu je zwölf Rottel, jeder ungefähr zehn Kilo schwer.* (see [1] page 51)

**Canna<sup>sicilian</sup> (Rute<sup>de</sup>, rod<sup>en</sup>)** About 2 m bzw. about 6 foot.

*"Unsinn, Stella, Unsinn; was soll mir zustoßen? Sie kennen mich alle: Männer, die eine Rute lange sind, gibt es wenige in Palermo."* (see [1] page 25)

**Stone [st]** 6.35 kg. According to a fellow student this unit is still used in Great Britain. I've also recently found it in a video game; in the german translation of said video game to be precise. Why is the german translation using stone and not kilogram (at least in braces)?

*As we had expected, the telegramm was soon followed by its sender, and the card of Mr. Cyril Overton, Trinity College, Cambridge, announced the arrival of an enormous young man, sixteen stone [101.6 kg] of solid bone and muscle, who spanned the doorway with his broad shoulders [...]* (see [2] page 988)

(Story "The missing Three Quarters")

**Foot [ft]** Equals exactly 0.3048 m or 12 in.

A bit of a strange unit (for me at least). Where I am from, people tend to have different feet sizes. Also present in the german translation of the video game that uses "Stone".

**degree Rèamur [°Ré]** Like degree Celsius, but instead of having the water boiling at 100° (Celsius), water boils at 80°. Water thankfully still freezes at 0°. Don't think that this unit is used anymore. I think I learned about in physics.

**Ell** Just read the Wikipedia article.

Fun Fact: At the Stephansdom in Vienna left of the main entrance are two metal bars. One is the “Tuchelle” (drapery ell, circa 78 cm), the other the “Leinenelle” (linen ell, around 89.6 cm).

**cup** I think the idea of having a “cup” and it not being equal to 250 ml is a bit strange, for me at least. What other sizes can a cup have? I can imagine 500 ml, but are there other sizes?

**stick** A unit I’ve made fun of because it is quite regional and doesn’t make any sense for foreigners. Then I realized that I am using the unit “Packerl” in my cookery book which is also quite locally<sup>8</sup> and – even worse – the weight changes depending the content (See *Packerl*).

**Packerl<sup>de</sup> (small bag)** I’m a bit split on this unit as I don’t actually know if it exists. The reason I have the unit *Packerl* for my cookery book is that in Austria you can buy baking powder, (dry) Germ, Natrium, etc. in small bags (similar to *stick*). The problem: Depending on the content, the weight of *Packerl* differs. Not only that, but it can also differ between different producers (but not more than 2 g bzw. 0.07 oz). Here is a table:

1 Packerl Backpulver	(baking powder)	16 g	(0.56 oz)
Natrium		14 g	(0.49 oz)
Vanillin(-zucker)	(vanillin(-sugar))	8 g	(0.28 oz)
Germ*		7 g	(0.25 oz)

\*Tockengerm (dry Germ) to be precise

For what kind of thing do I need *Natrium* for?

## A Translations

This section contains the list of available translations. Each table shows the available translations regarding the unit symbol, the unit name (printed if `\cutext` or `\Cutext` is used) and the plural form (if different from the singular form). A second table shows the translations used for phrases (if given).

If a translation is not available a “—” is shown.

---

<sup>8</sup>And maybe doesn’t even exist outside my family

## A.1 English

<i>&lt;unit-key&gt;</i>	printed unit	unitname	(plural)	gender
kg	kg	kilogramme		m
dag	dag	decagramme		m
g	g	gramme		m
oz	oz	ounce		m
lb	lb	pound	(pounds)	m
C	°C	degree Celsius	(degrees Celsius)	m
F	°F	degree Fahrenheit	(degrees Fahrenheit)	m
Re	°Ré	degree Réaumur	(degrees Réaumur)	m
K	K	kelvin		m
d	d	day	(days)	m
h	h	hour	(hours)	m
min	min	minute	(minutes)	m
s	s	second	(seconds)	m
m	m	metre	(metres)	m
dm	dm	decimetre	(decimetres)	m
cm	cm	centimetre	(centimetres)	m
mm	mm	millimetre	(millimetres)	m
in	in	inch	(inches)	m
l	ℓ	litre	(litres)	m
dl	dl	decilitre	(decilitres)	m
cl	cl	centilitre	(centilitres)	m
ml	ml	millilitre	(millilitres)	m
cal	cal	calorie	(calories)	m
kcal	kcal	kilocalorie	(kilocalories)	m
J	J	joule	(joules)	m
kJ	kJ	kilojoule	(kilojoules)	m
eV	eV	electron volt		m
pn	pinch	pinch	(pinches)	m
EL	tbsp.	tablespoon	(tablespoons)	m
TL	tsp.	teaspoon	(teaspoons)	m
csp	csp.	coffeespoonful		m
dsp	dsp.	dessertspoonful		m
ssp	ssp.	saltspoonful		m
Msp	Msp.	—		m
decimal-mark	—	.		m
one(m)	—	one		m
one(f)	—	one		m
one(n)	—	one		m

## A.2 american

<i>&lt;unit-key&gt;</i>	printed unit	unitname	(plural)	gender
kg	kg	kilogram		m
dag	dag	decagram		m
g	g	gram		m
oz	oz	ounce		m
lb	lb	pound	(pounds)	m
C	°C	degree Celsius	(degrees Celsius)	m
F	°F	degree Fahrenheit	(degrees Fahrenheit)	m
Re	°Ré	degree Réaumur	(degrees Réaumur)	m
K	K	kelvin		m
d	d	day	(days)	m
h	h	hour	(hours)	m
min	min	minute	(minutes)	m
s	s	second	(seconds)	m
m	m	meter	(meters)	m
dm	dm	decimeter	(decimeters)	m
cm	cm	centimeter	(centimeters)	m
mm	mm	millimeter	(millimeters)	m
in	in	inch	(inches)	m
l	<i>ℓ</i>	liter	(liters)	m
dl	dl	deciliter	(deciliters)	m
cl	cl	centiliter	(centiliters)	m
ml	ml	milliliter	(milliliters)	m
cal	cal	calorie	(calories)	m
kcal	kcal	kilocalorie	(kilocalories)	m
J	J	joule	(joules)	m
kJ	kJ	kilojoule	(kilojoules)	m
eV	eV	electron volt		m
pn.	pn.	pinch	(pinches)	m
EL	tbsp.	tablespoon	(tablespoons)	m
TL	tsp.	teaspoon	(teaspoons)	m
csp	csp.	coffeespoonful		m
dsp	dsp.	dessertspoonful		m
ssp	ssp.	saltspoonful		m
Msp	Msp.	—		m
decimal-mark	—	.		m
one(m)	—	one		m
one(f)	—	one		m
one(n)	—	one		m

### A.3 German

<i>&lt;unit-key&gt;</i>	printed unit	unitname	(plural)	gender
kg	kg	Kilogramm		n
dag	dag	Dekagramm		n
g	g	Gramm		n
oz	oz	Unze		f
lb	lb	Pfund		n
C	°C	Grad Celsius		m
F	°F	Grad Fahrenheit		m
Re	°Ré	Grad Réamur		m
K	K	Kelvin		n
d	d	Tag	(Tage)	m
h	h	Stunde	(Stunden)	f
min	min	Minute	(Minuten)	f
s	s	Sekunde	(Sekunden)	f
m	m	Meter		n
dm	dm	Dezimeter		n
cm	cm	Centimeter		n
mm	mm	Millimeter		n
in	in	Zoll		m
l	l	Liter		m
dl	dl	Deziliter		m
cl	cl	Centiliter		m
ml	ml	Milliliter		m
cal	cal	Kalorie	(Kalorien)	f
kcal	kcal	Kilokalorie	(Kilokalorien)	f
J	J	Joule		m
kJ	kJ	Kilojoule		m
eV	eV	Elektronenvolt		n
pn	Prise	Prise	(Prisen)	f
EL	EL	Esslöffel		m
TL	TL	Teelöffel		m
csp	KL	Mokkalöffel		m
dsp	dsp.	—		m
ssp	ssp.	—		m
Msp	Msp.	Messerspitze	(Messerspitzen)	f
decimal-mark	—	,		m
one(m)	—	ein		m
one(f)	—	eine		m
one(n)	—	ein		m

<i>&lt;Phrase-key&gt;</i>	phrase	(plural)	gender
12	Dutzend		n

Some further phrases, just to write them down (they are not implemented, as they are barely used).

<i>&lt;number&gt;</i>	name	Note	(plural)	gender
60	Schock	(5 Dutzend, 12 * 5)		n
144	Gros	(12 Dutzend, 12 * 12)		n
1728	Großgros	(12 Groß, 12 * 144)		n

Note that Großgros has other (probably more common) synonyms.



## A.4 French

<i>&lt;unit-key&gt;</i>	printed unit	unitname	(plural)	gender
kg	kg	kilogramme	(kilogrammes)	m
dag	dag	décagramme	(décagrammes)	m
g	g	gramme	(grammes)	m
oz	oz	once	(onces)	f
lb	lb	livre	(livres)	f
C	°C	degré Celsius	(degrés Celsius)	m
F	°F	kelvin	(kelvins)	m
Re	°Ré	échelle Réaumur	(degrés Réaumur)	m
K	K	degré Fahrenheit	(degrés Fahrenheit)	m
d	d	jour	(jours)	m
h	h	heure	(heures)	f
min	min	minute	(minutes)	f
s	s	seconde	(secondes)	f
m	m	mètre	(mètres)	m
dm	dm	décimètre	(décimètres)	m
cm	cm	centimètre	(centimètres)	m
mm	mm	millimètre	(millimètres)	m
in	po	pouce	(pouces)	m
l	L	litre	(litres)	m
dl	dL	décilitre	(décilitres)	m
cl	cL	centilitre	(centilitres)	m
ml	mL	millilitre	(millilitres)	m
cal	cal	calorie	(calories)	f
kcal	kcal	kilocalorie	(kilocalories)	f
J	J	joule	(joules)	m
kJ	kJ	kilojoule	(kilojoules)	m
eV	eV	électron-volt	(électron-volts)	m
pn	pincée	pincée	(pincées)	f
EL	c.à.s.	cuillère à soupe	(cuillères à soupe)	f
TL	c.à.c.	cuillère à café	(cuillères à café)	f
csp	csp.	—	—	m
dsp	dsp.	—	—	m
ssp	ssp.	—	—	m
Msp	Msp.	—	—	m
decimal-mark	—	,	—	m
one(m)	—	un	—	m
one(f)	—	une	—	m
one(n)	—	un	—	m

If the spoons should be extra full:

- cuillère à soupe rase
- cuillère à café rase

## B US, Imperial and Other units

As source [5] has been used for imperial units, while [4] and [3] were used for U.S. units. I hope someone will find this bringing together useful.

---

$$1 \text{ yard} = 0.9144 \text{ m (exact)}$$

$$1 \text{ yard} = 3 \text{ foot}$$

$$1 \text{ yard} = 36 \text{ Inch}$$

---

$$1 \text{ Inch} = 0.0254 \text{ m (also exact)}$$

---

---

$$1 \text{ liter} = 1 \text{ dm}^3$$

---

$$1 \text{ gallon} = 4.546 09 \text{ liter (exact)} \quad 1 \text{ U.S. gallon} = 231 \text{ Inch}^3 = 231 \times 0.016 387 064 \text{ liter}$$

$$1 \text{ gallon} = 4 \text{ Quart} \quad 1 \text{ U.S. gallon} = 4 \text{ Quart}^{\text{U.S.}}$$

$$1 \text{ gallon} = 8 \text{ Pint} \quad 1 \text{ U.S. gallon} = 8 \text{ Pint}^{\text{U.S.}}$$

$$1 \text{ gallon} = 32 \text{ Gill} \quad 1 \text{ U.S. gallon} = 32 \text{ Gill}^{\text{U.S.}}$$

$$1 \text{ gallon} = 160 \text{ fl. oz} \quad 1 \text{ U.S. gallon} = 128 \text{ fl. oz}^{\text{U.S.}}$$

---

$$1 \text{ fl. oz} = 0.028 413 062 5 \text{ liter} \quad 1 \text{ fl. oz}^{\text{U.S.}} = 0.029 573 529 562 5 \text{ liter}$$

---

Note 1: I think the American fl. oz<sup>U.S.</sup> is more common. Maybe. Most bottles have something like 10 fl. oz, which they say is equal to 30 ml. This would work really well with fl. oz<sup>U.S.</sup>.

Note 2: Sometimes “fl. oz” is written without the dot. I am also not sure what kind of spacing has to be between “fl.” and “oz” (currently using `\thinspace`).

Note 3: This maybe sounds stupid, but could we introduce something like “flouz”, “floiz” and “floeiz”? “flouz” would be “fl. oz<sup>U.S.</sup>”, “floiz” would be “Imperial fl. oz” and “floeiz” would simply be equal to 30 ml?

For “stick” see [6].

---

$$1 \text{ lb} = 0.453 592 37 \text{ kg (exact)}$$

$$1 \text{ lb} = 16 \text{ oz}$$

$$1 \text{ lb} = \frac{1}{14} \text{ st}$$

$$1 \text{ lb} = \frac{175}{12} \text{ ounce troy}$$

$$1 \text{ lb} = 4 \text{ stick}$$

---

---

$$\begin{array}{ll} 1 \text{ cup} \approx 0.25 \text{ litre} = 250 \text{ ml} & 1 \text{ cup}^{\text{U.S.}} = 8 \text{ fl. oz}^{\text{U.S.}} \\ 1 \text{ tablespoon} \approx 0.015 \text{ litre} = 15 \text{ ml} & 1 \text{ tablespoon}^{\text{U.S.}} = \frac{1}{2} \text{ fl. oz}^{\text{U.S.}} \\ 1 \text{ teaspoon} \approx 0.005 \text{ litre} = 5 \text{ ml} & 1 \text{ teaspoon}^{\text{U.S.}} = \frac{1}{6} \text{ fl. oz}^{\text{U.S.}} \end{array}$$

---

Note 1: I tested the approximation for tablespoon with water (1 mg  $\approx$  1 mg) and the approximation looks good enough. It of course depends on how full you fill your spoon.

If you ever encounter in a german cookery book the word “Packerl”, check out its entry in section 12.

## References

- [1] Guiseppe Tomasi di Lampedusa, *Der Gattopardo*, Piper, Volume 8 (2018), ISBN 978-3-492-24586-9

- [2] Sir Arthur Conan Doyle, *Sherlock Holmes The Complete Novels and Stories Volume II*, Bantam Books
- [3] *Guide for the Use of the International System of Units (SI)*, NIST Special Publication 811, 2008 Edition, Ambler Thompson and Barry N. Taylor
- [4] *The International System of Units (SI) – Conversion Factors for General Use*, NIST Special Publication 1038, May 2006, Kenneth Butcher, Linda Crown and Elizabeth J. Gentry
- [5] *Weights and Measures Act 1985*, <https://www.legislation.gov.uk/ukpga/1985/72>
- [6] <https://cooking.stackexchange.com/questions/784/translating-cooking-terms-between-us-uk-au-ca-nz>
- [7] Dictionnaire de l'Académie française. <https://www.dictionnaire-academie.fr/article/A9P2979> [Last checked: 2022-05-29]
- [8] <https://www.antidote.info/fr/blogue/enquetes/15-gramme-ou-15-grammes> [Last checked: 2022-05-29]
- [9] <https://french.stackexchange.com/q/1975> [Last checked: 2022-05-29]

## Change History

2016/06/11	General: Added the package option to load 'fmtcount'. . . . .	1	Changed name from <code>\@@_cunum_parse_range</code> (and derivatives) to <code>\@@_cutext_parse_range</code> . . . . .	1	
2016/08/31	General: Fixed calculation: degree Reamur to eV . . . . .	1	Changed name from <code>\@@_parse_fraction_in_input:www</code> to <code>\@@_parse_mixed_fraction_in_input:www</code> . . . . .	1	
2016/09/03	Initial version . . . . .	1	Corrected mistake: 'ELEktronenvolt' (note uppercase L) to 'Elektronenvolt' in german. . . . .	1	
	General: Added units 'ssp', 'csp', 'dsp' . . . . .	1	Delete 'single' from property lists of singlekeys cause it is not as safe as I thought. . . . .	1	
	British English: 'pinch' is written in full . . . . .	1	In <code>\@@_cutext_default:nnn</code> it is only checked once if a range is inside. . . . .	1	
	English unit: litre (and only litre) uses the curly l $\ell$ now . . . . .	1			
	Separated Messerspitze and pinch . . . . .	1	2016/09/16	General: Only use <code>\phantom</code> if the argument (for <code>\phantom</code> ) is not empty. . . . .	1
2016/09/05	General: New message: 'obsolete-command' . . . . .	1	2016/09/26	General: <code>\cuaddsinglekeys</code> now tests if the unit exists (it didn't before). . . . .	1
	Replaced <code>\cfrac</code> by <code>\cuam</code> . . . . .	1			
2016/09/09	General: <code>\@@_calculate_input_and_store_in:nN</code> optimiert durch neue property-key: single. . . . .	1			
	Add 'single' to property list of singlekeys. . . . .	1			

New option (and needed macros):	2017/03/10
add-temperature-to-check. . . . .	General: <code>\curef</code> is now defined by
New option: 'round-half'. . . . .	<code>\NewExpandableDocumentCommand</code>
Recalculated all electron volt values	instead of the <code>DeclareVariant</code> . . . . .
for conversion (as 'kg' was wrong	Removed <code>\translate</code> and others
before). Let's hope they are	from code and replaced them with
correct this time. . . . .	wrapper-macros. . . . .
Replaced <code>\prop_clear_new:c</code> by	Removed things like 'cu-unit' from
<code>\prop_clear:c</code> . . . . .	translate input and placed them
2016/10/19	into separate tl's. . . . .
General: 'convert-to-eV' now also as	2017/10/23
optional argument available. . . . .	General: Added "phrases". . . . .
Option 'load-time-option' now spells	Added unit "stick" (of butter). . . . .
'available' correct. . . . .	New option: <code>amount-unit-space</code> . . . . .
Update of documentation. . . . .	New option: <code>phrase-space</code> . . . . .
Use <code>\keys_set:nn</code> only if second	New option: <code>print-numerals</code> . . . . .
argument is not empty. . . . .	New option:
2016/10/28	<code>set-cutext-translation-message</code> .
General: <code>\cutext</code> (and <code>\Cutext</code> ) and	. . . . .
<code>\cuam</code> now parse their input like	New option: <code>use-phrases</code> . . . . .
<code>\cunum</code> . This is needed as they	Now checks for ranges if both values
also need to be changed. . . . .	can be printed as numerals (if
Start implementation of "Change	activated) (bug fix). . . . .
recipe from $n$ to $m$ persons.". . . . .	Replaced <code>translator</code> by <code>translations</code> . . . . .
2016/10/29	Reworked quite a lot of code. . . . .
General: Tiding code: Now every	2018/04/20
command is separated into a	General: Add "Division-by-zero" error. . . . .
"calc" function, a "print numeric	Allow round precision to be
value" and a "print unit" (if there)	negative. . . . .
function. At least, that's the plan. . . . .	Change large portions of code. . . . .
2016/10/30	Cooking Units-keys are not allowed
General: Fractions should now deal	to contain either " ," or "/". . . . .
correctly with minus signs. . . . .	Fix argument specifiers. . . . .
2016/11/07	Introduce key-groups (weight,
General: Finished writing v1.10. . . . .	volume, etc.). . . . .
2016/11/13	New feature: Hooks . . . . .
General: <code>\cutext</code> , <code>\Cutext</code> and <code>\cuam</code>	New Option: <code>42</code> . . . . .
check their input, allows	New option: <code>add-unit-to-group</code> . . . . .
conversion of units. . . . .	New option:
Change amounts for specific number	<code>erase-all-options-for</code> . . . . .
of persons. . . . .	New options: <code>expand-both</code> ,
New commands: <code>\culabel</code> and	<code>expand-amount</code> , <code>expand-unit</code> . . . . .
<code>\curef</code> . . . . .	New options: <code>set-option-for &amp;</code>
New commands:	<code>add-option-for</code> . . . . .
<code>\declarecookingunit</code> and	New parsing algorithm. Hopefully
<code>\providecookingunit</code> . . . . .	better error recovery (if signs for
New options: <code>cuam-version</code> and	fractions are in wrong order e.g.) . . . . .
<code>cutext-version</code> . . . . .	Option: <code>add-natural-unit</code> . . . . .
New options: <code>cutext-to-cunum</code> ,	2018/06/05
<code>cutext-change-unit</code> and	General: <code>set-unknown-message</code> : Fix
<code>cutext-space</code> . . . . .	default value. . . . .
New options: <code>recalculate-amount</code>	Add "range-sign" for translations
and <code>set-number-of-persons</code> ,	(not usable yet). . . . .
<code>label</code> , <code>get-label</code> , <code>ref</code> . . . . .	

Bugfix ( <b>phrases</b> ): Use the phrase from the first amount to check the second (and don't parse through the second amount). . . . .	1	2021/03/21	General: Adding keys to unit definition. . . . .	1
Bugfix ( <b>unit-change</b> ): <b>convert-to-eV</b> can be again used as a local argument. . . . .	1		Much better error handling. . . . .	1
true) will print the second word small. . . . .	1		New commands to define keys: <b>\cudefinekeychain</b> and <b>\cuaddtokeychain</b> . . . . .	1
Change ( <b>amount-not-known</b> ): Change message a bit. . . . .	1		New joke options: <b>nothing-special</b> , <b>going-bonkers</b> , <b>fully-bonkers</b> and <b>xD-lol</b> . . . . .	1
Convert <b>clist</b> to <b>seq</b> if possible. . .	1		New options: <b>definition/symbol</b> , <b>definition/gender</b> , <b>definition/set-option</b> , <b>definition/add-to-group</b> . . . . .	1
Fix some more argument specifiers. . .	1		Overall reworking of internal code. . .	1
Improve error-recovery by a <b>lot hdpindex</b> . . . . .	1		Remove exhaustive expansion from translations. Shouldn't really change anything. . . . .	1
Remove unnecessary variants. . . . .	1		Using commands as unit-keys now works. . . . .	1
Renaming of some internal commands. . . . .	1			
Rework parsing code (again). As this is basically an improved version of the old parsing algorithm, there is no huge version change. . . . .	1	2022/03/26	General: Bugfix: Fixing property list retrieval error (storing property lists via translations did not work too well). . . . .	1
This version introduces mayor internal changes. For users not many things change. . . . .	1		Bugfix: Remove <b>\peek_meaning_ignore_spaces:NTF</b> . . . . .	1
2018/09/24				
General: Changes prefix from <b>cooking_units</b> to <b>cookingunits</b> . . .	1	2022/06/06	General: Add two public commands <b>\cookingunits_print_fraction:nnn</b> and <b>\cookingunits_print_range:nn</b> . . .	1
Improved french (not in general, only for this package) . . . . .	1		Correction of french language. Thanks to Alexis Jeandeaun . . . . .	1
New language symbols: <b>cutext-range-sign</b> . . . . .	1		Implement a way to define the plural-finding algorithm. . . . .	1
New section in documentation. . . . .	1			
Remove exhaustive expansion from internals (shouldn't change anything for users). . . . .	1			

## Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

<b>Symbols</b>			
<b>&lt;group&gt;</b> . . . . .	19	<b>\@@_cutext_default:nnn</b> . . . . .	43
<b>&lt;unit&gt;</b> . . . . .	18	<b>\@@_cutext_parse_range</b> . . . . .	43
<b>@@</b> commands:		<b>\@@_parse_fraction_in_input:www</b> . .	43
<b>\@@_calculate_input_and_store_in:nN</b> . . . . .	43	<b>\@@_parse_mixed_fraction_in_input:www</b> . . . . .	43
<b>\@@_cunum_parse_range</b> . . . . .	43	<b>Numbers</b>	
	42		33

<b>A</b>		cutext-space	28
add-natural-unit	33	cutext-to-cunum	20
add-option-for	20	cutext-version	21
add-option-for-<unit-key>	20	<b>D</b>	
add-special-sign	22	decimal-mark	14
add-temperature-to-check	32	\declarecookingderivatives	9
add-to-group	9	\declarecookingunit	8, 44
add-unit-to-group	20	<b>E</b>	
amount-unit-space	29	erase-all-options	20
<b>C</b>		erase-all-options-for	20
check-temperature	32	eval-fraction	26
\command	27	expand-amount	22
commands-add-hook	21	expand-both	22
convert-fraction	27	expand-unit	22
convert-to-eV	32	<b>F</b>	
cookingunits commands:		fraction-command	27
\cookingunits_print_fraction:nnn		fraction-inline	27
.....	34, 45	fully-bonkers	33
\cookingunits_print_range:nn	34, 45	<b>G</b>	
\cuaddkeys	13	gender	9
\cuaddoptionfor	17	get-label	30
\cuaddsinglekeys	12, 43	going-bonkers	33
\cuaddtokeychain	12	<b>K</b>	
\cuaddtokeys	13	keys commands:	
\cuaddtounitgroup	19	\keys_set:nn	44
\cuam	43, 44	<b>L</b>	
cuam-add-hook	21	label	30
cuam-version	21	<b>M</b>	
\cuclearoptionfor	17	mixed-fraction-space	28
\cudeclareunitgroup	19	<b>N</b>	
\cudefinekeychain	10	natural-unit	9
cudefinekeys	13	\newcookingunit	8
\cudefinename	14	\NewExpandableDocumentCommand	44
\cudefinephrase	16	nothing-special	33
\cudefinesinglekey	10	\Numberstringnum	18
\cudefinesymbol	15	\numberstringnum	18
\cufrac	43	Numeral-function	24
\culabel	44	numeral-function	24
\cunum	44	<b>O</b>	
cunum-add-hook	21	one(f)	14
cunum-range-sign	24	one(m)	14
\curef	44	one(n)	14
curef-add-forbidden-unit	31	<b>P</b>	
curef-clear-forbidden-units	31	parse-number	24
curef-remove-forbidden-unit	31	peek commands:	
\cusetoptionfor	17	\peek_meaning_ignore_spaces:NTF	45
\cusetup	17	\phantom	43
\Cutext	44	phrase-space	29
\cutext	44		
Cutext-add-hook	21		
cutext-add-hook	21		
cutext-change-unit	21		
cutext-range-sign	14, 24		

print-numerals .....	23	set-option-for .....	20
prop commands:		set-option-for-<unit-key> .....	20
\prop_clear:N .....	44	set-special-sign .....	22
\prop_clear_new:N .....	44	set-unknown-message .....	22
\providecookingunit .....	8, 44	symbol .....	9
<b>R</b>		<b>T</b>	
range-sign .....	24	\thinspace .....	42
recalculate-amount .....	29	\translate .....	44
ref .....	31		
round-half .....	26	<b>U</b>	
round-precision .....	25	use-fmtcount-numerals .....	18
round-to-int .....	26	use-numerals-below .....	23
		use-phrases .....	25
<b>S</b>		\usepackage .....	18
set-cuttext-translation-message .....	22		
set-number-of-persons .....	30	<b>X</b>	
set-option .....	9	xD-lol .....	33