fmtcount.sty: Displaying the Values of LaTeX Counters

Nicola L.C. Talbot
dickimaw-books.com

Vincent Belaïche

Erik Nijenhuis
github.com/Xerdi/fmtcount

2026-11-11 (version 3.13)

Contents

1 Introduction 2

2 Available Commands 3

3 Package Options 8

4 Multilingual Support 9
- 4.1 Options for setting ordinal ending position raise/level . . . 10
- 4.2 Options for French . . . 11
- 4.3 Prefixes . . . 16

5 Configuration File `fmtcount.cfg` 16

6 LaTeX2HTML style 17

7 Miscellaneous 17
- 7.1 Handling of spaces with tailing optional argument . . . 17
- 7.2 Macro naming conventions . . . 18

8 Acknowledgements 18

9 Troubleshooting 18

10 The Code 18
- 10.1 Language definition files . . . 18
  - 10.1.1 fc-american.def . . . 18
  - 10.1.2 fc-brazilian.def . . . 19

10.1.3 fc-british.def . . . 21
10.1.4 fc-dutch.def . . . 21
10.1.5 fc-english.def . . . 29
10.1.6 fc-francais.def . . . 39
10.1.7 fc-french.def . . . 40
10.1.8 fc-frenchb.def . . . 71
10.1.9 fc-german-at-1901.def . . . 72
10.1.10 fc-german-at.def . . . 72
10.1.11 fc-german-austria-1901.def . . . 72
10.1.12 fc-german-austria.def . . . 73
10.1.13 fc-german-ch-1901.def . . . 73
10.1.14 fc-german-ch.def . . . 73
10.1.15 fc-german-de-1901.def . . . 75
10.1.16 fc-german-de.def . . . 75
10.1.17 fc-german-germany-1901.def . . . 76
10.1.18 fc-german-germany.def . . . 76
10.1.19 fc-german-switzerland-1901.def . . . 76
10.1.20 fc-german-switzerland.def . . . 76
10.1.21 fc-german.def . . . 77
10.1.22 fc-germanb.def . . . 87
10.1.23 fc-italian.def . . . 88
10.1.24 fc-ngerman.def . . . 90
10.1.25 fc-ngermanb.def . . . 90
10.1.26 fc-portuges.def . . . 91
10.1.27 fc-portuguese.def . . . 105
10.1.28 fc-spanish.def . . . 106
10.1.29 fc-UKenglish.def . . . 123
10.1.30 fc-USenglish.def . . . 124
10.2 fcnumparser.sty . . . 124
10.3 fcprefix.sty . . . 134
10.4 fmtcount.sty . . . 144
10.4.1 Multilinguage Definitions . . . 170

1 Introduction

The fmtcount package provides commands to display the values of LaTeX counters in a variety of formats. It also provides equivalent commands for actual numbers rather than counter names. Limited multilingual support is available. Currently, there is only support for English, French (including Belgian and Swiss variations), Spanish, Portuguese, German and Italian.

2 Available Commands

The commands can be divided into two categories: those that take the name of a counter as the argument, and those that take a number as the argument.

\ordinal `\ordinal{⟨counter⟩}[⟨gender⟩]`

This will print the value of a LaTeX counter ⟨*counter*⟩ as an ordinal, where the macro

\fmtord `\fmtord{⟨text⟩}`

is used to format the st, nd, rd, th bit. By default the ordinal is formatted as a superscript, if the package option level is used, it is level with the text. For example, if the current section is 2, then `\ordinal{section}` will produce the output: 2nd. Note that the optional argument ⟨*gender*⟩ occurs *at the end*. This argument may only take one of the following values: `m` (masculine), `f` (feminine) or `n` (neuter.) If ⟨*gender*⟩ is omitted, or if the given gender has no meaning in the current language, `m` is assumed.

Notes:

1. the memoir class also defines a command called `\ordinal` which takes a number as an argument instead of a counter. In order to overcome this incompatiblity, if you want to use the fmtcount package with the memoir class you should use

   \FCordinal `\FCordinal`

   to access fmtcount's version of `\ordinal`, and use `\ordinal` to use memoir's version of that command.

2. When the `[⟨gender⟩]` optional argument is omitted, no ignoring of spaces following the final argument occurs. So both `\ordinal{section}␣!` and `\ordinal{section}[m]␣!` will produce: 2nd␣!, where ␣ denotes a space. See § 7.1.

The commands below only work for numbers in the range 0 to 99999.

\ordinalnum `\ordinalnum{⟨n⟩}[⟨gender⟩]`

This is like `\ordinal` but takes an actual number rather than a counter as the argument. For example: `\ordinalnum{2}` will produce: 2nd.

\numberstring `\numberstring{⟨counter⟩}[⟨gender⟩]`

This will print the value of ⟨*counter*⟩ as text. E.g. `\numberstring{section}` will produce: two. The optional argument is the same as that for `\ordinal`.

\Numberstring `\Numberstring{⟨counter⟩}[⟨gender⟩]`

This does the same as \numberstring, but with initial letters in uppercase. For example, \Numberstring{section} will produce: Two.

\NUMBERstring `\NUMBERstring{⟨counter⟩}[⟨gender⟩]`

This does the same as \numberstring, but converts the string to upper case. Note that \MakeUppercase{\Numberstring{⟨counter⟩}} doesn't work, due to the way that \MakeUppercase expands its argument[1].

numberstringnum `\numberstringnum{⟨n⟩}[⟨gender⟩]`

Numberstringnum `\Numberstringnum{⟨n⟩}[⟨gender⟩]`

NUMBERstringnum `\NUMBERstringnum{⟨n⟩}[⟨gender⟩]`

Theses macros work like \numberstring, \Numberstring and \NUMBERstring, respectively, but take an actual number rather than a counter as the argument. For example: \Numberstringnum{105} will produce: One Hundred and Five.

\ordinalstring `\ordinalstring{⟨counter⟩}[⟨gender⟩]`

This will print the value of ⟨*counter*⟩ as a textual ordinal. E.g. \ordinalstring{section} will produce: third. The optional argument is the same as that for \ordinal.

\Ordinalstring `\Ordinalstring{⟨counter⟩}[⟨gender⟩]`

This does the same as \ordinalstring, but with initial letters in uppercase. For example, \Ordinalstring{section} will produce: Second.

\ORDINALstring `\ORDINALstring{⟨counter⟩}[⟨gender⟩]`

This does the same as \ordinalstring, but with all words in upper case (see previous note about \MakeUppercase).

rdinalstringnum `\ordinalstringnum{⟨n⟩}[⟨gender⟩]`

rdinalstringnum `\Ordinalstringnum{⟨n⟩}[⟨gender⟩]`

[1] See all the various postings to comp.text.tex about \MakeUppercase

RDINALstringnum `\ORDINALstringnum{⟨n⟩}[⟨gender⟩]`

These macros work like \ordinalstring, \Ordinalstring and \ORDINALstring, respectively, but take an actual number rather than a counter as the argument. For example, \ordinalstringnum{2} will produce: second.

As from version 1.09, textual representations can be stored for later use. This overcomes the problems encountered when you attempt to use one of the above commands in \edef.

Each of the following commands takes a label as the first argument, the other arguments are as the analogous commands above. These commands do not display anything, but store the textual representation. This can later be retrieved using

\FMCuse `\FMCuse{⟨label⟩}`

Note: with \storeordinal and \storeordinalnum, the only bit that doesn't get expanded is \fmtord. So, for example, \storeordinalnum{mylabel}{3} will be stored as 3\relax \fmtord{rd}.

\storeordinal `\storeordinal{⟨label⟩}{⟨counter⟩}[⟨gender⟩]`

oreordinalstring `\storeordinalstring{⟨label⟩}{⟨counter⟩}[⟨gender⟩]`

oreOrdinalstring `\storeOrdinalstring{⟨label⟩}{⟨counter⟩}[⟨gender⟩]`

oreORDINALstring `\storeORDINALstring{⟨label⟩}{⟨counter⟩}[⟨gender⟩]`

orenumberstring `\storenumberstring{⟨label⟩}{⟨counter⟩}[⟨gender⟩]`

oreNumberstring `\storeNumberstring{⟨label⟩}{⟨counter⟩}[⟨gender⟩]`

oreNUMBERstring `\storeNUMBERstring{⟨label⟩}{⟨counter⟩}[⟨gender⟩]`

storeordinalnum `\storeordinalnum{⟨label⟩}{⟨number⟩}[⟨gender⟩]`

oreordinalstringnum `\storeordinalstringnum{⟨label⟩}{⟨number⟩}[⟨gender⟩]`

oreOrdinalstringnum `\storeOrdinalstringnum{⟨label⟩}{⟨number⟩}[⟨gender⟩]`

oreORDINALstringnum `\storeORDINALstringnum{⟨label⟩}{⟨number⟩}[⟨gender⟩]`

orenumberstringnum `\storenumberstringnum{⟨label⟩}{⟨number⟩}[⟨gender⟩]`

oreNumberstringnum `\storeNumberstringnum{⟨label⟩}{⟨number⟩}[⟨gender⟩]`

oreNUMBERstringnum `\storeNUMBERstringnum{⟨label⟩}{⟨number⟩}[⟨gender⟩]`

\binary `\binary{⟨counter⟩}`

This will print the value of ⟨*counter*⟩ as a binary number. E.g. `\binary{section}` will produce: 10. The declaration

\padzeroes `\padzeroes[⟨n⟩]`

will ensure numbers are written to ⟨*n*⟩ digits, padding with zeroes if necessary. E.g. `\padzeroes[8]\binary{section}` will produce: 00000010. The default value for ⟨*n*⟩ is 17.

\binarynum `\binarynum{⟨n⟩}`

This is like `\binary` but takes an actual number rather than a counter as the argument. For example: `\binarynum{5}` will produce: 101.

The octal commands only work for values in the range 0 to 32768.

\octal `\octal{⟨counter⟩}`

This will print the value of ⟨*counter*⟩ as an octal number. For example, if you have a counter called, say `mycounter`, and you set the value to 125, then `\octal{mycounter}` will produce: 177. Again, the number will be padded with zeroes if necessary, depending on whether `\padzeroes` has been used.

\octalnum `\octalnum{⟨n⟩}`

This is like `\octal` but takes an actual number rather than a counter as the argument. For

example: \octalnum{125} will produce: 177.

\hexadecimal

\hexadecimal{⟨*counter*⟩}

This will print the value of ⟨*counter*⟩ as a hexadecimal number. Going back to the counter used in the previous example, \hexadecimal{mycounter} will produce: 7d. Again, the number will be padded with zeroes if necessary, depending on whether \padzeroes has been used.

\HEXADecimal

\HEXADecimal{⟨*counter*⟩}

This does the same thing, but uses uppercase characters, e.g. \HEXADecimal{mycounter} will produce: 7D.

\Hexadecimal The macro \Hexadecimal is a deprecated alias of \HEXADecimal. Its name was confusing so it was changed. See 7.2.

\hexadecimalnum

\hexadecimalnum{⟨*n*⟩}

\HEXADecimalnum

\HEXADecimalnum{⟨*n*⟩}

These are like \hexadecimal and \Hexadecimal but take an actual number rather than a counter as the argument. For example: \hexadecimalnum{125} will produce: 7d, and \HEXADecimalnum{125} will produce: 7D.

\Hexadecimalnum The macro \Hexadecimalnum is a deprecated alias of \HEXADecimalnum. Its name was confusing so it was changed. See 7.2.

\decimal

\decimal{⟨*counter*⟩}

This is similar to \arabic but the number can be padded with zeroes depending on whether \padzeroes has been used. For example: \padzeroes[8]\decimal{section} will produce: 00000002 still assuming current section is section 2.

\decimalnum

\decimalnum{⟨*n*⟩}

This is like \decimal but takes an actual number rather than a counter as the argument. For example: \padzeroes[8]\decimalnum{5} will produce: 00000005.

\aaalph

\aaalph{⟨*counter*⟩}

This will print the value of ⟨*counter*⟩ as: a b … z aa bb … zz etc. For example, \aaalph{mycounter} will produce: uuuuu if mycounter is set to 125.

\AAAlph

\AAAlph{⟨*counter*⟩}

This does the same thing, but uses uppercase characters, e.g. `\AAAlph{mycounter}` will produce: UUUUU.

`\aaalphnum` `\aaalphnum{⟨n⟩}`

`\AAAlphnum` `\AAAlphnum{⟨n⟩}`

These macros are like `\aaalph` and `\AAAlph` but take an actual number rather than a counter as the argument. For example: `\aaalphnum{125}` will produce: uuuuu, and `\AAAlphnum{125}` will produce: UUUUU.

The abalph commands described below only work for values in the range 0 to 17576.

`\abalph` `\abalph{⟨counter⟩}`

This will print the value of ⟨*counter*⟩ as: a b ... z aa ab ... az etc. For example, `\abalpha{mycounter}` will produce: du if `mycounter` is set to 125.

`\ABAlph` `\ABAlph{⟨counter⟩}`

This does the same thing, but uses uppercase characters, e.g. `\ABAlph{mycounter}` will produce: DU.

`\abalphnum` `\abalphnum{⟨n⟩}`

`\ABAlphnum` `\ABAlphnum{⟨n⟩}`

These macros are like `\abalph` and `\ABAlph` but take an actual number rather than a counter as the argument. For example: `\abalphnum{125}` will produce: du, and `\ABAlphnum{125}` will produce: DU.

3 Package Options

The following options can be passed to this package:

⟨***dialect***⟩ load language ⟨*dialect*⟩, supported ⟨*dialect*⟩ are the same as passed to `\FCloadlang`, see 4

raise make ordinal st,nd,rd,th appear as superscript

level make ordinal st,nd,rd,th appear level with rest of text

Options raise and level can also be set using the command:

countsetoptions `\fmtcountsetoptions{fmtord=⟨type⟩}`

where ⟨*type*⟩ is either `level` or `raise`. Since version 3.01 of fmtcount, it is also possible to set ⟨*type*⟩ on a language by language basis, see § 4.

4 Multilingual Support

Version 1.02 of the fmtcount package now has limited multilingual support. The following languages are implemented: English, Spanish, Portuguese, French, French (Swiss) and French (Belgian). German support was added in version 1.1.[2] Italian support was added in version 1.31.[3]

Actually, fmtcount has two modes:

- a multilingual mode, in which the commands `\numberstring`, `\ordinalstring`, `\ordinal`, and their variants will be formatted in the currently selected language, as per the `\languagename` macro set by babel, polyglossia or suchlikes, and
- a default mode for backward compatibility in which these commands are formatted in English irrespective of `\languagename`, and to which fmtcount falls back when it cannot detects packages such as babel or polyglossia are loaded.

For multilingual mode, fmtcount needs to load correctly the language definition for document dialects. To do this use

`\FCloadlang` `\FCloadlang{⟨dialect⟩}`

in the preamble — this will both switch on multilingual mode, and load the ⟨*dialect*⟩ definition. The ⟨*dialect*⟩ should match the options passed to babel or polyglossia. fmtcount currently supports the following ⟨*dialect*⟩'s: `english`, `UKenglish`, `brazilian`, `british`, `USenglish`, `american`, `spanish`, `portuges`, `portuguese`, `french`, `frenchb`, `francais`, `german`, `germanb`, `ngerman`, `ngermanb`, `german-de`, `german-germany`, `german-at`, `german-austria`, `german-de-1901`, `german-germany-1901`, `german-at-1901`, `german-austria-1901`, `german-ch`, `german-switzerland`, `german-ch-1901`, `german-switzerland-1901`, `italian`, and `dutch`.

If you don't use `\FCloadlang`, fmtcount will attempt to detect the required dialects and call `\FCloadlang` for you, but this isn't guaranteed to work. Notably, when `\FCloadlang` is not used and fmtcount has switched on multilingual mode, but without detecting the needed dialects in the preamble, and fmtcount has to format a number for a dialect for which definition has not been loaded (via `\FCloadlang` above), then if fmtcount detects a definition file for this dialect it will attempt to load it, and cause an error otherwise. This loading in body has not been tested extensively, and may may cause problems such as spurious spaces insertion before the first formatted number, so it's best to use `\FCloadlang` explicitely in the preamble.

[2] Thanks to K. H. Fricke for supplying the information.
[3] Thanks to Edoardo Pasca for supplying the information.

If the French language is selected, the `french` option let you configure the dialect and other aspects. The `abbr` also has some influence with French. Please refer to § 4.2.

The male gender for all languages is used by default, however the feminine or neuter forms can be obtained by passing `f` or `n` as an optional argument to `\ordinal`, `\ordinalnum` etc. For example: `\numberstring{section}[f]`. Note that the optional argument comes *after* the compulsory argument. If a gender is not defined in a given language, the masculine version will be used instead.

Let me know if you find any spelling mistakes (has been known to happen in English, let alone other languages with which I'm not so familiar.) If you want to add support for another language, you will need to let me know how to form the numbers and ordinals from 0 to 99999 in that language for each gender.

4.1 Options for setting ordinal ending position raise/level

countsetoptions

```
\fmtcountsetoptions{⟨language⟩={fmtord=⟨type⟩}}
```

where ⟨*language*⟩ is one of the supported language ⟨*type*⟩ is either `level` or `raise` or `undefine`. If the value is `level` or `raise`, then that will set the `fmtord` option accordingly[4] only for that language ⟨*language*⟩. If the value is `undefine`, then the non-language specific behaviour is followed.

Some ⟨*language*⟩ are synonyms, here is a table:

language	**alias(es)**
english	british
french	frenchb
german	germanb ngerman ngermanb german-de german-germany german-at german-austria german-de-1901 german-germany-1901 german-at-1901 german-austria-1901 german-ch german-switzerland german-ch-1901 german-switzerland-1901
USenglish	american

[4] see § 3

Beware that the four Swiss dialects — `german-ch`, `german-switzerland` and their `-1901` variants — are synonyms of `german` as far as these options are concerned, but not as far as spelling is concerned: Swiss German writes `ss` where the German and Austrian dialects write ß, so `\numberstring` gives `dreissig` rather than `dreißig`.

4.2 Options for French

This section is in French, as it is most useful to French speaking people.

Il est possible de configurer plusieurs aspects de la numérotation en français avec les options `french` et `abbr`. Ces options n'ont d'effet que si le langage `french` est chargé.

`\fmtcountsetoptions` `\fmtcountsetoptions{french={⟨french options⟩}}`

L'argument ⟨*french options*⟩ est une liste entre accolades et séparée par des virgules de réglages de la forme "⟨*clef*⟩=⟨*valeur*⟩", chacun de ces réglages est ci-après désigné par "option française" pour le distinguer des "options générales" telles que `french`.

Le dialecte peut être sélectionné avec l'option française `dialect` dont la valeur ⟨*dialect*⟩ peut être `france`, `belgian` ou `swiss`.

`dialect` `\fmtcountsetoptions{french={dialect={⟨dialect⟩}}}`

`french` `\fmtcountsetoptions{french=⟨dialect⟩}`

Pour alléger la notation et par souci de rétro-compatibilité `france`, `belgian` ou `swiss` sont également des ⟨*clef*⟩s pour ⟨*french options*⟩ à utiliser sans ⟨*valeur*⟩.

L'effet de l'option `dialect` est illustré ainsi :

france	soixante-dix pour 70, quatre-vingts pour 80, et quatre-vingts-dix pour 90,
belgian	septante pour 70, quatre-vingts pour 80, et nonante pour 90,
swiss	septante pour 70, huitante[5] pour 80, et nonante pour 90.

Il est à noter que la variante `belgian` est parfaitement correcte pour les francophones français[6], et qu'elle est également utilisée en Suisse Romande hormis dans les cantons de Vaud, du Valais et de Fribourg. En ce qui concerne le mot "octante", il n'est actuellement pas pris en charge et n'est guère plus utilisé, ce qui est sans doute dommage car il est sans doute plus acceptable que le "huitante" de certains de nos amis suisses.

`abbr` `\fmtcountsetoptions{abbr=⟨boolean⟩}`

L'option générale `abbr` permet de changer l'effet de `\ordinal`. Selon ⟨*boolean*⟩ on a :

true	pour produire des ordinaux de la forme 2e (par défaut), ou
false	pour produire des ordinaux de la forme 2ème.

[5] voir Octante et huitante sur le site d'Alain Lassine

[6] je précise que l'auteur de ces lignes est français

vingt plural `\fmtcountsetoptions{french={vingt plural=⟨french plural control⟩}}`

cent plural `\fmtcountsetoptions{french={cent plural=⟨french plural control⟩}}`

mil plural `\fmtcountsetoptions{french={mil plural=⟨french plural control⟩}}`

n-illion plural `\fmtcountsetoptions{french={n-illion plural=⟨french plural control⟩}}`

-illiard plural `\fmtcountsetoptions{french={n-illiard plural=⟨french plural control⟩}}`

all plural `\fmtcountsetoptions{french={all plural=⟨french plural control⟩}}`

Les options `vingt plural`, `cent plural`, `mil plural`, `n-illion plural`, et `n-illiard plural`, permettent de contrôler très finement l'accord en nombre des mots respectivement vingt, cent, mil, et des mots de la forme ⟨*n*⟩illion et ⟨*n*⟩illiard, où ⟨*n*⟩ désigne 'm' pour 1, 'b' pour 2, 'tr' pour 3, etc. L'option `all plural` est un raccourci permettant de contrôler de concert l'accord en nombre de tous ces mots. Tous ces paramètres valent `reformed` par défaut.

Attention, comme on va l'expliquer, seules quelques combinaisons de configurations de ces options donnent une orthographe correcte vis-à-vis des règles en vigueur. La raison d'être de ces options est la suivante :

- la règle de l'accord en nombre des noms de nombre dans un numéral cardinal dépend de savoir s'il a vraiment une valeur cardinale ou bien une valeur ordinale, ainsi on écrit « aller à la page deux-cent (sans s) d'un livre de deux-cents (avec s) pages », il faut donc pouvoir changer la configuration pour sélectionner le cas considéré,
- un autre cas demandant quelque configurabilité est celui de « mil » et « mille ». Pour rappel « mille » est le pluriel irrégulier de « mil », mais l'alternance mil/mille est rare, voire pédante, car aujourd'hui « mille » n'est utilisé que comme un mot invariable, en effet le sort des pluriels étrangers est systématiquement de finir par disparaître comme par exemple « scénarii » aujourd'hui supplanté par « scénarios ». Pour continuer à pouvoir écrire « mil », il aurait fallu former le pluriel comme « mils », ce qui n'est pas l'usage. Certaines personnes utilisent toutefois encore « mil » dans les dates, par exemple « mil neuf cent quatre-vingt quatre » au lieu de « mille neuf cent quatre-vingt quatre »,
- finalement les règles du français quoique bien définies ne sont pas très cohérentes et il est donc inévitable qu'un jour ou l'autre on les simplifie. Le paquetage fmtcount est déjà prêt à cette éventualité.

Le paramètre ⟨*french plural control*⟩ peut prendre les valeurs suivantes :

traditional	pour sélectionner la règle en usage chez les adultes à la date de parution de ce document, et dans le cas des numéraux cardinaux, lorsqu'ils ont une valeur cardinale,
reformed	pour suivre toute nouvelle recommandation à la date de parution de ce document, et dans le cas des numéraux cardinaux, lorsqu'ils ont une valeur cardinale, l'idée des options `traditional` et `reformed` est donc de pouvoir contenter à la fois les anciens et les modernes, mais à dire vrai à la date où ce document est écrit elles ont exactement le même effet,
traditional o	pareil que `traditional` mais dans le cas des numéraux cardinaux, lorsqu'ils ont une valeur ordinale,
reformed o	pareil que `reformed` mais dans le cas des numéraux cardinaux, lorsqu'ils ont une valeur ordinale, de même que précédemment `reformed o` et `traditional o` ont exactement le même effet,
always	pour marquer toujours le pluriel, ceci n'est correct que pour « mil » vis-à-vis des règles en vigueur,
never	pour ne jamais marquer le pluriel, ceci est incorrect vis-à-vis des règles d'orthographe en vigueur,
multiple	pour marquer le pluriel lorsque le nombre considéré est multiplié par au moins 2, ceci est la règle en vigueur pour les nombres de la forme ⟨*n*⟩illion et ⟨*n*⟩illiard lorsque le nombre a une valeur cardinale,
multiple g-last	pour marquer le pluriel lorsque le nombre considéré est multiplié par au moins 2 et est ***g****lobalement* en dernière position, où "globalement" signifie qu'on considère le nombre formaté en entier, ceci est incorrect vis-à-vis des règles d'orthographe en vigueur,
multiple l-last	pour marquer le pluriel lorsque le nombre considéré est multiplié par au moins 2 et est ***l****ocalement* en dernière position, où "localement" signifie qu'on considère seulement la portion du nombre qui multiplie soit l'unité, soit un ⟨*n*⟩illion ou un ⟨*n*⟩illiard ; ceci est la convention en vigueur pour le pluriel de "vingt" et de "cent" lorsque le nombre formaté a une valeur cardinale,
multiple lng-last	pour marquer le pluriel lorsque le nombre considéré est multiplié par au moins 2 et est ***l****ocalement* mais ***n****on* ***g****lobablement* en dernière position, où "localement" et *globablement* on la même siginification que pour les options `multiple g-last` et `multiple l-last` ; ceci est la convention en vigueur pour le pluriel de "vingt" et de "cent" lorsque le nombre formaté a une valeur ordinale,

multiple ng-last pour marquer le pluriel lorsque le nombre considéré est multiplié par au moins 2, et ***n***'est pas ***g****lobalement* en dernière position, où "globalement" a la même signification que pour l'option `multiple g-last`; ceci est la règle que j'infère être en vigueur pour les nombres de la forme ⟨*n*⟩illion et ⟨*n*⟩illiard lorsque le nombre a une valeur ordinale, mais à dire vrai pour des nombres aussi grands, par exemple « deux millions », je pense qu'il n'est tout simplement pas d'usage de dire « l'exemplaire deux million(s ?) » pour « le deux millionième exemplaire ».

L'effet des paramètres `traditional`, `traditional o`, `reformed`, et `reformed o`, est le suivant :

<table>
<tr><th>⟨x⟩ dans "⟨x⟩ plural"</th><th>traditional</th><th>reformed</th><th>traditional o</th><th>reformed o</th></tr>
<tr><td>vingt</td><td colspan="2" rowspan="2">multiple l-last</td><td colspan="2" rowspan="2">multiple lng-last</td></tr>
<tr><td>cent</td></tr>
<tr><td>mil</td><td colspan="4">always</td></tr>
<tr><td>n-illion</td><td colspan="2" rowspan="2">multiple</td><td colspan="2" rowspan="2">multiple ng-last</td></tr>
<tr><td>n-illiard</td></tr>
</table>

Les configurations qui respectent les règles d'orthographe sont les suivantes :

- `\fmtcountsetoptions{french={all plural=reformed o}}` pour formater les numéraux cardinaux à valeur ordinale,
- `\fmtcountsetoptions{french={mil plural=multiple}}` pour activer l'alternance mil/mille.
- `\fmtcountsetoptions{french={all plural=reformed}}` pour revenir dans la configuration par défaut.

dash or space `\fmtcountsetoptions{french={dash or space=`⟨*dash or space*⟩`}}`

Avant la réforme de l'orthographe de 1990, on ne met des traits d'union qu'entre les dizaines et les unités, et encore sauf quand le nombre n considéré est tel que $n \mod 10 = 1$, dans ce cas on écrit "et un" sans trait d'union. Après la réforme de 1990, on recommande de mettre des traits d'union de partout sauf autour de "mille", "million" et "milliard", et les mots analogues comme "billion", "billiard". Cette exception a toutefois été contestée par de nombreux auteurs, et on peut aussi mettre des traits d'union de partout. Mettre l'option ⟨*dash or space*⟩ à :

traditional	pour sélectionner la règle d'avant la réforme de 1990,
1990	pour suivre la recommandation de la réforme de 1990,
reformed	pour suivre la recommandation de la dernière réforme prise en charge, actuellement l'effet est le même que 1990, ou à
always	pour mettre systématiquement des traits d'union de partout.

Par défaut, l'option vaut `reformed`.

scale `\fmtcountsetoptions{french={scale=`⟨*scale*⟩`}}`

L'option `scale` permet de configurer l'écriture des grands nombres. Mettre ⟨*scale*⟩ à :

recursive	dans ce cas 10^{30} donne mille milliards de milliards de milliards, pour 10^n, on écrit $10^{n-9\times\max\{(n\div 9)-1,0\}}$ suivi de la répétition $\max\{(n\div 9)-1,0\}$ fois de "de milliards"
long	$10^{6\times n}$ donne un ⟨*n*⟩illion où ⟨*n*⟩ est remplacé par "bi" pour 2, "tri" pour 3, etc. et $10^{6\times n+3}$ donne un ⟨*n*⟩illiard avec la même convention pour ⟨*n*⟩. L'option `long` est correcte en Europe, par contre j'ignore l'usage au Québec.
short	$10^{6\times n}$ donne un ⟨*n*⟩illion où ⟨*n*⟩ est remplacé par "bi" pour 2, "tri" pour 3, etc. L'option `short` est incorrecte en Europe.

Par défaut, l'option vaut `recursive`.

`n-illiard upto` `\fmtcountsetoptions{french={n-illiard upto=⟨n-illiard upto⟩}}`

Cette option n'a de sens que si `scale` vaut `long`. Certaines personnes préfèrent dire "mille ⟨*n*⟩illions" qu'un "⟨*n*⟩illiard". Mettre l'option `n-illiard upto` à :

infinity	pour que $10^{6\times n+3}$ donne ⟨*n*⟩illiards pour tout $n>0$,
infty	même effet que `infinity`,
k	où k est un entier quelconque strictement positif, dans ce cas $10^{6\times n+3}$ donne "mille ⟨*n*⟩illions" lorsque $n>k$, et donne "⟨*n*⟩illiard" sinon

`mil plural mark` `\fmtcountsetoptions{french={mil plural mark=⟨any text⟩}}`

La valeur par défaut de cette option est « `le` ». Il s'agit de la terminaison ajoutée à « mil » pour former le pluriel, c'est à dire « mille », cette option ne sert pas à grand chose sauf dans l'éventualité où ce pluriel serait francisé un jour — à dire vrai si cela se produisait une alternance mille/milles est plus vraisemblable, car « mille » est plus fréquent que « mil » et que les pluriels francisés sont formés en ajoutant « s » à la forme la plus fréquente, par exemple « blini/blinis », alors que « blini » veut dire « crêpes » (au pluriel).

4.3 Prefixes

`\latinnumeralstring` `\latinnumeralstring{⟨counter⟩}[⟨prefix options⟩]`

`\latinnumeralstringnum` `\latinnumeralstringnum{⟨number⟩}[⟨prefix options⟩]`

5 Configuration File `fmtcount.cfg`

You can save your preferred default settings to a file called `fmtcount.cfg`, and place it on the TEX path. These settings will then be loaded by the fmtcount package.

Note that if you are using the datetime package, the `datetime.cfg` configuration file will override the `fmtcount.cfg` configuration file. For example, if `datetime.cfg` has the line:

```
\renewcommand{\fmtord}[1]{\textsuperscript{\underline{#1}}}
```

and if `fmtcount.cfg` has the line:

```
\fmtcountsetoptions{fmtord=level}
```

then the former definition of `\fmtord` will take precedence.

6 LaTeX2HTML style

The LaTeX2HTML style file `fmtcount.perl` is provided. The following limitations apply:

- `\padzeroes` only has an effect in the preamble.
- The configuration file `fmtcount.cfg` is currently ignored. (This is because I can't work out the correct code to do this. If you know how to do this, please let me know.) You can however do:

  ```
  \usepackage{fmtcount}
  \html{\input{fmtcount.cfg}}
  ```

  This, I agree, is an unpleasant cludge.

7 Miscellaneous

7.1 Handling of spaces with tailing optional argument

Quite some of the commands in fmtcount have a tailing optional argument, notably a `[`⟨*gender*⟩`]` argument, which is due to historical reasons, and is a little unfortunate.

When the tailing optional argument is omitted, then any subsequent space will:

- `not` be gobbled if the command make some typset output, like `\ordinal` or `\numbestring`, and
- be gobbled if the command stores a number into a label like `\storeordinalnum` or `\storenumberstring`, or make some other border effect like `\padzeroes` without any typeset output.

So (where we use visible spaces "␣" to demonstrate the point):

- "x`\ordinalnum{2}`␣x" will be typeset to "x2nd␣x", while
- "x`\storeordinalnum{mylabel}{2}`␣x" will be typeset to "xx".

The reason for this design choice is that the commands like like `\ordinal` or `\numbestring` are usually inserted in the flow of text, and one usually does not want subsequent spaces gobbled, while the commands like `\storeordinalnum` or `\storenumberstring` usually stands on their own line, and one usually does not want the tailing end-of-line to produce an extra-space.

7.2 Macro naming conventions

Macros that refer to upper-casing have upper case only in the main part of their name. That is to say the words “store”, “string” or “num” are not upper-cased for instance in `\storeORDINALstringnum`, `\storeOrdinalstringnum` or in `\NUMBERstringnum`.

Furthermore, when upper-casing all the number letters is considered, the main part of the name is:

- all in upper-case when it consist of a single word that is not composed of a prefix+radix, for instance “ORDINAL” or “NUMBER”, and
- with the prefix all in upper-case, and only the first letter of the radix in upper-case for words that consist of a prefix+radix, for instance “HEXADecimal” or “AAAlph” because they can be considered as a prefix+radix construct “hexa+decimal” or “aa+alph”.

Observance of this rule is the reason why macros `\Hexadecimal` and `\Hexadecimalnum` were respectively renamed as `\HEXADecimal` and `\HEXADecimalnum` from v3.06.

8 Acknowledgements

I would like to thank all the people who have provided translations and made bug reports.

9 Troubleshooting

Bug reporting should be done via the GitHub issue manager at:
github.com/Xerdi/fmtcount/issues/.

10 The Code

10.1 Language definition files

10.1.1 fc-american.def

American English definitions

```
\ProvidesFCLanguage{american}[2016/01/12]%
```

Loaded fc-USenglish.def if not already loaded

```
\FCloadlang{USenglish}%
```

These are all just synonyms for the commands provided by fc-USenglish.def.

```
\global\let\@ordinalMamerican\@ordinalMUSenglish
\global\let\@ordinalFamerican\@ordinalMUSenglish
\global\let\@ordinalNamerican\@ordinalMUSenglish
\global\let\@numberstringMamerican\@numberstringMUSenglish
\global\let\@numberstringFamerican\@numberstringMUSenglish
\global\let\@numberstringNamerican\@numberstringMUSenglish
\global\let\@NumberstringMamerican\@NumberstringMUSenglish
```

```
\global\let\@NumberstringFamerican\@NumberstringMUSenglish
\global\let\@NumberstringNamerican\@NumberstringMUSenglish
\global\let\@ordinalstringMamerican\@ordinalstringMUSenglish
\global\let\@ordinalstringFamerican\@ordinalstringMUSenglish
\global\let\@ordinalstringNamerican\@ordinalstringMUSenglish
\global\let\@OrdinalstringMamerican\@OrdinalstringMUSenglish
\global\let\@OrdinalstringFamerican\@OrdinalstringMUSenglish
\global\let\@OrdinalstringNamerican\@OrdinalstringMUSenglish
```

10.1.2 fc-brazilian.def

Brazilian definitions.

```
\ProvidesFCLanguage{brazilian}[2017/12/26]%
```

Load fc-portuges.def if not already loaded.

```
\FCloadlang{portuges}%
```

Set `brazilian` to be equivalent to `portuges` for all the numeral ordinals, and string ordinals.

```
\global\let\@ordinalMbrazilian=\@ordinalMportuges
\global\let\@ordinalFbrazilian=\@ordinalFportuges
\global\let\@ordinalNbrazilian=\@ordinalNportuges
\global\let\@ordinalstringFbrazilian\@ordinalstringFportuges
\global\let\@ordinalstringMbrazilian\@ordinalstringMportuges
\global\let\@ordinalstringNbrazilian\@ordinalstringMportuges
\global\let\@OrdinalstringMbrazilian\@OrdinalstringMportuges
\global\let\@OrdinalstringFbrazilian\@OrdinalstringFportuges
\global\let\@OrdinalstringNbrazilian\@OrdinalstringMportuges
```

Convert a number to a textual representation. To make it easier, split it up into units, tens, teens and hundreds. Units, tens, and hundreds are the same as for `portuges` and are not redefined, only the teens are Brazilian specific.
Teens (argument must be a number from 0 to 9):

```
\newcommand*\@@teenstringbrazilian[1]{%
  \ifcase#1\relax
    dez%
    \or onze%
    \or doze%
    \or treze%
    \or quatorze%
    \or quinze%
    \or dezesseis%
    \or dezessete%
    \or dezoito%
    \or dezenove%
  \fi
}%
\global\let\@@teenstringbrazilian\@@teenstringbrazilian
```

Teens (with initial letter in upper case):

```
\newcommand*\@@Teenstringbrazilian[1]{%
```

```
  \ifcase#1\relax
    Dez%
    \or Onze%
    \or Doze%
    \or Treze%
    \or Quatorze%
    \or Quinze%
    \or Dezesseis%
    \or Dezessete%
    \or Dezoito%
    \or Dezenove%
  \fi
}%
\global\let\@@Teenstringbrazilian\@@Teenstringbrazilian
```

This has changed in version 1.08, so that it now stores the result in the second argument, but doesn't display anything. Since it only affects internal macros, it shouldn't affect documents created with older versions. (These internal macros are not meant for use in documents.)

```
\newcommand*{\@numberstringMbrazilian}[2]{%
  \let\@unitstring=\@@unitstringportuges
  \let\@teenstring=\@@teenstringbrazilian
  \let\@tenstring=\@@tenstringportuges
  \let\@hundredstring=\@@hundredstringportuges
  \def\@hundred{cem}\def\@thousand{mil}%
  \def\@andname{e}%
  \@@numberstringportuges{#1}{#2}%
}%
\global\let\@numberstringMbrazilian\@numberstringMbrazilian
```

As above, but feminine form:

```
\newcommand*{\@numberstringFbrazilian}[2]{%
  \let\@unitstring=\@@unitstringFportuges
  \let\@teenstring=\@@teenstringbrazilian
  \let\@tenstring=\@@tenstringportuges
  \let\@hundredstring=\@@hundredstringFportuges
  \def\@hundred{cem}\def\@thousand{mil}%
  \def\@andname{e}%
  \@@numberstringportuges{#1}{#2}%
}%
\global\let\@numberstringFbrazilian\@numberstringFbrazilian
```

Make neuter same as masculine:

```
\global\let\@numberstringNbrazilian\@numberstringMbrazilian
```

As above, but initial letters in upper case:

```
\newcommand*{\@NumberstringMbrazilian}[2]{%
  \let\@unitstring=\@@unitstringportuges
  \let\@teenstring=\@@Teenstringbrazilian
  \let\@tenstring=\@@Tenstringportuges
  \let\@hundredstring=\@@hundredstringportuges
  \def\@hundred{Cem}\def\@thousand{Mil}%
```

```
  \def\@andname{e}%
  \@@numberstringportuges{#1}{#2}%
}%
\global\let\@NumberstringMbrazilian\@NumberstringMbrazilian
```

As above, but feminine form:

```
\newcommand*{\@NumberstringFbrazilian}[2]{%
  \let\@unitstring=\@@UnitstringFportuges
  \let\@teenstring=\@@Teenstringbrazilian
  \let\@tenstring=\@@Tenstringportuges
  \let\@hundredstring=\@@HundredstringFportuges
  \def\@hundred{Cem}\def\@thousand{Mil}%
  \def\@andname{e}%
  \@@numberstringportuges{#1}{#2}%
}%
\global\let\@NumberstringFbrazilian\@NumberstringFbrazilian
```

Make neuter same as masculine:

```
\global\let\@NumberstringNbrazilian\@NumberstringMbrazilian
```

10.1.3 fc-british.def

British definitions

```
\ProvidesFCLanguage{british}[2013/08/17]%
```

Load fc-english.def, if not already loaded

```
\FCloadlang{english}%
```

These are all just synonyms for the commands provided by fc-english.def.

```
\global\let\@ordinalMbritish\@ordinalMenglish
\global\let\@ordinalFbritish\@ordinalMenglish
\global\let\@ordinalNbritish\@ordinalMenglish
\global\let\@numberstringMbritish\@numberstringMenglish
\global\let\@numberstringFbritish\@numberstringMenglish
\global\let\@numberstringNbritish\@numberstringMenglish
\global\let\@NumberstringMbritish\@NumberstringMenglish
\global\let\@NumberstringFbritish\@NumberstringMenglish
\global\let\@NumberstringNbritish\@NumberstringMenglish
\global\let\@ordinalstringMbritish\@ordinalstringMenglish
\global\let\@ordinalstringFbritish\@ordinalstringMenglish
\global\let\@ordinalstringNbritish\@ordinalstringMenglish
\global\let\@OrdinalstringMbritish\@OrdinalstringMenglish
\global\let\@OrdinalstringFbritish\@OrdinalstringMenglish
\global\let\@OrdinalstringNbritish\@OrdinalstringMenglish
```

10.1.4 fc-dutch.def

Dutch definitions, initially added by Erik Nijenhuis.

```
\ProvidesFCLanguage{dutch}[2024/01/27]%
```

Define macro that converts a number or count register (first argument) to a numeric ordinal, and stores the result in the second argument, which should be a control sequence. Dutch numeric ordinals use “ste” for multiples of 10 from 20 upward (e.g., 20ste, 30ste, 100ste, 120ste), and “e” for all other numbers (e.g., 1e, 10e, 18e, 21e, 101e).

```
\newcommand{\@ordinalMdutch}[2]{%
  \@tempcnta=#1\relax
  \@FCmodulo{\@tempcnta}{10}%
  \ifnum\@tempcnta=0\relax
    \ifnum#1<20\relax
      \edef#2{\number#1\relax e}%
    \else
      \edef#2{\number#1\relax ste}%
    \fi
  \else
    \edef#2{\number#1\relax e}%
  \fi
}%
\global\let\@ordinalMdutch\@ordinalMdutch
```

Like English, there is no gender difference in Dutch, so make feminine and neuter the same as the masculine.

```
\global\let\@ordinalFdutch\@ordinalMdutch
\global\let\@ordinalNdutch\@ordinalMdutch
```

Define the macro that prints the value of a TEX count register as text. To make it easier, break it up into units, teens and tens. First, the units: the argument should be between 0 and 9 inclusive.

```
\newcommand*\@@unitstringdutch[1]{%
    \ifcase#1%
    nul%
    \or een% één and \’e\’en not working atm
    \or twee%
    \or drie%
    \or vier%
    \or vijf%
    \or zes%
    \or zeven%
    \or acht%
    \or negen%
    \fi
}%
\global\let\@@unitstringdutch\@@unitstringdutch
```

Next the tens, again the argument should be between 0 and 9 inclusive.

```
\global\let\@@unitstringdutch\@@unitstringdutch
\newcommand*\@@tenstringdutch[1]{%
    \ifcase#1%
    \or tien%
    \or twintig%
    \or dertig%
```

```
    \or veertig%
    \or vijftig%
    \or zestig%
    \or zeventig%
    \or tachtig%
    \or negentig%
    \or honderd%
    \fi
}%
\global\let\@@tenstringdutch\@@tenstringdutch
```

Finally the teens, again the argument should be between 0 and 9 inclusive.

```
\newcommand*\@@teenstringdutch[1]{%
    \ifcase#1%
    tien%
    \or elf%
    \or twaalf%
    \or dertien%
    \or veertien%
    \or vijftien%
    \or zestien%
    \or zeventien%
    \or achttien%
    \or negentien%
    \fi
}%
\global\let\@@teenstringdutch\@@teenstringdutch
```

Hunderd and thousand:

```
\providecommand*{\honderd}{honderd}%
\providecommand*{\duizend}{duizend}%
\global\let\honderd\honderd
\global\let\duizend\duizend
```

The numberstring implementation. Converts numbers to Dutch words (e.g., 18 becomes "achttien", 100 becomes "honderd"). Supports numbers from 0 to 99999.

```
\newcommand*\@@numberstringdutch[2]{%
    \ifnum#1>99999\relax
    \PackageError{fmtcount}{Out of range}%
    {This macro only works for values less than 100000}%
    \else
    \ifnum#1<0\relax
    \PackageError{fmtcount}{Negative numbers not permitted}%
    {This macro does not work for negative numbers, however
    you can try typing "minus" first, and then pass the modulus of
    this number}%
    \fi
    \fi
    \def#2{}%
    \@strctr=#1\relax \divide\@strctr by 1000\relax
    \ifnum\@strctr>1\relax
```

```
    \@@numberunderhundreddutch{\@strctr}{#2}%
    \appto#2{duizend}%
    \else
    \ifnum\@strctr=1\relax
    \eappto#2{\duizend}%
    \fi
    \fi
    \@strctr=#1\relax
    \@FCmodulo{\@strctr}{1000}%
    \divide\@strctr by 100\relax
    \ifnum\@strctr>1\relax
    \eappto#2{\@unitstring{\@strctr}honderd}%
    \else
    \ifnum\@strctr=1\relax
    \ifnum#1>1000\relax
    \appto#2{honderd}%
    \else
    \eappto#2{\honderd}%
    \fi
    \fi
    \fi
    \@strctr=#1\relax
    \@FCmodulo{\@strctr}{100}%
    \ifnum#1=0\relax
    \def#2{null}%
    \else
    \ifnum\@strctr=1\relax
    \appto#2{een}% één and \'e\'en not working atm
    \else
    \@@numberunderhundreddutch{\@strctr}{#2}%
    \fi
    \fi
}%
\global\let\@@numberstringdutch\@@numberstringdutch
```

All lower case version, the second argument must be a control sequence.

```
\newcommand*{\@numberstringMdutch}[2]{%
    \let\@unitstring=\@@unitstringdutch%
    \let\@teenstring=\@@teenstringdutch%
    \let\@tenstring=\@@tenstringdutch%
    \def\@hundred{honderd}\def\@thousand{duizend}%
    \@@numberstringdutch{#1}{#2}%
}%
\global\let\@numberstringMdutch\@numberstringMdutch
```

There is no gender in Dutch, so make feminine and neuter the same as the masculine.

```
\global\let\@numberstringFdutch=\@numberstringMdutch
\global\let\@numberstringNdutch=\@numberstringMdutch
```

This version makes the first letter of each word an uppercase character (except “and”). The

second argument must be a control sequence.

```
\newcommand*{\@NumberstringMdutch}[2]{%
    \@numberstringMdutch{#1}{\@@num@str}%
    \edef#2{\noexpand\MakeUppercase\expandonce\@@num@str}%
}%
\global\let\@NumberstringMdutch\@NumberstringMdutch
```

There is no gender in Dutch, so make feminine and neuter the same as the masculine.

```
\global\let\@NumberstringFdutch=\@NumberstringMdutch
\global\let\@NumberstringNdutch=\@NumberstringMdutch
```

Define a macro that produces an ordinal as a string. Again, break it up into units, teens and tens. First the units:

```
\newcommand*\@@unitthstringdutch[1]{%
    \ifcase#1%
    nulde%
    \or eerste% éérste and \'e\'erste not working atm
    \or tweede%
    \or derde%
    \or vierde%
    \or vijfde%
    \or zesde%
    \or zevende%
    \or achtste%
    \or negende%
    \fi
}%
\global\let\@@unitthstringdutch\@@unitthstringdutch
```

Next the tens:

```
\newcommand*\@@tenthstringdutch[1]{%
    \ifcase#1%
    \or tiende%
    \or twintigste%
    \or dertigste%
    \or veertigste%
    \or vijftigste%
    \or zestigste%
    \or zeventigste%
    \or tachtigste%
    \or negentigste%
    \fi
}%
\global\let\@@tenthstringdutch\@@tenthstringdutch
```

The teens:

```
\newcommand*\@@teenthstringdutch[1]{%
    \ifcase#1%
    tiende%
    \or elfde%
    \or twaalfde%
```

```
    \or dertiende%
    \or veertiende%
    \or vijftiende%
    \or zestiende%
    \or zeventiende%
    \or achttiende%
    \or negentiende%
    \fi
}%
\global\let\@@teenthstringdutch\@@teenthstringdutch
```

The ordinalstring implementation. Converts numbers to Dutch ordinal words (e.g., 18 becomes “achttiende”, 100 becomes “honderdste”). Supports numbers from 0 to 99999.

```
\newcommand*\@@ordinalstringdutch[2]{%
    \@orgargctr=#1\relax
    \ifnum\@orgargctr>99999\relax
    \PackageError{fmtcount}{Out of range}%
    {This macro only works for values less than 100000}%
    \else
    \ifnum\@orgargctr<0\relax
    \PackageError{fmtcount}{Negative numbers not permitted}%
    {This macro does not work for negative numbers, however
    you can try typing "minus" first, and then pass the modulus of
    this number}%
    \fi
    \fi
    \def#2{}%
    \@strctr=\@orgargctr\divide\@strctr by 1000\relax
    \ifnum\@strctr>1\relax
    \@@numberunderhundreddutch{\@strctr}{#2}%
    \@tmpstrctr=\@orgargctr\@FCmodulo{\@tmpstrctr}{1000}%
    \ifnum\@tmpstrctr=0\relax
    \eappto#2{\@thousandth}%
    \else
    \appto#2{duizend}%
    \fi
    \else
    \ifnum\@strctr=1\relax
    \ifnum\@orgargctr=1000\relax
    \eappto#2{\@thousandth}%
    \else
    \eappto#2{\duizend}%
    \fi
    \fi
    \fi
    \@strctr=\@orgargctr%
    \@FCmodulo{\@strctr}{1000}%
    \divide\@strctr by 100\relax
    \ifnum\@strctr>1\relax
    \@tmpstrctr=\@orgargctr \@FCmodulo{\@tmpstrctr}{100}%
```

```
    \ifnum\@tmpstrctr=0\relax
    \ifnum\@strctr=1\relax
    \eappto#2{\@hundredth}%
    \else
    \eappto#2{\@unitstring{\@strctr}\@hundredth}%
    \fi
    \else
    \eappto#2{\@unitstring{\@strctr}honderd}%
    \fi
    \else
    \ifnum\@strctr=1\relax
    \@tmpstrctr=\@orgargctr \@FCmodulo{\@tmpstrctr}{100}%
    \ifnum\@tmpstrctr=0\relax
    \eappto#2{\@hundredth}%
    \else
    \ifnum\@orgargctr>1000\relax
    \appto#2{honderd}%
    \else
    \eappto#2{\honderd}%
    \fi
    \fi
    \fi
    \fi
    \@strctr=\@orgargctr%
    \@FCmodulo{\@strctr}{100}%
    \ifthenelse{\@strctr=0 \and \@orgargctr>0 }{}{%
        \@@numberunderhundredthdutch{\@strctr}{#2}%
    }%
}%
\global\let\@@ordinalstringdutch\@@ordinalstringdutch
```

All lower case version. Again, the second argument must be a control sequence in which the resulting text is stored.

```
\newcommand*{\@ordinalstringMdutch}[2]{%
    \let\@unitthstring=\@@unitthstringdutch%
    \let\@teenthstring=\@@teenthstringdutch%
    \let\@tenthstring=\@@tenthstringdutch%
    \let\@unitstring=\@@unitstringdutch%
    \let\@teenstring=\@@teenstringdutch%
    \let\@tenstring=\@@tenstringdutch%
    \def\@thousandth{duizendste}%
    \def\@hundredth{honderdste}%
    \@@ordinalstringdutch{#1}{#2}%
}%
\global\let\@ordinalstringMdutch\@ordinalstringMdutch
```

No gender in Dutch, so make feminine and neuter same as masculine:

```
\global\let\@ordinalstringFdutch=\@ordinalstringMdutch
\global\let\@ordinalstringNdutch=\@ordinalstringMdutch
```

First letter of each word in upper case:

```
\newcommand*{\@OrdinalstringMdutch}[2]{%
    \@ordinalstringMdutch{#1}{\@@num@str}%
    \def\@hundred{Honderd}\def\@thousand{Duizend}%
    \def\@hundredth{Honderdste}\def\@thousandth{Duizendste}%
    \edef#2{\noexpand\MakeUppercase\expandonce\@@num@str}%
}%
\global\let\@OrdinalstringMdutch\@OrdinalstringMdutch
```

No gender in Dutch, so make feminine and neuter same as masculine:

```
\global\let\@OrdinalstringFdutch=\@OrdinalstringMdutch
\global\let\@OrdinalstringNdutch=\@OrdinalstringMdutch
```

Helper macro for formatting numbers under 100 as words. Handles units (1–9), teens (10–19), and compound numbers (20–99) with proper diaeresis where needed.

```
\newcommand*{\@@numberunderhundreddutch}[2]{%
    \ifnum#1<10\relax
    \ifnum#1>0\relax
    \eappto#2{\@unitstring{#1}}%
    \fi
    \else
    \@tmpstrctr=#1\relax
    \@FCmodulo{\@tmpstrctr}{10}%
    \ifnum#1<20\relax
    \eappto#2{\@teenstring{\@tmpstrctr}}%
    \else
    \ifnum\@tmpstrctr=0\relax
    \else
```

For digits ending with an ‘e’, a diaeresis (trema) gets added to `\@andname` to prevent ambiguity in pronunciation. Examples: drieëntwintig (23), tweeënveertig (42).

```
    \ifnum\@tmpstrctr=2\relax\def\@andname{ën}%
    \else\ifnum\@tmpstrctr=3\relax\def\@andname{ën}%
    \else\def\@andname{en}%
    \fi\fi%
    \eappto#2{\@unitstring{\@tmpstrctr}\@andname}%
    \fi
    \@tmpstrctr=#1\relax
    \divide\@tmpstrctr by 10\relax
    \eappto#2{\@tenstring{\@tmpstrctr}}%
    \fi
    \fi
}%
\global\let\@@numberunderhundreddutch\@@numberunderhundreddutch
\newcommand*{\@@numberunderhundredthdutch}[2]{%
    \ifnum#1<10\relax
    \eappto#2{\@unitthstring{#1}}%
    \else
    \@tmpstrctr=#1\relax
    \@FCmodulo{\@tmpstrctr}{10}%
    \ifnum#1<20\relax
```

```
    \eappto#2{\@teenthstring{\@tmpstrctr}}%
    \else
    \ifnum\@tmpstrctr=0\relax
    \else
```

Again, for digits ending with an ‘e’, a trema gets added for `\@andname` (drieëntwintig or tweeënveertig).

```
    \ifnum\@tmpstrctr=2\relax\def\@andname{ën}%
    \else\ifnum\@tmpstrctr=3\relax\def\@andname{ën}%
    \else\def\@andname{en}%
    \fi\fi%
    \eappto#2{\@unitstring{\@tmpstrctr}\@andname}%
    \fi
    \@tmpstrctr=#1\relax
    \divide\@tmpstrctr by 10\relax
    \eappto#2{\@tenthstring{\@tmpstrctr}}%
    \fi
    \fi
}%
\global\let\@@numberunderhundredthdutch\@@numberunderhundredthdutch
```

10.1.5 fc-english.def

English definitions

```
\ProvidesFCLanguage{english}[2016/01/12]%
```

Define macro that converts a number or count register (first argument) to an ordinal, and stores the result in the second argument, which should be a control sequence.

```
\newcommand*\@ordinalMenglish[2]{%
\def\@fc@ord{}%
\@orgargctr=#1\relax
\@ordinalctr=#1%
\@FCmodulo{\@ordinalctr}{100}%
\ifnum\@ordinalctr=11\relax
  \def\@fc@ord{th}%
\else
  \ifnum\@ordinalctr=12\relax
    \def\@fc@ord{th}%
  \else
    \ifnum\@ordinalctr=13\relax
      \def\@fc@ord{th}%
    \else
      \@FCmodulo{\@ordinalctr}{10}%
      \ifcase\@ordinalctr
        \def\@fc@ord{th}%      case 0
        \or \def\@fc@ord{st}%  case 1
        \or \def\@fc@ord{nd}%  case 2
        \or \def\@fc@ord{rd}%  case 3
      \else
        \def\@fc@ord{th}%      default case
```

```
      \fi
    \fi
  \fi
\fi
\edef#2{\number#1\relax\noexpand\fmtord{\@fc@ord}}%
}%
\global\let\@ordinalMenglish\@ordinalMenglish
```

There is no gender difference in English, so make feminine and neuter the same as the masculine.

```
\global\let\@ordinalFenglish=\@ordinalMenglish
\global\let\@ordinalNenglish=\@ordinalMenglish
```

Define the macro that prints the value of a TEX count register as text. To make it easier, break it up into units, teens and tens. First, the units: the argument should be between 0 and 9 inclusive.

```
\newcommand*\@@unitstringenglish[1]{%
  \ifcase#1\relax
    zero%
    \or one%
    \or two%
    \or three%
    \or four%
    \or five%
    \or six%
    \or seven%
    \or eight%
    \or nine%
\fi
}%
\global\let\@@unitstringenglish\@@unitstringenglish
```

Next the tens, again the argument should be between 0 and 9 inclusive.

```
\newcommand*\@@tenstringenglish[1]{%
  \ifcase#1\relax
    \or ten%
    \or twenty%
    \or thirty%
    \or forty%
    \or fifty%
    \or sixty%
    \or seventy%
    \or eighty%
    \or ninety%
  \fi
}%
\global\let\@@tenstringenglish\@@tenstringenglish
```

Finally the teens, again the argument should be between 0 and 9 inclusive.

```
\newcommand*\@@teenstringenglish[1]{%
  \ifcase#1\relax
```

```
    ten%
    \or eleven%
    \or twelve%
    \or thirteen%
    \or fourteen%
    \or fifteen%
    \or sixteen%
    \or seventeen%
    \or eighteen%
    \or nineteen%
  \fi
}%
\global\let\@@teenstringenglish\@@teenstringenglish
```

As above, but with the initial letter in uppercase. The units:

```
\newcommand*\@@Unitstringenglish[1]{%
  \ifcase#1\relax
    Zero%
    \or One%
    \or Two%
    \or Three%
    \or Four%
    \or Five%
    \or Six%
    \or Seven%
    \or Eight%
    \or Nine%
  \fi
}%
\global\let\@@Unitstringenglish\@@Unitstringenglish
```

The tens:

```
\newcommand*\@@Tenstringenglish[1]{%
  \ifcase#1\relax
    \or Ten%
    \or Twenty%
    \or Thirty%
    \or Forty%
    \or Fifty%
    \or Sixty%
    \or Seventy%
    \or Eighty%
    \or Ninety%
  \fi
}%
\global\let\@@Tenstringenglish\@@Tenstringenglish
```

The teens:

```
\newcommand*\@@Teenstringenglish[1]{%
  \ifcase#1\relax
    Ten%
```

```
    \or Eleven%
    \or Twelve%
    \or Thirteen%
    \or Fourteen%
    \or Fifteen%
    \or Sixteen%
    \or Seventeen%
    \or Eighteen%
    \or Nineteen%
  \fi
}%
\global\let\@@Teenstringenglish\@@Teenstringenglish
```

This has changed in version 1.09, so that it now stores the result in the second argument, but doesn't display anything. Since it only affects internal macros, it shouldn't affect documents created with older versions. (These internal macros are not meant for use in documents.)

```
\newcommand*\@@numberstringenglish[2]{%
\ifnum#1>99999
\PackageError{fmtcount}{Out of range}%
{This macro only works for values less than 100000}%
\else
\ifnum#1<0
\PackageError{fmtcount}{Negative numbers not permitted}%
{This macro does not work for negative numbers, however
you can try typing "minus" first, and then pass the modulus of
this number}%
\fi
\fi
\def#2{}%
\@strctr=#1\relax \divide\@strctr by 1000\relax
\ifnum\@strctr>9
  \divide\@strctr by 10
  \ifnum\@strctr>1\relax
    \let\@@fc@numstr#2\relax
    \edef#2{\@@fc@numstr\@tenstring{\@strctr}}%
    \@strctr=#1 \divide\@strctr by 1000\relax
    \@FCmodulo{\@strctr}{10}%
    \ifnum\@strctr>0\relax
      \let\@@fc@numstr#2\relax
      \edef#2{\@@fc@numstr-\@unitstring{\@strctr}}%
    \fi
  \else
    \@strctr=#1\relax
    \divide\@strctr by 1000\relax
    \@FCmodulo{\@strctr}{10}%
    \let\@@fc@numstr#2\relax
    \edef#2{\@@fc@numstr\@teenstring{\@strctr}}%
  \fi
  \let\@@fc@numstr#2\relax
  \edef#2{\@@fc@numstr\ \@thousand}%
```

```
\else
  \ifnum\@strctr>0\relax
    \let\@@fc@numstr#2\relax
    \edef#2{\@@fc@numstr\@unitstring{\@strctr}\ \@thousand}%
  \fi
\fi
\@strctr=#1\relax \@FCmodulo{\@strctr}{1000}%
\divide\@strctr by 100
\ifnum\@strctr>0\relax
   \ifnum#1>1000\relax
      \let\@@fc@numstr#2\relax
      \edef#2{\@@fc@numstr\ }%
   \fi
   \let\@@fc@numstr#2\relax
   \edef#2{\@@fc@numstr\@unitstring{\@strctr}\ \@hundred}%
\fi
\@strctr=#1\relax \@FCmodulo{\@strctr}{100}%
\ifnum#1>100\relax
  \ifnum\@strctr>0\relax
    \let\@@fc@numstr#2\relax
    \edef#2{\@@fc@numstr\ \@andname\ }%
  \fi
\fi
\ifnum\@strctr>19\relax
  \divide\@strctr by 10\relax
  \let\@@fc@numstr#2\relax
  \edef#2{\@@fc@numstr\@tenstring{\@strctr}}%
  \@strctr=#1\relax \@FCmodulo{\@strctr}{10}%
  \ifnum\@strctr>0\relax
    \let\@@fc@numstr#2\relax
    \edef#2{\@@fc@numstr-\@unitstring{\@strctr}}%
  \fi
\else
  \ifnum\@strctr<10\relax
    \ifnum\@strctr=0\relax
       \ifnum#1<100\relax
          \let\@@fc@numstr#2\relax
          \edef#2{\@@fc@numstr\@unitstring{\@strctr}}%
       \fi
    \else
      \let\@@fc@numstr#2\relax
      \edef#2{\@@fc@numstr\@unitstring{\@strctr}}%
    \fi
  \else
    \@FCmodulo{\@strctr}{10}%
    \let\@@fc@numstr#2\relax
    \edef#2{\@@fc@numstr\@teenstring{\@strctr}}%
  \fi
\fi
```

```
}%
\global\let\@@numberstringenglish\@@numberstringenglish
```

All lower case version, the second argument must be a control sequence.

```
\newcommand*{\@numberstringMenglish}[2]{%
  \let\@unitstring=\@@unitstringenglish
  \let\@teenstring=\@@teenstringenglish
  \let\@tenstring=\@@tenstringenglish
  \def\@hundred{hundred}\def\@thousand{thousand}%
  \def\@andname{and}%
  \@@numberstringenglish{#1}{#2}%
}%
\global\let\@numberstringMenglish\@numberstringMenglish
```

There is no gender in English, so make feminine and neuter the same as the masculine.

```
\global\let\@numberstringFenglish=\@numberstringMenglish
\global\let\@numberstringNenglish=\@numberstringMenglish
```

This version makes the first letter of each word an uppercase character (except “and”). The second argument must be a control sequence.

```
\newcommand*\@NumberstringMenglish[2]{%
  \let\@unitstring=\@@Unitstringenglish
  \let\@teenstring=\@@Teenstringenglish
  \let\@tenstring=\@@Tenstringenglish
  \def\@hundred{Hundred}\def\@thousand{Thousand}%
  \def\@andname{and}%
  \@@numberstringenglish{#1}{#2}%
}%
\global\let\@NumberstringMenglish\@NumberstringMenglish
```

There is no gender in English, so make feminine and neuter the same as the masculine.

```
\global\let\@NumberstringFenglish=\@NumberstringMenglish
\global\let\@NumberstringNenglish=\@NumberstringMenglish
```

Define a macro that produces an ordinal as a string. Again, break it up into units, teens and tens. First the units:

```
\newcommand*\@@unitthstringenglish[1]{%
  \ifcase#1\relax
    zeroth%
    \or first%
    \or second%
    \or third%
    \or fourth%
    \or fifth%
    \or sixth%
    \or seventh%
    \or eighth%
    \or ninth%
  \fi
}%
\global\let\@@unitthstringenglish\@@unitthstringenglish
```

Next the tens:

```
\newcommand*\@@tenthstringenglish[1]{%
  \ifcase#1\relax
    \or tenth%
    \or twentieth%
    \or thirtieth%
    \or fortieth%
    \or fiftieth%
    \or sixtieth%
    \or seventieth%
    \or eightieth%
    \or ninetieth%
  \fi
}%
\global\let\@@tenthstringenglish\@@tenthstringenglish
```

The teens:

```
\newcommand*\@@teenthstringenglish[1]{%
  \ifcase#1\relax
    tenth%
    \or eleventh%
    \or twelfth%
    \or thirteenth%
    \or fourteenth%
    \or fifteenth%
    \or sixteenth%
    \or seventeenth%
    \or eighteenth%
    \or nineteenth%
  \fi
}%
\global\let\@@teenthstringenglish\@@teenthstringenglish
```

As before, but with the first letter in upper case. The units:

```
\newcommand*\@@Unitthstringenglish[1]{%
  \ifcase#1\relax
    Zeroth%
    \or First%
    \or Second%
    \or Third%
    \or Fourth%
    \or Fifth%
    \or Sixth%
    \or Seventh%
    \or Eighth%
    \or Ninth%
  \fi
}%
\global\let\@@Unitthstringenglish\@@Unitthstringenglish
```

The tens:

```
\newcommand*\@@Tenthstringenglish[1]{%
  \ifcase#1\relax
    \or Tenth%
    \or Twentieth%
    \or Thirtieth%
    \or Fortieth%
    \or Fiftieth%
    \or Sixtieth%
    \or Seventieth%
    \or Eightieth%
    \or Ninetieth%
  \fi
}%
\global\let\@@Tenthstringenglish\@@Tenthstringenglish
```

The teens:

```
\newcommand*\@@Teenthstringenglish[1]{%
  \ifcase#1\relax
    Tenth%
    \or Eleventh%
    \or Twelfth%
    \or Thirteenth%
    \or Fourteenth%
    \or Fifteenth%
    \or Sixteenth%
    \or Seventeenth%
    \or Eighteenth%
    \or Nineteenth%
  \fi
}%
\global\let\@@Teenthstringenglish\@@Teenthstringenglish
```

Again, as from version 1.09, this has been changed to take two arguments, where the second argument is a control sequence. The resulting text is stored in the control sequence, and nothing is displayed.

```
\newcommand*\@@ordinalstringenglish[2]{%
\@strctr=#1\relax
\ifnum#1>99999
\PackageError{fmtcount}{Out of range}%
{This macro only works for values less than 100000 (value given: \number\@strctr)}%
\else
\ifnum#1<0
\PackageError{fmtcount}{Negative numbers not permitted}%
{This macro does not work for negative numbers, however
you can try typing "minus" first, and then pass the modulus of
this number}%
\fi
\def#2{}%
\fi
\@strctr=#1\relax \divide\@strctr by 1000\relax
```

```
\ifnum\@strctr>9\relax
```
#1 is greater or equal to 10000
```
  \divide\@strctr by 10
  \ifnum\@strctr>1\relax
    \let\@@fc@ordstr#2\relax
    \edef#2{\@@fc@ordstr\@tenstring{\@strctr}}%
    \@strctr=#1\relax
    \divide\@strctr by 1000\relax
    \@FCmodulo{\@strctr}{10}%
    \ifnum\@strctr>0\relax
      \let\@@fc@ordstr#2\relax
      \edef#2{\@@fc@ordstr-\@unitstring{\@strctr}}%
    \fi
  \else
    \@strctr=#1\relax \divide\@strctr by 1000\relax
    \@FCmodulo{\@strctr}{10}%
    \let\@@fc@ordstr#2\relax
    \edef#2{\@@fc@ordstr\@teenstring{\@strctr}}%
  \fi
  \@strctr=#1\relax \@FCmodulo{\@strctr}{1000}%
  \ifnum\@strctr=0\relax
    \let\@@fc@ordstr#2\relax
    \edef#2{\@@fc@ordstr\ \@thousandth}%
  \else
    \let\@@fc@ordstr#2\relax
    \edef#2{\@@fc@ordstr\ \@thousand}%
  \fi
\else
  \ifnum\@strctr>0\relax
    \let\@@fc@ordstr#2\relax
    \edef#2{\@@fc@ordstr\@unitstring{\@strctr}}%
    \@strctr=#1\relax \@FCmodulo{\@strctr}{1000}%
    \let\@@fc@ordstr#2\relax
    \ifnum\@strctr=0\relax
      \edef#2{\@@fc@ordstr\ \@thousandth}%
    \else
      \edef#2{\@@fc@ordstr\ \@thousand}%
    \fi
  \fi
\fi
\@strctr=#1\relax \@FCmodulo{\@strctr}{1000}%
\divide\@strctr by 100
\ifnum\@strctr>0\relax
  \ifnum#1>1000\relax
    \let\@@fc@ordstr#2\relax
    \edef#2{\@@fc@ordstr\ }%
  \fi
  \let\@@fc@ordstr#2\relax
  \edef#2{\@@fc@ordstr\@unitstring{\@strctr}}%
```

```
  \@strctr=#1\relax \@FCmodulo{\@strctr}{100}%
  \let\@@fc@ordstr#2\relax
  \ifnum\@strctr=0\relax
    \edef#2{\@@fc@ordstr\ \@hundredth}%
  \else
    \edef#2{\@@fc@ordstr\ \@hundred}%
  \fi
\fi
\@strctr=#1\relax \@FCmodulo{\@strctr}{100}%
\ifnum#1>100\relax
  \ifnum\@strctr>0\relax
    \let\@@fc@ordstr#2\relax
    \edef#2{\@@fc@ordstr\ \@andname\ }%
  \fi
\fi
\ifnum\@strctr>19\relax
  \@tmpstrctr=\@strctr
  \divide\@strctr by 10\relax
  \@FCmodulo{\@tmpstrctr}{10}%
  \let\@@fc@ordstr#2\relax
  \ifnum\@tmpstrctr=0\relax
    \edef#2{\@@fc@ordstr\@tenthstring{\@strctr}}%
  \else
    \edef#2{\@@fc@ordstr\@tenstring{\@strctr}}%
  \fi
  \@strctr=#1\relax \@FCmodulo{\@strctr}{10}%
  \ifnum\@strctr>0\relax
    \let\@@fc@ordstr#2\relax
    \edef#2{\@@fc@ordstr-\@unitthstring{\@strctr}}%
  \fi
\else
  \ifnum\@strctr<10\relax
    \ifnum\@strctr=0\relax
      \ifnum#1<100\relax
        \let\@@fc@ordstr#2\relax
        \edef#2{\@@fc@ordstr\@unitthstring{\@strctr}}%
      \fi
    \else
      \let\@@fc@ordstr#2\relax
      \edef#2{\@@fc@ordstr\@unitthstring{\@strctr}}%
    \fi
  \else
    \@FCmodulo{\@strctr}{10}%
    \let\@@fc@ordstr#2\relax
    \edef#2{\@@fc@ordstr\@teenthstring{\@strctr}}%
  \fi
\fi
}%
\global\let\@@ordinalstringenglish\@@ordinalstringenglish
```

All lower case version. Again, the second argument must be a control sequence in which the resulting text is stored.

```
\newcommand*{\@ordinalstringMenglish}[2]{%
  \let\@unitthstring=\@@unitthstringenglish
  \let\@teenthstring=\@@teenthstringenglish
  \let\@tenthstring=\@@tenthstringenglish
  \let\@unitstring=\@@unitstringenglish
  \let\@teenstring=\@@teenstringenglish
  \let\@tenstring=\@@tenstringenglish
  \def\@andname{and}%
  \def\@hundred{hundred}\def\@thousand{thousand}%
  \def\@hundredth{hundredth}\def\@thousandth{thousandth}%
  \@@ordinalstringenglish{#1}{#2}%
}%
\global\let\@ordinalstringMenglish\@ordinalstringMenglish
```

No gender in English, so make feminine and neuter same as masculine:

```
\global\let\@ordinalstringFenglish=\@ordinalstringMenglish
\global\let\@ordinalstringNenglish=\@ordinalstringMenglish
```

First letter of each word in upper case:

```
\newcommand*{\@OrdinalstringMenglish}[2]{%
  \let\@unitthstring=\@@Unitthstringenglish
  \let\@teenthstring=\@@Teenthstringenglish
  \let\@tenthstring=\@@Tenthstringenglish
  \let\@unitstring=\@@Unitstringenglish
  \let\@teenstring=\@@Teenstringenglish
  \let\@tenstring=\@@Tenstringenglish
  \def\@andname{and}%
  \def\@hundred{Hundred}\def\@thousand{Thousand}%
  \def\@hundredth{Hundredth}\def\@thousandth{Thousandth}%
  \@@ordinalstringenglish{#1}{#2}%
}%
\global\let\@OrdinalstringMenglish\@OrdinalstringMenglish
```

No gender in English, so make feminine and neuter same as masculine:

```
\global\let\@OrdinalstringFenglish=\@OrdinalstringMenglish
\global\let\@OrdinalstringNenglish=\@OrdinalstringMenglish
```

10.1.6 fc-francais.def

```
\ProvidesFCLanguage{francais}[2013/08/17]%
\FCloadlang{french}%
```

Set `francais` to be equivalent to `french`.

```
\global\let\@ordinalMfrancais=\@ordinalMfrench
\global\let\@ordinalFfrancais=\@ordinalFfrench
\global\let\@ordinalNfrancais=\@ordinalNfrench
\global\let\@numberstringMfrancais=\@numberstringMfrench
\global\let\@numberstringFfrancais=\@numberstringFfrench
\global\let\@numberstringNfrancais=\@numberstringNfrench
```

```
\global\let\@NumberstringMfrancais=\@NumberstringMfrench
\global\let\@NumberstringFfrancais=\@NumberstringFfrench
\global\let\@NumberstringNfrancais=\@NumberstringNfrench
\global\let\@ordinalstringMfrancais=\@ordinalstringMfrench
\global\let\@ordinalstringFfrancais=\@ordinalstringFfrench
\global\let\@ordinalstringNfrancais=\@ordinalstringNfrench
\global\let\@OrdinalstringMfrancais=\@OrdinalstringMfrench
\global\let\@OrdinalstringFfrancais=\@OrdinalstringFfrench
\global\let\@OrdinalstringNfrancais=\@OrdinalstringNfrench
```

10.1.7 fc-french.def

Definitions for French.

```
\ProvidesFCLanguage{french}[2017/06/15]%
```

Package fcprefix is needed to format the prefix ⟨*n*⟩ in ⟨*n*⟩illion or ⟨*n*⟩illiard. Big numbers were developped based on reference: http://www.alain.be/boece/noms_de_nombre.html. Package fcprefix is now loaded by fmtcount.

First of all we define two macros `\fc@gl@let` and `\fc@gl@def` used in place of `\let` and `\def` within options setting macros. This way we can control from outside these macros whether the respective `\let` or `\def` is group-local or global. By default they are defined to be group-local.

```
\ifcsundef{fc@gl@let}{\global\let\fc@gl@let\let}{\PackageError{fmtcount}{Command already define
\protect\fc@gl@let\space already defined.}}
\ifcsundef{fc@gl@def}{\global\let\fc@gl@def\def}{\PackageError{fmtcount}{Command already define
\protect\fc@gl@def\space already defined.}}
```

Options for controlling plural mark. First of all we define some temporary macro `\fc@french@set@plural` in order to factorize code that defines a plural mark option:

#1 key name,
#2 key value,
#3 configuration index for '`reformed`',
#4 configuration index for '`traditional`',
#5 configuration index for '`reformed o`', and
#6 configuration index for '`traditional o`'.

```
\gdef\fc@french@set@plural#1#2#3#4#5#6{%
  \ifthenelse{\equal{#2}{reformed}}{%
    \expandafter\fc@gl@def\csname fc@frenchoptions@#1@plural\endcsname{#3}%
  }{%
    \ifthenelse{\equal{#2}{traditional}}{%
      \expandafter\fc@gl@def\csname fc@frenchoptions@#1@plural\endcsname{#4}%
    }{%
      \ifthenelse{\equal{#2}{reformed o}}{%
        \expandafter\fc@gl@def\csname fc@frenchoptions@#1@plural\endcsname{#5}%
      }{%
        \ifthenelse{\equal{#2}{traditional o}}{%
          \expandafter\fc@gl@def\csname fc@frenchoptions@#1@plural\endcsname{#6}%
        }{%
          \ifthenelse{\equal{#2}{always}}{%
```

```
            \expandafter\fc@gl@def\csname fc@frenchoptions@#1@plural\endcsname{0}%
          }{%
            \ifthenelse{\equal{#2}{never}}{%
              \expandafter\fc@gl@def\csname fc@frenchoptions@#1@plural\endcsname{1}%
            }{%
              \ifthenelse{\equal{#2}{multiple}}{%
                \expandafter\fc@gl@def\csname fc@frenchoptions@#1@plural\endcsname{2}%
              }{%
                \ifthenelse{\equal{#2}{multiple g-last}}{%
                  \expandafter\fc@gl@def\csname fc@frenchoptions@#1@plural\endcsname{3}%
                }{%
                  \ifthenelse{\equal{#2}{multiple l-last}}{%
                    \expandafter\fc@gl@def\csname fc@frenchoptions@#1@plural\endcsname{4}%
                  }{%
                    \ifthenelse{\equal{#2}{multiple lng-last}}{%
                      \expandafter\fc@gl@def\csname fc@frenchoptions@#1@plural\endcsname{5}%
                    }{%
                      \ifthenelse{\equal{#2}{multiple ng-last}}{%
                        \expandafter\fc@gl@def\csname fc@frenchoptions@#1@plural\endcsname{6}%
                      }{%
                        \PackageError{fmtcount}{Unexpected argument}{%
                          '#2' was unexpected: french option '#1 plural' expects 'reformed', 't
                          'reformed o', 'traditional o', 'always', 'never', 'multiple', 'multip
                          'multiple l-last', 'multiple lng-last', or 'multiple ng-last'.%
                        }}}}}}}}}}}}%
```

Now a shorthand `\@tempa` is defined just to define all the options controlling plural mark. This shorthand takes into account that '`reformed`' and '`traditional`' have the same effect, and so do '`reformed o`' and '`traditional o`'.

```
\def\@tempa#1#2#3{%
  \define@key{fcfrench}{#1 plural}[reformed]{%
    \fc@french@set@plural{#1}{##1}{#2}{#2}{#3}{#3}%
  }%
```

Macro `\@tempb` takes a macro as argument, and makes its current definition global. Like here it is useful when the macro name contains non-letters, and we have to resort to the `\csname`…`\endcsname` construct.

```
  \expandafter\@tempb\csname KV@fcfrench@#1 plural\endcsname
}%
\def\@tempb#1{%
  \global\let#1#1
}%
\@tempa{vingt}{4}{5}
\@tempa{cent}{4}{5}
\@tempa{mil}{0}{0}
\@tempa{n-illion}{2}{6}
\@tempa{n-illiard}{2}{6}
```

For option '`all plural`' we cannot use the `\@tempa` shorthand, because '`all plural`' is just a multiplexer.

```
\define@key{fcfrench}{all plural}[reformed]{%
  \csname KV@fcfrench@vingt plural\endcsname{#1}%
  \csname KV@fcfrench@cent plural\endcsname{#1}%
  \csname KV@fcfrench@mil plural\endcsname{#1}%
  \csname KV@fcfrench@n-illion plural\endcsname{#1}%
  \csname KV@fcfrench@n-illiard plural\endcsname{#1}%
}%
\expandafter\@tempb\csname KV@fcfrench@all plural\endcsname
```

Now options ‘`dash or space`’, we have three possible key values:

`traditional` use dash for numbers below 100, except when ‘et’ is used, and space otherwise

`reformed` reform of 1990, use dash except with million & milliard, and suchlikes, i.e. ⟨*n*⟩illion and ⟨*n*⟩illiard,

`always` always use dashes to separate all words

```
\define@key{fcfrench}{dash or space}[reformed]{%
  \ifthenelse{\equal{#1}{traditional}}{%
    \let\fc@frenchoptions@supermillion@dos\space%
    \let\fc@frenchoptions@submillion@dos\space
  }{%
    \ifthenelse{\equal{#1}{reformed}\or\equal{#1}{1990}}{%
      \let\fc@frenchoptions@supermillion@dos\space
      \def\fc@frenchoptions@submillion@dos{-}%
    }{%
      \ifthenelse{\equal{#1}{always}}{%
        \def\fc@frenchoptions@supermillion@dos{-}%
        \def\fc@frenchoptions@submillion@dos{-}%
      }{%
        \PackageError{fmtcount}{Unexpected argument}{%
          French option ‘dash or space’ expects ‘always’, ‘reformed’ or ‘traditional’
        }
      }%
    }%
  }%
}%
```

Option ‘`scale`’, can take 3 possible values:

`long` for which ⟨*n*⟩illions & ⟨*n*⟩illiards are used with $10^{6\times n} = 1$ ⟨*n*⟩illion, and $10^{6\times n+3} = 1$ ⟨*n*⟩illiard

`short` for which ⟨*n*⟩illions only are used with $10^{3\times n+3} = 1$ ⟨*n*⟩illion

`recursive` for which 10^{18} = un milliard de milliards

```
\define@key{fcfrench}{scale}[recursive]{%
  \ifthenelse{\equal{#1}{long}}{%
      \let\fc@poweroften\fc@@pot@longscalefrench
  }{%
    \ifthenelse{\equal{#1}{recursive}}{%
      \let\fc@poweroften\fc@@pot@recursivefrench
    }{%
      \ifthenelse{\equal{#1}{short}}{%
```

```
        \let\fc@poweroften\fc@@pot@shortscalefrench
      }{%
        \PackageError{fmtcount}{Unexpected argument}{%
          French option ‘scale’ expects ‘long’, ‘recursive’ or ‘short’
        }
      }%
    }%
  }%
}%
```

Option ‘`n-illiard upto`’ is ignored if ‘`scale`’ is different from ‘`long`’. It can take the following values:

`infinity` in that case ⟨*n*⟩illard are never disabled,
`infty` this is just a shorthand for ‘`infinity`’, and
n any integer that is such that $n > 0$, and that $\forall k \in \mathbb{N}, k \geq n$, number $10^{6\times k+3}$ will be formatted as “mille ⟨*n*⟩illions”

```
\define@key{fcfrench}{n-illiard upto}[infinity]{%
  \ifthenelse{\equal{#1}{infinity}}{%
      \def\fc@longscale@nilliard@upto{0}%
  }{%
    \ifthenelse{\equal{#1}{infty}}{%
      \def\fc@longscale@nilliard@upto{0}%
    }{%
      \if Q\ifnum9<1#1Q\fi\else
      \PackageError{fmtcount}{Unexpected argument}{%
        French option ‘milliard threshold’ expects ‘infinity’, or equivalently ‘infty’, or a no
        integer.}%
      \fi
      \def\fc@longscale@nilliard@upto{#1}%
    }}%
}%
```

Now, the options ‘`france`’, ‘`swiss`’ and ‘`belgian`’ are defined to select the dialect to use. Macro `\@tempa` is just a local shorthand to define each one of this option.

```
\def\@tempa#1{%
  \define@key{fcfrench}{#1}[]{%
    \PackageError{fmtcount}{Unexpected argument}{French option with key ‘#1’ does not take
      any value}}%
  \csgdef{KV@fcfrench@#1@default}{%
    \fc@gl@def\fmtcount@french{#1}}%
}%
\@tempa{france}\@tempa{swiss}\@tempa{belgian}%
```

Make ‘`france`’ the default dialect for ‘`french`’ language

```
\gdef\fmtcount@french{france}%
```

Now, option ‘`dialect`’ is now defined so that ‘`france`’, ‘`swiss`’ and ‘`belgian`’ can also be used as key values, which is more conventional although less concise.

```
\define@key{fcfrench}{dialect}[france]{%
  \ifthenelse{\equal{#1}{france}
```

```
    \or\equal{#1}{swiss}
    \or\equal{#1}{belgian}}{%
    \def\fmtcount@french{#1}}{%
    \PackageError{fmtcount}{Invalid value ‘#1’ to french option dialect key}
    {Option ‘french’ can only take the values ‘france’,
      ‘belgian’ or ‘swiss’}}%
\expandafter\@tempb\csname KV@fcfrench@dialect\endcsname
```

The option `mil plural mark` allows to make the plural of `mil` to be regular, i.e. `mils`, instead of `mille`. By default it is ‘`le`’.

```
\define@key{fcfrench}{mil plural mark}[le]{%
  \def\fc@frenchoptions@mil@plural@mark{#1}}
\expandafter\@tempb\csname KV@fcfrench@mil plural mark\endcsname
```

Definition of case handling macros. This should be moved somewhere else to be commonalized between all languages.

`@UpperCaseFirstLetter` The macro `\fc@UpperCaseFirstLetter` is such that `\fc@UpperCaseFirstLetter`⟨*word*⟩`\@nil` expands to `\word` with first letter capitalized and remainder unchanged.

```
\gdef\fc@UpperCaseFirstLetter#1#2\@nil{%
  \uppercase{#1}#2}
```

`\fc@CaseIden` The macro `\fc@CaseIden` is such that `\fc@CaseIden`⟨*word*⟩`\@nil` expands to `\word` unchanged.

```
\gdef\fc@CaseIden#1\@nil{%
  #1%
}%
```

`fc@UpperCaseAll` The macro `\fc@UpperCaseAll` is such that `\fc@UpperCaseAll`⟨*word*⟩`\@nil` expands to `\word` all capitalized.

```
\gdef\fc@UpperCaseAll#1\@nil{%
  \uppercase{#1}%
}%
```

`\fc@wcase` The macro `\fc@wcase` is the capitalizing macro for word-by-word capitalization. By default we set it to identity, ie. no capitalization.

```
\global\let\fc@wcase\fc@CaseIden
```

`\fc@gcase` The macro `\fc@gcase` is the capitalizing macro for global (the completed number) capitalization. By default we set it to identity, ie. no capitalization.

```
\global\let\fc@gcase\fc@CaseIden
```

`\fc@apply@gcase` The macro `\fc@apply@gcase` simply applies `\fc@gcase` to `\@tempa`, knowing that `\@tempa` is the macro containing the result of formatting.

```
\gdef\fc@apply@gcase{%
```

First of all we expand whatever `\fc@wcase`…`\@nil` found within `\@tempa`.

```
  \protected@edef\@tempa{\@tempa}%
  \protected@edef\@tempa{\expandafter\fc@gcase\@tempa\@nil}%
}
```

`@ordinalMfrench`

```
\newcommand*{\@ordinalMfrench}[2]{%
```

```
\iffmtord@abbrv
  \ifnum#1=1 %
    \edef#2{\number#1\relax\noexpand\fmtord{er}}%
  \else
    \edef#2{\number#1\relax\noexpand\fmtord{e}}%
  \fi
\else
  \PackageWarning{fmtcount}{Non abbreviated ordinal finals (‘eme) are
    considered incorrect in French.}%
  \ifnum#1=1 %
    \edef#2{\number#1\relax\noexpand\fmtord{er}}%
  \else
    \protected@edef#2{\number#1\relax\noexpand\fmtord{\protect\‘eme}}%
  \fi
\fi}
\global\let\@ordinalMfrench\@ordinalMfrench
```

@ordinalFfrench

```
\newcommand*{\@ordinalFfrench}[2]{%
\iffmtord@abbrv
  \ifnum#1=1 %
     \edef#2{\number#1\relax\noexpand\fmtord{re}}%
  \else
     \edef#2{\number#1\relax\noexpand\fmtord{e}}%
  \fi
\else
  \PackageWarning{fmtcount}{Non abbreviated ordinal finals (‘eme) are
    considered incorrect in French.}%
  \ifnum#1=1 %
     \protected@edef#2{\number#1\relax\noexpand\fmtord{\protect\‘ere}}%
  \else
     \protected@edef#2{\number#1\relax\noexpand\fmtord{\protect\‘eme}}%
  \fi
\fi}
\global\let\@ordinalFfrench\@ordinalFfrench
```

In French neutral gender and masculine gender are formally identical.

```
\global\let\@ordinalNfrench\@ordinalMfrench
```

unitstringfrench

```
\newcommand*{\@@unitstringfrench}[1]{%
\noexpand\fc@wcase
\ifcase#1 %
z\’ero%
\or un%
\or deux%
\or trois%
\or quatre%
\or cinq%
\or six%
\or sept%
```

```
\or huit%
\or neuf%
\fi
\noexpand\@nil
}%
\global\let\@@unitstringfrench\@@unitstringfrench
```

tenstringfrench

```
\newcommand*{\@@tenstringfrench}[1]{%
\noexpand\fc@wcase
\ifcase#1 %
\or dix%
\or vingt%
\or trente%
\or quarante%
\or cinquante%
\or soixante%
\or septante%
\or huitante%
\or nonante%
\or cent%
\fi
\noexpand\@nil
}%
\global\let\@@tenstringfrench\@@tenstringfrench
```

teenstringfrench

```
\newcommand*{\@@teenstringfrench}[1]{%
\noexpand\fc@wcase
\ifcase#1 %
    dix%
\or onze%
\or douze%
\or treize%
\or quatorze%
\or quinze%
\or seize%
\or dix\noexpand\@nil-\noexpand\fc@wcase sept%
\or dix\noexpand\@nil-\noexpand\fc@wcase huit%
\or dix\noexpand\@nil-\noexpand\fc@wcase neuf%
\fi
\noexpand\@nil
}%
\global\let\@@teenstringfrench\@@teenstringfrench
```

seventiesfrench

```
\newcommand*{\@@seventiesfrench}[1]{%
\@tenstring{6}%
\ifnum#1=1 %
\fc@frenchoptions@submillion@dos\@andname\fc@frenchoptions@submillion@dos
\else
```

```
-%
\fi
\@teenstring{#1}%
}%
\global\let\@@seventiesfrench\@@seventiesfrench
```

@eightiesfrench Macro `\@@eightiesfrench` is used to format numbers in the interval [80..89]. Argument as follows:

`#1` digit d_w such that the number to be formatted is $80 + d_w$

Implicit arguments as:

`\count0` weight w of the number $d_{w+1}d_w$ to be formatted

`\count1` same as `\#1`

`\count6` input, counter giving the least weight of non zero digits in top level formatted number integral part, with rounding down to a multiple of 3,

`\count9` input, counter giving the power type of the power of ten following the eighties to be formatted; that is '1' for "mil" and '2' for "⟨*n*⟩illion|⟨*n*⟩illiard".

```
\newcommand*\@@eightiesfrench[1]{%
\fc@wcase quatre\@nil-\noexpand\fc@wcase vingt%
\ifnum#1>0 %
  \ifnum\fc@frenchoptions@vingt@plural=0 % vingt plural=always
  s%
  \fi
  \noexpand\@nil
  -\@unitstring{#1}%
\else
  \ifcase\fc@frenchoptions@vingt@plural\space
    s% 0: always
  \or
    % 1: never
  \or
    s% 2: multiple
  \or
    % 3: multiple g-last
    \ifnum\count0=\count6\ifnum\count9=0 s\fi\fi
  \or
    % 4: multiple l-last
    \ifnum\count9=1 %
    \else
      s%
    \fi
  \or
    % 5: multiple lng-last
    \ifnum\count9=1 %
    \else
      \ifnum\count0>0 %
        s%
      \fi
    \fi
  \or
```

```
    % or 6: multiple ng-last
    \ifnum\count0>0 %
      s%
    \fi
  \fi
  \noexpand\@nil
\fi
}%
\global\let\@@eightiesfrench\@@eightiesfrench
\newcommand*{\@@ninetiesfrench}[1]{%
\fc@wcase quatre\@nil-\noexpand\fc@wcase vingt%
\ifnum\fc@frenchoptions@vingt@plural=0 % vingt plural=always
  s%
\fi
\noexpand\@nil
-\@teenstring{#1}%
}%
\global\let\@@ninetiesfrench\@@ninetiesfrench
\newcommand*{\@@seventiesfrenchswiss}[1]{%
\@tenstring{7}%
\ifnum#1=1\ \@andname\ \fi
\ifnum#1>1-\fi
\ifnum#1>0 \@unitstring{#1}\fi
}%
\global\let\@@seventiesfrenchswiss\@@seventiesfrenchswiss
\newcommand*{\@@eightiesfrenchswiss}[1]{%
\@tenstring{8}%
\ifnum#1=1\ \@andname\ \fi
\ifnum#1>1-\fi
\ifnum#1>0 \@unitstring{#1}\fi
}%
\global\let\@@eightiesfrenchswiss\@@eightiesfrenchswiss
\newcommand*{\@@ninetiesfrenchswiss}[1]{%
\@tenstring{9}%
\ifnum#1=1\ \@andname\ \fi
\ifnum#1>1-\fi
\ifnum#1>0 \@unitstring{#1}\fi
}%
\global\let\@@ninetiesfrenchswiss\@@ninetiesfrenchswiss
```

`c@french@common` Macro `\fc@french@common` does all the preliminary settings common to all French dialects & formatting options.

```
\newcommand*\fc@french@common{%
  \let\fc@wcase\fc@CaseIden
  \let\@unitstring=\@@unitstringfrench
  \let\@teenstring=\@@teenstringfrench
  \let\@tenstring=\@@tenstringfrench
  \def\@hundred{cent}%
  \def\@andname{et}%
}%
```

```
\global\let\fc@french@common\fc@french@common

\newcommand*{\@numberstringMfrenchswiss}[2]{%
\fc@french@common
\let\fc@gcase\fc@CaseIden
\let\@seventies=\@@seventiesfrenchswiss
\let\@eighties=\@@eightiesfrenchswiss
\let\@nineties=\@@ninetiesfrenchswiss
\let\fc@nbrstr@preamble\@empty
\let\fc@nbrstr@postamble\@empty
\@@numberstringfrench{#1}{#2}}
\global\let\@numberstringMfrenchswiss\@numberstringMfrenchswiss
\newcommand*{\@numberstringMfrenchfrance}[2]{%
\fc@french@common
\let\fc@gcase\fc@CaseIden
\let\@seventies=\@@seventiesfrench
\let\@eighties=\@@eightiesfrench
\let\@nineties=\@@ninetiesfrench
\let\fc@nbrstr@preamble\@empty
\let\fc@nbrstr@postamble\@empty
\@@numberstringfrench{#1}{#2}}
\global\let\@numberstringMfrenchfrance\@numberstringMfrenchfrance
\newcommand*{\@numberstringMfrenchbelgian}[2]{%
\fc@french@common
\let\fc@gcase\fc@CaseIden
\let\@seventies=\@@seventiesfrenchswiss
\let\@eighties=\@@eightiesfrench
\let\@nineties=\@@ninetiesfrench
\let\fc@nbrstr@preamble\@empty
\let\fc@nbrstr@postamble\@empty
\@@numberstringfrench{#1}{#2}}
\global\let\@numberstringMfrenchbelgian\@numberstringMfrenchbelgian
\let\@numberstringMfrench=\@numberstringMfrenchfrance
\newcommand*{\@numberstringFfrenchswiss}[2]{%
\fc@french@common
\let\fc@gcase\fc@CaseIden
\let\@seventies=\@@seventiesfrenchswiss
\let\@eighties=\@@eightiesfrenchswiss
\let\@nineties=\@@ninetiesfrenchswiss
\let\fc@nbrstr@preamble\fc@@nbrstr@Fpreamble
\let\fc@nbrstr@postamble\@empty
\@@numberstringfrench{#1}{#2}}
\global\let\@numberstringFfrenchswiss\@numberstringFfrenchswiss
\newcommand*{\@numberstringFfrenchfrance}[2]{%
\fc@french@common
\let\fc@gcase\fc@CaseIden
\let\@seventies=\@@seventiesfrench
\let\@eighties=\@@eightiesfrench
\let\@nineties=\@@ninetiesfrench
\let\fc@nbrstr@preamble\fc@@nbrstr@Fpreamble
```

```
\let\fc@nbrstr@postamble\@empty
\@@numberstringfrench{#1}{#2}}
\global\let\@numberstringFfrenchfrance\@numberstringFfrenchfrance
\newcommand*{\@numberstringFfrenchbelgian}[2]{%
\fc@french@common
\let\fc@gcase\fc@CaseIden
\let\@seventies=\@@seventiesfrenchswiss
\let\@eighties=\@@eightiesfrench
\let\@nineties=\@@ninetiesfrench
\let\fc@nbrstr@preamble\fc@@nbrstr@Fpreamble
\let\fc@nbrstr@postamble\@empty
\@@numberstringfrench{#1}{#2}}
\global\let\@numberstringFfrenchbelgian\@numberstringFfrenchbelgian
\global\let\@numberstringFfrench=\@numberstringFfrenchfrance
\global\let\@ordinalstringNfrench\@ordinalstringMfrench
\newcommand*{\@NumberstringMfrenchswiss}[2]{%
\fc@french@common
\let\fc@gcase\fc@UpperCaseFirstLetter
\let\@seventies=\@@seventiesfrenchswiss
\let\@eighties=\@@eightiesfrenchswiss
\let\@nineties=\@@ninetiesfrenchswiss
\let\fc@nbrstr@preamble\@empty
\let\fc@nbrstr@postamble\fc@apply@gcase
\@@numberstringfrench{#1}{#2}}
\global\let\@NumberstringMfrenchswiss\@NumberstringMfrenchswiss
\newcommand*{\@NumberstringMfrenchfrance}[2]{%
\fc@french@common
\let\fc@gcase\fc@UpperCaseFirstLetter
\let\@seventies=\@@seventiesfrench
\let\@eighties=\@@eightiesfrench
\let\@nineties=\@@ninetiesfrench
\let\fc@nbrstr@preamble\@empty
\let\fc@nbrstr@postamble\fc@apply@gcase
\@@numberstringfrench{#1}{#2}}
\global\let\@NumberstringMfrenchfrance\@NumberstringMfrenchfrance
\newcommand*{\@NumberstringMfrenchbelgian}[2]{%
\fc@french@common
\let\fc@gcase\fc@UpperCaseFirstLetter
\let\@seventies=\@@seventiesfrenchswiss
\let\@eighties=\@@eightiesfrench
\let\@nineties=\@@ninetiesfrench
\let\fc@nbrstr@preamble\@empty
\let\fc@nbrstr@postamble\fc@apply@gcase
\@@numberstringfrench{#1}{#2}}
\global\let\@NumberstringMfrenchbelgian\@NumberstringMfrenchbelgian
\global\let\@NumberstringMfrench=\@NumberstringMfrenchfrance
\newcommand*{\@NumberstringFfrenchswiss}[2]{%
\fc@french@common
\let\fc@gcase\fc@UpperCaseFirstLetter
```

```
\let\@seventies=\@@seventiesfrenchswiss
\let\@eighties=\@@eightiesfrenchswiss
\let\@nineties=\@@ninetiesfrenchswiss
\let\fc@nbrstr@preamble\fc@@nbrstr@Fpreamble
\let\fc@nbrstr@postamble\fc@apply@gcase
\@@numberstringfrench{#1}{#2}}
\global\let\@NumberstringFfrenchswiss\@NumberstringFfrenchswiss
\newcommand*{\@NumberstringFfrenchfrance}[2]{%
\fc@french@common
\let\fc@gcase\fc@UpperCaseFirstLetter
\let\@seventies=\@@seventiesfrench
\let\@eighties=\@@eightiesfrench
\let\@nineties=\@@ninetiesfrench
\let\fc@nbrstr@preamble\fc@@nbrstr@Fpreamble
\let\fc@nbrstr@postamble\fc@apply@gcase
\@@numberstringfrench{#1}{#2}}
\global\let\@NumberstringFfrenchfrance\@NumberstringFfrenchfrance
\newcommand*{\@NumberstringFfrenchbelgian}[2]{%
\fc@french@common
\let\fc@gcase\fc@UpperCaseFirstLetter
\let\@seventies=\@@seventiesfrenchswiss
\let\@eighties=\@@eightiesfrench
\let\@nineties=\@@ninetiesfrench
\let\fc@nbrstr@preamble\fc@@nbrstr@Fpreamble
\let\fc@nbrstr@postamble\fc@apply@gcase
\@@numberstringfrench{#1}{#2}}
\global\let\@NumberstringFfrenchbelgian\@NumberstringFfrenchbelgian
\global\let\@NumberstringFfrench=\@NumberstringFfrenchfrance
\global\let\@NumberstringNfrench\@NumberstringMfrench
\newcommand*{\@ordinalstringMfrenchswiss}[2]{%
\fc@french@common
\let\fc@gcase\fc@CaseIden
\let\fc@first\fc@@firstfrench
\let\@seventies=\@@seventiesfrenchswiss
\let\@eighties=\@@eightiesfrenchswiss
\let\@nineties=\@@ninetiesfrenchswiss
\@@ordinalstringfrench{#1}{#2}%
}%
\global\let\@ordinalstringMfrenchswiss\@ordinalstringMfrenchswiss
\newcommand*\fc@@firstfrench{premier}
\global\let\fc@@firstfrench\fc@@firstfrench

\newcommand*\fc@@firstFfrench{premi\protect\‘ere}
\global\let\fc@@firstFfrench\fc@@firstFfrench
\newcommand*{\@ordinalstringMfrenchfrance}[2]{%
\fc@french@common
\let\fc@gcase\fc@CaseIden
\let\fc@first=\fc@@firstfrench
\let\@seventies=\@@seventiesfrench
\let\@eighties=\@@eightiesfrench
```

```
\let\@nineties=\@@ninetiesfrench
\@@ordinalstringfrench{#1}{#2}}
\global\let\@ordinalstringMfrenchfrance\@ordinalstringMfrenchfrance
\newcommand*{\@ordinalstringMfrenchbelgian}[2]{%
\fc@french@common
\let\fc@gcase\fc@CaseIden
\let\fc@first=\fc@@firstfrench
\let\@seventies=\@@seventiesfrench
\let\@eighties=\@@eightiesfrench
\let\@nineties=\@@ninetiesfrench
\@@ordinalstringfrench{#1}{#2}%
}%
\global\let\@ordinalstringMfrenchbelgian\@ordinalstringMfrenchbelgian
\global\let\@ordinalstringMfrench=\@ordinalstringMfrenchfrance
\newcommand*{\@ordinalstringFfrenchswiss}[2]{%
\fc@french@common
\let\fc@gcase\fc@CaseIden
\let\fc@first\fc@@firstFfrench
\let\@seventies=\@@seventiesfrenchswiss
\let\@eighties=\@@eightiesfrenchswiss
\let\@nineties=\@@ninetiesfrenchswiss
\@@ordinalstringfrench{#1}{#2}%
}%
\global\let\@ordinalstringFfrenchswiss\@ordinalstringFfrenchswiss
\newcommand*{\@ordinalstringFfrenchfrance}[2]{%
\fc@french@common
\let\fc@gcase\fc@CaseIden
\let\fc@first=\fc@@firstFfrench
\let\@seventies=\@@seventiesfrench
\let\@eighties=\@@eightiesfrench
\let\@nineties=\@@ninetiesfrench
\@@ordinalstringfrench{#1}{#2}%
}%
\global\let\@ordinalstringFfrenchfrance\@ordinalstringFfrenchfrance
\newcommand*{\@ordinalstringFfrenchbelgian}[2]{%
\fc@french@common
\let\fc@gcase\fc@CaseIden
\let\fc@first=\fc@@firstFfrench
\let\@seventies=\@@seventiesfrench
\let\@eighties=\@@eightiesfrench
\let\@nineties=\@@ninetiesfrench
\@@ordinalstringfrench{#1}{#2}%
}%
\global\let\@ordinalstringFfrenchbelgian\@ordinalstringFfrenchbelgian
\global\let\@ordinalstringFfrench=\@ordinalstringFfrenchfrance
\global\let\@ordinalstringNfrench\@ordinalstringMfrench
\newcommand*{\@OrdinalstringMfrenchswiss}[2]{%
\fc@french@common
\let\fc@gcase\fc@UpperCaseFirstLetter
```

```
\let\fc@first=\fc@@firstfrench
\let\@seventies=\@@seventiesfrenchswiss
\let\@eighties=\@@eightiesfrenchswiss
\let\@nineties=\@@ninetiesfrenchswiss
\@@ordinalstringfrench{#1}{#2}%
}%
\global\let\@OrdinalstringMfrenchswiss\@OrdinalstringMfrenchswiss
\newcommand*{\@OrdinalstringMfrenchfrance}[2]{%
\fc@french@common
\let\fc@gcase\fc@UpperCaseFirstLetter
\let\fc@first\fc@@firstfrench
\let\@seventies=\@@seventiesfrench
\let\@eighties=\@@eightiesfrench
\let\@nineties=\@@ninetiesfrench
\@@ordinalstringfrench{#1}{#2}%
}%
\global\let\@OrdinalstringMfrenchfrance\@OrdinalstringMfrenchfrance
\newcommand*{\@OrdinalstringMfrenchbelgian}[2]{%
\fc@french@common
\let\fc@gcase\fc@UpperCaseFirstLetter
\let\fc@first\fc@@firstfrench
\let\@seventies=\@@seventiesfrench
\let\@eighties=\@@eightiesfrench
\let\@nineties=\@@ninetiesfrench
\@@ordinalstringfrench{#1}{#2}%
}%
\global\let\@OrdinalstringMfrenchbelgian\@OrdinalstringMfrenchbelgian
\global\let\@OrdinalstringMfrench=\@OrdinalstringMfrenchfrance
\newcommand*{\@OrdinalstringFfrenchswiss}[2]{%
\fc@french@common
\let\fc@gcase\fc@UpperCaseFirstLetter
\let\fc@first\fc@@firstfrench
\let\@seventies=\@@seventiesfrenchswiss
\let\@eighties=\@@eightiesfrenchswiss
\let\@nineties=\@@ninetiesfrenchswiss
\@@ordinalstringfrench{#1}{#2}%
}%
\global\let\@OrdinalstringFfrenchswiss\@OrdinalstringFfrenchswiss
\newcommand*{\@OrdinalstringFfrenchfrance}[2]{%
\fc@french@common
\let\fc@gcase\fc@UpperCaseFirstLetter
\let\fc@first\fc@@firstFfrench
\let\@seventies=\@@seventiesfrench
\let\@eighties=\@@eightiesfrench
\let\@nineties=\@@ninetiesfrench
\@@ordinalstringfrench{#1}{#2}%
}%
\global\let\@OrdinalstringFfrenchfrance\@OrdinalstringFfrenchfrance
\newcommand*{\@OrdinalstringFfrenchbelgian}[2]{%
```

```
\fc@french@common
\let\fc@gcase\fc@UpperCaseFirstLetter
\let\fc@first\fc@@firstFfrench
\let\@seventies=\@@seventiesfrench
\let\@eighties=\@@eightiesfrench
\let\@nineties=\@@ninetiesfrench
\@@ordinalstringfrench{#1}{#2}%
}%
\global\let\@OrdinalstringFfrenchbelgian\@OrdinalstringFfrenchbelgian
\global\let\@OrdinalstringFfrench=\@OrdinalstringFfrenchfrance
\global\let\@OrdinalstringNfrench\@OrdinalstringMfrench
```

`@@do@plural@mark` Macro `\fc@@do@plural@mark` will expand to the plural mark of ⟨*n*⟩illiard, ⟨*n*⟩illion, mil, cent or vingt, whichever is applicable. First check that the macro is not yet defined.

```
\ifcsundef{fc@@do@plural@mark}{}%
{\PackageError{fmtcount}{Duplicate definition}{Redefinition of macro
    `fc@@do@plural@mark'}}
```

Arguments as follows:

`#1` plural mark, 's' in general, but for mil it is `\fc@frenchoptions@mil@plural@mark`

Implicit arguments as follows:

`\count0` input, counter giving the weight w, this is expected to be multiple of 3,

`\count1` input, counter giving the plural value of multiplied object ⟨*n*⟩illiard, ⟨*n*⟩illion, mil, cent or vingt, whichever is applicable, that is to say it is 1 when the considered objet is not multiplied, and 2 or more when it is multiplied,

`\count6` input, counter giving the least weight of non zero digits in top level formatted number integral part, with rounding down to a multiple of 3,

`\count10` input, counter giving the plural mark control option.

```
\def\fc@@do@plural@mark#1{%
  \ifcase\count10 %
    #1% 0=always
   \or% 1=never
   \or% 2=multiple
     \ifnum\count1>1 %
       #1%
     \fi
  \or% 3= multiple g-last
     \ifnum\count1>1 %
       \ifnum\count0=\count6 %
         #1%
       \fi
     \fi
  \or% 4= multiple l-last
     \ifnum\count1>1 %
       \ifnum\count9=1 %
       \else
         #1%
       \fi
     \fi
```

```
  \or% 5= multiple lng-last
     \ifnum\count1>1 %
       \ifnum\count9=1 %
       \else
         \if\count0>\count6 %
           #1%
         \fi
       \fi
     \fi
  \or% 6= multiple ng-last
     \ifnum\count1>1 %
       \ifnum\count0>\count6 %
         #1%
       \fi
     \fi
  \fi
}%
\global\let\fc@@do@plural@mark\fc@@do@plural@mark
```

@@nbrstr@Fpreamble Macro `\fc@@nbrstr@Fpreamble` do the necessary preliminaries before formatting a cardinal with feminine gender.

```
\ifcsundef{fc@@nbrstr@Fpreamble}{}{%
  \PackageError{fmtcount}{Duplicate definition}{Redefinition of macro
    `fc@@nbrstr@Fpreamble'}}
```

@@nbrstr@Fpreamble

```
\def\fc@@nbrstr@Fpreamble{%
  \fc@read@unit{\count1}{0}%
  \ifnum\count1=1 %
      \let\fc@wcase@save\fc@wcase
      \def\fc@wcase{\noexpand\fc@wcase}%
      \def\@nil{\noexpand\@nil}%
     \let\fc@nbrstr@postamble\fc@@nbrstr@Fpostamble
  \fi
}%
\global\let\fc@@nbrstr@Fpreamble\fc@@nbrstr@Fpreamble
```

@@nbrstr@Fpostamble

```
\def\fc@@nbrstr@Fpostamble{%
  \let\fc@wcase\fc@wcase@save
  \expandafter\fc@get@last@word\expandafter{\@tempa}\@tempb\@tempc
  \def\@tempd{un}%
  \ifx\@tempc\@tempd
    \let\@tempc\@tempa
    \edef\@tempa{\@tempb\fc@wcase une\@nil}%
  \fi
}%
\global\let\fc@@nbrstr@Fpostamble\fc@@nbrstr@Fpostamble
```

@@pot@longscalefrench Macro `\fc@@pot@longscalefrench` is used to produce powers of ten with long scale con-

vention. The long scale convention is correct for French and elsewhere in Europe. First we check that the macro is not yet defined.

```
\ifcsundef{fc@@pot@longscalefrench}{}{%
  \PackageError{fmtcount}{Duplicate definition}{Redefinition of macro
    'fc@@pot@longscalefrench'}}
```

Argument are as follows:

- `#1` input, plural value of d, that is to say: let d be the number multiplying the considered power of ten, then the plural value #2 is expected to be 0 if $d = 0$, 1 if $d = 1$, or > 1 if $d > 1$
- `#2` output, counter, maybe 0 when power of ten is 1, 1 when power of ten starts with "mil(le)", or 2 when power of ten is a "⟨n⟩illion(s)|⟨n⟩illiard(s)"
- `#3` output, macro into which to place the formatted power of ten

Implicit arguments as follows:

- `\count0` input, counter giving the weight w, this is expected to be multiple of 3

```
\def\fc@@pot@longscalefrench#1#2#3{%
  {%
```

First the input arguments are saved into local objects: `#1` and `#1` are respectively saved into `\@tempa` and `\@tempb`.

```
    \edef\@tempb{\number#1}%
```

Let `\count1` be the plural value.

```
    \count1=\@tempb
```

Let n and r be the quotient and remainder of division of weight w by 6, that is to say $w = n \times 6 + r$ and $0 \leq r < 6$, then `\count2` is set to n and `\count3` is set to r.

```
    \count2\count0 %
    \divide\count2 by 6 %
    \count3\count2 %
    \multiply\count3 by 6 %
    \count3-\count3 %
    \advance\count3 by \count0 %
    \ifnum\count0>0 %
```

If weight w (a.k.a. `\count0`) is such that $w > 0$, then $w \geq 3$ because w is a multiple of 3. So we *may* have to append "mil(le)" or "⟨n⟩illion(s)" or "⟨n⟩illiard(s)".

```
      \ifnum\count1>0 %
```

Plural value is > 0 so have at least one "mil(le)" or "⟨n⟩illion(s)" or "⟨n⟩illiard(s)". We need to distinguish between the case of "mil(le)" and that of "⟨n⟩illion(s)" or "⟨n⟩illiard(s)", so we `\define` `\@temph` to '1' for "mil(le)", and to '2' otherwise.

```
        \edef\@temph{%
          \ifnum\count2=0 % weight=3
```

Here $n = 0$, with $n = w \div 6$,but we also know that $w \geq 3$, so we have $w = 3$ which means we are in the "mil(le)" case.

```
            1%
          \else
            \ifnum\count3>2 %
```

Here we are in the case of $3 \leq r < 6$, with r the remainder of division of weight w by 6, we should have "⟨n⟩illiard(s)", but that may also be "mil(le)" instead depending on option '`n-illiard upto`', known as `\fc@longscale@nilliard@upto`.

```
            \ifnum\fc@longscale@nilliard@upto=0 %
```

Here option '`n-illiard upto`' is '`infinity`', so we always use "⟨n⟩illiard(s)".

```
              2%
            \else
```

Here option '`n-illiard upto`' indicate some threshold to which to compare n (a.k.a. `\count2`).

```
              \ifnum\count2>\fc@longscale@nilliard@upto
                1%
              \else
                2%
              \fi
            \fi
          \else
            2%
          \fi
        \fi
      }%
      \ifnum\@temph=1 %
```

Here 10^w is formatted as "mil(le)".

```
        \count10=\fc@frenchoptions@mil@plural\space
        \edef\@tempe{%
          \noexpand\fc@wcase
           mil%
           \fc@@do@plural@mark\fc@frenchoptions@mil@plural@mark
          \noexpand\@nil
        }%
      \else
        % weight >= 6
        \expandafter\fc@@latin@cardinal@pefix\expandafter{\the\count2}\@tempg
        % now form the xxx-illion(s) or xxx-illiard(s) word
        \ifnum\count3>2 %
           \toks10{illiard}%
           \count10=\csname fc@frenchoptions@n-illiard@plural\endcsname\space
        \else
           \toks10{illion}%
           \count10=\csname fc@frenchoptions@n-illion@plural\endcsname\space
        \fi
        \edef\@tempe{%
          \noexpand\fc@wcase
          \@tempg
          \the\toks10 %
          \fc@@do@plural@mark s%
          \noexpand\@nil
        }%
```

```
        \fi
      \else
```

Here plural indicator of d indicates that $d = 0$, so we have 0×10^w, and it is not worth to format 10^w, because there are none of them.

```
        \let\@tempe\@empty
        \def\@temph{0}%
      \fi
    \else
```

Case of $w = 0$.

```
      \let\@tempe\@empty
      \def\@temph{0}%
    \fi
```

Now place into cs@tempa the assignment of results \@temph and \@tempe to #2 and #3 for further propagation after closing brace.

```
    \expandafter\toks\expandafter1\expandafter{\@tempe}%
    \toks0{#2}%
    \edef\@tempa{\the\toks0 \@temph \def\noexpand#3{\the\toks1}}%
    \expandafter
  }\@tempa
}%
\global\let\fc@@pot@longscalefrench\fc@@pot@longscalefrench
```

Macro \fc@@pot@shortscalefrench is used to produce powers of ten with short scale convention. This convention is the US convention and is not correct for French and elsewhere in Europe. First we check that the macro is not yet defined.

```
\ifcsundef{fc@@pot@shortscalefrench}{}{%
  \PackageError{fmtcount}{Duplicate definition}{Redefinition of macro
    `fc@@pot@shortscalefrench'}}
```

Arguments as follows — same interface as for \fc@@pot@longscalefrench:

- #1 input, plural value of d, that is to say: let d be the number multiplying the considered power of ten, then the plural value #2 is expected to be 0 if $d = 0$, 1 if $d = 1$, or > 1 if $d > 1$
- #2 output, counter, maybe 0 when power of ten is 1, 1 when power of ten starts with "mil(le)", or 2 when power of ten is a "⟨n⟩illion(s)|⟨n⟩illiard(s)"
- #3 output, macro into which to place the formatted power of ten

Implicit arguments as follows:

- \count0 input, counter giving the weight w, this is expected to be multiple of 3

```
\def\fc@@pot@shortscalefrench#1#2#3{%
  {%
```

First save input arguments #1, #2, and #3 into local macros respectively \@tempa, \@tempb, \@tempc and \@tempd.

```
    \edef\@tempb{\number#1}%
```

And let \count1 be the plural value.

```
    \count1=\@tempb
```

Now, let \count2 be the integer n generating the pseudo latin prefix, i.e. n is such that $w = 3 \times n + 3$.

```
    \count2\count0 %
    \divide\count2 by 3 %
    \advance\count2 by -1 %
```

Here is the real job, the formatted power of ten will go to \@tempe, and its power type will go to \@temph. Please remember that the power type is an index in $[0..2]$ indicating whether 10^w is formatted as ⟨*nothing*⟩, "mil(le)" or "⟨*n*⟩illion(s)|⟨*n*⟩illiard(s)".

```
    \ifnum\count0>0 % If weight>=3, i.e we do have to append thousand or n-illion(s)/n-illiard(
      \ifnum\count1>0 % we have at least one thousand/n-illion/n-illiard
         \ifnum\count2=0 %
           \def\@temph{1}%
           \count1=\fc@frenchoptions@mil@plural\space
           \edef\@tempe{%
             mil%
             \fc@@do@plural@mark\fc@frenchoptions@mil@plural@mark
           }%
         \else
           \def\@temph{2}%
           % weight >= 6
           \expandafter\fc@@latin@cardinal@pefix\expandafter{\the\count2}\@tempg
           \count10=\csname fc@frenchoptions@n-illion@plural\endcsname\space
           \edef\@tempe{%
             \noexpand\fc@wcase
             \@tempg
             illion%
             \fc@@do@plural@mark s%
             \noexpand\@nil
           }%
         \fi
      \else
```

Here we have $d = 0$, so nothing is to be formatted for $d \times 10^w$.

```
        \def\@temph{0}%
        \let\@tempe\@empty
      \fi
    \else
```

Here $w = 0$.

```
      \def\@temph{0}%
      \let\@tempe\@empty
    \fi
% now place into \@cs{@tempa} the assignment of results \cs{@temph} and \cs{@tempe} to to \text
% \texttt{\#3} for further propagation after closing brace.
%    \begin{macrocode}
    \expandafter\toks\expandafter1\expandafter{\@tempe}%
    \toks0{#2}%
    \edef\@tempa{\the\toks0 \@temph \def\noexpand#3{\the\toks1}}%
    \expandafter
```

```
  }\@tempa
}%
\global\let\fc@@pot@shortscalefrench\fc@@pot@shortscalefrench
```

@@pot@recursivefrenMacro `\fc@@pot@recursivefrench` is used to produce power of tens that are of the form "million de milliards de milliards" for 10^{24}. First we check that the macro is not yet defined.

```
\ifcsundef{fc@@pot@recursivefrench}{}{%
  \PackageError{fmtcount}{Duplicate definition}{Redefinition of macro
    `fc@@pot@recursivefrench'}}
```

The arguments are as follows — same interface as for `\fc@@pot@longscalefrench`:

- `#1` input, plural value of d, that is to say: let d be the number multiplying the considered power of ten, then the plural value `#2` is expected to be 0 if $d = 0$, 1 if $d = 1$, or > 1 if $d > 1$
- `#2` output, counter, maybe 0 when power of ten is 1, 1 when power of ten starts with "mil(le)", or 2 when power of ten is a "⟨n⟩illion(s)|⟨n⟩illiard(s)"
- `#3` output, macro into which to place the formatted power of ten

Implicit arguments as follows:

- `\count0` input, counter giving the weight w, this is expected to be multiple of 3

```
\def\fc@@pot@recursivefrench#1#2#3{%
  {%
```

First the input arguments are saved into local objects: `#1` and `#1` are respectively saved into `\@tempa` and `\@tempb`.

```
    \edef\@tempb{\number#1}%
    \let\@tempa\@@tempa
```

New get the inputs `#1` and `#1` into counters `\count0` and `\count1` as this is more practical.

```
    \count1=\@tempb\space
```

Now compute into `\count2` how many times "de milliards" has to be repeated.

```
    \ifnum\count1>0 %
      \count2\count0 %
      \divide\count2 by 9 %
      \advance\count2 by -1 %
      \let\@tempe\@empty
      \edef\@tempf{\fc@frenchoptions@supermillion@dos
        de\fc@frenchoptions@supermillion@dos\fc@wcase milliards\@nil}%
      \count11\count0 %
      \ifnum\count2>0 %
        \count3\count2 %
        \count3-\count3 %
        \multiply\count3 by 9 %
        \advance\count11 by \count3 %
        \loop
           % (\count2, \count3) <- (\count2 div 2, \count2 mod 2)
           \count3\count2 %
           \divide\count3 by 2 %
           \multiply\count3 by 2 %
           \count3-\count3 %
           \advance\count3 by \count2 %
```

```
805           \divide\count2 by 2 %
806           \ifnum\count3=1 %
807             \let\@tempg\@tempe
808             \edef\@tempe{\@tempg\@tempf}%
809           \fi
810           \let\@tempg\@tempf
811           \edef\@tempf{\@tempg\@tempg}%
812           \ifnum\count2>0 %
813         \repeat
814       \fi
815       \divide\count11 by 3 %
816       \ifcase\count11 % 0 .. 5
817         % 0 => d milliard(s) (de milliards)*
818         \def\@temph{2}%
819         \count10=\csname fc@frenchoptions@n-illiard@plural\endcsname\space
820       \or  % 1 => d mille milliard(s) (de milliards)*
821         \def\@temph{1}%
822         \count10=\fc@frenchoptions@mil@plural\space
823       \or % 2 => d million(s) (de milliards)*
824         \def\@temph{2}%
825         \count10=\csname fc@frenchoptions@n-illion@plural\endcsname\space
826       \or % 3 => d milliard(s) (de milliards)*
827         \def\@temph{2}%
828         \count10=\csname fc@frenchoptions@n-illiard@plural\endcsname\space
829       \or % 4 => d mille milliards (de milliards)*
830         \def\@temph{1}%
831         \count10=\fc@frenchoptions@mil@plural\space
832       \else % 5 => d million(s) (de milliards)*
833         \def\@temph{2}%
834         \count10=\csname fc@frenchoptions@n-illion@plural\endcsname\space
835       \fi
836       \let\@tempg\@tempe
837       \edef\@tempf{%
838         \ifcase\count11 % 0 .. 5
839         \or
840           mil\fc@@do@plural@mark \fc@frenchoptions@mil@plural@mark
841         \or
842           million\fc@@do@plural@mark s%
843         \or
844           milliard\fc@@do@plural@mark s%
845         \or
846           mil\fc@@do@plural@mark\fc@frenchoptions@mil@plural@mark
847           \noexpand\@nil\fc@frenchoptions@supermillion@dos
848           \noexpand\fc@wcase milliards% 4
849         \or
850           million\fc@@do@plural@mark s%
851           \noexpand\@nil\fc@frenchoptions@supermillion@dos
852           de\fc@frenchoptions@supermillion@dos\noexpand\fc@wcase  milliards% 5
853         \fi
```

```
      }%
      \edef\@tempe{%
        \ifx\@tempf\@empty\else
         \expandafter\fc@wcase\@tempf\@nil
        \fi
        \@tempg
      }%
    \else
       \def\@temph{0}%
       \let\@tempe\@empty
    \fi
```

Now place into cs@tempa the assignment of results `\@temph` and `\@tempe` to #2 and #3 for further propagation after closing brace.

```
    \expandafter\toks\expandafter1\expandafter{\@tempe}%
    \toks0{#2}%
    \edef\@tempa{\the\toks0 \@temph \def\noexpand#3{\the\toks1}}%
    \expandafter
  }\@tempa
}%
\global\let\fc@@pot@recursivefrench\fc@@pot@recursivefrench
```

`fc@muladdfrench` Macro `\fc@muladdfrench` is used to format the sum of a number a and the product of a number d by a power of ten 10^w. Number d is made of three consecutive digits $d_{w+2}d_{w+1}d_w$ of respective weights $w+2$, $w+1$, and w, while number a is made of all digits with weight $w' > w+2$ that have already been formatted. First check that the macro is not yet defined.

```
\ifcsundef{fc@muladdfrench}{}{%
  \PackageError{fmtcount}{Duplicate definition}{Redefinition of macro
    `fc@muladdfrench'}}
```

Arguments as follows:

- #2 input, plural indicator for number d
- #3 input, formatted number d
- #5 input, formatted number 10^w, i.e. power of ten which is multiplied by d

Implicit arguments from context:

- `\@tempa` input, formatted number a
  output, macro to which place the mul-add result
- `\count8` input, power type indicator for $10^{w'}$, where w' is a weight of a, this is an index in $[0..2]$ that reflects whether $10^{w'}$ is formatted by "mil(le)" — for index = 1 — or by "⟨n⟩illion(s)|⟨n⟩illiard(s)" — for index = 2
- `\count9` input, power type indicator for 10^w, this is an index in $[0..2]$ that reflect whether the weight w of d is formatted by "metanothing" — for index = 0, "mil(le)" — for index = 1 — or by "⟨n⟩illion(s)|⟨n⟩illiard(s)" — for index = 2

```
\def\fc@muladdfrench#1#2#3{%
  {%
```

First we save input arguments #1 – #3 to local macros `\@tempc`, `\@tempd` and `\@tempf`.

```
    \edef\@@tempc{#1}%
    \edef\@@tempd{#2}%
```

```
    \edef\@tempf{#3}%
    \let\@tempc\@@tempc
    \let\@tempd\@@tempd
```

First we want to do the "multiplication" of $d \Rightarrow$ `\@tempd` and of $10^w \Rightarrow$ `\@tempf`. So, prior to this we do some preprocessing of $d \Rightarrow$ `\@tempd`: we force `\@tempd` to ⟨*empty*⟩ if both $d = 1$ and $10^w \Rightarrow$ "mil(le)", this is because we, French, we do not say "un mil", but just "mil".

```
    \ifnum\@tempc=1 %
      \ifnum\count9=1 %
        \let\@tempd\@empty
      \fi
    \fi
```

Now we do the "multiplication" of $d =$ `\@tempd` and of $10^w =$ `\@tempf`, and place the result into `\@tempg`.

```
    \edef\@tempg{%
      \@tempd
      \ifx\@tempd\@empty\else
        \ifx\@tempf\@empty\else
           \ifcase\count9 %
           \or
             \fc@frenchoptions@submillion@dos
           \or
              \fc@frenchoptions@supermillion@dos
           \fi
         \fi
       \fi
     \@tempf
   }%
```

Now to the "addition" of $a \Rightarrow$ `\@tempa` and $d \times 10^w \Rightarrow$ `\@tempg`, and place the results into `\@temph`.

```
   \edef\@temph{%
     \@tempa
     \ifx\@tempa\@empty\else
       \ifx\@tempg\@empty\else
         \ifcase\count8 %
         \or
           \fc@frenchoptions@submillion@dos
         \or
           \fc@frenchoptions@supermillion@dos
         \fi
       \fi
     \fi
     \@tempg
   }%
```

Now propagate the result — i.e. the expansion of `\@temph` — into macro `\@tempa` after closing brace.

```
    \def\@tempb##1{\def\@tempa{\def\@tempa{##1}}}%
```

```
    \expandafter\@tempb\expandafter{\@temph}%
    \expandafter
  }\@tempa
}%
\global\let\fc@muladdfrench\fc@muladdfrench
```

\fc@lthundredstringfrench Macro `\fc@lthundredstringfrench` is used to format a number in interval [0..99]. First we check that it is not already defined.

```
\ifcsundef{fc@lthundredstringfrench}{}{%
  \PackageError{fmtcount}{Duplicate definition}{Redefinition of macro
    `fc@lthundredstringfrench'}}
```

The number to format is not passed as an argument to this macro, instead each digits of it is in a `\fc@digit@`⟨w⟩ macro after this number has been parsed. So the only thing that `\fc@lthundredstringfrench` needs is to know ⟨w⟩ which is passed as `\count0` for the less significant digit.

`#1` intput/output macro to which append the result

Implicit input arguments as follows:

`\count0` weight w of least significant digit d_w.

The formatted number is appended to the content of #1, and the result is placed into #1.

```
\def\fc@lthundredstringfrench#1{%
  {%
```

First save arguments into local temporary macro.

```
    \let\@tempc#1%
```

Read units d_w to `\count1`.

```
    \fc@read@unit{\count1}{\count0}%
```

Read tens d_{w+1} to `\count2`.

```
    \count3\count0 %
    \advance\count3 1 %
    \fc@read@unit{\count2}{\count3}%
```

Now do the real job, set macro `\@tempa` to `#1` followed by $d_{w+1}d_w$ formatted.

```
    \edef\@tempa{%
      \@tempc
      \ifnum\count2>1 %
        % 20 .. 99
        \ifnum\count2>6 %
          % 70 .. 99
          \ifnum\count2<8 %
             % 70 .. 79
             \@seventies{\count1}%
          \else
            % 80..99
            \ifnum\count2<9 %
              % 80 .. 89
              \@eighties{\count1}%
            \else
              % 90 .. 99
```

```
              \@nineties{\count1}%
            \fi
          \fi
        \else
          % 20..69
          \@tenstring{\count2}%
          \ifnum\count1>0 %
             % x1 .. x0
             \ifnum\count1=1 %
               % x1
               \fc@frenchoptions@submillion@dos\@andname\fc@frenchoptions@submillion@dos
             \else
               % x2 .. x9
               -%
             \fi
             \@unitstring{\count1}%
          \fi
        \fi
      \else
        % 0 .. 19
        \ifnum\count2=0 % when tens = 0
          % 0 .. 9
          \ifnum\count1=0 % when units = 0
            % \count3=1 when #1 = 0, i.e. only for the unit of the top level number
            \ifnum\count3=1 %
              \ifnum\fc@max@weight=0 %
                \@unitstring{0}%
              \fi
            \fi
          \else
            % 1 .. 9
            \@unitstring{\count1}%
          \fi
        \else
          % 10 .. 19
          \@teenstring{\count1}%
        \fi
      \fi
    }%
```

Now propagate the expansion of `\@tempa` into `#1` after closing brace.

```
    \def\@tempb##1{\def\@tempa{\def#1{##1}}}%
    \expandafter\@tempb\expandafter{\@tempa}%
    \expandafter
  }\@tempa
}%
\global\let\fc@lthundredstringfrench\fc@lthundredstringfrench
```

Macro `\fc@ltthousandstringfrench` is used to format a number in interval [0..999]. First we check that it is not already defined.

```
\ifcsundef{fc@ltthousandstringfrench}{}{%
  \PackageError{fmtcount}{Duplicate definition}{Redefinition of macro
    `fc@ltthousandstringfrench'}}
```

Output is empty for 0. Arguments as follows:

#2 output, macro, formatted number $d = d_{w+2}d_{w+1}d_w$

Implicit input arguments as follows:

\count0 input weight 10^w of number $d_{w+2}d_{w+1}d_w$ to be formatted.

\count5 least weight of formatted number with a non null digit.

\count9 input, power type indicator of 10^w 0 ⇒ ∅, 1 ⇒ "mil(le)", 2 ⇒ ⟨n⟩illion(s)|⟨n⟩illiard(s)

```
\def\fc@ltthousandstringfrench#1{%
  {%
```

Set counter \count2 to digit d_{w+2}, i.e. hundreds.

```
    \count4\count0 %
    \advance\count4 by 2 %
    \fc@read@unit{\count2 }{\count4 }%
```

Check that the two subsequent digits $d_{w+1}d_w$ are non zero, place check-result into \@tempa.

```
    \advance\count4 by -1 %
    \count3\count4 %
    \advance\count3 by -1 %
    \fc@check@nonzeros{\count3 }{\count4 }\@tempa
```

Compute plural mark of 'cent' into \@temps.

```
    \edef\@temps{%
      \ifcase\fc@frenchoptions@cent@plural\space
      % 0 => always
      s%
      \or
      % 1 => never
      \or
      % 2 => multiple
      \ifnum\count2>1s\fi
      \or
      % 3 => multiple g-last
        \ifnum\count2>1 \ifnum\@tempa=0 \ifnum\count0=\count6s\fi\fi\fi
      \or
      % 4 => multiple l-last
        \ifnum\count2>1 \ifnum\@tempa=0 \ifnum\count9=0s\else\ifnum\count9=2s\fi\fi\fi\fi
      \fi
    }%
    % compute spacing after cent(s?) into \@tempb
    \expandafter\let\expandafter\@tempb
       \ifnum\@tempa>0 \fc@frenchoptions@submillion@dos\else\@empty\fi
    % now place into \@tempa the hundreds
    \edef\@tempa{%
       \ifnum\count2=0 %
       \else
```

```
        \ifnum\count2=1 %
          \expandafter\fc@wcase\@hundred\@nil
        \else
          \@unitstring{\count2}\fc@frenchoptions@submillion@dos
          \noexpand\fc@wcase\@hundred\@temps\noexpand\@nil
        \fi
        \@tempb
      \fi
    }%
    % now append to \@tempa the ten and unit
    \fc@lthundredstringfrench\@tempa
```

Propagate expansion of `\@tempa` into macro #1 after closing brace.

```
    \def\@tempb##1{\def\@tempa{\def#1{##1}}}%
    \expandafter\@tempb\expandafter{\@tempa}%
    \expandafter
  }\@tempa
}%
\global\let\fc@ltthousandstringfrench\fc@ltthousandstringfrench
```

umberstringfrench Macro `\@@numberstringfrench` is the main engine for formatting cadinal numbers in French. First we check that the control sequence is not yet defined.

```
\ifcsundef{@@numberstringfrench}{}{%
  \PackageError{fmtcount}{Duplicate definition}{Redefinition of macro ‘@@numberstringfrench’}}
```

Arguments are as follows:

#1 number to convert to string

#2 macro into which to place the result

```
\def\@@numberstringfrench#1#2{%
  {%
```

First parse input number to be formatted and do some error handling.

```
    \edef\@tempa{#1}%
    \expandafter\fc@number@parser\expandafter{\@tempa}%
    \ifnum\fc@min@weight<0 %
       \PackageError{fmtcount}{Out of range}%
          {This macro does not work with fractional numbers}%
    \fi
```

In the sequel, `\@tempa` is used to accumulate the formatted number. Please note that `\space` after `\fc@sign@case` is eaten by preceding number collection. This `\space` is needed so that when `\fc@sign@case` expands to ‘0’, then `\@tempa` is defined to ‘’ (i.e. empty) rather than to ‘`\relax`’.

```
    \edef\@tempa{\ifcase\fc@sign@case\space\or\fc@wcase plus\@nil\or\fc@wcase moins\@nil\fi}%
    \fc@nbrstr@preamble
    \fc@@nbrstrfrench@inner
    \fc@nbrstr@postamble
```

Propagate the result — i.e. expansion of `\@tempa` — into macro #2 after closing brace.

```
    \def\@tempb##1{\def\@tempa{\def#2{##1}}}%
    \expandafter\@tempb\expandafter{\@tempa}%
```

```
    \expandafter
  }\@tempa
}%
\global\let\@@numberstringfrench\@@numberstringfrench
```

\@@nbrstrfrench@inner Common part of \@@numberstringfrench and \@@ordinalstringfrench. Arguments are as follows:

\@tempa input/output, macro to which the result is to be aggregated, initially empty or contains the sign indication.

```
\def\fc@@nbrstrfrench@inner{%
```

Now loop, first we compute starting weight as $3 \times \left\lfloor \frac{\texttt{\fc@max@weight}}{3} \right\rfloor$ into \count0.

```
    \count0=\fc@max@weight
    \divide\count0 by 3 %
    \multiply\count0 by 3 %
```

Now we compute final weight into \count5, and round down to multiple of 3 into \count6. Warning: \count6 is an implicit input argument to macro \fc@ltthousandstringfrench.

```
    \fc@intpart@find@last{\count5 }%
    \count6\count5 %
    \divide\count6 3 %
    \multiply\count6 3 %
    \count8=0 %
    \loop
```

First we check whether digits in weight interval $[w..(w+2)]$ are all zero and place check result into macro \@tempt.

```
      \count1\count0 %
      \advance\count1 by 2 %
      \fc@check@nonzeros{\count0 }{\count1 }\@tempt
```

Now we generate the power of ten 10^w, formatted power of ten goes to \@tempb, while power type indicator goes to \count9.

```
      \fc@poweroften\@tempt{\count9 }\@tempb
```

Now we generate the formatted number d into macro \@tempd by which we need to multiply 10^w. Implicit input argument is \count9 for power type of 10^9, and \count6

```
      \fc@ltthousandstringfrench\@tempd
```

Finally do the multiplication-addition. Implicit arguments are \@tempa for input/output growing formatted number, \count8 for input previous power type, i.e. power type of 10^{w+3}, \count9 for input current power type, i.e. power type of 10^w.

```
      \fc@muladdfrench\@tempt\@tempd\@tempb
```

Then iterate. \count8 must hold the power type of the last *non zero* group that went into \@tempa, because that is what decides the separator in front of the next non zero group. A group of three zero digits yields power type 0, so it must not overwrite \count8: otherwise with 2 000 005 the zero thousands group would reset it and the units would be glued to "millions" without any space or dash, giving "deux millionscinq".

```
      \ifnum\@tempt>0 \count8\count9 \fi
      \advance\count0 by -3 %
```

```
      \ifnum\count6>\count0 \else
    \repeat
}%
\global\let\fc@@nbrstrfrench@inner\fc@@nbrstrfrench@inner
```

rdinalstringfrench Macro `\@@ordinalstringfrench` is the main engine for formatting ordinal numbers in French. First check it is not yet defined.

```
\ifcsundef{@@ordinalstringfrench}{}{%
  \PackageError{fmtcount}{Duplicate definition}{Redefinition of macro
    `@@ordinalstringfrench'}}
```

Arguments are as follows:

#1 number to convert to string

#2 macro into which to place the result

```
\def\@@ordinalstringfrench#1#2{%
  {%
```

First parse input number to be formatted and do some error handling.

```
    \edef\@tempa{#1}%
    \expandafter\fc@number@parser\expandafter{\@tempa}%
    \ifnum\fc@min@weight<0 %
       \PackageError{fmtcount}{Out of range}%
          {This macro does not work with fractional numbers}%
    \fi
    \ifnum\fc@sign@case>0 %
       \PackageError{fmtcount}{Out of range}%
          {This macro does with negative or explicitly marked as positive numbers}%
    \fi
```

Now handle the special case of first. We set `\count0` to `1` if we are in this case, and to `0` otherwise

```
    \ifnum\fc@max@weight=0 %
      \ifnum\csname fc@digit@0\endcsname=1 %
        \count0=1 %
      \else
        \count0=0 %
      \fi
    \else
      \count0=0 %
    \fi
    \ifnum\count0=1 %
        \expandafter\@firstoftwo
    \else
        \expandafter\@secondoftwo
    \fi

        {%
      \protected@edef\@tempa{\expandafter\fc@wcase\fc@first\@nil}%
        }%
```

Now we tamper a little bit with the plural handling options to ensure that there is no final plural mark.

```
      {%
    \def\@tempa##1{%
      \expandafter\edef\csname fc@frenchoptions@##1@plural\endcsname{%
        \ifcase\csname fc@frenchoptions@##1@plural\endcsname\space
        0% 0: always => always
        \or
        1% 1: never => never
        \or
        6% 2: multiple => multiple  ng-last
        \or
        1% 3: multiple g-last => never
        \or
        5% 4: multiple l-last => multiple lng-last
        \or
        5% 5: multiple lng-last => multiple lng-last
        \or
        6% 6: multiple ng-last => multiple ng-last
        \fi
      }%
    }%
    \@tempa{vingt}%
    \@tempa{cent}%
    \@tempa{mil}%
    \@tempa{n-illion}%
    \@tempa{n-illiard}%
```

Now make `\fc@wcase` and `\@nil` non expandable

```
    \let\fc@wcase@save\fc@wcase
    \def\fc@wcase{\noexpand\fc@wcase}%
    \def\@nil{\noexpand\@nil}%
```

In the sequel, `\@tempa` is used to accumulate the formatted number.

```
    \let\@tempa\@empty
    \fc@@nbrstrfrench@inner
```

Now restore `\fc@wcase`

```
  \let\fc@wcase\fc@wcase@save
```

Now we add the “ième” ending

```
    \expandafter\fc@get@last@word\expandafter{\@tempa}\@tempb\@tempc
    \expandafter\fc@get@last@letter\expandafter{\@tempc}\@tempd\@tempe
    \def\@tempf{e}%
    \ifx\@tempe\@tempf
      \protected@edef\@tempa{\@tempb\expandafter\fc@wcase\@tempd i\protect\‘eme\@nil}%
    \else
      \def\@tempf{q}%
      \ifx\@tempe\@tempf
        \protected@edef\@tempa{\@tempb\expandafter\fc@wcase\@tempd qui\protect\‘eme\@nil}%
      \else
```

```
          \def\@tempf{f}%
          \ifx\@tempe\@tempf
            \protected@edef\@tempa{\@tempb\expandafter\fc@wcase\@tempd vi\protect\‘eme\@nil}%
          \else
            \protected@edef\@tempa{\@tempb\expandafter\fc@wcase\@tempc i\protect\‘eme\@nil}%
          \fi
        \fi
      \fi
  }%
```

Apply `\fc@gcase` to the result.

```
    \fc@apply@gcase
```

Propagate the result — i.e. expansion of `\@tempa` — into macro #2 after closing brace.

```
    \def\@tempb##1{\def\@tempa{\def#2{##1}}}%
    \expandafter\@tempb\expandafter{\@tempa}%
    \expandafter
  }\@tempa
}%
\global\let\@@ordinalstringfrench\@@ordinalstringfrench
```

Macro `\fc@frenchoptions@setdefaults` allows to set all options to default for the French.

```
\newcommand*\fc@frenchoptions@setdefaults{%
  \csname KV@fcfrench@all plural\endcsname{reformed}%
  \fc@gl@def\fc@frenchoptions@submillion@dos{-}%
  \fc@gl@let\fc@frenchoptions@supermillion@dos\space
  \fc@gl@let\fc@u@in@duo\@empty% Could be ‘u’
  % \fc@gl@let\fc@poweroften\fc@@pot@longscalefrench
  \fc@gl@let\fc@poweroften\fc@@pot@recursivefrench
  \fc@gl@def\fc@longscale@nilliard@upto{0}% infinity
  \fc@gl@def\fc@frenchoptions@mil@plural@mark{le}%
}%
\global\let\fc@frenchoptions@setdefaults\fc@frenchoptions@setdefaults
{%
  \let\fc@gl@def\gdef
  \def\fc@gl@let{\global\let}%
  \fc@frenchoptions@setdefaults
}%
```

Make some indirection to call the current French dialect corresponding macro.

```
\gdef\@ordinalstringMfrench{\csuse{@ordinalstringMfrench\fmtcount@french}}%
\gdef\@ordinalstringFfrench{\csuse{@ordinalstringFfrench\fmtcount@french}}%
\gdef\@OrdinalstringMfrench{\csuse{@OrdinalstringMfrench\fmtcount@french}}%
\gdef\@OrdinalstringFfrench{\csuse{@OrdinalstringFfrench\fmtcount@french}}%
\gdef\@numberstringMfrench{\csuse{@numberstringMfrench\fmtcount@french}}%
\gdef\@numberstringFfrench{\csuse{@numberstringFfrench\fmtcount@french}}%
\gdef\@NumberstringMfrench{\csuse{@NumberstringMfrench\fmtcount@french}}%
\gdef\@NumberstringFfrench{\csuse{@NumberstringFfrench\fmtcount@french}}%
```

10.1.8 fc-frenchb.def

```
\ProvidesFCLanguage{frenchb}[2013/08/17]%
\FCloadlang{french}%
```

Set `frenchb` to be equivalent to `french`.

```
\global\let\@ordinalMfrenchb=\@ordinalMfrench
\global\let\@ordinalFfrenchb=\@ordinalFfrench
\global\let\@ordinalNfrenchb=\@ordinalNfrench
\global\let\@numberstringMfrenchb=\@numberstringMfrench
\global\let\@numberstringFfrenchb=\@numberstringFfrench
\global\let\@numberstringNfrenchb=\@numberstringNfrench
\global\let\@NumberstringMfrenchb=\@NumberstringMfrench
\global\let\@NumberstringFfrenchb=\@NumberstringFfrench
\global\let\@NumberstringNfrenchb=\@NumberstringNfrench
\global\let\@ordinalstringMfrenchb=\@ordinalstringMfrench
\global\let\@ordinalstringFfrenchb=\@ordinalstringFfrench
\global\let\@ordinalstringNfrenchb=\@ordinalstringNfrench
\global\let\@OrdinalstringMfrenchb=\@OrdinalstringMfrench
\global\let\@OrdinalstringFfrenchb=\@OrdinalstringFfrench
\global\let\@OrdinalstringNfrenchb=\@OrdinalstringNfrench
```

10.1.9 fc-german-at-1901.def

Dialect name provided by the babel-german package (pre-1996 orthography).

```
\ProvidesFCLanguage{german-at-1901}[2026/09/02]%
```

Load fc-german.def if not already loaded

```
\FCloadlang{german}%
```

Set `german-at-1901` to be equivalent to `german`: the number and ordinal words are not affected by the 1996 spelling reform, and the German and Austrian variants spell them the same way as `german` does.

```
\FCaliaslang{german-at-1901}{german}%
```

10.1.10 fc-german-at.def

Dialect name provided by the babel-german package (post-1996 orthography).

```
\ProvidesFCLanguage{german-at}[2026/09/02]%
```

Load fc-german.def if not already loaded

```
\FCloadlang{german}%
```

Set `german-at` to be equivalent to `german`: the number and ordinal words are not affected by the 1996 spelling reform, and the German and Austrian variants spell them the same way as `german` does.

```
\FCaliaslang{german-at}{german}%
```

10.1.11 fc-german-austria-1901.def

Dialect name provided by the babel-german package (pre-1996 orthography).

```
\ProvidesFCLanguage{german-austria-1901}[2026/09/02]%
```

Load fc-german.def if not already loaded

```
\FCloadlang{german}%
```

Set german-austria-1901 to be equivalent to german: the number and ordinal words are not affected by the 1996 spelling reform, and the German and Austrian variants spell them the same way as german does.

```
\FCaliaslang{german-austria-1901}{german}%
```

10.1.12 fc-german-austria.def

Dialect name provided by the babel-german package (post-1996 orthography).

```
\ProvidesFCLanguage{german-austria}[2026/09/02]%
```

Load fc-german.def if not already loaded

```
\FCloadlang{german}%
```

Set german-austria to be equivalent to german: the number and ordinal words are not affected by the 1996 spelling reform, and the German and Austrian variants spell them the same way as german does.

```
\FCaliaslang{german-austria}{german}%
```

10.1.13 fc-german-ch-1901.def

Swiss German, one of the dialect names provided by the babel-german package (pre-1996 orthography).

```
\ProvidesFCLanguage{german-ch-1901}[2026/09/02]%
```

Load fc-german-ch.def if not already loaded, and use its definitions

```
\FCloadlang{german-ch}%
\FCaliaslang{german-ch-1901}{germanswiss}%
```

10.1.14 fc-german-ch.def

Swiss German, one of the dialect names provided by the babel-german package (post-1996 orthography).

```
\ProvidesFCLanguage{german-ch}[2026/09/02]%
```

Load fc-german.def if not already loaded

```
\FCloadlang{german}%
```

Swiss German spells ss where the German and Austrian variants spell ß, so dreissig rather than dreißig. Everything else is the same, hence the definitions below reuse the word lists of fc-german.def through the setup macros defined there, and only differ from their german counterparts by letting \fc@german@sz to \fc@german@ss.

The definitions are made under the name germanswiss rather than german-ch. A hyphenated control sequence name is perfectly legal, but it cannot be written down literally — it has to be built with \csname, so each of the definitions below would need an

\expandafter\newcommand\csname…\endcsname dance. Defining them once under a hyphen free name and then letting \FCaliaslang — which does use \csname — map them onto the four hyphenated dialect names keeps them readable.

The numeric ordinals hold no sharp s, so they are plain synonyms:

```
\global\let\@ordinalMgermanswiss\@ordinalMgerman
\global\let\@ordinalFgermanswiss\@ordinalFgerman
\global\let\@ordinalNgermanswiss\@ordinalNgerman
```

Numbers as text:

```
\newcommand*{\@numberstringMgermanswiss}[2]{%
  \@fc@german@numberstringsetup
  \let\fc@german@sz\fc@german@ss
  \@@numberstringgerman{#1}{#2}%
}%
\global\let\@numberstringMgermanswiss\@numberstringMgermanswiss
\global\let\@numberstringFgermanswiss=\@numberstringMgermanswiss
\global\let\@numberstringNgermanswiss=\@numberstringMgermanswiss
```

As above, but initial letters in upper case:

```
\newcommand*{\@NumberstringMgermanswiss}[2]{%
  \@numberstringMgermanswiss{#1}{\@@num@str}%
  \edef#2{\noexpand\MakeUppercase\expandonce\@@num@str}%
}%
\global\let\@NumberstringMgermanswiss\@NumberstringMgermanswiss
\global\let\@NumberstringFgermanswiss=\@NumberstringMgermanswiss
\global\let\@NumberstringNgermanswiss=\@NumberstringMgermanswiss
```

Ordinals as text, masculine:

```
\newcommand*{\@ordinalstringMgermanswiss}[2]{%
  \@fc@german@ordinalstringMsetup
  \let\fc@german@sz\fc@german@ss
  \@@ordinalstringgerman{#1}{#2}%
}%
\global\let\@ordinalstringMgermanswiss\@ordinalstringMgermanswiss
```

Feminine form:

```
\newcommand*{\@ordinalstringFgermanswiss}[2]{%
  \@fc@german@ordinalstringFsetup
  \let\fc@german@sz\fc@german@ss
  \@@ordinalstringgerman{#1}{#2}%
}%
\global\let\@ordinalstringFgermanswiss\@ordinalstringFgermanswiss
```

Neuter form:

```
\newcommand*{\@ordinalstringNgermanswiss}[2]{%
  \@fc@german@ordinalstringNsetup
  \let\fc@german@sz\fc@german@ss
  \@@ordinalstringgerman{#1}{#2}%
}%
\global\let\@ordinalstringNgermanswiss\@ordinalstringNgermanswiss
```

As above, but with initial letters in upper case.

```
\newcommand*{\@OrdinalstringMgermanswiss}[2]{%
 \@ordinalstringMgermanswiss{#1}{\@@num@str}%
 \edef#2{\noexpand\MakeUppercase\expandonce\@@num@str}%
}%
\global\let\@OrdinalstringMgermanswiss\@OrdinalstringMgermanswiss
```

Feminine form:

```
\newcommand*{\@OrdinalstringFgermanswiss}[2]{%
 \@ordinalstringFgermanswiss{#1}{\@@num@str}%
 \edef#2{\noexpand\MakeUppercase\expandonce\@@num@str}%
}%
\global\let\@OrdinalstringFgermanswiss\@OrdinalstringFgermanswiss
```

Neuter form:

```
\newcommand*{\@OrdinalstringNgermanswiss}[2]{%
 \@ordinalstringNgermanswiss{#1}{\@@num@str}%
 \edef#2{\noexpand\MakeUppercase\expandonce\@@num@str}%
}%
\global\let\@OrdinalstringNgermanswiss\@OrdinalstringNgermanswiss
```

Finally make `german-ch` use these definitions.

```
\FCaliaslang{german-ch}{germanswiss}%
```

10.1.15 fc-german-de-1901.def

Dialect name provided by the babel-german package (pre-1996 orthography).

```
\ProvidesFCLanguage{german-de-1901}[2026/09/02]%
```

Load fc-german.def if not already loaded

```
\FCloadlang{german}%
```

Set `german-de-1901` to be equivalent to `german`: the number and ordinal words are not affected by the 1996 spelling reform, and the German and Austrian variants spell them the same way as `german` does.

```
\FCaliaslang{german-de-1901}{german}%
```

10.1.16 fc-german-de.def

Dialect name provided by the babel-german package (post-1996 orthography).

```
\ProvidesFCLanguage{german-de}[2026/09/02]%
```

Load fc-german.def if not already loaded

```
\FCloadlang{german}%
```

Set `german-de` to be equivalent to `german`: the number and ordinal words are not affected by the 1996 spelling reform, and the German and Austrian variants spell them the same way as `german` does.

```
\FCaliaslang{german-de}{german}%
```

10.1.17 fc-german-germany-1901.def

Dialect name provided by the babel-german package (pre-1996 orthography).

```
\ProvidesFCLanguage{german-germany-1901}[2026/09/02]%
```

Load fc-german.def if not already loaded

```
\FCloadlang{german}%
```

Set german-germany-1901 to be equivalent to german: the number and ordinal words are not affected by the 1996 spelling reform, and the German and Austrian variants spell them the same way as german does.

```
\FCaliaslang{german-germany-1901}{german}%
```

10.1.18 fc-german-germany.def

Dialect name provided by the babel-german package (post-1996 orthography).

```
\ProvidesFCLanguage{german-germany}[2026/09/02]%
```

Load fc-german.def if not already loaded

```
\FCloadlang{german}%
```

Set german-germany to be equivalent to german: the number and ordinal words are not affected by the 1996 spelling reform, and the German and Austrian variants spell them the same way as german does.

```
\FCaliaslang{german-germany}{german}%
```

10.1.19 fc-german-switzerland-1901.def

Swiss German, one of the dialect names provided by the babel-german package (pre-1996 orthography).

```
\ProvidesFCLanguage{german-switzerland-1901}[2026/09/02]%
```

Load fc-german-ch.def if not already loaded, and use its definitions

```
\FCloadlang{german-ch}%
\FCaliaslang{german-switzerland-1901}{germanswiss}%
```

10.1.20 fc-german-switzerland.def

Swiss German, one of the dialect names provided by the babel-german package (post-1996 orthography).

```
\ProvidesFCLanguage{german-switzerland}[2026/09/02]%
```

Load fc-german-ch.def if not already loaded, and use its definitions

```
\FCloadlang{german-ch}%
\FCaliaslang{german-switzerland}{germanswiss}%
```

10.1.21 fc-german.def

German definitions (thank you to K. H. Fricke for supplying this information)

```
\ProvidesFCLanguage{german}[2026/09/02]%
```

Swiss German has no sharp s, it writes `ss` where the German and Austrian variants write ß — `dreissig` rather than `dreißig`. Rather than duplicating the whole word list, the spelling is parametrised: the number and ordinal word lists below write `\fc@german@sz`, and every entry point `\let`s it to `\fc@german@sharpS` or to `\fc@german@ss` before building a string. It has to be set by the entry points rather than once and for all, because one document may well use both `german` and `german-ch`.

```
\newcommand*\fc@german@sharpS{ß}%
\newcommand*\fc@german@ss{ss}%
\global\let\fc@german@sharpS\fc@german@sharpS
\global\let\fc@german@ss\fc@german@ss
\global\let\fc@german@sz\fc@german@sharpS
```

Define macro that converts a number or count register (first argument) to an ordinal, and stores the result in the second argument, which must be a control sequence. Masculine:

```
\newcommand{\@ordinalMgerman}[2]{%
  \edef#2{\number#1\relax.}%
}%
\global\let\@ordinalMgerman\@ordinalMgerman
```

Feminine:

```
\newcommand{\@ordinalFgerman}[2]{%
  \edef#2{\number#1\relax.}%
}%
\global\let\@ordinalFgerman\@ordinalFgerman
```

Neuter:

```
\newcommand{\@ordinalNgerman}[2]{%
  \edef#2{\number#1\relax.}%
}%
\global\let\@ordinalNgerman\@ordinalNgerman
```

Convert a number to text. The easiest way to do this is to break it up into units, tens and teens. Units (argument must be a number from 0 to 9, 1 on its own (eins) is dealt with separately):

```
\newcommand*\@@unitstringgerman[1]{%
  \ifcase#1%
    null%
    \or ein%
    \or zwei%
    \or drei%
    \or vier%
    \or fünf%
    \or sechs%
    \or sieben%
    \or acht%
    \or neun%
```

```
  \fi
}%
\global\let\@@unitstringgerman\@@unitstringgerman
```

Tens (argument must go from 1 to 10):

```
\newcommand*\@@tenstringgerman[1]{%
  \ifcase#1%
    \or zehn%
    \or zwanzig%
    \or drei\fc@german@sz ig%
    \or vierzig%
    \or fünfzig%
    \or sechzig%
    \or siebzig%
    \or achtzig%
    \or neunzig%
    \or einhundert%
  \fi
}%
\global\let\@@tenstringgerman\@@tenstringgerman
```

`\einhundert` is set to `einhundert` by default, user can redefine this command to just `hundert` if required, similarly for `\eintausend`.

```
\providecommand*{\einhundert}{einhundert}%
\providecommand*{\eintausend}{eintausend}%
\global\let\einhundert\einhundert
\global\let\eintausend\eintausend
```

Teens:

```
\newcommand*\@@teenstringgerman[1]{%
  \ifcase#1%
    zehn%
    \or elf%
    \or zwölf%
    \or dreizehn%
    \or vierzehn%
    \or fünfzehn%
    \or sechzehn%
    \or siebzehn%
    \or achtzehn%
    \or neunzehn%
  \fi
}%
\global\let\@@teenstringgerman\@@teenstringgerman
```

The results are stored in the second argument, but doesn't display anything. The word lists are selected by `\@fc@german@numberstringsetup` and by `\@fc@german@ordinalstring`⟨*gender*⟩`setup`, so that `fc-german-ch.def` can reuse them for the Swiss spelling instead of repeating them.

```
\newcommand*\@fc@german@numberstringsetup{%
  \let\@unitstring=\@@unitstringgerman
  \let\@teenstring=\@@teenstringgerman
```

```
  \let\@tenstring=\@@tenstringgerman
}%
\global\let\@fc@german@numberstringsetup\@fc@german@numberstringsetup
\newcommand*{\@numberstringMgerman}[2]{%
  \@fc@german@numberstringsetup
  \let\fc@german@sz\fc@german@sharpS
  \@@numberstringgerman{#1}{#2}%
}%
\global\let\@numberstringMgerman\@numberstringMgerman
```

Feminine and neuter forms:

```
\global\let\@numberstringFgerman=\@numberstringMgerman
\global\let\@numberstringNgerman=\@numberstringMgerman
```

As above, but initial letters in upper case:

```
\newcommand*{\@NumberstringMgerman}[2]{%
  \@numberstringMgerman{#1}{\@@num@str}%
  \edef#2{\noexpand\MakeUppercase\expandonce\@@num@str}%
}%
\global\let\@NumberstringMgerman\@numberstringMgerman
```

Feminine and neuter form:

```
\global\let\@NumberstringFgerman=\@NumberstringMgerman
\global\let\@NumberstringNgerman=\@NumberstringMgerman
```

As above, but for ordinals.

```
\newcommand*\@fc@german@ordinalstringMsetup{%
  \let\@unitthstring=\@@unitthstringMgerman
  \let\@teenthstring=\@@teenthstringMgerman
  \let\@tenthstring=\@@tenthstringMgerman
  \@fc@german@numberstringsetup
  \def\@thousandth{tausendster}%
  \def\@hundredth{hundertster}%
}%
\global\let\@fc@german@ordinalstringMsetup\@fc@german@ordinalstringMsetup
\newcommand*{\@ordinalstringMgerman}[2]{%
  \@fc@german@ordinalstringMsetup
  \let\fc@german@sz\fc@german@sharpS
  \@@ordinalstringgerman{#1}{#2}%
}%
\global\let\@ordinalstringMgerman\@ordinalstringMgerman
```

Feminine form:

```
\newcommand*\@fc@german@ordinalstringFsetup{%
  \let\@unitthstring=\@@unitthstringFgerman
  \let\@teenthstring=\@@teenthstringFgerman
  \let\@tenthstring=\@@tenthstringFgerman
  \@fc@german@numberstringsetup
  \def\@thousandth{tausendste}%
  \def\@hundredth{hundertste}%
}%
```

```
\global\let\@fc@german@ordinalstringFsetup\@fc@german@ordinalstringFsetup
\newcommand*{\@ordinalstringFgerman}[2]{%
  \@fc@german@ordinalstringFsetup
  \let\fc@german@sz\fc@german@sharpS
  \@@ordinalstringgerman{#1}{#2}%
}%
\global\let\@ordinalstringFgerman\@ordinalstringFgerman
```

Neuter form:

```
\newcommand*\@fc@german@ordinalstringNsetup{%
  \let\@unitthstring=\@@unitthstringNgerman
  \let\@teenthstring=\@@teenthstringNgerman
  \let\@tenthstring=\@@tenthstringNgerman
  \@fc@german@numberstringsetup
  \def\@thousandth{tausendstes}%
  \def\@hundredth{hunderstes}%
}%
\global\let\@fc@german@ordinalstringNsetup\@fc@german@ordinalstringNsetup
\newcommand*{\@ordinalstringNgerman}[2]{%
  \@fc@german@ordinalstringNsetup
  \let\fc@german@sz\fc@german@sharpS
  \@@ordinalstringgerman{#1}{#2}%
}%
\global\let\@ordinalstringNgerman\@ordinalstringNgerman
```

As above, but with initial letters in upper case.

```
\newcommand*{\@OrdinalstringMgerman}[2]{%
 \@ordinalstringMgerman{#1}{\@@num@str}%
 \edef#2{\noexpand\MakeUppercase\expandonce\@@num@str}%
}%
\global\let\@OrdinalstringMgerman\@OrdinalstringMgerman
```

Feminine form:

```
\newcommand*{\@OrdinalstringFgerman}[2]{%
 \@ordinalstringFgerman{#1}{\@@num@str}%
 \edef#2{\noexpand\MakeUppercase\expandonce\@@num@str}%
}%
\global\let\@OrdinalstringFgerman\@OrdinalstringFgerman
```

Neuter form:

```
\newcommand*{\@OrdinalstringNgerman}[2]{%
 \@ordinalstringNgerman{#1}{\@@num@str}%
 \edef#2{\noexpand\MakeUppercase\expandonce\@@num@str}%
}%
\global\let\@OrdinalstringNgerman\@OrdinalstringNgerman
```

Code for converting numbers into textual ordinals. As before, it is easier to split it into units, tens and teens. Units:

```
\newcommand*\@@unitthstringMgerman[1]{%
  \ifcase#1%
    nullter%
```

```
    \or erster%
    \or zweiter%
    \or dritter%
    \or vierter%
    \or fünfter%
    \or sechster%
    \or siebter%
    \or achter%
    \or neunter%
  \fi
}%
\global\let\@@unitthstringMgerman\@@unitthstringMgerman
```

Tens:

```
\newcommand*\@@tenthstringMgerman[1]{%
  \ifcase#1%
    \or zehnter%
    \or zwanzigster%
    \or drei\fc@german@sz igster%
    \or vierzigster%
    \or fünfzigster%
    \or sechzigster%
    \or siebzigster%
    \or achtzigster%
    \or neunzigster%
  \fi
}%
\global\let\@@tenthstringMgerman\@@tenthstringMgerman
```

Teens:

```
\newcommand*\@@teenthstringMgerman[1]{%
  \ifcase#1%
    zehnter%
    \or elfter%
    \or zwölfter%
    \or dreizehnter%
    \or vierzehnter%
    \or fünfzehnter%
    \or sechzehnter%
    \or siebzehnter%
    \or achtzehnter%
    \or neunzehnter%
  \fi
}%
\global\let\@@teenthstringMgerman\@@teenthstringMgerman
```

Units (feminine):

```
\newcommand*\@@unitthstringFgerman[1]{%
  \ifcase#1%
    nullte%
    \or erste%
```

```
    \or zweite%
    \or dritte%
    \or vierte%
    \or fünfte%
    \or sechste%
    \or siebte%
    \or achte%
    \or neunte%
  \fi
}%
\global\let\@@unitthstringFgerman\@@unitthstringFgerman
```

Tens (feminine):

```
\newcommand*\@@tenthstringFgerman[1]{%
  \ifcase#1%
    \or zehnte%
    \or zwanzigste%
    \or drei\fc@german@sz igste%
    \or vierzigste%
    \or fünfzigste%
    \or sechzigste%
    \or siebzigste%
    \or achtzigste%
    \or neunzigste%
  \fi
}%
\global\let\@@tenthstringFgerman\@@tenthstringFgerman
```

Teens (feminine)

```
\newcommand*\@@teenthstringFgerman[1]{%
  \ifcase#1%
    zehnte%
    \or elfte%
    \or zwölfte%
    \or dreizehnte%
    \or vierzehnte%
    \or fünfzehnte%
    \or sechzehnte%
    \or siebzehnte%
    \or achtzehnte%
    \or neunzehnte%
  \fi
}%
\global\let\@@teenthstringFgerman\@@teenthstringFgerman
```

Units (neuter):

```
\newcommand*\@@unitthstringNgerman[1]{%
  \ifcase#1%
    nulltes%
    \or erstes%
    \or zweites%
```

```
    \or drittes%
    \or viertes%
    \or fünftes%
    \or sechstes%
    \or siebtes%
    \or achtes%
    \or neuntes%
  \fi
}%
\global\let\@@unitthstringNgerman\@@unitthstringNgerman
```

Tens (neuter):

```
\newcommand*\@@tenthstringNgerman[1]{%
  \ifcase#1%
    \or zehntes%
    \or zwanzigstes%
    \or drei\fc@german@sz igstes%
    \or vierzigstes%
    \or fünfzigstes%
    \or sechzigstes%
    \or siebzigstes%
    \or achtzigstes%
    \or neunzigstes%
  \fi
}%
\global\let\@@tenthstringNgerman\@@tenthstringNgerman
```

Teens (neuter)

```
\newcommand*\@@teenthstringNgerman[1]{%
  \ifcase#1%
    zehntes%
    \or elftes%
    \or zwölftes%
    \or dreizehntes%
    \or vierzehntes%
    \or fünfzehntes%
    \or sechzehntes%
    \or siebzehntes%
    \or achtzehntes%
    \or neunzehntes%
  \fi
}%
\global\let\@@teenthstringNgerman\@@teenthstringNgerman
```

This appends the results to \#2 for number \#2 (in range 0 to 100.) null and eins are dealt with separately in \@@numberstringgerman.

```
\newcommand*\@@numberunderhundredgerman[2]{%
\ifnum#1<10\relax
  \ifnum#1>0\relax
    \eappto#2{\@unitstring{#1}}%
  \fi
```

```
\else
  \@tmpstrctr=#1\relax
  \@FCmodulo{\@tmpstrctr}{10}%
  \ifnum#1<20\relax
    \eappto#2{\@teenstring{\@tmpstrctr}}%
  \else
    \ifnum\@tmpstrctr=0\relax
    \else
      \eappto#2{\@unitstring{\@tmpstrctr}und}%
    \fi
    \@tmpstrctr=#1\relax
    \divide\@tmpstrctr by 10\relax
    \eappto#2{\@tenstring{\@tmpstrctr}}%
  \fi
\fi
}%
\global\let\@@numberunderhundredgerman\@@numberunderhundredgerman
```

This stores the results in the second argument (which must be a control sequence), but it doesn't display anything.

```
\newcommand*\@@numberstringgerman[2]{%
\ifnum#1>99999\relax
  \PackageError{fmtcount}{Out of range}%
  {This macro only works for values less than 100000}%
\else
  \ifnum#1<0\relax
    \PackageError{fmtcount}{Negative numbers not permitted}%
    {This macro does not work for negative numbers, however
    you can try typing "minus" first, and then pass the modulus of
    this number}%
  \fi
\fi
\def#2{}%
\@strctr=#1\relax \divide\@strctr by 1000\relax
\ifnum\@strctr>1\relax
```

#1 is ≥ 2000, `\@strctr` now contains the number of thousands

```
 \@@numberunderhundredgerman{\@strctr}{#2}%
  \appto#2{tausend}%
\else
```

#1 lies in range [1000,1999]

```
  \ifnum\@strctr=1\relax
    \eappto#2{\eintausend}%
  \fi
\fi
\@strctr=#1\relax
\@FCmodulo{\@strctr}{1000}%
\divide\@strctr by 100\relax
\ifnum\@strctr>1\relax
```

now dealing with number in range [200,999]

```
  \eappto#2{\@unitstring{\@strctr}hundert}%
\else
   \ifnum\@strctr=1\relax
```

dealing with number in range [100,199]

```
     \ifnum#1>1000\relax
```

if original number > 1000, use einhundert

```
        \appto#2{einhundert}%
     \else
```

otherwise use \einhundert

```
        \eappto#2{\einhundert}%
      \fi
   \fi
\fi
\@strctr=#1\relax
\@FCmodulo{\@strctr}{100}%
\ifnum#1=0\relax
  \def#2{null}%
\else
  \ifnum\@strctr=1\relax
    \appto#2{eins}%
  \else
    \@@numberunderhundredgerman{\@strctr}{#2}%
  \fi
\fi
}%
\global\let\@@numberstringgerman\@@numberstringgerman
```

As above, but for ordinals

```
\newcommand*\@@numberunderhundredthgerman[2]{%
\ifnum#1<10\relax
 \eappto#2{\@unitthstring{#1}}%
\else
  \@tmpstrctr=#1\relax
  \@FCmodulo{\@tmpstrctr}{10}%
  \ifnum#1<20\relax
    \eappto#2{\@teenthstring{\@tmpstrctr}}%
  \else
    \ifnum\@tmpstrctr=0\relax
    \else
      \eappto#2{\@unitstring{\@tmpstrctr}und}%
    \fi
    \@tmpstrctr=#1\relax
    \divide\@tmpstrctr by 10\relax
    \eappto#2{\@tenthstring{\@tmpstrctr}}%
  \fi
\fi
}%
```

```
\global\let\@@numberunderhundredthgerman\@@numberunderhundredthgerman

\newcommand*\@@ordinalstringgerman[2]{%
\@orgargctr=#1\relax
\ifnum\@orgargctr>99999\relax
  \PackageError{fmtcount}{Out of range}%
  {This macro only works for values less than 100000}%
\else
  \ifnum\@orgargctr<0\relax
    \PackageError{fmtcount}{Negative numbers not permitted}%
    {This macro does not work for negative numbers, however
    you can try typing "minus" first, and then pass the modulus of
    this number}%
  \fi
\fi
\def#2{}%
\@strctr=\@orgargctr\divide\@strctr by 1000\relax
\ifnum\@strctr>1\relax
```

#1 is ≥ 2000, `\@strctr` now contains the number of thousands

```
\@@numberunderhundredgerman{\@strctr}{#2}%
```

is that it, or is there more?

```
  \@tmpstrctr=\@orgargctr\@FCmodulo{\@tmpstrctr}{1000}%
  \ifnum\@tmpstrctr=0\relax
    \eappto#2{\@thousandth}%
  \else
    \appto#2{tausend}%
  \fi
\else
```

#1 lies in range [1000,1999]

```
  \ifnum\@strctr=1\relax
    \ifnum\@orgargctr=1000\relax
      \eappto#2{\@thousandth}%
    \else
      \eappto#2{\eintausend}%
    \fi
  \fi
\fi
\@strctr=\@orgargctr
\@FCmodulo{\@strctr}{1000}%
\divide\@strctr by 100\relax
\ifnum\@strctr>1\relax
```

now dealing with number in range [200,999] is that it, or is there more?

```
  \@tmpstrctr=\@orgargctr \@FCmodulo{\@tmpstrctr}{100}%
  \ifnum\@tmpstrctr=0\relax
     \ifnum\@strctr=1\relax
       \eappto#2{\@hundredth}%
     \else
```

```
      \eappto#2{\@unitstring{\@strctr}\@hundredth}%
    \fi
  \else
    \eappto#2{\@unitstring{\@strctr}hundert}%
  \fi
\else
  \ifnum\@strctr=1\relax
```

dealing with number in range [100,199] is that it, or is there more?

```
    \@tmpstrctr=\@orgargctr \@FCmodulo{\@tmpstrctr}{100}%
    \ifnum\@tmpstrctr=0\relax
       \eappto#2{\@hundredth}%
    \else
    \ifnum\@orgargctr>1000\relax
       \appto#2{einhundert}%
    \else
       \eappto#2{\einhundert}%
    \fi
    \fi
  \fi
\fi
\@strctr=\@orgargctr
\@FCmodulo{\@strctr}{100}%
\ifthenelse{\@strctr=0 \and \@orgargctr>0 }{}{%
\@@numberunderhundredthgerman{\@strctr}{#2}%
}%
}%
\global\let\@@ordinalstringgerman\@@ordinalstringgerman
```

Load fc-germanb.def if not already loaded

```
\FCloadlang{germanb}%
```

10.1.22 fc-germanb.def

```
\ProvidesFCLanguage{germanb}[2013/08/17]%
```

Load fc-german.def if not already loaded

```
\FCloadlang{german}%
```

Set germanb to be equivalent to german.

```
\global\let\@ordinalMgermanb=\@ordinalMgerman
\global\let\@ordinalFgermanb=\@ordinalFgerman
\global\let\@ordinalNgermanb=\@ordinalNgerman
\global\let\@numberstringMgermanb=\@numberstringMgerman
\global\let\@numberstringFgermanb=\@numberstringFgerman
\global\let\@numberstringNgermanb=\@numberstringNgerman
\global\let\@NumberstringMgermanb=\@NumberstringMgerman
\global\let\@NumberstringFgermanb=\@NumberstringFgerman
\global\let\@NumberstringNgermanb=\@NumberstringNgerman
\global\let\@ordinalstringMgermanb=\@ordinalstringMgerman
\global\let\@ordinalstringFgermanb=\@ordinalstringFgerman
```

```
\global\let\@ordinalstringNgermanb=\@ordinalstringNgerman
\global\let\@OrdinalstringMgermanb=\@OrdinalstringMgerman
\global\let\@OrdinalstringFgermanb=\@OrdinalstringFgerman
\global\let\@OrdinalstringNgermanb=\@OrdinalstringNgerman
```

10.1.23 fc-italian.def

Italian support is now handled by interfacing to Enrico Gregorio's itnumpar package.

```
\ProvidesFCLanguage{italian}[2013/08/17]

\RequirePackage{itnumpar}

\newcommand{\@numberstringMitalian}[2]{%
  \begingroup
    \def\np@oa{o}%
    \count@=#1
    \edef\@tempa{\def\noexpand#2{\@numeroinparole{\count@}}}%
    \expandafter
  \endgroup\@tempa
}
\global\let\@numberstringMitalian\@numberstringMitalian

\newcommand{\@numberstringFitalian}[2]{%
  \begingroup
    \def\np@oa{a}%
    \count@=#1
    \edef\@tempa{\def\noexpand#2{\@numeroinparole{\count@}}}%
    \expandafter
  \endgroup\@tempa
}

\global\let\@numberstringFitalian\@numberstringFitalian

\newcommand{\@NumberstringMitalian}[2]{%
  \begingroup
    \def\np@oa{o}%
    \count@=#1
    \edef\@tempa{\def\noexpand#2{\@Numeroinparole{\count@}}}%
    \expandafter
  \endgroup\@tempa
}
\global\let\@NumberstringMitalian\@NumberstringMitalian

\newcommand{\@NumberstringFitalian}[2]{%
  \begingroup
    \def\np@oa{a}%
    \count@=#1
    \edef\@tempa{\def\noexpand#2{\@Numeroinparole{\count@}}}%
    \expandafter
  \endgroup\@tempa
```

```
}
\global\let\@NumberstringFitalian\@NumberstringFitalian

\newcommand{\@ordinalstringMitalian}[2]{%
  \begingroup
    \count@=#1
    \edef\@tempa{\def\noexpand#2{\@ordinalem{\count@}}}%
    \expandafter
  \endgroup\@tempa
}
\global\let\@ordinalstringMitalian\@ordinalstringMitalian

\newcommand{\@ordinalstringFitalian}[2]{%
  \begingroup
    \count@=#1
    \edef\@tempa{\def\noexpand#2{\@ordinalef{\count@}}}%
    \expandafter
  \endgroup\@tempa
}
\global\let\@ordinalstringFitalian\@ordinalstringFitalian

\newcommand{\@OrdinalstringMitalian}[2]{%
  \begingroup
    \count@=#1
    \edef\@tempa{\def\noexpand#2{\@Ordinalem{\count@}}}%
    \expandafter
  \endgroup\@tempa
}
\global\let\@OrdinalstringMitalian\@OrdinalstringMitalian

\newcommand{\@ORDINALSTRINGMitalian}[2]{%
  \begingroup
    \count@=#1
    \edef\@tempa{\def\noexpand#2{\MakeUppercase{\@ordinalem{\count@}}}}%
    \expandafter
  \endgroup\@tempa
}
\global\let\@ORDINALSTRINGMitalian\@ORDINALSTRINGMitalian

\newcommand{\@OrdinalstringFitalian}[2]{%
  \begingroup
    \count@=#1
    \edef\@tempa{\def\noexpand#2{\@Ordinalef{\count@}}}%
    \expandafter
  \endgroup\@tempa
}
\global\let\@OrdinalstringFitalian\@OrdinalstringFitalian

\newcommand{\@ORDINALSTRINGFitalian}[2]{%
```

```
  \begingroup
    \count@=#1
    \edef\@tempa{\def\noexpand#2{\MakeUppercase{\@ordinalef{\count@}}}}%
    \expandafter
  \endgroup\@tempa
}
\global\let\@ORDINALSTRINGFitalian\@ORDINALSTRINGFitalian

\newcommand{\@ordinalMitalian}[2]{%
  \edef#2{#1\relax\noexpand\fmtord{o}}}

\global\let\@ordinalMitalian\@ordinalMitalian

\newcommand{\@ordinalFitalian}[2]{%
  \edef#2{#1\relax\noexpand\fmtord{a}}}
\global\let\@ordinalFitalian\@ordinalFitalian
```

10.1.24 fc-ngerman.def

```
\ProvidesFCLanguage{ngerman}[2012/06/18]%
\FCloadlang{german}%
\FCloadlang{ngermanb}%
```

Set ngerman to be equivalent to german. Is it okay to do this? (I don't know the difference between the two.)

```
\global\let\@ordinalMngerman=\@ordinalMgerman
\global\let\@ordinalFngerman=\@ordinalFgerman
\global\let\@ordinalNngerman=\@ordinalNgerman
\global\let\@numberstringMngerman=\@numberstringMgerman
\global\let\@numberstringFngerman=\@numberstringFgerman
\global\let\@numberstringNngerman=\@numberstringNgerman
\global\let\@NumberstringMngerman=\@NumberstringMgerman
\global\let\@NumberstringFngerman=\@NumberstringFgerman
\global\let\@NumberstringNngerman=\@NumberstringNgerman
\global\let\@ordinalstringMngerman=\@ordinalstringMgerman
\global\let\@ordinalstringFngerman=\@ordinalstringFgerman
\global\let\@ordinalstringNngerman=\@ordinalstringNgerman
\global\let\@OrdinalstringMngerman=\@OrdinalstringMgerman
\global\let\@OrdinalstringFngerman=\@OrdinalstringFgerman
\global\let\@OrdinalstringNngerman=\@OrdinalstringNgerman
```

10.1.25 fc-ngermanb.def

```
\ProvidesFCLanguage{ngermanb}[2013/08/17]%
\FCloadlang{german}%
```

Set ngermanb to be equivalent to german. Is it okay to do this? (I don't know the difference between the two.)

```
\global\let\@ordinalMngermanb=\@ordinalMgerman
\global\let\@ordinalFngermanb=\@ordinalFgerman
\global\let\@ordinalNngermanb=\@ordinalNgerman
```

```
\global\let\@numberstringMngermanb=\@numberstringMgerman
\global\let\@numberstringFngermanb=\@numberstringFgerman
\global\let\@numberstringNngermanb=\@numberstringNgerman
\global\let\@NumberstringMngermanb=\@NumberstringMgerman
\global\let\@NumberstringFngermanb=\@NumberstringFgerman
\global\let\@NumberstringNngermanb=\@NumberstringNgerman
\global\let\@ordinalstringMngermanb=\@ordinalstringMgerman
\global\let\@ordinalstringFngermanb=\@ordinalstringFgerman
\global\let\@ordinalstringNngermanb=\@ordinalstringNgerman
\global\let\@OrdinalstringMngermanb=\@OrdinalstringMgerman
\global\let\@OrdinalstringFngermanb=\@OrdinalstringFgerman
\global\let\@OrdinalstringNngermanb=\@OrdinalstringNgerman
```

Load fc-ngerman.def if not already loaded

```
\FCloadlang{ngerman}%
```

10.1.26 fc-portuges.def

Portuguese definitions

```
\ProvidesFCLanguage{portuges}[2017/12/26]%
```

Define macro that converts a number or count register (first argument) to an ordinal, and stores the result in the second argument, which should be a control sequence. Masculine:

```
\newcommand*\@ordinalMportuges[2]{%
  \ifnum#1=0\relax
    \edef#2{\number#1}%
  \else
    \edef#2{\number#1\relax\noexpand\fmtord{o}}%
  \fi
}%
\global\let\@ordinalMportuges\@ordinalMportuges
```

Feminine:

```
\newcommand*\@ordinalFportuges[2]{%
  \ifnum#1=0\relax
    \edef#2{\number#1}%
  \else
    \edef#2{\number#1\relax\noexpand\fmtord{a}}%
  \fi
}%
\global\let\@ordinalFportuges\@ordinalFportuges
```

Make neuter same as masculine:

```
\global\let\@ordinalNportuges\@ordinalMportuges
```

Convert a number to a textual representation. To make it easier, split it up into units, tens, teens and hundreds. Units (argument must be a number from 0 to 9):

```
\newcommand*\@@unitstringportuges[1]{%
  \ifcase#1\relax
    zero%
    \or um%
    \or dois%
```

```
    \or tr\^es%
    \or quatro%
    \or cinco%
    \or seis%
    \or sete%
    \or oito%
    \or nove%
  \fi
}%
\global\let\@@unitstringportuges\@@unitstringportuges
%   \end{macrocode}
% As above, but for feminine:
%   \begin{macrocode}
\newcommand*\@@unitstringFportuges[1]{%
  \ifcase#1\relax
    zero%
    \or uma%
    \or duas%
    \or tr\^es%
    \or quatro%
    \or cinco%
    \or seis%
    \or sete%
    \or oito%
    \or nove%
  \fi
}%
\global\let\@@unitstringFportuges\@@unitstringFportuges
```

Tens (argument must be a number from 0 to 10):

```
\newcommand*\@@tenstringportuges[1]{%
  \ifcase#1\relax
    \or dez%
    \or vinte%
    \or trinta%
    \or quarenta%
    \or cinquenta%
    \or sessenta%
    \or setenta%
    \or oitenta%
    \or noventa%
    \or cem%
  \fi
}%
\global\let\@@tenstringportuges\@@tenstringportuges
```

Teens (argument must be a number from 0 to 9):

```
\newcommand*\@@teenstringportuges[1]{%
  \ifcase#1\relax
    dez%
```

```
    \or onze%
    \or doze%
    \or treze%
    \or catorze%
    \or quinze%
    \or dezasseis%
    \or dezassete%
    \or dezoito%
    \or dezanove%
  \fi
}%
\global\let\@@teenstringportuges\@@teenstringportuges
```

Hundreds:

```
\newcommand*\@@hundredstringportuges[1]{%
  \ifcase#1\relax
    \or cento%
    \or duzentos%
    \or trezentos%
    \or quatrocentos%
    \or quinhentos%
    \or seiscentos%
    \or setecentos%
    \or oitocentos%
    \or novecentos%
  \fi
}%
\global\let\@@hundredstringportuges\@@hundredstringportuges
```

Hundreds (feminine):

```
\newcommand*\@@hundredstringFportuges[1]{%
  \ifcase#1\relax
    \or cento%
    \or duzentas%
    \or trezentas%
    \or quatrocentas%
    \or quinhentas%
    \or seiscentas%
    \or setecentas%
    \or oitocentas%
    \or novecentas%
  \fi
}%
\global\let\@@hundredstringFportuges\@@hundredstringFportuges
```

Units (initial letter in upper case):

```
\newcommand*\@@Unitstringportuges[1]{%
  \ifcase#1\relax
    Zero%
    \or Um%
    \or Dois%
```

```
    \or Tr\^es%
    \or Quatro%
    \or Cinco%
    \or Seis%
    \or Sete%
    \or Oito%
    \or Nove%
  \fi
}%
\global\let\@@Unitstringportuges\@@Unitstringportuges
```

As above, but feminine:

```
\newcommand*\@@UnitstringFportuges[1]{%
  \ifcase#1\relax
    Zera%
    \or Uma%
    \or Duas%
    \or Tr\^es%
    \or Quatro%
    \or Cinco%
    \or Seis%
    \or Sete%
    \or Oito%
    \or Nove%
  \fi
}%
\global\let\@@UnitstringFportuges\@@UnitstringFportuges
```

Tens (with initial letter in upper case):

```
\newcommand*\@@Tenstringportuges[1]{%
  \ifcase#1\relax
    \or Dez%
    \or Vinte%
    \or Trinta%
    \or Quarenta%
    \or Cinquenta%
    \or Sessenta%
    \or Setenta%
    \or Oitenta%
    \or Noventa%
    \or Cem%
  \fi
}%
\global\let\@@Tenstringportuges\@@Tenstringportuges
```

Teens (with initial letter in upper case):

```
\newcommand*\@@Teenstringportuges[1]{%
  \ifcase#1\relax
    Dez%
    \or Onze%
    \or Doze%
```

```
    \or Treze%
    \or Catorze%
    \or Quinze%
    \or Dezasseis%
    \or Dezassete%
    \or Dezoito%
    \or Dezanove%
  \fi
}%
\global\let\@@Teenstringportuges\@@Teenstringportuges
```

Hundreds (with initial letter in upper case):

```
\newcommand*\@@Hundredstringportuges[1]{%
  \ifcase#1\relax
    \or Cento%
    \or Duzentos%
    \or Trezentos%
    \or Quatrocentos%
    \or Quinhentos%
    \or Seiscentos%
    \or Setecentos%
    \or Oitocentos%
    \or Novecentos%
  \fi
}%
\global\let\@@Hundredstringportuges\@@Hundredstringportuges
```

As above, but feminine:

```
\newcommand*\@@HundredstringFportuges[1]{%
  \ifcase#1\relax
    \or Cento%
    \or Duzentas%
    \or Trezentas%
    \or Quatrocentas%
    \or Quinhentas%
    \or Seiscentas%
    \or Setecentas%
    \or Oitocentas%
    \or Novecentas%
  \fi
}%
\global\let\@@HundredstringFportuges\@@HundredstringFportuges
```

This has changed in version 1.08, so that it now stores the result in the second argument, but doesn't display anything. Since it only affects internal macros, it shouldn't affect documents created with older versions. (These internal macros are not meant for use in documents.)

```
\newcommand*{\@numberstringMportuges}[2]{%
  \let\@unitstring=\@@unitstringportuges
  \let\@teenstring=\@@teenstringportuges
  \let\@tenstring=\@@tenstringportuges
```

```
  \let\@hundredstring=\@@hundredstringportuges
  \def\@hundred{cem}\def\@thousand{mil}%
  \def\@andname{e}%
  \@@numberstringportuges{#1}{#2}%
}%
\global\let\@numberstringMportuges\@numberstringMportuges
```

As above, but feminine form:

```
\newcommand*{\@numberstringFportuges}[2]{%
  \let\@unitstring=\@@unitstringFportuges
  \let\@teenstring=\@@teenstringportuges
  \let\@tenstring=\@@tenstringportuges
  \let\@hundredstring=\@@hundredstringFportuges
  \def\@hundred{cem}\def\@thousand{mil}%
  \def\@andname{e}%
  \@@numberstringportuges{#1}{#2}%
}%
\global\let\@numberstringFportuges\@numberstringFportuges
```

Make neuter same as masculine:

```
\global\let\@numberstringNportuges\@numberstringMportuges
```

As above, but initial letters in upper case:

```
\newcommand*{\@NumberstringMportuges}[2]{%
  \let\@unitstring=\@@Unitstringportuges
  \let\@teenstring=\@@Teenstringportuges
  \let\@tenstring=\@@Tenstringportuges
  \let\@hundredstring=\@@Hundredstringportuges
  \def\@hundred{Cem}\def\@thousand{Mil}%
  \def\@andname{e}%
  \@@numberstringportuges{#1}{#2}%
}%
\global\let\@NumberstringMportuges\@NumberstringMportuges
```

As above, but feminine form:

```
\newcommand*{\@NumberstringFportuges}[2]{%
  \let\@unitstring=\@@UnitstringFportuges
  \let\@teenstring=\@@Teenstringportuges
  \let\@tenstring=\@@Tenstringportuges
  \let\@hundredstring=\@@HundredstringFportuges
  \def\@hundred{Cem}\def\@thousand{Mil}%
  \def\@andname{e}%
  \@@numberstringportuges{#1}{#2}%
}%
\global\let\@NumberstringFportuges\@NumberstringFportuges
```

Make neuter same as masculine:

```
\global\let\@NumberstringNportuges\@NumberstringMportuges
```

As above, but for ordinals.

```
\newcommand*{\@ordinalstringMportuges}[2]{%
  \let\@unitthstring=\@@unitthstringportuges
```

```
  \let\@unitstring=\@@unitstringportuges
  \let\@teenthstring=\@@teenthstringportuges
  \let\@tenthstring=\@@tenthstringportuges
  \let\@hundredthstring=\@@hundredthstringportuges
  \def\@thousandth{mil\'esimo}%
  \@@ordinalstringportuges{#1}{#2}%
}%
\global\let\@ordinalstringMportuges\@ordinalstringMportuges
```

Feminine form:

```
\newcommand*{\@ordinalstringFportuges}[2]{%
  \let\@unitthstring=\@@unitthstringFportuges
  \let\@unitstring=\@@unitstringFportuges
  \let\@teenthstring=\@@teenthstringportuges
  \let\@tenthstring=\@@tenthstringFportuges
  \let\@hundredthstring=\@@hundredthstringFportuges
  \def\@thousandth{mil\'esima}%
  \@@ordinalstringportuges{#1}{#2}%
}%
\global\let\@ordinalstringFportuges\@ordinalstringFportuges
```

Make neuter same as masculine:

```
\global\let\@ordinalstringNportuges\@ordinalstringMportuges
```

As above, but initial letters in upper case (masculine):

```
\newcommand*{\@OrdinalstringMportuges}[2]{%
  \let\@unitthstring=\@@Unitthstringportuges
  \let\@unitstring=\@@Unitstringportuges
  \let\@teenthstring=\@@teenthstringportuges
  \let\@tenthstring=\@@Tenthstringportuges
  \let\@hundredthstring=\@@Hundredthstringportuges
  \def\@thousandth{Mil\'esimo}%
  \@@ordinalstringportuges{#1}{#2}%
}%
\global\let\@OrdinalstringMportuges\@OrdinalstringMportuges
```

Feminine form:

```
\newcommand*{\@OrdinalstringFportuges}[2]{%
  \let\@unitthstring=\@@UnitthstringFportuges
  \let\@unitstring=\@@UnitstringFportuges
  \let\@teenthstring=\@@teenthstringportuges
  \let\@tenthstring=\@@TenthstringFportuges
  \let\@hundredthstring=\@@HundredthstringFportuges
  \def\@thousandth{Mil\'esima}%
  \@@ordinalstringportuges{#1}{#2}%
}%
\global\let\@OrdinalstringFportuges\@OrdinalstringFportuges
```

Make neuter same as masculine:

```
\global\let\@OrdinalstringNportuges\@OrdinalstringMportuges
```

In order to do the ordinals, split into units, teens, tens and hundreds. Units:

```
\newcommand*\@@unitthstringportuges[1]{%
  \ifcase#1\relax
    zero%
    \or primeiro%
    \or segundo%
    \or terceiro%
    \or quarto%
    \or quinto%
    \or sexto%
    \or s\'etimo%
    \or oitavo%
    \or nono%
  \fi
}%
\global\let\@@unitthstringportuges\@@unitthstringportuges
```

Tens:

```
\newcommand*\@@tenthstringportuges[1]{%
  \ifcase#1\relax
    \or d\'ecimo%
    \or vig\'esimo%
    \or trig\'esimo%
    \or quadrag\'esimo%
    \or quinquag\'esimo%
    \or sexag\'esimo%
    \or setuag\'esimo%
    \or octog\'esimo%
    \or nonag\'esimo%
  \fi
}%
\global\let\@@tenthstringportuges\@@tenthstringportuges
```

Teens:

```
\newcommand*\@@teenthstringportuges[1]{%
  \@tenthstring{1}%
  \ifnum#1>0\relax
    -\@unitthstring{#1}%
  \fi
}%
\global\let\@@teenthstringportuges\@@teenthstringportuges
```

Hundreds:

```
\newcommand*\@@hundredthstringportuges[1]{%
  \ifcase#1\relax
    \or cent\'esimo%
    \or ducent\'esimo%
    \or trecent\'esimo%
    \or quadringent\'esimo%
    \or quingent\'esimo%
    \or seiscent\'esimo%
    \or setingent\'esimo%
```

```
    \or octingent\'esimo%
    \or nongent\'esimo%
  \fi
}%
\global\let\@@hundredthstringportuges\@@hundredthstringportuges
```

Units (feminine):

```
\newcommand*\@@unitthstringFportuges[1]{%
  \ifcase#1\relax
    zero%
    \or primeira%
    \or segunda%
    \or terceira%
    \or quarta%
    \or quinta%
    \or sexta%
    \or s\'etima%
    \or oitava%
    \or nona%
  \fi
}%
\global\let\@@unitthstringFportuges\@@unitthstringFportuges
```

Tens (feminine):

```
\newcommand*\@@tenthstringFportuges[1]{%
  \ifcase#1\relax
    \or d\'ecima%
    \or vig\'esima%
    \or trig\'esima%
    \or quadrag\'esima%
    \or quinquag\'esima%
    \or sexag\'esima%
    \or setuag\'esima%
    \or octog\'esima%
    \or nonag\'esima%
  \fi
}%
\global\let\@@tenthstringFportuges\@@tenthstringFportuges
```

Hundreds (feminine):

```
\newcommand*\@@hundredthstringFportuges[1]{%
  \ifcase#1\relax
    \or cent\'esima%
    \or ducent\'esima%
    \or trecent\'esima%
    \or quadringent\'esima%
    \or quingent\'esima%
    \or seiscent\'esima%
    \or setingent\'esima%
    \or octingent\'esima%
    \or nongent\'esima%
```

```
  \fi
}%
\global\let\@@hundredthstringFportuges\@@hundredthstringFportuges
```

As above, but with initial letter in upper case. Units:

```
\newcommand*\@@Unitthstringportuges[1]{%
  \ifcase#1\relax
    Zero%
    \or Primeiro%
    \or Segundo%
    \or Terceiro%
    \or Quarto%
    \or Quinto%
    \or Sexto%
    \or S\'etimo%
    \or Oitavo%
    \or Nono%
  \fi
}%
\global\let\@@Unitthstringportuges\@@Unitthstringportuges
```

Tens:

```
\newcommand*\@@Tenthstringportuges[1]{%
  \ifcase#1\relax
    \or D\'ecimo%
    \or Vig\'esimo%
    \or Trig\'esimo%
    \or Quadrag\'esimo%
    \or Quinquag\'esimo%
    \or Sexag\'esimo%
    \or Setuag\'esimo%
    \or Octog\'esimo%
    \or Nonag\'esimo%
  \fi
}%
\global\let\@@Tenthstringportuges\@@Tenthstringportuges
```

Hundreds:

```
\newcommand*\@@Hundredthstringportuges[1]{%
  \ifcase#1\relax
    \or Cent\'esimo%
    \or Ducent\'esimo%
    \or Trecent\'esimo%
    \or Quadringent\'esimo%
    \or Quingent\'esimo%
    \or Seiscent\'esimo%
    \or Setingent\'esimo%
    \or Octingent\'esimo%
    \or Nongent\'esimo%
  \fi
}%
```

```
\global\let\@@Hundredthstringportuges\@@Hundredthstringportuges
```

As above, but feminine. Units:

```
\newcommand*\@@UnitthstringFportuges[1]{%
  \ifcase#1\relax
    Zera%
    \or Primeira%
    \or Segunda%
    \or Terceira%
    \or Quarta%
    \or Quinta%
    \or Sexta%
    \or S\'etima%
    \or Oitava%
    \or Nona%
  \fi
}%
\global\let\@@UnitthstringFportuges\@@UnitthstringFportuges
```

Tens (feminine);

```
\newcommand*\@@TenthstringFportuges[1]{%
  \ifcase#1\relax
    \or D\'ecima%
    \or Vig\'esima%
    \or Trig\'esima%
    \or Quadrag\'esima%
    \or Quinquag\'esima%
    \or Sexag\'esima%
    \or Setuag\'esima%
    \or Octog\'esima%
    \or Nonag\'esima%
  \fi
}%
\global\let\@@TenthstringFportuges\@@TenthstringFportuges
```

Hundreds (feminine):

```
\newcommand*\@@HundredthstringFportuges[1]{%
  \ifcase#1\relax
    \or Cent\'esima%
    \or Ducent\'esima%
    \or Trecent\'esima%
    \or Quadringent\'esima%
    \or Quingent\'esima%
    \or Seiscent\'esima%
    \or Setingent\'esima%
    \or Octingent\'esima%
    \or Nongent\'esima%
  \fi
}%
\global\let\@@HundredthstringFportuges\@@HundredthstringFportuges
```

This has changed in version 1.09, so that it now stores the result in the second argument (a control sequence), but it doesn't display anything. Since it only affects internal macros, it shouldn't affect documents created with older versions. (These internal macros are not meant for use in documents.)

```
\newcommand*\@@numberstringportuges[2]{%
\ifnum#1>99999\relax
  \PackageError{fmtcount}{Out of range}%
  {This macro only works for values less than 100000}%
\else
  \ifnum#1<0\relax
    \PackageError{fmtcount}{Negative numbers not permitted}%
    {This macro does not work for negative numbers, however
    you can try typing "minus" first, and then pass the modulus of
    this number}%
  \fi
\fi
\def#2{}%
\@strctr=#1\relax \divide\@strctr by 1000\relax
\ifnum\@strctr>9\relax
```

#1 is greater or equal to 10000

```
  \divide\@strctr by 10\relax
  \ifnum\@strctr>1\relax
    \let\@@fc@numstr#2\relax
    \protected@edef#2{\@@fc@numstr\@tenstring{\@strctr}}%
    \@strctr=#1 \divide\@strctr by 1000\relax
    \@FCmodulo{\@strctr}{10}%
    \ifnum\@strctr>0
      \let\@@fc@numstr#2\relax
      \protected@edef#2{\@@fc@numstr\ \@andname\ \@unitstring{\@strctr}}%
    \fi
  \else
    \@strctr=#1\relax
    \divide\@strctr by 1000\relax
    \@FCmodulo{\@strctr}{10}%
    \let\@@fc@numstr#2\relax
    \protected@edef#2{\@@fc@numstr\@teenstring{\@strctr}}%
  \fi
  \let\@@fc@numstr#2\relax
  \protected@edef#2{\@@fc@numstr\ \@thousand}%
\else
  \ifnum\@strctr>0\relax
    \ifnum\@strctr>1\relax
      \let\@@fc@numstr#2\relax
      \protected@edef#2{\@@fc@numstr\@unitstring{\@strctr}\ }%
    \fi
    \let\@@fc@numstr#2\relax
    \protected@edef#2{\@@fc@numstr\@thousand}%
  \fi
```

```
\fi
\@strctr=#1\relax \@FCmodulo{\@strctr}{1000}%
\divide\@strctr by 100\relax
\ifnum\@strctr>0\relax
  \ifnum#1>1000 \relax
    \let\@@fc@numstr#2\relax
    \protected@edef#2{\@@fc@numstr\ \@andname\ }%
  \fi
  \@tmpstrctr=#1\relax
  \@FCmodulo{\@tmpstrctr}{1000}%
  \let\@@fc@numstr#2\relax
  \ifnum\@tmpstrctr=100\relax
    \protected@edef#2{\@@fc@numstr\@tenstring{10}}%
  \else
    \protected@edef#2{\@@fc@numstr\@hundredstring{\@strctr}}%
  \fi%
\fi
\@strctr=#1\relax \@FCmodulo{\@strctr}{100}%
\ifnum#1>100\relax
  \ifnum\@strctr>0\relax
    \let\@@fc@numstr#2\relax
    \protected@edef#2{\@@fc@numstr\ \@andname\ }%
  \fi
\fi
\ifnum\@strctr>19\relax
  \divide\@strctr by 10\relax
  \let\@@fc@numstr#2\relax
  \protected@edef#2{\@@fc@numstr\@tenstring{\@strctr}}%
  \@strctr=#1\relax \@FCmodulo{\@strctr}{10}%
  \ifnum\@strctr>0
    \let\@@fc@numstr#2\relax
    \protected@edef#2{\@@fc@numstr\ \@andname}%
    \let\@@fc@numstr#2\relax
    \protected@edef#2{\@@fc@numstr\ \@unitstring{\@strctr}}%
  \fi
\else
  \ifnum\@strctr<10\relax
    \ifnum\@strctr=0\relax
      \ifnum#1<100\relax
        \let\@@fc@numstr#2\relax
        \protected@edef#2{\@@fc@numstr\@unitstring{\@strctr}}%
      \fi
    \else %(>0,<10)
      \let\@@fc@numstr#2\relax
      \protected@edef#2{\@@fc@numstr\@unitstring{\@strctr}}%
    \fi
  \else%>10
    \@FCmodulo{\@strctr}{10}%
    \let\@@fc@numstr#2\relax
```

```
    \protected@edef#2{\@@fc@numstr\@teenstring{\@strctr}}%
  \fi
\fi
}%
\global\let\@@numberstringportuges\@@numberstringportuges
```

As above, but for ordinals.

```
\newcommand*\@@ordinalstringportuges[2]{%
\@strctr=#1\relax
\ifnum#1>99999
\PackageError{fmtcount}{Out of range}%
{This macro only works for values less than 100000}%
\else
\ifnum#1<0
\PackageError{fmtcount}{Negative numbers not permitted}%
{This macro does not work for negative numbers, however
you can try typing "minus" first, and then pass the modulus of
this number}%
\else
\def#2{}%
\ifnum\@strctr>999\relax
  \divide\@strctr by 1000\relax
  \ifnum\@strctr>1\relax
    \ifnum\@strctr>9\relax
      \@tmpstrctr=\@strctr
      \ifnum\@strctr<20
        \@FCmodulo{\@tmpstrctr}{10}%
        \let\@@fc@ordstr#2\relax
        \protected@edef#2{\@@fc@ordstr\@teenthstring{\@tmpstrctr}}%
      \else
        \divide\@tmpstrctr by 10\relax
        \let\@@fc@ordstr#2\relax
        \protected@edef#2{\@@fc@ordstr\@tenthstring{\@tmpstrctr}}%
        \@tmpstrctr=\@strctr
        \@FCmodulo{\@tmpstrctr}{10}%
        \ifnum\@tmpstrctr>0\relax
          \let\@@fc@ordstr#2\relax
          \protected@edef#2{\@@fc@ordstr\@unitthstring{\@tmpstrctr}}%
        \fi
      \fi
    \else
      \let\@@fc@ordstr#2\relax
      \protected@edef#2{\@@fc@ordstr\@unitstring{\@strctr}}%
    \fi
  \fi
  \let\@@fc@ordstr#2\relax
  \protected@edef#2{\@@fc@ordstr\@thousandth}%
\fi
\@strctr=#1\relax
\@FCmodulo{\@strctr}{1000}%
```

```
\ifnum\@strctr>99\relax
  \@tmpstrctr=\@strctr
  \divide\@tmpstrctr by 100\relax
  \ifnum#1>1000\relax
    \let\@@fc@ordstr#2\relax
    \protected@edef#2{\@@fc@ordstr-}%
  \fi
  \let\@@fc@ordstr#2\relax
  \protected@edef#2{\@@fc@ordstr\@hundredthstring{\@tmpstrctr}}%
\fi
\@FCmodulo{\@strctr}{100}%
\ifnum#1>99\relax
  \ifnum\@strctr>0\relax
    \let\@@fc@ordstr#2\relax
    \protected@edef#2{\@@fc@ordstr-}%
  \fi
\fi
\ifnum\@strctr>9\relax
  \@tmpstrctr=\@strctr
  \divide\@tmpstrctr by 10\relax
  \let\@@fc@ordstr#2\relax
  \protected@edef#2{\@@fc@ordstr\@tenthstring{\@tmpstrctr}}%
  \@tmpstrctr=\@strctr
  \@FCmodulo{\@tmpstrctr}{10}%
  \ifnum\@tmpstrctr>0\relax
    \let\@@fc@ordstr#2\relax
    \protected@edef#2{\@@fc@ordstr-\@unitthstring{\@tmpstrctr}}%
  \fi
\else
  \ifnum\@strctr=0\relax
    \ifnum#1=0\relax
      \let\@@fc@ordstr#2\relax
      \protected@edef#2{\@@fc@ordstr\@unitstring{0}}%
    \fi
  \else
    \let\@@fc@ordstr#2\relax
    \protected@edef#2{\@@fc@ordstr\@unitthstring{\@strctr}}%
  \fi
\fi
\fi
\fi
}%
\global\let\@@ordinalstringportuges\@@ordinalstringportuges
```

10.1.27 fc-portuguese.def

```
\ProvidesFCLanguage{portuguese}[2014/06/09]%
```

Load fc-portuges.def if not already loaded.

```
\FCloadlang{portuges}%
```

Set portuguese to be equivalent to portuges.

```
\global\let\@ordinalMportuguese=\@ordinalMportuges
\global\let\@ordinalFportuguese=\@ordinalFportuges
\global\let\@ordinalNportuguese=\@ordinalNportuges
\global\let\@numberstringMportuguese=\@numberstringMportuges
\global\let\@numberstringFportuguese=\@numberstringFportuges
\global\let\@numberstringNportuguese=\@numberstringNportuges
\global\let\@NumberstringMportuguese=\@NumberstringMportuges
\global\let\@NumberstringFportuguese=\@NumberstringFportuges
\global\let\@NumberstringNportuguese=\@NumberstringNportuges
\global\let\@ordinalstringMportuguese=\@ordinalstringMportuges
\global\let\@ordinalstringFportuguese=\@ordinalstringFportuges
\global\let\@ordinalstringNportuguese=\@ordinalstringNportuges
\global\let\@OrdinalstringMportuguese=\@OrdinalstringMportuges
\global\let\@OrdinalstringFportuguese=\@OrdinalstringFportuges
\global\let\@OrdinalstringNportuguese=\@OrdinalstringNportuges
```

10.1.28 fc-spanish.def

Spanish definitions

```
\ProvidesFCLanguage{spanish}[2016/01/12]%
```

Define macro that converts a number or count register (first argument) to an ordinal, and stores the result in the second argument, which must be a control sequence. Masculine:

```
\newcommand*\@ordinalMspanish[2]{%
  \edef#2{\number#1\relax\noexpand\fmtord{o}}%
}%
\global\let\@ordinalMspanish\@ordinalMspanish
```

Feminine:

```
\newcommand{\@ordinalFspanish}[2]{%
  \edef#2{\number#1\relax\noexpand\fmtord{a}}%
}%
\global\let\@ordinalFspanish\@ordinalFspanish
```

Make neuter same as masculine:

```
\global\let\@ordinalNspanish\@ordinalMspanish
```

Convert a number to text. The easiest way to do this is to break it up into units, tens, teens, twenties and hundreds. Units (argument must be a number from 0 to 9):

```
\newcommand*\@@unitstringspanish[1]{%
  \ifcase#1\relax
    cero%
    \or uno%
    \or dos%
    \or tres%
    \or cuatro%
    \or cinco%
    \or seis%
    \or siete%
    \or ocho%
```

```
    \or nueve%
  \fi
}%
\global\let\@@unitstringspanish\@@unitstringspanish
```

Feminine:

```
\newcommand*\@@unitstringFspanish[1]{%
  \ifcase#1\relax
    cera%
    \or una%
    \or dos%
    \or tres%
    \or cuatro%
    \or cinco%
    \or seis%
    \or siete%
    \or ocho%
    \or nueve%
  \fi
}%
\global\let\@@unitstringFspanish\@@unitstringFspanish
```

Tens (argument must go from 1 to 10):

```
\newcommand*\@@tenstringspanish[1]{%
  \ifcase#1\relax
    \or diez%
    \or veinte%
    \or treinta%
    \or cuarenta%
    \or cincuenta%
    \or sesenta%
    \or setenta%
    \or ochenta%
    \or noventa%
    \or cien%
  \fi
}%
\global\let\@@tenstringspanish\@@tenstringspanish
```

Teens:

```
\newcommand*\@@teenstringspanish[1]{%
  \ifcase#1\relax
    diez%
    \or once%
    \or doce%
    \or trece%
    \or catorce%
    \or quince%
    \or dieciséis%
    \or diecisiete%
    \or dieciocho%
```

```
    \or diecinueve%
  \fi
}%
\global\let\@@teenstringspanish\@@teenstringspanish
```

Twenties:

```
\newcommand*\@@twentystringspanish[1]{%
  \ifcase#1\relax
    veinte%
    \or veintiuno%
    \or veintidós%
    \or veintitrés%
    \or veinticuatro%
    \or veinticinco%
    \or veintiséis%
    \or veintisiete%
    \or veintiocho%
    \or veintinueve%
  \fi
}%
\global\let\@@twentystringspanish\@@twentystringspanish
```

Feminine form:

```
\newcommand*\@@twentystringFspanish[1]{%
  \ifcase#1\relax
    veinte%
    \or veintiuna%
    \or veintidós%
    \or veintitrés%
    \or veinticuatro%
    \or veinticinco%
    \or veintiséis%
    \or veintisiete%
    \or veintiocho%
    \or veintinueve%
  \fi
}%
\global\let\@@twentystringFspanish\@@twentystringFspanish
```

Hundreds:

```
\newcommand*\@@hundredstringspanish[1]{%
  \ifcase#1\relax
    \or ciento%
    \or doscientos%
    \or trescientos%
    \or cuatrocientos%
    \or quinientos%
    \or seiscientos%
    \or setecientos%
    \or ochocientos%
    \or novecientos%
```

```
  \fi
}%
\global\let\@@hundredstringspanish\@@hundredstringspanish
```
Feminine form:
```
\newcommand*\@@hundredstringFspanish[1]{%
  \ifcase#1\relax
    \or cienta%
    \or doscientas%
    \or trescientas%
    \or cuatrocientas%
    \or quinientas%
    \or seiscientas%
    \or setecientas%
    \or ochocientas%
    \or novecientas%
  \fi
}%
\global\let\@@hundredstringFspanish\@@hundredstringFspanish
```
As above, but with initial letter uppercase:
```
\newcommand*\@@Unitstringspanish[1]{%
  \ifcase#1\relax
    Cero%
    \or Uno%
    \or Dos%
    \or Tres%
    \or Cuatro%
    \or Cinco%
    \or Seis%
    \or Siete%
    \or Ocho%
    \or Nueve%
  \fi
}%
\global\let\@@Unitstringspanish\@@Unitstringspanish
```
Feminine form:
```
\newcommand*\@@UnitstringFspanish[1]{%
  \ifcase#1\relax
    Cera%
    \or Una%
    \or Dos%
    \or Tres%
    \or Cuatro%
    \or Cinco%
    \or Seis%
    \or Siete%
    \or Ocho%
    \or Nueve%
  \fi
```

```
}%
\global\let\@@UnitstringFspanish\@@UnitstringFspanish
```

Tens:

```
%\changes{2.0}{2012-06-18}{fixed spelling mistake (correction
%provided by Fernando Maldonado)}
\newcommand*\@@Tenstringspanish[1]{%
  \ifcase#1\relax
    \or Diez%
    \or Veinte%
    \or Treinta%
    \or Cuarenta%
    \or Cincuenta%
    \or Sesenta%
    \or Setenta%
    \or Ochenta%
    \or Noventa%
    \or Cien%
  \fi
}%
\global\let\@@Tenstringspanish\@@Tenstringspanish
```

Teens:

```
\newcommand*\@@Teenstringspanish[1]{%
  \ifcase#1\relax
    Diez%
    \or Once%
    \or Doce%
    \or Trece%
    \or Catorce%
    \or Quince%
    \or Dieciséis%
    \or Diecisiete%
    \or Dieciocho%
    \or Diecinueve%
  \fi
}%
\global\let\@@Teenstringspanish\@@Teenstringspanish
```

Twenties:

```
\newcommand*\@@Twentystringspanish[1]{%
  \ifcase#1\relax
    Veinte%
    \or Veintiuno%
    \or Veintidós%
    \or Veintitrés%
    \or Veinticuatro%
    \or Veinticinco%
    \or Veintiséis%
    \or Veintisiete%
    \or Veintiocho%
```

```
    \or Veintinueve%
  \fi
}%
\global\let\@@Twentystringspanish\@@Twentystringspanish
```

Feminine form:

```
\newcommand*\@@TwentystringFspanish[1]{%
  \ifcase#1\relax
    Veinte%
    \or Veintiuna%
    \or Veintidós%
    \or Veintitrés%
    \or Veinticuatro%
    \or Veinticinco%
    \or Veintiséis%
    \or Veintisiete%
    \or Veintiocho%
    \or Veintinueve%
  \fi
}%
\global\let\@@TwentystringFspanish\@@TwentystringFspanish
```

Hundreds:

```
\newcommand*\@@Hundredstringspanish[1]{%
  \ifcase#1\relax
    \or Ciento%
    \or Doscientos%
    \or Trescientos%
    \or Cuatrocientos%
    \or Quinientos%
    \or Seiscientos%
    \or Setecientos%
    \or Ochocientos%
    \or Novecientos%
  \fi
}%
\global\let\@@Hundredstringspanish\@@Hundredstringspanish
```

Feminine form:

```
\newcommand*\@@HundredstringFspanish[1]{%
  \ifcase#1\relax
    \or Cienta%
    \or Doscientas%
    \or Trescientas%
    \or Cuatrocientas%
    \or Quinientas%
    \or Seiscientas%
    \or Setecientas%
    \or Ochocientas%
    \or Novecientas%
  \fi
```

```
}%
\global\let\@@HundredstringFspanish\@@HundredstringFspanish
```

This has changed in version 1.09, so that it now stores the result in the second argument, but doesn't display anything. Since it only affects internal macros, it shouldn't affect documents created with older versions. (These internal macros are not meant for use in documents.)

```
\newcommand*{\@numberstringMspanish}[2]{%
  \let\@unitstring=\@@unitstringspanish
  \let\@teenstring=\@@teenstringspanish
  \let\@tenstring=\@@tenstringspanish
  \let\@twentystring=\@@twentystringspanish
  \let\@hundredstring=\@@hundredstringspanish
  \def\@hundred{cien}\def\@thousand{mil}%
  \def\@andname{y}%
  \@@numberstringspanish{#1}{#2}%
}%
\global\let\@numberstringMspanish\@numberstringMspanish
```

Feminine form:

```
\newcommand*{\@numberstringFspanish}[2]{%
  \let\@unitstring=\@@unitstringFspanish
  \let\@teenstring=\@@teenstringspanish
  \let\@tenstring=\@@tenstringspanish
  \let\@twentystring=\@@twentystringFspanish
  \let\@hundredstring=\@@hundredstringFspanish
  \def\@hundred{cien}\def\@thousand{mil}%
  \def\@andname{b}%
  \@@numberstringspanish{#1}{#2}%
}%
\global\let\@numberstringFspanish\@numberstringFspanish
```

Make neuter same as masculine:

```
\global\let\@numberstringNspanish\@numberstringMspanish
```

As above, but initial letters in upper case:

```
\newcommand*{\@NumberstringMspanish}[2]{%
  \let\@unitstring=\@@Unitstringspanish
  \let\@teenstring=\@@Teenstringspanish
  \let\@tenstring=\@@Tenstringspanish
  \let\@twentystring=\@@Twentystringspanish
  \let\@hundredstring=\@@Hundredstringspanish
  \def\@andname{y}%
  \def\@hundred{Cien}\def\@thousand{Mil}%
  \@@numberstringspanish{#1}{#2}%
}%
\global\let\@NumberstringMspanish\@NumberstringMspanish
```

Feminine form:

```
\newcommand*{\@NumberstringFspanish}[2]{%
  \let\@unitstring=\@@UnitstringFspanish
  \let\@teenstring=\@@Teenstringspanish
```

```
  \let\@tenstring=\@@Tenstringspanish
  \let\@twentystring=\@@TwentystringFspanish
  \let\@hundredstring=\@@HundredstringFspanish
  \def\@andname{b}%
  \def\@hundred{Cien}\def\@thousand{Mil}%
  \@@numberstringspanish{#1}{#2}%
}%
\global\let\@NumberstringFspanish\@NumberstringFspanish
```

Make neuter same as masculine:

```
\global\let\@NumberstringNspanish\@NumberstringMspanish
```

As above, but for ordinals.

```
\newcommand*{\@ordinalstringMspanish}[2]{%
  \let\@unitthstring=\@@unitthstringspanish
  \let\@unitstring=\@@unitstringspanish
  \let\@teenthstring=\@@teenthstringspanish
  \let\@tenthstring=\@@tenthstringspanish
  \let\@hundredthstring=\@@hundredthstringspanish
  \def\@thousandth{milésimo}%
  \@@ordinalstringspanish{#1}{#2}%
}%
\global\let\@ordinalstringMspanish\@ordinalstringMspanish
```

Feminine form:

```
\newcommand*{\@ordinalstringFspanish}[2]{%
  \let\@unitthstring=\@@unitthstringFspanish
  \let\@unitstring=\@@unitstringFspanish
  \let\@teenthstring=\@@teenthstringFspanish
  \let\@tenthstring=\@@tenthstringFspanish
  \let\@hundredthstring=\@@hundredthstringFspanish
  \def\@thousandth{milésima}%
  \@@ordinalstringspanish{#1}{#2}%
}%
\global\let\@ordinalstringFspanish\@ordinalstringFspanish
```

Make neuter same as masculine:

```
\global\let\@ordinalstringNspanish\@ordinalstringMspanish
```

As above, but with initial letters in upper case.

```
\newcommand*{\@OrdinalstringMspanish}[2]{%
  \let\@unitthstring=\@@Unitthstringspanish
  \let\@unitstring=\@@Unitstringspanish
  \let\@teenthstring=\@@Teenthstringspanish
  \let\@tenthstring=\@@Tenthstringspanish
  \let\@hundredthstring=\@@Hundredthstringspanish
  \def\@thousandth{Milésimo}%
  \@@ordinalstringspanish{#1}{#2}%
}
\global\let\@OrdinalstringMspanish\@OrdinalstringMspanish
```

Feminine form:

```
\newcommand*{\@OrdinalstringFspanish}[2]{%
  \let\@unitthstring=\@@UnitthstringFspanish
  \let\@unitstring=\@@UnitstringFspanish
  \let\@teenthstring=\@@TeenthstringFspanish
  \let\@tenthstring=\@@TenthstringFspanish
  \let\@hundredthstring=\@@HundredthstringFspanish
  \def\@thousandth{Milésima}%
  \@@ordinalstringspanish{#1}{#2}%
}%
\global\let\@OrdinalstringFspanish\@OrdinalstringFspanish
```

Make neuter same as masculine:

```
\global\let\@OrdinalstringNspanish\@OrdinalstringMspanish
```

Code for convert numbers into textual ordinals. As before, it is easier to split it into units, tens, teens and hundreds. Units:

```
\newcommand*\@@unitthstringspanish[1]{%
  \ifcase#1\relax
    cero%
    \or primero%
    \or segundo%
    \or tercero%
    \or cuarto%
    \or quinto%
    \or sexto%
    \or séptimo%
    \or octavo%
    \or noveno%
  \fi
}%
\global\let\@@unitthstringspanish\@@unitthstringspanish
```

Tens:

```
\newcommand*\@@tenthstringspanish[1]{%
  \ifcase#1\relax
    \or décimo%
    \or vigésimo%
    \or trigésimo%
    \or cuadragésimo%
    \or quincuagésimo%
    \or sexagésimo%
    \or septuagésimo%
    \or octogésimo%
    \or nonagésimo%
  \fi
}%
\global\let\@@tenthstringspanish\@@tenthstringspanish
```

Teens:

```
\newcommand*\@@teenthstringspanish[1]{%
  \ifcase#1\relax
```

```
    décimo%
    \or undécimo%
    \or duodécimo%
    \or decimotercero%
    \or decimocuarto%
    \or decimoquinto%
    \or decimosexto%
    \or decimoséptimo%
    \or decimoctavo%
    \or decimonoveno%
  \fi
}%
\global\let\@@teenthstringspanish\@@teenthstringspanish
```

Hundreds:

```
\newcommand*\@@hundredthstringspanish[1]{%
  \ifcase#1\relax
    \or centésimo%
    \or ducentésimo%
    \or tricentésimo%
    \or cuadringentésimo%
    \or quingentésimo%
    \or sexcentésimo%
    \or septingésimo%
    \or octingentésimo%
    \or noningentésimo%
  \fi
}%
\global\let\@@hundredthstringspanish\@@hundredthstringspanish
```

Units (feminine):

```
\newcommand*\@@unitthstringFspanish[1]{%
  \ifcase#1\relax
    cera%
    \or primera%
    \or segunda%
    \or tercera%
    \or cuarta%
    \or quinta%
    \or sexta%
    \or séptima%
    \or octava%
    \or novena%
  \fi
}%
\global\let\@@unitthstringFspanish\@@unitthstringFspanish
```

Tens (feminine):

```
\newcommand*\@@tenthstringFspanish[1]{%
  \ifcase#1\relax
    \or décima%
```

```
    \or vigésima%
    \or trigésima%
    \or cuadragésima%
    \or quincuagésima%
    \or sexagésima%
    \or septuagésima%
    \or octogésima%
    \or nonagésima%
  \fi
}%
\global\let\@@tenthstringFspanish\@@tenthstringFspanish
```

Teens (feminine)

```
\newcommand*\@@teenthstringFspanish[1]{%
  \ifcase#1\relax
    décima%
    \or undécima%
    \or duodécima%
    \or decimotercera%
    \or decimocuarta%
    \or decimoquinta%
    \or decimosexta%
    \or decimoséptima%
    \or decimoctava%
    \or decimonovena%
  \fi
}%
\global\let\@@teenthstringFspanish\@@teenthstringFspanish
```

Hundreds (feminine)

```
\newcommand*\@@hundredthstringFspanish[1]{%
  \ifcase#1\relax
    \or centésima%
    \or ducentésima%
    \or tricentésima%
    \or cuadringentésima%
    \or quingentésima%
    \or sexcentésima%
    \or septingésima%
    \or octingentésima%
    \or noningentésima%
  \fi
}%
\global\let\@@hundredthstringFspanish\@@hundredthstringFspanish
```

As above, but with initial letters in upper case

```
\newcommand*\@@Unitthstringspanish[1]{%
  \ifcase#1\relax
    Cero%
    \or Primero%
    \or Segundo%
```

```
    \or Tercero%
    \or Cuarto%
    \or Quinto%
    \or Sexto%
    \or Séptimo%
    \or Octavo%
    \or Noveno%
  \fi
}%
\global\let\@@Unitthstringspanish\@@Unitthstringspanish
```

Tens:

```
\newcommand*\@@Tenthstringspanish[1]{%
  \ifcase#1\relax
    \or Décimo%
    \or Vigésimo%
    \or Trigésimo%
    \or Cuadragésimo%
    \or Quincuagésimo%
    \or Sexagésimo%
    \or Septuagésimo%
    \or Octogésimo%
    \or Nonagésimo%
  \fi
}%
\global\let\@@Tenthstringspanish\@@Tenthstringspanish
```

Teens:

```
\newcommand*\@@Teenthstringspanish[1]{%
  \ifcase#1\relax
    Décimo%
    \or Undécimo%
    \or Duodécimo%
    \or Decimotercero%
    \or Decimocuarto%
    \or Decimoquinto%
    \or Decimosexto%
    \or Decimoséptimo%
    \or Decimoctavo%
    \or Decimonoveno%
  \fi
}%
\global\let\@@Teenthstringspanish\@@Teenthstringspanish
```

Hundreds

```
\newcommand*\@@Hundredthstringspanish[1]{%
  \ifcase#1\relax
    \or Centésimo%
    \or Ducentésimo%
    \or Tricentésimo%
    \or Cuadringentésimo%
```

```
    \or Quingentésimo%
    \or Sexcentésimo%
    \or Septingésimo%
    \or Octingentésimo%
    \or Noningentésimo%
  \fi
}%
\global\let\@@Hundredthstringspanish\@@Hundredthstringspanish
```

As above, but feminine.

```
\newcommand*\@@UnitthstringFspanish[1]{%
  \ifcase#1\relax
    Cera%
    \or Primera%
    \or Segunda%
    \or Tercera%
    \or Cuarta%
    \or Quinta%
    \or Sexta%
    \or Séptima%
    \or Octava%
    \or Novena%
  \fi
}%
\global\let\@@UnitthstringFspanish\@@UnitthstringFspanish
```

Tens (feminine)

```
\newcommand*\@@TenthstringFspanish[1]{%
  \ifcase#1\relax
    \or Décima%
    \or Vigésima%
    \or Trigésima%
    \or Cuadragésima%
    \or Quincuagésima%
    \or Sexagésima%
    \or Septuagésima%
    \or Octogésima%
    \or Nonagésima%
  \fi
}%
\global\let\@@TenthstringFspanish\@@TenthstringFspanish
```

Teens (feminine):

```
\newcommand*\@@TeenthstringFspanish[1]{%
  \ifcase#1\relax
    Décima%
    \or Undécima%
    \or Duodécima%
    \or Decimotercera%
    \or Decimocuarta%
    \or Decimoquinta%
```

```
    \or Decimosexta%
    \or Decimoséptima%
    \or Decimoctava%
    \or Decimonovena%
  \fi
}%
\global\let\@@TeenthstringFspanish\@@TeenthstringFspanish
```

Hundreds (feminine):

```
\newcommand*\@@HundredthstringFspanish[1]{%
  \ifcase#1\relax
    \or Centésima%
    \or Ducentésima%
    \or Tricentésima%
    \or Cuadringentésima%
    \or Quingentésima%
    \or Sexcentésima%
    \or Septingésima%
    \or Octingentésima%
    \or Noningentésima%
  \fi
}%
\global\let\@@HundredthstringFspanish\@@HundredthstringFspanish
```

This has changed in version 1.09, so that it now stores the results in the second argument (which must be a control sequence), but it doesn't display anything. Since it only affects internal macros, it shouldn't affect documnets created with older versions. (These internal macros are not meant for use in documents.)

```
\newcommand*\@@numberstringspanish[2]{%
\ifnum#1>99999
\PackageError{fmtcount}{Out of range}%
{This macro only works for values less than 100000}%
\else
\ifnum#1<0
\PackageError{fmtcount}{Negative numbers not permitted}%
{This macro does not work for negative numbers, however
you can try typing "minus" first, and then pass the modulus of
this number}%
\fi
\fi
\def#2{}%
\@strctr=#1\relax \divide\@strctr by 1000\relax
\ifnum\@strctr>9
```

#1 is greater or equal to 10000

```
  \divide\@strctr by 10
  \ifnum\@strctr>1
    \let\@@fc@numstr#2\relax
    \edef#2{\@@fc@numstr\@tenstring{\@strctr}}%
    \@strctr=#1 \divide\@strctr by 1000\relax
```

```
    \@FCmodulo{\@strctr}{10}%
    \ifnum\@strctr>0\relax
       \let\@@fc@numstr#2\relax
       \edef#2{\@@fc@numstr\ \@andname\ \@unitstring{\@strctr}}%
    \fi
  \else
    \@strctr=#1\relax
    \divide\@strctr by 1000\relax
    \@FCmodulo{\@strctr}{10}%
    \let\@@fc@numstr#2\relax
    \edef#2{\@@fc@numstr\@teenstring{\@strctr}}%
  \fi
  \let\@@fc@numstr#2\relax
  \edef#2{\@@fc@numstr\ \@thousand}%
\else
  \ifnum\@strctr>0\relax
    \ifnum\@strctr>1\relax
       \let\@@fc@numstr#2\relax
       \edef#2{\@@fc@numstr\@unitstring{\@strctr}\ }%
    \fi
    \let\@@fc@numstr#2\relax
    \edef#2{\@@fc@numstr\@thousand}%
  \fi
\fi
\@strctr=#1\relax \@FCmodulo{\@strctr}{1000}%
\divide\@strctr by 100\relax
\ifnum\@strctr>0\relax
  \ifnum#1>1000\relax
    \let\@@fc@numstr#2\relax
    \edef#2{\@@fc@numstr\ }%
  \fi
  \@tmpstrctr=#1\relax
  \@FCmodulo{\@tmpstrctr}{1000}%
  \ifnum\@tmpstrctr=100\relax
    \let\@@fc@numstr#2\relax
    \edef#2{\@@fc@numstr\@tenstring{10}}%
  \else
    \let\@@fc@numstr#2\relax
    \edef#2{\@@fc@numstr\@hundredstring{\@strctr}}%
  \fi
\fi
\@strctr=#1\relax \@FCmodulo{\@strctr}{100}%
\ifnum#1>100\relax
  \ifnum\@strctr>0\relax
    \let\@@fc@numstr#2\relax

    \edef#2{\@@fc@numstr\ }%
  \fi
\fi
\ifnum\@strctr>29\relax
```

```
  \divide\@strctr by 10\relax
  \let\@@fc@numstr#2\relax
  \edef#2{\@@fc@numstr\@tenstring{\@strctr}}%
  \@strctr=#1\relax \@FCmodulo{\@strctr}{10}%
  \ifnum\@strctr>0\relax
    \let\@@fc@numstr#2\relax
    \edef#2{\@@fc@numstr\ \@andname\ \@unitstring{\@strctr}}%
  \fi
\else
  \ifnum\@strctr<10\relax
    \ifnum\@strctr=0\relax
      \ifnum#1<100\relax
        \let\@@fc@numstr#2\relax
        \edef#2{\@@fc@numstr\@unitstring{\@strctr}}%
      \fi
    \else
      \let\@@fc@numstr#2\relax
      \edef#2{\@@fc@numstr\@unitstring{\@strctr}}%
    \fi
  \else
    \ifnum\@strctr>19\relax
      \@FCmodulo{\@strctr}{10}%
      \let\@@fc@numstr#2\relax
      \edef#2{\@@fc@numstr\@twentystring{\@strctr}}%
    \else
      \@FCmodulo{\@strctr}{10}%
      \let\@@fc@numstr#2\relax
      \edef#2{\@@fc@numstr\@teenstring{\@strctr}}%
    \fi
  \fi
\fi
}%
\global\let\@@numberstringspanish\@@numberstringspanish
```

As above, but for ordinals

```
\newcommand*\@@ordinalstringspanish[2]{%
\@strctr=#1\relax
\ifnum#1>99999
\PackageError{fmtcount}{Out of range}%
{This macro only works for values less than 100000}%
\else
\ifnum#1<0
\PackageError{fmtcount}{Negative numbers not permitted}%
{This macro does not work for negative numbers, however
you can try typing "minus" first, and then pass the modulus of
this number}%
\else
\def#2{}%
\ifnum\@strctr>999\relax
  \divide\@strctr by 1000\relax
```

```
  \ifnum\@strctr>1\relax
    \ifnum\@strctr>9\relax
      \@tmpstrctr=\@strctr
      \ifnum\@strctr<20
        \@FCmodulo{\@tmpstrctr}{10}%
        \let\@@fc@ordstr#2\relax
        \edef#2{\@@fc@ordstr\@teenthstring{\@tmpstrctr}}%
      \else
        \divide\@tmpstrctr by 10\relax
        \let\@@fc@ordstr#2\relax
        \edef#2{\@@fc@ordstr\@tenthstring{\@tmpstrctr}}%
        \@tmpstrctr=\@strctr
        \@FCmodulo{\@tmpstrctr}{10}%
        \ifnum\@tmpstrctr>0\relax
          \let\@@fc@ordstr#2\relax
          \edef#2{\@@fc@ordstr\@unitthstring{\@tmpstrctr}}%
        \fi
      \fi
    \else
       \let\@@fc@ordstr#2\relax
       \edef#2{\@@fc@ordstr\@unitstring{\@strctr}}%
    \fi
  \fi
  \let\@@fc@ordstr#2\relax
  \edef#2{\@@fc@ordstr\@thousandth}%
\fi
\@strctr=#1\relax
\@FCmodulo{\@strctr}{1000}%
\ifnum\@strctr>99\relax
  \@tmpstrctr=\@strctr
  \divide\@tmpstrctr by 100\relax
  \ifnum#1>1000\relax
    \let\@@fc@ordstr#2\relax
    \edef#2{\@@fc@ordstr\ }%
  \fi
  \let\@@fc@ordstr#2\relax
  \edef#2{\@@fc@ordstr\@hundredthstring{\@tmpstrctr}}%
\fi
\@FCmodulo{\@strctr}{100}%
\ifnum#1>99\relax
  \ifnum\@strctr>0\relax
    \let\@@fc@ordstr#2\relax
    \edef#2{\@@fc@ordstr\ }%
  \fi
\fi
\ifnum\@strctr>19\relax
  \@tmpstrctr=\@strctr
  \divide\@tmpstrctr by 10\relax
  \let\@@fc@ordstr#2\relax
```

```
  \edef#2{\@@fc@ordstr\@tenthstring{\@tmpstrctr}}%
  \@tmpstrctr=\@strctr
  \@FCmodulo{\@tmpstrctr}{10}%
  \ifnum\@tmpstrctr>0\relax
    \let\@@fc@ordstr#2\relax
    \edef#2{\@@fc@ordstr\ \@unitthstring{\@tmpstrctr}}%
  \fi
\else
  \ifnum\@strctr>9\relax
    \@FCmodulo{\@strctr}{10}%
    \let\@@fc@ordstr#2\relax
    \edef#2{\@@fc@ordstr\@teenthstring{\@strctr}}%
  \else
    \ifnum\@strctr=0\relax
      \ifnum#1=0\relax
        \let\@@fc@ordstr#2\relax
        \edef#2{\@@fc@ordstr\@unitstring{0}}%
      \fi
    \else
      \let\@@fc@ordstr#2\relax
      \edef#2{\@@fc@ordstr\@unitthstring{\@strctr}}%
    \fi
  \fi
\fi
\fi
\fi
}%
\global\let\@@ordinalstringspanish\@@ordinalstringspanish
```

10.1.29 fc-UKenglish.def

English definitions

```
\ProvidesFCLanguage{UKenglish}[2013/08/17]%
```

Loaded fc-english.def if not already loaded

```
\FCloadlang{english}%
```

These are all just synonyms for the commands provided by fc-english.def.

```
\global\let\@ordinalMUKenglish\@ordinalMenglish
\global\let\@ordinalFUKenglish\@ordinalMenglish
\global\let\@ordinalNUKenglish\@ordinalMenglish
\global\let\@numberstringMUKenglish\@numberstringMenglish
\global\let\@numberstringFUKenglish\@numberstringMenglish
\global\let\@numberstringNUKenglish\@numberstringMenglish
\global\let\@NumberstringMUKenglish\@NumberstringMenglish
\global\let\@NumberstringFUKenglish\@NumberstringMenglish
\global\let\@NumberstringNUKenglish\@NumberstringMenglish
\global\let\@ordinalstringMUKenglish\@ordinalstringMenglish
\global\let\@ordinalstringFUKenglish\@ordinalstringMenglish
\global\let\@ordinalstringNUKenglish\@ordinalstringMenglish
```

```
\global\let\@OrdinalstringMUKenglish\@OrdinalstringMenglish
\global\let\@OrdinalstringFUKenglish\@OrdinalstringMenglish
\global\let\@OrdinalstringNUKenglish\@OrdinalstringMenglish
```

10.1.30 fc-USenglish.def

US English definitions

```
\ProvidesFCLanguage{USenglish}[2013/08/17]%
```

Loaded fc-english.def if not already loaded

```
\FCloadlang{english}%
```

These are all just synonyms for the commands provided by fc-english.def. (This needs fixing as there are some differences between UK and US number strings.)

```
\global\let\@ordinalMUSenglish\@ordinalMenglish
\global\let\@ordinalFUSenglish\@ordinalMenglish
\global\let\@ordinalNUSenglish\@ordinalMenglish
\global\let\@numberstringMUSenglish\@numberstringMenglish
\global\let\@numberstringFUSenglish\@numberstringMenglish
\global\let\@numberstringNUSenglish\@numberstringMenglish
\global\let\@NumberstringMUSenglish\@NumberstringMenglish
\global\let\@NumberstringFUSenglish\@NumberstringMenglish
\global\let\@NumberstringNUSenglish\@NumberstringMenglish
\global\let\@ordinalstringMUSenglish\@ordinalstringMenglish
\global\let\@ordinalstringFUSenglish\@ordinalstringMenglish
\global\let\@ordinalstringNUSenglish\@ordinalstringMenglish
\global\let\@OrdinalstringMUSenglish\@OrdinalstringMenglish
\global\let\@OrdinalstringFUSenglish\@OrdinalstringMenglish
\global\let\@OrdinalstringNUSenglish\@OrdinalstringMenglish
```

10.2 fcnumparser.sty

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{fcnumparser}[2017/06/15]
```

`\fc@counter@parser` is just a shorthand to parse a number held in a counter.

```
\def\fc@counter@parser#1{%
  \expandafter\fc@number@parser\expandafter{\the#1.}%
}
\newcount\fc@digit@counter

\def\fc@end@{\fc@end}
```

`@number@analysis` First of all we need to separate the number between integer and fractional part. Number to be analysed is in '#1'. Decimal separator may be . or , whichever first. At end of this macro, integer part goes to `\fc@integer@part` and fractional part goes to `\fc@fractional@part`.

```
\def\fc@number@analysis#1\fc@nil{%
```

First check for the presence of a decimal point in the number.

```
  \def\@tempb##1.##2\fc@nil{\def\fc@integer@part{##1}\def\@tempa{##2}}%
```

```
  \@tempb#1.\fc@end\fc@nil
  \ifx\@tempa\fc@end@
```

Here `\@tempa` is `\ifx`-equal to `\fc@end`, which means that the number does not contain any decimal point. So we do the same trick to search for a comma.

```
    \def\@tempb##1,##2\fc@nil{\def\fc@integer@part{##1}\def\@tempa{##2}}%
    \@tempb#1,\fc@end\fc@nil
    \ifx\@tempa\fc@end@
```

No comma either, so fractional part is set empty.

```
      \def\fc@fractional@part{}%
    \else
```

Comma has been found, so we just need to drop '`,\fc@end`' from the end of `\@tempa` to get the fractional part.

```
      \def\@tempb##1,\fc@end{\def\fc@fractional@part{##1}}%
      \expandafter\@tempb\@tempa
    \fi
  \else
```

Decimal point has been found, so we just need to drop '`.\fc@end`' from the end `\@tempa` to get the fractional part.

```
      \def\@tempb##1.\fc@end{\def\fc@fractional@part{##1}}%
      \expandafter\@tempb\@tempa
  \fi
}
```

`c@number@parser` Macro `\fc@number@parser` is the main engine to parse a number. Argument '#1' is input and contains the number to be parsed. At end of this macro, each digit is stored separately in a `\fc@digit@`⟨*n*⟩, and macros `\fc@min@weight` and `\fc@max@weight` are set to the bounds for ⟨*n*⟩.

```
\def\fc@number@parser#1{%
```

First remove all the spaces in `#1`, and place the result into `\@tempa`.

```
  \let\@tempa\@empty
  \def\@tempb##1##2\fc@nil{%
    \def\@tempc{##1}%
    \ifx\@tempc\space
    \else
      \expandafter\def\expandafter\@tempa\expandafter{\@tempa ##1}%
    \fi
    \def\@tempc{##2}%
    \ifx\@tempc\@empty
      \expandafter\@gobble
    \else
      \expandafter\@tempb
    \fi
    ##2\fc@nil
  }%
  \@tempb#1\fc@nil
```

Get the sign into `\fc@sign` and the unsigned number part into `\fc@number`.

```
  \def\@tempb##1##2\fc@nil{\def\fc@sign{##1}\def\fc@number{##2}}%
```

```
\expandafter\@tempb\@tempa\fc@nil
\expandafter\if\fc@sign+%
  \def\fc@sign@case{1}%
\else
  \expandafter\if\fc@sign-%
    \def\fc@sign@case{2}%
  \else
    \def\fc@sign{}%
    \def\fc@sign@case{0}%
    \let\fc@number\@tempa
  \fi
\fi
\ifx\fc@number\@empty
  \PackageError{fcnumparser}{Invalid number}{Number must contain at least one non blank
    character after sign}%
\fi
```

Now, split `\fc@number` into `\fc@integer@part` and `\fc@fractional@part`.

```
\expandafter\fc@number@analysis\fc@number\fc@nil
```

Now, split `\fc@integer@part` into a sequence of `\fc@digit@`$\langle n\rangle$ with $\langle n\rangle$ ranging from `\fc@unit@weight` to `\fc@max@weight`. We will use macro `\fc@parse@integer@digits` for that, but that will place the digits into `\fc@digit@`$\langle n\rangle$ with $\langle n\rangle$ ranging from $2\times$ `\fc@unit@weight` $-$ `\fc@max@weight` upto `\fc@unit@weight` -1.

```
\expandafter\fc@digit@counter\fc@unit@weight
\expandafter\fc@parse@integer@digits\fc@integer@part\fc@end\fc@nil
```

First we compute the weight of the most significant digit: after `\fc@parse@integer@digits`, `\fc@digit@counter` is equal to `\fc@unit@weight`$-$mw-1 and we want to set `\fc@max@weight` to `\fc@unit@weight` + mw so we do:

$$\texttt{\textbackslash fc@max@weight} \leftarrow (-\texttt{\textbackslash fc@digit@counter}) + 2\times\texttt{\textbackslash fc@unit@weight} - 1$$

```
\fc@digit@counter -\fc@digit@counter
\advance\fc@digit@counter by \fc@unit@weight
\advance\fc@digit@counter by \fc@unit@weight
\advance\fc@digit@counter by -1 %
\edef\fc@max@weight{\the\fc@digit@counter}%
```

Now we loop for i = `\fc@unit@weight` to `\fc@max@weight` in order to copy all the digits from `\fc@digit@`$\langle i+\text{offset}\rangle$ to `\fc@digit@`$\langle i\rangle$. First we compute offset into `\@tempi`.

```
{%
  \count0 \fc@unit@weight\relax
  \count1 \fc@max@weight\relax
  \advance\count0 by -\count1 %
  \advance\count0 by -1 %
  \def\@tempa##1{\def\@tempb{\def\@tempi{##1}}}%
  \expandafter\@tempa\expandafter{\the\count0}%
  \expandafter
}\@tempb
```

Now we loop to copy the digits. To do that we define a macro `\@templ` for terminal recursion.

```
  \expandafter\fc@digit@counter\fc@unit@weight
  \def\@templ{%
     \ifnum\fc@digit@counter>\fc@max@weight
        \let\next\relax
     \else
```

Here is the loop body:

```
        {%
          \count0 \@tempi
          \advance\count0 by \fc@digit@counter
          \expandafter\def\expandafter\@tempd\expandafter{\csname fc@digit@\the\count0\endcsnam
          \expandafter\def\expandafter\@tempe\expandafter{\csname fc@digit@\the\fc@digit@counte
          \def\@tempa####1####2{\def\@tempb{\let####1####2}}%
          \expandafter\expandafter\expandafter\@tempa\expandafter\@tempe\@tempd
          \expandafter
        }\@tempb
        \advance\fc@digit@counter by 1 %
     \fi
     \next
  }%
  \let\next\@templ
  \@templ
```

Split `\fc@fractional@part` into a sequence of `\fc@digit@`⟨*n*⟩ with ⟨*n*⟩ ranging from `\fc@unit@weight` − 1 to `\fc@min@weight` by step of −1. This is much more simpler because we get the digits with the final range of index, so no post-processing loop is needed.

```
  \expandafter\fc@digit@counter\fc@unit@weight
  \expandafter\fc@parse@integer@digits\fc@fractional@part\fc@end\fc@nil
  \edef\fc@min@weight{\the\fc@digit@counter}%
}
```

@parse@integer@digMacro `\fc@parse@integer@digits` is used to

```
\ifcsundef{fc@parse@integer@digits}{}{%
  \PackageError{fcnumparser}{Duplicate definition}{Redefinition of
    macro `fc@parse@integer@digits'}}
\def\fc@parse@integer@digits#1#2\fc@nil{%
  \def\@tempa{#1}%
  \ifx\@tempa\fc@end@
     \def\next##1\fc@nil{}%
  \else
  \let\next\fc@parse@integer@digits
  \advance\fc@digit@counter by -1
  \expandafter\def\csname fc@digit@\the\fc@digit@counter\endcsname{#1}%
  \fi
  \next#2\fc@nil
}


\newcommand*{\fc@unit@weight}{0}

```

Now we have macros to read a few digits from the `\fc@digit@`⟨*n*⟩ array and form a corre-

spoding number.

\fc@read@unit `\fc@read@unit` just reads one digit and form an integer in the range [0..9]. First we check that the macro is not yet defined.

```
\ifcsundef{fc@read@unit}{}{%
  \PackageError{fcnumparser}{Duplicate definition}{Redefinition of macro ‘fc@read@unit’}}
```

Arguments as follows:

#1 output counter: into which the read value is placed

#2 input number: unit weight at which reach the value is to be read

#2 does not need to be comprised between `\fc@min@weight` and fc@min@weight, if outside this interval, then a zero is read.

```
\def\fc@read@unit#1#2{%
  \ifnum#2>\fc@max@weight
     #1=0\relax
  \else
     \ifnum#2<\fc@min@weight
        #1=0\relax
     \else
         {%
           \edef\@tempa{\number#2}%
           \count0=\@tempa
           \edef\@tempa{\csname fc@digit@\the\count0\endcsname}%
           \def\@tempb##1{\def\@tempa{#1=##1\relax}}%
           \expandafter\@tempb\expandafter{\@tempa}%
           \expandafter
         }\@tempa
     \fi
  \fi
}
```

fc@read@hundred Macro `\fc@read@hundred` is used to read a pair of digits and form an integer in the range [0..99]. First we check that the macro is not yet defined.

```
\ifcsundef{fc@read@hundred}{}{%
  \PackageError{fcnumparser}{Duplicate definition}{Redefinition of macro ‘fc@read@hundred’}}
```

Arguments as follows — same interface as `\fc@read@unit`:

#1 output counter: into which the read value is placed

#2 input number: unit weight at which reach the value is to be read

```
\def\fc@read@hundred#1#2{%
  {%
    \fc@read@unit{\count0}{#2}%
    \def\@tempa##1{\fc@read@unit{\count1}{##1}}%
    \count2=#2%
    \advance\count2 by 1 %
    \expandafter\@tempa{\the\count2}%
    \multiply\count1 by 10 %
    \advance\count1 by \count0 %
    \def\@tempa##1{\def\@tempb{#1=##1\relax}}
    \expandafter\@tempa\expandafter{\the\count1}%
    \expandafter
```

```
  }\@tempb
}
```

c@read@thousand Macro \fc@read@thousand is used to read a trio of digits and form an integer in the range [0..999]. First we check that the macro is not yet defined.

```
\ifcsundef{fc@read@thousand}{}{%
  \PackageError{fcnumparser}{Duplicate definition}{Redefinition of macro
    'fc@read@thousand'}}
```

Arguments as follows — same interface as \fc@read@unit:

#1 output counter: into which the read value is placed

#2 input number: unit weight at which reach the value is to be read

```
\def\fc@read@thousand#1#2{%
  {%
    \fc@read@unit{\count0}{#2}%
    \def\@tempa##1{\fc@read@hundred{\count1}{##1}}%
    \count2=#2%
    \advance\count2 by 1 %
    \expandafter\@tempa{\the\count2}%
    \multiply\count1 by 10 %
    \advance\count1 by \count0 %
    \def\@tempa##1{\def\@tempb{#1=##1\relax}}
    \expandafter\@tempa\expandafter{\the\count1}%
    \expandafter
  }\@tempb
}
```

c@read@thousand Note: one myriad is ten thousand. Macro \fc@read@myriad is used to read a quatuor of digits and form an integer in the range [0..9999]. First we check that the macro is not yet defined.

```
\ifcsundef{fc@read@myriad}{}{%
  \PackageError{fcnumparser}{Duplicate definition}{Redefinition of macro
    'fc@read@myriad'}}
```

Arguments as follows — same interface as \fc@read@unit:

#1 output counter: into which the read value is placed

#2 input number: unit weight at which reach the value is to be read

```
\def\fc@read@myriad#1#2{%
  {%
    \fc@read@hundred{\count0}{#2}%
    \def\@tempa##1{\fc@read@hundred{\count1}{##1}}%
    \count2=#2
    \advance\count2 by 2
    \expandafter\@tempa{\the\count2}%
    \multiply\count1 by 100 %
    \advance\count1 by \count0 %
    \def\@tempa##1{\def\@tempb{#1=##1\relax}}%
    \expandafter\@tempa\expandafter{\the\count1}%
    \expandafter
  }\@tempb
}
```

@check@nonzeros Macro \fc@check@nonzeros is used to check whether the number represented by digits \fc@digit@⟨*n*⟩, with *n* in some interval, is zero, one, or more than one. First we check that the macro is not yet defined.

```
\ifcsundef{fc@check@nonzeros}{}{%
  \PackageError{fcnumparser}{Duplicate definition}{Redefinition of macro
    `fc@check@nonzeros'}}
```

Arguments as follows:

- #1 input number: minimum unit unit weight at which start to search the non-zeros
- #2 input number: maximum unit weight at which end to seach the non-zeros
- #3 output macro: let *n* be the number represented by digits the weight of which span from #1 to #2, then #3 is set to the number min(n,9).

Actually \fc@check@nonzeros is just a wrapper to collect arguments, and the real job is delegated to \fc@@check@nonzeros@inner which is called inside a group.

```
\def\fc@check@nonzeros#1#2#3{%
  {%
```

So first we save inputs into local macros used by \fc@@check@nonzeros@inner as input arguments

```
    \edef\@@tempa{\number#1}%
    \edef\@tempb{\number#2}%
    \count0=\@@tempa
    \count1=\@tempb\relax
```

Then we do the real job

```
    \fc@@check@nonzeros@inner
```

And finally, we propagate the output after end of group — i.e. closing brace.

```
    \def\@tempd##1{\def\@tempa{\def#3{##1}}}%
    \expandafter\@tempd\expandafter{\@tempc}%
    \expandafter
  }\@tempa
}
```

@@check@nonzeros@inner Macro \fc@@check@nonzeros@inner Check whether some part of the parsed value contains some non-zero digit At the call of this macro we expect that:

- \@tempa input/output macro:
  - *input* minimum unit unit weight at which start to search the non-zeros
  - *output* macro may have been redefined
- \@tempb input/output macro:
  - *input* maximum unit weight at which end to seach the non-zeros
  - *output* macro may have been redefined
- \@tempc ouput macro: 0 if all-zeros, 1 if at least one zero is found
- \count0 output counter: weight + 1 of the first found non zero starting from minimum weight.

```
\def\fc@@check@nonzeros@inner{%
  \ifnum\count0<\fc@min@weight
     \count0=\fc@min@weight\relax
  \fi
  \ifnum\count1>\fc@max@weight\relax
```

```
      \count1=\fc@max@weight
    \fi
    \count2\count0 %
    \advance\count2 by 1 %
    \ifnum\count0>\count1 %
      \PackageError{fcnumparser}{Unexpected arguments}{Number in argument 2 of macro
        `fc@check@nonzeros' must be at least equal to number in argument 1}%
    \else
      \fc@@check@nonzeros@inner@loopbody
      \ifnum\@tempc>0 %
        \ifnum\@tempc<9 %
          \ifnum\count0>\count1 %
          \else
            \let\@tempd\@tempc
            \fc@@check@nonzeros@inner@loopbody
            \ifnum\@tempc=0 %
              \let\@tempc\@tempd
            \else
              \def\@tempc{9}%
            \fi
          \fi
        \fi
      \fi
    \fi
}
\def\fc@@check@nonzeros@inner@loopbody{%
    % \@tempc <-  digit of weight \count0
    \expandafter\let\expandafter\@tempc\csname fc@digit@\the\count0\endcsname
    \advance\count0 by 1 %
    \ifnum\@tempc=0 %
       \ifnum\count0>\count1 %
         \let\next\relax
       \else
         \let\next\fc@@check@nonzeros@inner@loopbody
       \fi
    \else
       \ifnum\count0>\count2 %
         \def\@tempc{9}%
       \fi
       \let\next\relax
    \fi
    \next
}
```

@intpart@find@last Macro `\fc@intpart@find@last` find the rightmost non zero digit in the integer part. First check that the macro is not yet defined.

```
\ifcsundef{fc@intpart@find@last}{}{%
  \PackageError{fcnumparser}{Duplicate definition}{Redefinition of macro
    `fc@intpart@find@last'}}
```

When macro is called, the number of interest is already parsed, that is to say each digit of weight w is stored in macro \fc@digit@⟨w⟩. Macro \fc@intpart@find@last takes one single argument which is a counter to set to the result.

```
\def\fc@intpart@find@last#1{%
  {%
```

Counter \count0 will hold the result. So we will loop on \count0, starting from $\min\{u, w_{\min}\}$, where $u \triangleq$ \fc@unit@weight, and $w_{\min} \triangleq$ \fc@min@weight. So first set \count0 to $\min\{u, w_{\min}\}$:

```
    \count0=\fc@unit@weight\space
    \ifnum\count0<\fc@min@weight\space
      \count0=\fc@min@weight\space
    \fi
```

Now the loop. This is done by defining macro \@templ for final recursion.

```
    \def\@templ{%
      \ifnum\csname fc@digit@\the\count0\endcsname=0 %
        \advance\count0 by 1 %
        \ifnum\count0>\fc@max@weight\space
          \let\next\relax
        \fi
      \else
        \let\next\relax
      \fi
      \next
    }%
    \let\next\@templ
    \@templ
```

Now propagate result after closing bracket into counter #1.

```
     \toks0{#1}%
     \edef\@tempa{\the\toks0=\the\count0}%
     \expandafter
  }\@tempa\space
}
```

c@get@last@word Getting last word. Arguments as follows:

#1 input: full sequence

#2 output macro 1: all sequence without last word

#3 output macro 2: last word

```
\ifcsundef{fc@get@last@word}{}{\PackageError{fcnumparser}{Duplicate definition}{Redefinition
    of macro `fc@get@last@word'}}%
\def\fc@get@last@word#1#2#3{%
  {%
```

First we split #1 into two parts: everything that is upto \fc@wcase exclusive goes to \toks0, and evrything from \fc@wcase exclusive upto the final \@nil exclusive goes to \toks1.

```
    \def\@tempa##1\fc@wcase##2\@nil\fc@end{%
      \toks0{##1}%
```

Actually a dummy \fc@wcase is appended to \toks1, because that makes easier further checking that it does not contains any other \fc@wcase.

```
      \toks1{##2\fc@wcase}%
    }%
    \@tempa#1\fc@end
```

Now leading part upto last word should be in \toks0, and last word should be in \toks1. However we need to check that this is really the last word, i.e. we need to check that there is no \fc@wcase inside \toks1 other than the tailing dummy one. To that purpose we will loop while we find that \toks1 contains some \fc@wcase. First we define \@tempa to split \the\toks1 between parts before and after some potential \fc@wcase.

```
    \def\@tempa##1\fc@wcase##2\fc@end{%
      \toks2{##1}%
      \def\@tempb{##2}%
      \toks3{##2}%
    }%
```

\@tempt is just an aliases of \toks0 to make its handling easier later on.

```
    \toksdef\@tempt0 %
```

Now the loop itself, this is done by terminal recursion with macro \@templ.

```
    \def\@templ{%
      \expandafter\@tempa\the\toks1 \fc@end
      \ifx\@tempb\@empty
```

\@tempb empty means that the only \fc@wcase found in \the\toks1 is the dummy one. So we end the loop here, \toks2 contains the last word.

```
        \let\next\relax
      \else
```

\@tempb is not empty, first we use

```
        \expandafter\expandafter\expandafter\@tempt
        \expandafter\expandafter\expandafter{%
          \expandafter\the\expandafter\@tempt
          \expandafter\fc@wcase\the\toks2}%
        \toks1\toks3 %
      \fi
      \next
    }%
    \let\next\@templ
    \@templ
    \edef\@tempa{\def\noexpand#2{\the\toks0}\def\noexpand#3{\the\toks2}}%
    \expandafter
  }\@tempa
}
```

\fc@get@last@word Getting last letter. Arguments as follows:

#1 input: full word

#2 output macro 1: all word without last letter

#3 output macro 2: last letter

```
\ifcsundef{fc@get@last@letter}{}{\PackageError{fcnumparser}{Duplicate definition}{Redefinition
    of macro `fc@get@last@letter'}}%
\def\fc@get@last@letter#1#2#3{%
  {%
```

First copy input to local \toks1. What we are going to to is to bubble one by one letters from \toks1 which initial contains the whole word, into \toks0. At the end of the macro \toks0 will therefore contain the whole work but the last letter, and the last letter will be in \toks1.

```
    \toks1{#1}%
    \toks0{}%
    \toksdef\@tempt0 %
```

We define \@tempa in order to pop the first letter from the remaining of word.

```
    \def\@tempa##1##2\fc@nil{%
      \toks2{##1}%
      \toks3{##2}%
      \def\@tempb{##2}%
    }%
```

Now we define \@templ to do the loop by terminal recursion.

```
    \def\@templ{%
      \expandafter\@tempa\the\toks1 \fc@nil
      \ifx\@tempb\@empty
```

Stop loop, as \toks1 has been detected to be one single letter.

```
        \let\next\relax
      \else
```

Here we append to \toks0 the content of \toks2, i.e. the next letter.

```
        \expandafter\expandafter\expandafter\@tempt
        \expandafter\expandafter\expandafter{%
          \expandafter\the\expandafter\@tempt
          \the\toks2}%
```

And the remaining letters go to \toks1 for the next iteration.

```
        \toks1\toks3 %
      \fi
      \next
    }%
```

Here run the loop.

```
    \let\next\@templ
    \next
```

Now propagate the results into macros #2 and #3 after closing brace.

```
    \edef\@tempa{\def\noexpand#2{\the\toks0}\def\noexpand#3{\the\toks1}}%
    \expandafter
  }\@tempa
}%
```

10.3 fcprefix.sty

Pseudo-latin prefixes.

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{fcprefix}[2012/09/28]
\RequirePackage{ifthen}
\RequirePackage{keyval}
\RequirePackage{fcnumparser}
```

Option ‘use duode and unde’ is to select whether 18 and suchlikes (⟨*x*⟩8, ⟨*x*⟩9) writes like duodevicies, or like octodecies. For French it should be ‘below 20’. Possible values are ‘below 20’ and ‘never’.

```
\define@key{fcprefix}{use duode and unde}[below20]{%
  \ifthenelse{\equal{#1}{below20}}{%
    \def\fc@duodeandunde{2}%
  }{%
    \ifthenelse{\equal{#1}{never}}{%
      \def\fc@duodeandunde{0}%
    }{%
      \PackageError{fcprefix}{Unexpected option}{%
        Option ‘use duode and unde’ expects ‘below 20’ or ‘never’ }%
    }%
  }%
}
```

Default is ‘below 20’ like in French.

```
\def\fc@duodeandunde{2}
```

Option ‘numeral u in duo’, this can be ‘true’ or ‘false’ and is used to select whether 12 and suchlikes write like dodec⟨*xxx*⟩ or duodec⟨*xxx*⟩ for numerals.

```
\define@key{fcprefix}{numeral u in duo}[false]{%
  \ifthenelse{\equal{#1}{false}}{%
    \let\fc@u@in@duo\@empty
  }{%
    \ifthenelse{\equal{#1}{true}}{%
      \def\fc@u@in@duo{u}%
    }{%
      \PackageError{fcprefix}{Unexpected option}{%
        Option ‘numeral u in duo’ expects ‘true’ or ‘false’ }%
    }%
  }%
}
```

Option ‘e accute’, this can be ‘true’ or ‘false’ and is used to select whether letter ‘e’ has an accute accent when it pronounce [e] in French.

```
\define@key{fcprefix}{e accute}[false]{%
  \ifthenelse{\equal{#1}{false}}{%
    \let\fc@prefix@eaccute\@firstofone
  }{%
    \ifthenelse{\equal{#1}{true}}{%
      \let\fc@prefix@eaccute\’%
    }{%
      \PackageError{fcprefix}{Unexpected option}{%
        Option ‘e accute’ expects ‘true’ or ‘false’ }%
    }%
  }%
}
```

Default is to set accute accent like in French.

```
\let\fc@prefix@eaccute\’%
```

Option ‘power of millia’ tells how millia is raise to power n. It expects value:

recursive for which millia squared is noted as ‘milliamillia’

arabic for which millia squared is noted as ‘millia^2’

prefix for which millia squared is noted as ‘bismillia’

```
\define@key{fcprefix}{power of millia}[prefix]{%
  \ifthenelse{\equal{#1}{prefix}}{%
       \let\fc@power@of@millia@init\@gobbletwo
       \let\fc@power@of@millia\fc@@prefix@millia
  }{%
    \ifthenelse{\equal{#1}{arabic}}{%
       \let\fc@power@of@millia@init\@gobbletwo
       \let\fc@power@of@millia\fc@@arabic@millia
    }{%
      \ifthenelse{\equal{#1}{recursive}}{%
        \let\fc@power@of@millia@init\fc@@recurse@millia@init
        \let\fc@power@of@millia\fc@@recurse@millia
      }{%
        \PackageError{fcprefix}{Unexpected option}{%
          Option ‘power of millia’ expects ‘recursive’, ‘arabic’, or ‘prefix’ }%
      }%
    }%
  }%
}
```

Arguments as follows:

#1 output macro

#2 number with current weight w

```
\def\fc@@recurse@millia#1#2{%
  \let\@tempp#1%
  \edef#1{millia\@tempp}%
}
```

Arguments as follows — same interface as `\fc@@recurse@millia`:

#1 output macro

#2 number with current weight w

```
\def\fc@@recurse@millia@init#1#2{%
  {%
```

Save input argument current weight w into local macro `\@tempb`.

```
    \edef\@tempb{\number#2}%
```

Now main loop from 0 to w. Final value of `\@tempa` will be the result.

```
    \count0=0 %
    \let\@tempa\@empty
    \loop
       \ifnum\count0<\@tempb
         \advance\count0 by 1 %
         \expandafter\def
           \expandafter\@tempa\expandafter{\@tempa millia}%
    \repeat
```

Now propagate the expansion of `\@tempa` into `#1` after closing bace.

```
    \edef\@tempb{\def\noexpand#1{\@tempa}}%
    \expandafter
  }\@tempb
}
```

Arguments as follows — same interface as `\fc@@recurse@millia`:

#1 output macro

#2 number with current weight w

```
\def\fc@@arabic@millia#1#2{%
  \ifnum#2=0 %
    \let#1\@empty
  \else
    \edef#1{millia\^{}\the#2}%
  \fi
}
```

Arguments as follows — same interface as `\fc@@recurse@millia`:

#1 output macro

#2 number with current weight w

```
\def\fc@@prefix@millia#1#2{%
  \fc@@latin@numeral@pefix{#2}{#1}%
}
```

Default value of option ‘`power of millia`’ is ‘`prefix`’:

```
\let\fc@power@of@millia@init\@gobbletwo
\let\fc@power@of@millia\fc@@prefix@millia
```

`@@latin@cardinal@pefix` Compute a cardinal prefix for n-illion, like 1 ⇒ ‘m’, 2 ⇒ ‘bi’, 3 ⇒ ‘tri’. The algorithm to derive this prefix is that of Russ Rowlett I founds its documentation on Alain Lassine’s site: http://www.alain.be/Boece/grands_nombres.html. First check that macro is not yet defined.

```
\ifcsundef{fc@@latin@cardinal@pefix}{}{%
  \PackageError{fmtcount}{Duplicate definition}{Redefinition of macro ‘fc@@latin@cardinal@pefix
```

Arguments as follows:

#1 input number to be formated

#2 outut macro name into which to place the formatted result

```
\def\fc@@latin@cardinal@pefix#1#2{%
  {%
```

First we put input argument into local macro @cs@tempa with full expansion.

```
    \edef\@tempa{\number#1}%
```

Now parse number from expanded input.

```
    \expandafter\fc@number@parser\expandafter{\@tempa}%
    \count2=0 %
```

`\@tempt` will hold the optional final `t`, `\@tempu` is used to initialize `\@tempt` to ‘t’ when the firt non-zero 3digit group is met, which is the job made by `\@tempi`.

```
    \let\@tempt\@empty
    \def\@tempu{t}%
```

\@tempm will hold the millia^$n\div 3$

```
\let\@tempm\@empty
```

Loop by means of terminal recursion of herinafter defined macro \@templ. We loop by group of 3 digits.

```
\def\@templ{%
  \ifnum\count2>\fc@max@weight
    \let\next\relax
  \else
```

Loop body. Here we read a group of 3 consecutive digits $d_2d_1d_0$ and place them respectively into \count3, \count4, and \count5.

```
    \fc@read@unit{\count3}{\count2}%
    \advance\count2 by 1 %
    \fc@read@unit{\count4}{\count2}%
    \advance\count2 by 1 %
    \fc@read@unit{\count5}{\count2}%
    \advance\count2 by 1 %
```

If the 3 considered digits $d_2d_1d_0$ are not all zero, then set \@tempt to 't' for the first time this event is met.

```
    \edef\@tempn{%
      \ifnum\count3=0\else 1\fi
      \ifnum\count4=0\else 1\fi
      \ifnum\count5=0\else 1\fi
    }%
    \ifx\@tempn\@empty\else
      \let\@tempt\@tempu
      \let\@tempu\@empty
    \fi
```

Now process the current group $d_2d_1d_0$ of 3 digits.

```
    \let\@tempp\@tempa
    \edef\@tempa{%
```

Here we process d_2 held by \count5, that is to say hundreds.

```
      \ifcase\count5 %
      \or cen%
      \or ducen%
      \or trecen%
      \or quadringen%
      \or quingen%
      \or sescen%
      \or septigen%
      \or octingen%
      \or nongen%
      \fi
```

Here we process d_1d_0 held by \count4 & \count3, that is to say tens and units.

```
      \ifnum\count4=0 %
        % x0(0..9)
```

```
            \ifnum\count2=3 %
              % Absolute weight zero
              \ifcase\count3 \@tempt
              \or m%
              \or b%
              \or tr%
              \or quadr%
              \or quin\@tempt
              \or sex\@tempt
              \or sep\@tempt
              \or oc\@tempt
              \or non%
              \fi
            \else
```

Here the weight of `\count3` is $3 \times n$, with $n > 0$, i.e. this is followed by a `millia^`n.

```
              \ifcase\count3 %
              \or \ifnum\count2>\fc@max@weight\else un\fi
              \or d\fc@u@in@duo o%
              \or tre%
              \or quattuor%
              \or quin%
              \or sex%
              \or septen%
              \or octo%
              \or novem%
              \fi
            \fi
          \else
             % x(10..99)
             \ifcase\count3 %
             \or un%
             \or d\fc@u@in@duo o%
             \or tre%
             \or quattuor%
             \or quin%
             \or sex%
             \or septen%
             \or octo%
             \or novem%
             \fi
             \ifcase\count4 %
             \or dec%
             \or vigin\@tempt
             \or trigin\@tempt
             \or quadragin\@tempt
             \or quinquagin\@tempt
             \or sexagin\@tempt
             \or septuagin\@tempt
             \or octogin\@tempt
```

```
            \or nonagin\@tempt
            \fi
          \fi
```

Insert the `millia^(n÷3)` only if $d_2 d_1 d_0 \neq 0$, i.e. if one of `\count3` `\count4` or `\count5` is non zero.

```
          \@tempm
```

And append previous version of `\@tempa`.

```
          \@tempp
        }%
```

"Concatenate" `millia` to `\@tempm`, so that `\@tempm` will expand to `millia^(n÷3)+1` at the next iteration. Actually whether this is a concatenation or some `millia` prefixing depends of option '`power of millia`'.

```
        \fc@power@of@millia\@tempm{\count2}%
      \fi
      \next
    }%
    \let\@tempa\@empty
    \let\next\@templ
    \@templ
```

Propagate expansion of `\@tempa` into #2 after closing bracket.

```
    \def\@tempb##1{\def\@tempa{\def#2{##1}}}%
    \expandafter\@tempb\expandafter{\@tempa}%
    \expandafter
  }\@tempa
}
```

`\fc@@latin@numeral@pefix` Compute a numeral prefix like 'sémel', 'bis', 'ter', 'quater', etc... I found the algorithm to derive this prefix on Alain Lassine's site: http://www.alain.be/Boece/nombres_gargantuesques.html. First check that the macro is not yet defined.

```
\ifcsundef{fc@@latin@numeral@pefix}{}{%
  \PackageError{fmtcount}{Duplicate definition}{Redefinition of macro
    'fc@@latin@numeral@pefix'}}
```

Arguments as follows:

#1 input number to be formatted,

#2 outut macro name into which to place the result

```
\def\fc@@latin@numeral@pefix#1#2{%
  {%
    \edef\@tempa{\number#1}%
    \def\fc@unit@weight{0}%
    \expandafter\fc@number@parser\expandafter{\@tempa}%
    \count2=0 %
```

Macro `\@tempm` will hold the `millies^`$n\div 3$.

```
    \let\@tempm\@empty
```

Loop over digits. This is done by defining macro `\@templ` for terminal recursion.

```
    \def\@templ{%
```

```
      \ifnum\count2>\fc@max@weight
        \let\next\relax
      \else
```

Loop body. Three consecutive digits $d_2 d_1 d_0$ are read into counters `\count3`, `\count4`, and `\count5`.

```
        \fc@read@unit{\count3}{\count2}%
        \advance\count2 by 1 %
        \fc@read@unit{\count4}{\count2}%
        \advance\count2 by 1 %
        \fc@read@unit{\count5}{\count2}%
        \advance\count2 by 1 %
```

Check the use of `duodevicies` instead of `octodecies`.

```
        \let\@tempn\@secondoftwo
        \ifnum\count3>7 %
          \ifnum\count4<\fc@duodeandunde
            \ifnum\count4>0 %
               \let\@tempn\@firstoftwo
             \fi
          \fi
        \fi
        \@tempn
        {% use duodevicies for eighteen
          \advance\count4 by 1 %
          \let\@temps\@secondoftwo
        }{%  do not use duodevicies for eighteen
          \let\@temps\@firstoftwo
        }%
        \let\@tempp\@tempa
        \edef\@tempa{%
          % hundreds
          \ifcase\count5 %
          \expandafter\@gobble
          \or c%
          \or duc%
          \or trec%
          \or quadring%
          \or quing%
          \or sesc%
          \or septing%
          \or octing%
          \or nong%
          \fi
          {enties}%
          \ifnum\count4=0 %
```

Here $d_2 d_1 d_0$ is such that $d_1 = 0$.

```
            \ifcase\count3 %
            \or
              \ifnum\count2=3 %
```

```
              s\fc@prefix@eaccute emel%
            \else
              \ifnum\count2>\fc@max@weight\else un\fi
            \fi
          \or bis%
          \or ter%
          \or quater%
          \or quinquies%
          \or sexies%
          \or septies%
          \or octies%
          \or novies%
          \fi
        \else
```

Here $d_2 d_1 d_0$ is such that $d_1 \geq 1$.

```
            \ifcase\count3 %
            \or un%
            \or d\fc@u@in@duo o%
            \or ter%
            \or quater%
            \or quin%
            \or sex%
            \or septen%
            \or \@temps{octo}{duod\fc@prefix@eaccute e}% x8 = two before next (x+1)0
            \or \@temps{novem}{und\fc@prefix@eaccute e}% x9 = one before next (x+1)0
            \fi
            \ifcase\count4 %
            % can't get here
            \or d\fc@prefix@eaccute ec%
            \or vic%
            \or tric%
            \or quadrag%
            \or quinquag%
            \or sexag%
            \or septuag%
            \or octog%
            \or nonag%
            \fi
            ies%
          \fi
          % Insert the millies^(n/3) only if one of \count3 \count4 \count5 is non zero
          \@tempm
          % add up previous version of \@tempa
          \@tempp
        }%
```

Concatenate `millies` to `\@tempm` so that it is equal to `millies`$^{n\div 3}$ at the next iteration. Here we just have plain concatenation, contrary to cardinal for which a prefix can be used instead.

```
        \let\@tempp\@tempp
```

```
        \edef\@tempm{millies\@tempp}%
      \fi
      \next
    }%
    \let\@tempa\@empty
    \let\next\@templ
    \@templ
```

Now propagate expansion of tempa into #2 after closing bracket.

```
    \def\@tempb##1{\def\@tempa{\def#2{##1}}}%
    \expandafter\@tempb\expandafter{\@tempa}%
    \expandafter
  }\@tempa
}
```

Stuff for calling macros. Construct `\fc@call`⟨*some macro*⟩ can be used to pass two arguments to ⟨*some macro*⟩ with a configurable calling convention:

- the calling convention is such that there is one mandatory argument ⟨*marg*⟩ and an optional argument ⟨*oarg*⟩
- either `\fc@call` is `\let` to be equal to `\fc@call@opt@arg@second`, and then calling convention is that the ⟨*marg*⟩ is first and ⟨*oarg*⟩ is second,
- or `\fc@call` is `\let` to be equal to `\fc@call@opt@arg@first`, and then calling convention is that the ⟨*oarg*⟩ is first and ⟨*aarg*⟩ is second,
- if ⟨*oarg*⟩ is absent, then it is by convention set empty,
- ⟨*some macro*⟩ is supposed to have two mandatory arguments of which ⟨*oarg*⟩ is passed to the first, and ⟨*marg*⟩ is passed to the second, and
- ⟨*some macro*⟩ is called within a group.

```
\def\fc@call@opt@arg@second#1#2{%
  \def\@tempb{%
    \ifx[\@tempa
      \def\@tempc[####1]{%
            {#1{####1}{#2}}%
          }%
    \else
      \def\@tempc{{#1{}{#2}}}%
    \fi
    \@tempc
  }%
  \futurelet\@tempa
  \@tempb
}

\def\fc@call@opt@arg@first#1{%
  \def\@tempb{%
```

```
    \ifx[\@tempa
      \def\@tempc[####1]####2{{#1{####1}{####2}}}%
    \else
      \def\@tempc####1{{#1{}{####1}}}%
    \fi
    \@tempc
  }%
  \futurelet\@tempa
  \@tempb
}

\let\fc@call\fc@call@opt@arg@first
```

User API.

atinnumeralstringnumMacro `\@latinnumeralstringnum`. Arguments as follows:

#1 local options

#2 input number

```
\newcommand*{\@latinnumeralstringnum}[2]{%
  \setkeys{fcprefix}{#1}%
  \fc@@latin@numeral@pefix{#2}\@tempa
  \@tempa
}
```

Arguments as follows:

#1 local options

#2 input counter

```
\newcommand*{\@latinnumeralstring}[2]{%
  \setkeys{fcprefix}{#1}%
  \expandafter\let\expandafter
     \@tempa\expandafter\csname c@#2\endcsname
  \expandafter\fc@@latin@numeral@pefix\expandafter{\the\@tempa}\@tempa
  \@tempa
}

\newcommand*{\latinnumeralstring}{%
  \fc@call\@latinnumeralstring
}

\newcommand*{\latinnumeralstringnum}{%
  \fc@call\@latinnumeralstringnum
}
```

10.4 fmtcount.sty

This section deals with the code for `fmtcount.sty`.

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{fmtcount}[2026/11/11 v3.13 Displaying the values of LaTeX counters (NT,VB,NE)]
\RequirePackage{ifthen}

\RequirePackage{xkeyval}
```

```
\RequirePackage{etoolbox}
\RequirePackage{fcprefix}
```

Need to use `\new@ifnextchar` instead of `\@ifnextchar` in commands that have a final optional argument (such as `\gls`) so require amsgen.

```
\RequirePackage{amsgen}
```

These commands need to be defined before the configuration file is loaded.

Define the macro to format the `st`, `nd`, `rd` or `th` of an ordinal.

`\fc@orddef@ult`

```
\providecommand*{\fc@orddef@ult}[1]{\fc@textsuperscript{#1}}
```

`c@ord@multiling`

```
\providecommand*{\fc@ord@multiling}[1]{%
  \ifcsundef{fc@\languagename @alias@of}{%
```

Not a supported language, just use the default setting:

```
  \fc@orddef@ult{#1}}{%
  \expandafter\let\expandafter\@tempa\csname fc@\languagename @alias@of\endcsname
  \ifcsundef{fc@ord@\@tempa}{%
```

Not language specfic setting, just use the default setting:

```
    \fc@orddef@ult{#1}}{%
```

Language with specific setting, use that setting:

```
\csname fc@ord@\@tempa\endcsname{#1}}}}
```

`\padzeroes` `\padzeroes[⟨n⟩]`

Specifies how many digits should be displayed for commands such as `\decimal` and `\binary`.

```
\newcount\c@padzeroesN
\c@padzeroesN=1\relax
\providecommand*{\padzeroes}[1][17]{\c@padzeroesN=#1}
```

`\FCloadlang` `\FCloadlang{⟨language⟩}`

Load fmtcount language file, `fc-`⟨*language*⟩`.def`, unless already loaded. Unfortunately neither babel nor polyglossia keep a list of loaded dialects, so we can't load all the necessary def files in the preamble as we don't know which dialects the user requires. Therefore the dialect definitions get loaded when a command such as `\ordinalnum` is used, if they haven't already been loaded.

```
\newcount\fc@tmpcatcode
\def\fc@languages{}%
\def\fc@mainlang{}%
\newcommand*{\FCloadlang}[1]{%
  \@FC@iflangloaded{#1}{}%
  {%
```

```
    \fc@tmpcatcode=\catcode`\@\relax
    \catcode `\@ 11\relax
    \InputIfFileExists{fc-#1.def}%
    {%
      \ifdefempty{\fc@languages}%
      {%
        \gdef\fc@languages{#1}%
      }%
      {%
         \gappto\fc@languages{,#1}%
      }%
      \gdef\fc@mainlang{#1}%
    }%
    {}%
    \catcode `\@ \fc@tmpcatcode\relax
  }%
}
```

\FCaliaslang

\FCaliaslang{⟨*alias*⟩}{⟨*language*⟩}

Make ⟨*alias*⟩ a synonym of ⟨*language*⟩, that is to say \global\let each of the fifteen \@⟨*command*⟩⟨*gender*⟩⟨*alias*⟩ macros to its ⟨*language*⟩ counterpart. The language definition file of ⟨*language*⟩ must have been loaded beforehand with \FCloadlang. Contrary to spelling out the \lets, this also works when ⟨*alias*⟩ contains characters — such as a hyphen — that cannot be written down literally in a control sequence name, as it builds the names with \csname.

```
\newcommand*{\@FC@aliaslangmacro}[3]{%
  \expandafter\let\expandafter\@FC@tmp@alias\csname @#1#3\endcsname
  \expandafter\global\expandafter\let\csname @#1#2\endcsname\@FC@tmp@alias
}
\newcommand*{\FCaliaslang}[2]{%
  \@FC@aliaslangmacro{ordinalM}{#1}{#2}%
  \@FC@aliaslangmacro{ordinalF}{#1}{#2}%
  \@FC@aliaslangmacro{ordinalN}{#1}{#2}%
  \@FC@aliaslangmacro{numberstringM}{#1}{#2}%
  \@FC@aliaslangmacro{numberstringF}{#1}{#2}%
  \@FC@aliaslangmacro{numberstringN}{#1}{#2}%
  \@FC@aliaslangmacro{NumberstringM}{#1}{#2}%
  \@FC@aliaslangmacro{NumberstringF}{#1}{#2}%
  \@FC@aliaslangmacro{NumberstringN}{#1}{#2}%
  \@FC@aliaslangmacro{ordinalstringM}{#1}{#2}%
  \@FC@aliaslangmacro{ordinalstringF}{#1}{#2}%
  \@FC@aliaslangmacro{ordinalstringN}{#1}{#2}%
  \@FC@aliaslangmacro{OrdinalstringM}{#1}{#2}%
  \@FC@aliaslangmacro{OrdinalstringF}{#1}{#2}%
  \@FC@aliaslangmacro{OrdinalstringN}{#1}{#2}%
}
```

FC@iflangloaded

\@FC@iflangloaded{⟨*language*⟩}{⟨*true*⟩}{⟨*false*⟩}

If fmtcount language definition file `fc-`⟨*language*⟩`.def` has been loaded, do ⟨*true*⟩ otherwise do ⟨*false*⟩

```
\newcommand{\@FC@iflangloaded}[3]{%
  \ifcsundef{ver@fc-#1.def}{#3}{#2}%
}
```

videsFCLanguage

Declare fmtcount language definition file. Adapted from `\ProvidesFile`

```
\newcommand*{\ProvidesFCLanguage}[1]{%
  \ProvidesFile{fc-#1.def}%
}
```

We need that flag to remember that a language has been loaded via package option, so that in the end we can set fmtcount in multiling

```
\newif\iffmtcount@language@option
\fmtcount@language@optionfalse
```

d@language@list

Declare list of supported languages, as a comma separated list. No space, no empty items. Each item is a language for which fmtcount is able to load language specific definitions. `Aliases but be` *`after`* `their meaning, for instance 'american' being an alias of 'USenglish', it has to appear after it in the list`. The raison d'être of this list is to commonalize iteration on languages for the two following purposes:

- loading language definition as a result of the language being used by babel/polyglossia
- loading language definition as a result of package option

These two purposes cannot be handled in the same pass, we need two different passes otherwise there would be some corner cases when a package would be required — as a result of loading language definition for one language — between a `\DeclareOption` and a `\ProcessOption` which is forbidden by LaTeX 2_ε.

```
\newcommand*\fc@supported@language@list{%
english,%
UKenglish,%
brazilian,%
british,%
USenglish,%
american,%
spanish,%
portuges,%
portuguese,%
french,%
frenchb,%
francais,%
german,%
germanb,%
ngerman,%
```

```
ngermanb,%
german-de,%
german-germany,%
german-at,%
german-austria,%
german-de-1901,%
german-germany-1901,%
german-at-1901,%
german-austria-1901,%
german-ch,%
german-switzerland,%
german-ch-1901,%
german-switzerland-1901,%
italian,%
dutch}
```

te@on@languages

`\fc@iterate@on@languages{`⟨*body*⟩`}`

Now make some language iterator, note that for the following to work properly `\fc@supported@language@list` must not be empty. ⟨*body*⟩ is a macro that takes one argument, and `\fc@iterate@on@languages` applies it iteratively :

```
\newcommand*\fc@iterate@on@languages[1]{%
  \ifx\fc@supported@language@list\@empty
```

That case should never happen !

```
    \PackageError{fmtcount}{Macro ‘\protect\@fc@iterate@on@languages’ is empty}{You should neve
      Something is broken within \texttt{fmtcount}, please report the issue on
      \texttt{https://github.com/search?q=fmtcount\&ref=cmdform\&type=Issues}}%
  \else
    \let\fc@iterate@on@languages@body#1
    \expandafter\@fc@iterate@on@languages\fc@supported@language@list,\@nil,%
  \fi
}
\def\@fc@iterate@on@languages#1,{%
    {%
      \def\@tempa{#1}%
      \ifx\@tempa\@nnil
        \let\@tempa\@empty
      \else
        \def\@tempa{%
          \fc@iterate@on@languages@body{#1}%
          \@fc@iterate@on@languages
        }%
      \fi
      \expandafter
    }\@tempa
}%
```

rpolyglossialdf `\@fc@loadifbabelorpolyglossialdf{⟨language⟩}`

Loads fmtcount language file, `fc-`⟨*language*⟩`.def`, if one of the following condition is met:

- babel language definition file ⟨*language*⟩`.ldf` has been loaded — conditionally to compilation with `latex`, not `xelatex`.
- polyglossia language definition file `gloss-`⟨*language*⟩`.ldf` has been loaded — conditionally to compilation with `xelatex`, not `latex`.
- ⟨*language*⟩ option has been passed to package fmtcount.

```
\newcommand*\@fc@loadifbabelldf[1]{\ifcsundef{ver@#1.ldf}{}{\FCloadlang{#1}}}
\newcommand*{\@fc@loadifbabelorpolyglossialdf}[1]{}
\@ifpackageloaded{polyglossia}{%
  \def\@fc@loadifbabelorpolyglossialdf#1{\IfFileExists{gloss-#1.ldf}{\iflanguageloaded{#1}{\FCl
    \@fc@loadifbabelldf{#1}%
  }%
}{\@ifpackageloaded{babel}{%
  \let\@fc@loadifbabelorpolyglossialdf\@fc@loadifbabelldf
}{}}
```

Load appropriate language definition files:

```
\fc@iterate@on@languages\@fc@loadifbabelorpolyglossialdf
```

By default all languages are unique — i.e. aliases not yet defined.

```
\def\fc@iterate@on@languages@body#1{%
  \expandafter\def\csname fc@#1@alias@of\endcsname{#1}}
\expandafter\@fc@iterate@on@languages\fc@supported@language@list,\@nil,%
```

Now define those languages that are aliases of another language. This is done with: `\@tempa {`⟨*alias*⟩`}{`⟨*language*⟩`}`

```
\def\@tempa#1#2{%
  \expandafter\def\csname fc@#1@alias@of\endcsname{#2}%
}%
\@tempa{frenchb}{french}
\@tempa{francais}{french}
\@tempa{germanb}{german}
\@tempa{ngermanb}{german}
\@tempa{ngerman}{german}
\@tempa{german-de}{german}
\@tempa{german-germany}{german}
\@tempa{german-at}{german}
\@tempa{german-austria}{german}
\@tempa{german-de-1901}{german}
\@tempa{german-germany-1901}{german}
\@tempa{german-at-1901}{german}
\@tempa{german-austria-1901}{german}
\@tempa{german-ch}{german}
\@tempa{german-switzerland}{german}
```

```
\@tempa{german-ch-1901}{german}
\@tempa{german-switzerland-1901}{german}
\@tempa{british}{english}
\@tempa{american}{USenglish}
```

Now, thanks to the aliases, we are going to define one option for each language, so that each language can have its own settings.

```
\def\fc@iterate@on@languages@body#1{%
  \define@key{fmtcount}{#1}[]{%
    \@FC@iflangloaded{#1}%
    {%
      \setkeys{fc\csname fc@#1@alias@of\endcsname}{##1}%
    }{%
      \PackageError{fmtcount}%
      {Language `#1' not defined}%
      {You need to load \ifxetex polyglossia\else babel\fi\space before loading fmtcount}%
    }%
  }%
  \ifthenelse{\equal{\csname fc@#1@alias@of\endcsname}{#1}}{%
    \define@key{fc\csname fc@#1@alias@of\endcsname}{fmtord}{%
      \ifthenelse{\equal{##1}{raise}\or\equal{##1}{level}}{%
        \expandafter\let\expandafter\@tempa\csname fc@set@ord@as@##1\endcsname
        \expandafter\@tempa\csname fc@ord@#1\endcsname
      }{%
        \ifthenelse{\equal{##1}{undefine}}{%
          \expandafter\let\csname fc@ord@#1\endcsname\undefined
        }{%
          \PackageError{fmtcount}%
          {Invalid value `##1' to fmtord key}%
          {Option `fmtord' can only take the values `level', `raise'
            or `undefine'}%
        }}
    }%
  }{%
```

When the language #1 is an alias, do the same as the language of which it is an alias:

```
    \expandafter\let\expandafter\@tempa\csname KV@\csname fc@#1@alias@of\endcsname @fmtord\endc
    \expandafter\let\csname KV@#1@fmtord\endcsname\@tempa
  }%
}
\expandafter\@fc@iterate@on@languages\fc@supported@language@list,\@nil,%
```

`fmtord` Key to determine how to display the ordinal

```
\def\fc@set@ord@as@level#1{%
  \def#1##1{##1}%
}
\def\fc@set@ord@as@raise#1{%
  \let#1\fc@textsuperscript
}
\define@key{fmtcount}{fmtord}{%
```

```
  \ifthenelse{\equal{#1}{level}
            \or\equal{#1}{raise}}%
  {%
    \csname fc@set@ord@as@#1\endcsname\fc@orddef@ult
    \def\fmtcount@fmtord{#1}%
  }%
  {%
    \PackageError{fmtcount}%
    {Invalid value `#1' to fmtord key}%
    {Option `fmtord' can only take the values `level' or `raise'}%
  }%
}
```

\iffmtord@abbrv Key to determine whether the ordinal superscript should be abbreviated (language dependent, currently only affects French ordinals, non-abbreviated French ordinals ending — i.e. 'ier' and 'ième' — are considered faulty.)

```
\newif\iffmtord@abbrv

\fmtord@abbrvtrue
\define@key{fmtcount}{abbrv}[true]{%
  \ifthenelse{\equal{#1}{true}\or\equal{#1}{false}}%
  {%
    \csname fmtord@abbrv#1\endcsname
  }%
  {%
    \PackageError{fmtcount}%
    {Invalid value `#1' to fmtord key}%
    {Option `abbrv' can only take the values `true' or
     `false'}%
  }%
}
```

prefix

```
\define@key{fmtcount}{prefix}[scale=long]{%
  \RequirePackage{fmtprefix}%
  \fmtprefixsetoption{#1}%
}
```

countsetoptions Define command to set options.

```
\def\fmtcountsetoptions{%
  \def\fmtcount@fmtord{}%
  \setkeys{fmtcount}}%
```

Load configuration file if it exists. This needs to be done before the package options, to allow the user to override the settings in the configuration file.

```
\InputIfFileExists{fmtcount.cfg}%
{%
  \PackageInfo{fmtcount}{Using configuration file fmtcount.cfg}%
}%
```

```
237 {%
238 }
```

ption@lang@list

```
239 \newcommand*{\fmtcount@loaded@by@option@lang@list}{}
```

\metalanguage Option ⟨*language*⟩ causes language ⟨*language*⟩ to be registered for loading.

```
240 \newcommand*\@fc@declare@language@option[1]{%
241   \DeclareOption{#1}{%
242     \ifx\fmtcount@loaded@by@option@lang@list\@empty
243        \def\fmtcount@loaded@by@option@lang@list{#1}%
244     \else
245        \edef\fmtcount@loaded@by@option@lang@list{\fmtcount@loaded@by@option@lang@list,#1}%
246     \fi
247   }}%
248 \fc@iterate@on@languages\@fc@declare@language@option
```

level

```
249 \DeclareOption{level}{\def\fmtcount@fmtord{level}%
250   \def\fc@orddef@ult#1{#1}}
```

raise

```
251 \DeclareOption{raise}{\def\fmtcount@fmtord{raise}%
252   \def\fc@orddef@ult#1{\fc@textsuperscript{#1}}}
```

Process package options

```
253 \ProcessOptions\relax
```

Now we do the loading of all languages that have been set by option to be loaded.

```
254 \ifx\fmtcount@loaded@by@option@lang@list\@empty\else
255 \def\fc@iterate@on@languages@body#1{%
256     \@FC@iflangloaded{#1}{}{%
257       \fmtcount@language@optiontrue
258       \FCloadlang{#1}%
259      }}
260 \expandafter\@fc@iterate@on@languages\fmtcount@loaded@by@option@lang@list,\@nil,%
261 \fi
```

\@FCmodulo `\@FCmodulo{⟨count reg⟩}{⟨n⟩}`

Sets the count register to be its value modulo ⟨*n*⟩. This is used for the date, time, ordinal and numberstring commands. (The fmtcount package was originally part of the datetime package.)

```
262 \newcount\@DT@modctr
263 \newcommand*{\@FCmodulo}[2]{%
264   \@DT@modctr=#1\relax
265   \divide \@DT@modctr by #2\relax
```

```
  \multiply \@DT@modctr by #2\relax
  \advance #1 by -\@DT@modctr
}
```

The following registers are needed by `\@ordinal` etc

```
\newcount\@ordinalctr
\newcount\@orgargctr
\newcount\@strctr
\newcount\@tmpstrctr
```

Define commands that display numbers in different bases. Define counters and conditionals needed.

```
\newif\if@DT@padzeroes
\newcount\@DT@loopN
\newcount\@DT@X
```

`\binarynum` Converts a decimal number to binary, and display.

```
\newrobustcmd*{\@binary}[1]{%
  \@DT@padzeroestrue
  \@DT@loopN=17\relax
  \@strctr=\@DT@loopN
  \whiledo{\@strctr<\c@padzeroesN}{0\advance\@strctr by \@ne}%
  \@strctr=65536\relax
  \@DT@X=#1\relax
  \loop
    \@DT@modctr=\@DT@X
    \divide\@DT@modctr by \@strctr
    \ifthenelse{\boolean{@DT@padzeroes}
       \and \(\@DT@modctr=0\)
       \and \(\@DT@loopN>\c@padzeroesN\)}%
    {}%
    {\the\@DT@modctr}%
    \ifnum\@DT@modctr=0\else\@DT@padzeroesfalse\fi
    \multiply\@DT@modctr by \@strctr
    \advance\@DT@X by -\@DT@modctr
    \divide\@strctr by \tw@
    \advance\@DT@loopN by \m@ne
  \ifnum\@strctr>\@ne
  \repeat
  \the\@DT@X
}

\let\binarynum=\@binary
```

`\octalnum` Converts a decimal number to octal, and displays.

```
\newrobustcmd*{\@octal}[1]{%
  \@DT@X=#1\relax
  \ifnum\@DT@X>32768
    \PackageError{fmtcount}%
```

```
    {Value of counter too large for \protect\@octal}
    {Maximum value 32768}
  \else
  \@DT@padzeroestrue
  \@DT@loopN=6\relax
  \@strctr=\@DT@loopN
  \whiledo{\@strctr<\c@padzeroesN}{0\advance\@strctr by \@ne}%
  \@strctr=32768\relax
  \loop
    \@DT@modctr=\@DT@X
    \divide\@DT@modctr by \@strctr
    \ifthenelse{\boolean{@DT@padzeroes}
       \and \(\@DT@modctr=0\)
       \and \(\@DT@loopN>\c@padzeroesN\)}%
    {}{\the\@DT@modctr}%
    \ifnum\@DT@modctr=0\else\@DT@padzeroesfalse\fi
    \multiply\@DT@modctr by \@strctr
    \advance\@DT@X by -\@DT@modctr
    \divide\@strctr by \@viiipt
    \advance\@DT@loopN by \m@ne
  \ifnum\@strctr>\@ne
  \repeat
  \the\@DT@X
  \fi
}
\let\octalnum=\@octal
```

`\@@hexadecimal` Converts number from 0 to 15 into lowercase hexadecimal notation.

```
\newcommand*{\@@hexadecimal}[1]{%
  \ifcase#10\or1\or2\or3\or4\or5\or
  6\or7\or8\or9\or a\or b\or c\or d\or e\or f\fi
}
```

`\hexadecimalnum` Converts a decimal number to a lowercase hexadecimal number, and displays it.

```
\newrobustcmd*{\hexadecimalnum}{\@hexadecimalengine\@@hexadecimal}
```

`\@@Hexadecimal` Converts number from 0 to 15 into uppercase hexadecimal notation.

```
\newcommand*{\@@Hexadecimal}[1]{%
  \ifcase#10\or1\or2\or3\or4\or5\or6\or
  7\or8\or9\or A\or B\or C\or D\or E\or F\fi
}
```

`\HEXADecimalnum` Uppercase hexadecimal

```
\newrobustcmd*{\HEXADecimalnum}{\@hexadecimalengine\@@Hexadecimal}
\newcommand*{\@hexadecimalengine}[2]{%
  \@DT@padzeroestrue
  \@DT@loopN=\@vpt
  \@strctr=\@DT@loopN
  \whiledo{\@strctr<\c@padzeroesN}{0\advance\@strctr by \@ne}%
```

```
  \@strctr=65536\relax
  \@DT@X=#2\relax
  \loop
    \@DT@modctr=\@DT@X
    \divide\@DT@modctr by \@strctr
    \ifthenelse{\boolean{@DT@padzeroes}
      \and \(\@DT@modctr=0\)
      \and \(\@DT@loopN>\c@padzeroesN\)}
    {}{#1\@DT@modctr}%
    \ifnum\@DT@modctr=0\else\@DT@padzeroesfalse\fi
    \multiply\@DT@modctr by \@strctr
    \advance\@DT@X by -\@DT@modctr
    \divide\@strctr by 16\relax
    \advance\@DT@loopN by \m@ne
  \ifnum\@strctr>\@ne
  \repeat
  #1\@DT@X
}
\def\Hexadecimalnum{%
  \PackageWarning{fmtcount}{\string\Hexadecimalnum\space is deprecated, use \string\HEXADecimali
    instead. The \string\Hexadecimalnum\space control sequence name is confusing as it can misl
    that only the 1st letter is upper-cased.}%
  \HEXADecimalnum}
```

\aaalphnum Lowercase alphabetical representation (a … z aa … zz)

```
\newrobustcmd*{\@aaalph}{\fc@aaalph\@alph}
\newcommand*\fc@aaalph[2]{%
  \@DT@loopN=#2\relax
  \@DT@X\@DT@loopN
  \advance\@DT@loopN by \m@ne
  \divide\@DT@loopN by 26\relax
  \@DT@modctr=\@DT@loopN
  \multiply\@DT@modctr by 26\relax
  \advance\@DT@X by \m@ne
  \advance\@DT@X by -\@DT@modctr
  \advance\@DT@loopN by \@ne
  \advance\@DT@X by \@ne
  \edef\@tempa{#1\@DT@X}%
  \loop
    \@tempa
    \advance\@DT@loopN by \m@ne
  \ifnum\@DT@loopN>0
  \repeat
}

\let\aaalphnum=\@aaalph
```

\AAAlphnum Uppercase alphabetical representation (a … z aa … zz)

```
\newrobustcmd*{\@AAAlph}{\fc@aaalph\@Alph}%
```

```
\let\AAAlphnum=\@AAAlph
```

\abalphnum Lowercase alphabetical representation

```
\newrobustcmd*{\@abalph}{\fc@abalph\@alph}%
\newcommand*\fc@abalph[2]{%
  \@DT@X=#2\relax
  \ifnum\@DT@X>17576\relax
    \ifx#1\@alph\def\@tempa{\@abalph}%
    \else\def\@tempa{\@ABAlph}\fi
    \PackageError{fmtcount}%
    {Value of counter too large for \expandafter\protect\@tempa}%
    {Maximum value 17576}%
  \else
    \@DT@padzeroestrue
    \@strctr=17576\relax
    \advance\@DT@X by \m@ne
    \loop
      \@DT@modctr=\@DT@X
      \divide\@DT@modctr by \@strctr
      \ifthenelse{\boolean{@DT@padzeroes}
        \and \(\@DT@modctr=1\)}%
      {}{#1\@DT@modctr}%
      \ifnum\@DT@modctr=\@ne\else\@DT@padzeroesfalse\fi
      \multiply\@DT@modctr by \@strctr
      \advance\@DT@X by -\@DT@modctr
      \divide\@strctr by 26\relax
    \ifnum\@strctr>\@ne
    \repeat
    \advance\@DT@X by \@ne
    #1\@DT@X
  \fi
}

\let\abalphnum=\@abalph
```

\ABAlphnum Uppercase alphabetical representation

```
\newrobustcmd*{\@ABAlph}{\fc@abalph\@Alph}%
\let\ABAlphnum=\@ABAlph
```

\@fmtc@count Recursive command to count number of characters in argument. \@strctr should be set to zero before calling it.

```
\def\@fmtc@count#1#2\relax{%
  \if\relax#1%
  \else
    \advance\@strctr by 1\relax
    \@fmtc@count#2\relax
  \fi
}
```

\@decimal Format number as a decimal, possibly padded with zeroes in front.

```
\newrobustcmd*{\@decimal}[1]{%
  \@strctr=0\relax
  \expandafter\@fmtc@count\number#1\relax
  \@DT@loopN=\c@padzeroesN
  \advance\@DT@loopN by -\@strctr
  \ifnum\@DT@loopN>0\relax
    \@strctr=0\relax
    \whiledo{\@strctr < \@DT@loopN}{0\advance\@strctr by 1\relax}%
  \fi
  \number#1\relax
}

\let\decimalnum=\@decimal
```

\FCordinal `\FCordinal{⟨number⟩}`

This is a bit cumbersome. Previously \@ordinal was defined in a similar way to \abalph etc. This ensured that the actual value of the counter was written in the new label stuff in the .aux file. However adding in an optional argument to determine the gender for multilingual compatibility messed things up somewhat. This was the only work around I could get to keep the the cross-referencing stuff working, which is why the optional argument comes *after* the compulsory argument, instead of the usual manner of placing it before. Note however, that putting the optional argument means that any spaces will be ignored after the command if the optional argument is omitted. Version 1.04 changed \ordinal to \FCordinal to prevent it clashing with the memoir class.

```
\newcommand{\FCordinal}[1]{%
  \ordinalnum{%
    \the\value{#1}}%
}
```

\ordinal If \ordinal isn't defined make \ordinal a synonym for \FCordinal to maintain compatibility with previous versions.

```
\ifcsundef{ordinal}
 {\let\ordinal\FCordinal}%
 {%
   \PackageWarning{fmtcount}%
   {\protect\ordinal \space already defined use
    \protect\FCordinal \space instead.}
 }
```

\ordinalnum Display ordinal where value is given as a number or count register instead of a counter:

```
\newrobustcmd*{\ordinalnum}[1]{%
  \new@ifnextchar[%
  {\@ordinalnum{#1}}%
  {\@ordinalnum{#1}[m]}%
}
```

\@ordinalnum Display ordinal according to gender (neuter added in v1.1, \xspace added in v1.2, and removed in v1.3[7]):

```
\def\@ordinalnum#1[#2]{%
  {%
    \ifthenelse{\equal{#2}{f}}%
    {%
      \protect\@ordinalF{#1}{\@fc@ordstr}%
    }%
    {%
      \ifthenelse{\equal{#2}{n}}%
      {%
        \protect\@ordinalN{#1}{\@fc@ordstr}%
      }%
      {%
        \ifthenelse{\equal{#2}{m}}%
        {}%
        {%
          \PackageError{fmtcount}%
           {Invalid gender option `#2'}%
           {Available options are m, f or n}%
        }%
        \protect\@ordinalM{#1}{\@fc@ordstr}%
      }%
    }%
    \@fc@ordstr
  }%
}
```

\storeordinal Store the ordinal (first argument is identifying name, second argument is a counter.)

```
\newcommand*{\storeordinal}[2]{%
  {%
    \toks0{\storeordinalnum{#1}}%
    \expandafter
   }\the\toks0\expandafter{%
    \the\value{#2}}%
}
```

\storeordinalnum Store ordinal (first argument is identifying name, second argument is a number or count register.)

```
\newrobustcmd*{\storeordinalnum}[2]{%
  \@ifnextchar[%
  {\@storeordinalnum{#1}{#2}}%
  {\@storeordinalnum{#1}{#2}[m]}%
}
```

\storeordinalnum Store ordinal according to gender:

```
\def\@storeordinalnum#1#2[#3]{%
```

[7] I couldn't get it to work consistently both with and without the optional argument

```
  \ifthenelse{\equal{#3}{f}}%
  {%
    \protect\@ordinalF{#2}{\@fc@ord}
  }%
  {%
    \ifthenelse{\equal{#3}{n}}%
    {%
      \protect\@ordinalN{#2}{\@fc@ord}%
    }%
    {%
      \ifthenelse{\equal{#3}{m}}%
      {}%
      {%
        \PackageError{fmtcount}%
        {Invalid gender option `#3'}%
        {Available options are m or f}%
      }%
      \protect\@ordinalM{#2}{\@fc@ord}%
    }%
  }%
  \expandafter\let\csname @fcs@#1\endcsname\@fc@ord
}
```

`\FMCuse` Get stored information:

```
\newcommand*{\FMCuse}[1]{\csname @fcs@#1\endcsname}
```

`\ordinalstring` Display ordinal as a string (argument is a counter)

```
\newcommand*{\ordinalstring}[1]{%
  \ordinalstringnum{\expandafter\expandafter\expandafter
    \the\value{#1}}%
}
```

`rdinalstringnum` Display ordinal as a string (argument is a count register or number.)

```
\newrobustcmd*{\ordinalstringnum}[1]{%
  \new@ifnextchar[%
  {\@ordinal@string{#1}}%
  {\@ordinal@string{#1}[m]}%
}
```

`@ordinal@string` Display ordinal as a string according to gender.

```
\def\@ordinal@string#1[#2]{%
  {%
    \ifthenelse{\equal{#2}{f}}%
    {%
      \protect\@ordinalstringF{#1}{\@fc@ordstr}%
    }%
    {%
      \ifthenelse{\equal{#2}{n}}%
      {%
```

```
        \protect\@ordinalstringN{#1}{\@fc@ordstr}%
      }%
      {%
        \ifthenelse{\equal{#2}{m}}%
        {}%
        {%
          \PackageError{fmtcount}%
          {Invalid gender option `#2' to \protect\ordinalstring}%
          {Available options are m, f or n}%
        }%
        \protect\@ordinalstringM{#1}{\@fc@ordstr}%
      }%
    }%
    \@fc@ordstr
  }%
}
```

reordinalstring Store textual representation of number. First argument is identifying name, second argument is the counter set to the required number.

```
\newcommand*{\storeordinalstring}[2]{%
  {%
    \toks0{\storeordinalstringnum{#1}}%
    \expandafter
  }\the\toks0\expandafter{\the\value{#2}}%
}
```

rdinalstringnum Store textual representation of number. First argument is identifying name, second argument is a count register or number.

```
\newrobustcmd*{\storeordinalstringnum}[2]{%
  \@ifnextchar[%
  {\@store@ordinal@string{#1}{#2}}%
  {\@store@ordinal@string{#1}{#2}[m]}%
}
```

@ordinal@string Store textual representation of number according to gender.

```
\def\@store@ordinal@string#1#2[#3]{%
  \ifthenelse{\equal{#3}{f}}%
  {%
    \protect\@ordinalstringF{#2}{\@fc@ordstr}%
  }%
  {%
    \ifthenelse{\equal{#3}{n}}%
    {%
      \protect\@ordinalstringN{#2}{\@fc@ordstr}%
    }%
    {%
      \ifthenelse{\equal{#3}{m}}%
      {}%
      {%
```

```
        \PackageError{fmtcount}%
        {Invalid gender option `#3' to \protect\ordinalstring}%
        {Available options are m, f or n}%
      }%
      \protect\@ordinalstringM{#2}{\@fc@ordstr}%
    }%
  }%
  \expandafter\let\csname @fcs@#1\endcsname\@fc@ordstr
}
```

\Ordinalstring Display ordinal as a string with initial letters in upper case (argument is a counter)

```
\newcommand*{\Ordinalstring}[1]{%
  \Ordinalstringnum{\expandafter\expandafter\expandafter\the\value{#1}}%
}
```

rdinalstringnum Display ordinal as a string with initial letters in upper case (argument is a number or count register)

```
\newrobustcmd*{\Ordinalstringnum}[1]{%
  \new@ifnextchar[%
  {\@Ordinal@string{#1}}%
  {\@Ordinal@string{#1}[m]}%
}
```

@Ordinal@string Display ordinal as a string with initial letters in upper case according to gender

```
\def\@Ordinal@string#1[#2]{%
  {%
    \ifthenelse{\equal{#2}{f}}%
    {%
      \protect\@OrdinalstringF{#1}{\@fc@ordstr}%
    }%
    {%
      \ifthenelse{\equal{#2}{n}}%
      {%
        \protect\@OrdinalstringN{#1}{\@fc@ordstr}%
      }%
      {%
        \ifthenelse{\equal{#2}{m}}%
        {}%
        {%
          \PackageError{fmtcount}%
          {Invalid gender option `#2'}%
          {Available options are m, f or n}%
        }%
        \protect\@OrdinalstringM{#1}{\@fc@ordstr}%
      }%
    }%
    \@fc@ordstr
  }%
}
```

reOrdinalstring Store textual representation of number, with initial letters in upper case. First argument is identifying name, second argument is the counter set to the required number.

```
\newcommand*{\storeOrdinalstring}[2]{%
  {%
    \toks0{\storeOrdinalstringnum{#1}}%
    \expandafter
  }\the\toks0\expandafter{\the\value{#2}}%
}
```

rdinalstringnum Store textual representation of number, with initial letters in upper case. First argument is identifying name, second argument is a count register or number.

```
\newrobustcmd*{\storeOrdinalstringnum}[2]{%
  \@ifnextchar[%
  {\@store@Ordinal@string{#1}{#2}}%
  {\@store@Ordinal@string{#1}{#2}[m]}%
}
```

@Ordinal@string Store textual representation of number according to gender, with initial letters in upper case.

```
\def\@store@Ordinal@string#1#2[#3]{%
  \ifthenelse{\equal{#3}{f}}%
  {%
    \protect\@OrdinalstringF{#2}{\@fc@ordstr}%
  }%
  {%
    \ifthenelse{\equal{#3}{n}}%
    {%
      \protect\@OrdinalstringN{#2}{\@fc@ordstr}%
    }%
    {%
      \ifthenelse{\equal{#3}{m}}%
      {}%
      {%
        \PackageError{fmtcount}%
        {Invalid gender option `#3'}%
        {Available options are m or f}%
      }%
      \protect\@OrdinalstringM{#2}{\@fc@ordstr}%
    }%
  }%
  \expandafter\let\csname @fcs@#1\endcsname\@fc@ordstr
}
```

reORDINALstring Store upper case textual representation of ordinal. The first argument is identifying name, the second argument is a counter.

```
\newcommand*{\storeORDINALstring}[2]{%
  {%
    \toks0{\storeORDINALstringnum{#1}}%
    \expandafter
```

```
  }\the\toks0\expandafter{\the\value{#2}}%
}
```

RDINALstringnum As above, but the second argument is a count register or a number.

```
\newrobustcmd*{\storeORDINALstringnum}[2]{%
  \@ifnextchar[%
  {\@store@ORDINAL@string{#1}{#2}}%
  {\@store@ORDINAL@string{#1}{#2}[m]}%
}
```

@ORDINAL@string Gender is specified as an optional argument at the end.

```
\def\@store@ORDINAL@string#1#2[#3]{%
  \ifthenelse{\equal{#3}{f}}%
  {%
    \protect\@ordinalstringF{#2}{\@fc@ordstr}%
  }%
  {%
    \ifthenelse{\equal{#3}{n}}%
    {%
      \protect\@ordinalstringN{#2}{\@fc@ordstr}%
    }%
    {%
      \ifthenelse{\equal{#3}{m}}%
      {}%
      {%
        \PackageError{fmtcount}%
        {Invalid gender option `#3'}%
        {Available options are m or f}%
      }%
      \protect\@ordinalstringM{#2}{\@fc@ordstr}%
    }%
  }%

  \expandafter\protected@edef\csname @fcs@#1\endcsname{%
    \noexpand\MakeUppercase{\@fc@ordstr}%
  }%
}
```

\ORDINALstring Display upper case textual representation of an ordinal. The argument must be a counter.

```
\newcommand*{\ORDINALstring}[1]{%
  \ORDINALstringnum{\expandafter\expandafter\expandafter
    \the\value{#1}%
  }%
}
```

RDINALstringnum As above, but the argument is a count register or a number.

```
\newrobustcmd*{\ORDINALstringnum}[1]{%
  \new@ifnextchar[%
  {\@ORDINAL@string{#1}}%
```

```
  {\@ORDINAL@string{#1}[m]}%
}
```

`@ORDINAL@string` Gender is specified as an optional argument at the end.

```
\def\@ORDINAL@string#1[#2]{%
  {%
    \ifthenelse{\equal{#2}{f}}%
    {%
      \protect\@ordinalstringF{#1}{\@fc@ordstr}%
    }%
    {%
      \ifthenelse{\equal{#2}{n}}%
      {%
        \protect\@ordinalstringN{#1}{\@fc@ordstr}%
      }%
      {%
        \ifthenelse{\equal{#2}{m}}%
        {}%
        {%
          \PackageError{fmtcount}%
          {Invalid gender option `#2'}%
          {Available options are m, f or n}%
        }%
        \protect\@ordinalstringM{#1}{\@fc@ordstr}%
      }%
    }%
    \MakeUppercase{\@fc@ordstr}%
  }%
}
```

`orenumberstring` Convert number to textual respresentation, and store. First argument is the identifying name, second argument is a counter containing the number.

```
\newcommand*{\storenumberstring}[2]{%
  \expandafter\protect\expandafter\storenumberstringnum{#1}{%
    \expandafter\the\value{#2}}%
}
```

`numberstringnum` As above, but second argument is a number or count register.

```
\newcommand{\storenumberstringnum}[2]{%
  \@ifnextchar[%
  {\@store@number@string{#1}{#2}}%
  {\@store@number@string{#1}{#2}[m]}%
}
```

`e@number@string` Gender is given as optional argument, *at the end*.

```
\def\@store@number@string#1#2[#3]{%
  \ifthenelse{\equal{#3}{f}}%
  {%
    \protect\@numberstringF{#2}{\@fc@numstr}%
```

```
  }%
  {%
    \ifthenelse{\equal{#3}{n}}%
    {%
      \protect\@numberstringN{#2}{\@fc@numstr}%
    }%
    {%
      \ifthenelse{\equal{#3}{m}}%
      {}%
      {%
        \PackageError{fmtcount}
        {Invalid gender option `#3'}%
        {Available options are m, f or n}%
      }%
      \protect\@numberstringM{#2}{\@fc@numstr}%
    }%
  }%
  \expandafter\let\csname @fcs@#1\endcsname\@fc@numstr
}
```

`\numberstring` Display textual representation of a number. The argument must be a counter.

```
\newcommand*{\numberstring}[1]{%
  \numberstringnum{\expandafter\expandafter\expandafter
    \the\value{#1}}%
}
```

`numberstringnum` As above, but the argument is a count register or a number.

```
\newrobustcmd*{\numberstringnum}[1]{%
  \new@ifnextchar[%
  {\@number@string{#1}}%
  {\@number@string{#1}[m]}%
}
```

`\@number@string` Gender is specified as an optional argument *at the end*.

```
\def\@number@string#1[#2]{%
  {%
    \ifthenelse{\equal{#2}{f}}%
    {%
      \protect\@numberstringF{#1}{\@fc@numstr}%
    }%
    {%
      \ifthenelse{\equal{#2}{n}}%
      {%
          \protect\@numberstringN{#1}{\@fc@numstr}%
      }%
      {%
        \ifthenelse{\equal{#2}{m}}%
        {}%
        {%
```

```
          \PackageError{fmtcount}%
          {Invalid gender option `#2'}%
          {Available options are m, f or n}%
        }%
        \protect\@numberstringM{#1}{\@fc@numstr}%
      }%
    }%
    \@fc@numstr
  }%
}
```

oreNumberstring Store textual representation of number. First argument is identifying name, second argument is a counter.

```
\newcommand*{\storeNumberstring}[2]{%
  {%
    \toks0{\storeNumberstringnum{#1}}%
    \expandafter
  }\the\toks0\expandafter{\the\value{#2}}%
}
```

Numberstringnum As above, but second argument is a count register or number.

```
\newcommand{\storeNumberstringnum}[2]{%
  \@ifnextchar[%
  {\@store@Number@string{#1}{#2}}%
  {\@store@Number@string{#1}{#2}[m]}%
}
```

e@Number@string Gender is specified as an optional argument *at the end*:

```
\def\@store@Number@string#1#2[#3]{%
  \ifthenelse{\equal{#3}{f}}%
  {%
    \protect\@NumberstringF{#2}{\@fc@numstr}%
  }%
  {%
    \ifthenelse{\equal{#3}{n}}%
    {%
      \protect\@NumberstringN{#2}{\@fc@numstr}%
    }%
    {%
      \ifthenelse{\equal{#3}{m}}%
      {}%
      {%
        \PackageError{fmtcount}%
        {Invalid gender option `#3'}%
        {Available options are m, f or n}%
      }%
      \protect\@NumberstringM{#2}{\@fc@numstr}%
    }%
  }%
```

```
  \expandafter\let\csname @fcs@#1\endcsname\@fc@numstr
}
```

\Numberstring Display textual representation of number. The argument must be a counter.

```
\newcommand*{\Numberstring}[1]{%
  \Numberstringnum{\expandafter\expandafter\expandafter
    \the\value{#1}}%
}
```

\Numberstringnum As above, but the argument is a count register or number.

```
\newrobustcmd*{\Numberstringnum}[1]{%
  \new@ifnextchar[%
  {\@Number@string{#1}}%
  {\@Number@string{#1}[m]}%
}
```

\@Number@string Gender is specified as an optional argument at the end.

```
\def\@Number@string#1[#2]{%
  {%
    \ifthenelse{\equal{#2}{f}}%
    {%
      \protect\@NumberstringF{#1}{\@fc@numstr}%
    }%
    {%
      \ifthenelse{\equal{#2}{n}}%
      {%
        \protect\@NumberstringN{#1}{\@fc@numstr}%
      }%
      {%
        \ifthenelse{\equal{#2}{m}}%
        {}%
        {%
          \PackageError{fmtcount}%
          {Invalid gender option `#2'}%
          {Available options are m, f or n}%
        }%
        \protect\@NumberstringM{#1}{\@fc@numstr}%
      }%
    }%
    \@fc@numstr
  }%
}
```

oreNUMBERstring Store upper case textual representation of number. The first argument is identifying name, the second argument is a counter.

```
\newcommand{\storeNUMBERstring}[2]{%
  {%
    \toks0{\storeNUMBERstringnum{#1}}%
    \expandafter
```

```
    }\the\toks0\expandafter{\the\value{#2}}%
}
```

NUMBERstringnum As above, but the second argument is a count register or a number.

```
\newcommand{\storeNUMBERstringnum}[2]{%
  \@ifnextchar[%
  {\@store@NUMBER@string{#1}{#2}}%
  {\@store@NUMBER@string{#1}{#2}[m]}%
}
```

e@NUMBER@string Gender is specified as an optional argument at the end.

```
\def\@store@NUMBER@string#1#2[#3]{%
  \ifthenelse{\equal{#3}{f}}%
  {%
    \protect\@numberstringF{#2}{\@fc@numstr}%
  }%
  {%
    \ifthenelse{\equal{#3}{n}}%
    {%
      \protect\@numberstringN{#2}{\@fc@numstr}%
    }%
    {%
      \ifthenelse{\equal{#3}{m}}%
      {}%
      {%
        \PackageError{fmtcount}%
        {Invalid gender option `#3'}%
        {Available options are m or f}%
      }%
      \protect\@numberstringM{#2}{\@fc@numstr}%
    }%
  }%
  \expandafter\edef\csname @fcs@#1\endcsname{%
    \noexpand\MakeUppercase{\@fc@numstr}%
  }%
}
```

\NUMBERstring Display upper case textual representation of a number. The argument must be a counter.

```
\newcommand*{\NUMBERstring}[1]{%
  \NUMBERstringnum{\expandafter\expandafter\expandafter
    \the\value{#1}}%
}
```

NUMBERstringnum As above, but the argument is a count register or a number.

```
\newrobustcmd*{\NUMBERstringnum}[1]{%
  \new@ifnextchar[%
  {\@NUMBER@string{#1}}%
  {\@NUMBER@string{#1}[m]}%
}
```

\@NUMBER@string Gender is specified as an optional argument at the end.

```
\def\@NUMBER@string#1[#2]{%
  {%
    \ifthenelse{\equal{#2}{f}}%
    {%
      \protect\@numberstringF{#1}{\@fc@numstr}%
    }%
    {%
      \ifthenelse{\equal{#2}{n}}%
      {%
          \protect\@numberstringN{#1}{\@fc@numstr}%
      }%
      {%
        \ifthenelse{\equal{#2}{m}}%
        {}%
        {%
          \PackageError{fmtcount}%
          {Invalid gender option `#2'}%
          {Available options are m, f or n}%
        }%
        \protect\@numberstringM{#1}{\@fc@numstr}%
      }%
    }%
    \protect\MakeUppercase{\@fc@numstr}%
  }%
}
```

\binary Number representations in other bases. Binary:

```
\providecommand*{\binary}[1]{%
  \@binary{\expandafter\expandafter\expandafter
    \the\value{#1}}%
}
```

\aaalph Like \alph but goes beyond 26. (a ... z aa ... zz ...)

```
\providecommand*{\aaalph}[1]{%
  \@aaalph{\expandafter\expandafter\expandafter
    \the\value{#1}}%
}
```

\AAAlph As before, but upper case.

```
\providecommand*{\AAAlph}[1]{%
  \@AAAlph{\expandafter\expandafter\expandafter
    \the\value{#1}}%
}
```

\abalph Like \alph but goes beyond 26. (a ... z ab ... az ...)

```
\providecommand*{\abalph}[1]{%
  \@abalph{\expandafter\expandafter\expandafter
    \the\value{#1}}%
```

```
}
```

\ABAlph As above, but upper case.

```
\providecommand*{\ABAlph}[1]{%
  \@ABAlph{\expandafter\expandafter\expandafter
    \the\value{#1}}%
}
```

\hexadecimal Hexadecimal:

```
\providecommand*{\hexadecimal}[1]{%
  \hexadecimalnum{\expandafter\expandafter\expandafter
    \the\value{#1}}%
}
```

\HEXADecimal As above, but in upper case.

```
\providecommand*{\HEXADecimal}[1]{%
  \HEXADecimalnum{\expandafter\expandafter\expandafter
    \the\value{#1}}%
}
\newrobustcmd*\FC@Hexadecimal@warning{%
  \PackageWarning{fmtcount}{\string\Hexadecimal\space is deprecated, use \string\HEXADecimal\sp
    instead. The \string\Hexadecimal\space control sequence name is confusing as it can mislead
    that only the 1st letter is upper-cased.}%
}
\def\Hexadecimal{%
  \FC@Hexadecimal@warning
  \HEXADecimal}
```

\octal Octal:

```
\providecommand*{\octal}[1]{%
  \@octal{\expandafter\expandafter\expandafter
    \the\value{#1}}%
}
```

\decimal Decimal:

```
\providecommand*{\decimal}[1]{%
  \@decimal{\expandafter\expandafter\expandafter
    \the\value{#1}}%
}
```

10.4.1 Multilinguage Definitions

Flag \fc@languagemode@detected allows to stop scanning for multilingual mode trigger conditions. It is initialized to false as no such scanning as taken place yet.

```
\newif\iffc@languagemode@detected
\fc@languagemode@detectedfalse
```

def@ultfmtcount If multilingual support is provided, make \@numberstring etc use the correct language (if defined). Otherwise use English definitions. \@setdef@ultfmtcount sets the macros to use English.

```
\def\@setdef@ultfmtcount{%
  \fc@languagemode@detectedtrue
  \ifcsundef{@ordinalMenglish}{\FCloadlang{english}}{}%
  \def\@ordinalstringM{\@ordinalstringMenglish}%
  \let\@ordinalstringF=\@ordinalstringMenglish
  \let\@ordinalstringN=\@ordinalstringMenglish
  \def\@OrdinalstringM{\@OrdinalstringMenglish}%
  \let\@OrdinalstringF=\@OrdinalstringMenglish
  \let\@OrdinalstringN=\@OrdinalstringMenglish
  \def\@numberstringM{\@numberstringMenglish}%
  \let\@numberstringF=\@numberstringMenglish
  \let\@numberstringN=\@numberstringMenglish
  \def\@NumberstringM{\@NumberstringMenglish}%
  \let\@NumberstringF=\@NumberstringMenglish
  \let\@NumberstringN=\@NumberstringMenglish
  \def\@ordinalM{\@ordinalMenglish}%
  \let\@ordinalF=\@ordinalM
  \let\@ordinalN=\@ordinalM
  \let\fmtord\fc@orddef@ult
}
```

\fc@multiling \fc@multiling{⟨*name*⟩}{⟨*gender*⟩}

```
\newcommand*{\fc@multiling}[2]{%
  \ifcsundef{@#1#2\languagename}%
  {% try loading it
     \FCloadlang{\languagename}%
  }%
  {%
  }%
  \ifcsundef{@#1#2\languagename}%
  {%
    \PackageWarning{fmtcount}%
    {No support for \expandafter\protect\csname #1\endcsname\space for
     language '\languagename'}%
    \ifthenelse{\equal{\languagename}{\fc@mainlang}}%
    {%
       \FCloadlang{english}%
    }%
    {%
    }%
```

Beware that \fc@mainlang may be empty — this happens when babel or polyglossia selects a language for which fmtcount has no definition file and no other language was ever loaded. The fallback would then be \@⟨*name*⟩⟨*gender*⟩ with an empty language appended, which is the very macro that called us, so using it as a fallback would loop for ever.

```
    \ifboolexpr{ test {\ifdefempty{\fc@mainlang}}
```

```
                or not test {\ifcsdef{@#1#2\fc@mainlang}} }%
   {%
      \PackageWarningNoLine{fmtcount}%
      {No languages loaded at all! Loading english definitions}%
      \FCloadlang{english}%
      \gdef\fc@mainlang{english}%
      \csuse{@#1#2english}%
   }%
   {%
      \csuse{@#1#2\fc@mainlang}%
   }%
 }%
 {%
   \csuse{@#1#2\languagename}%
 }%
}
```

itling@fmtcount This defines the number and ordinal string macros to use \languagename:

```
\def\@set@mulitling@fmtcount{%
  \fc@languagemode@detectedtrue
```

The masculine version of \numberstring:

```
  \def\@numberstringM{%
    \fc@multiling{numberstring}{M}%
  }%
```

The feminine version of \numberstring:

```
  \def\@numberstringF{%
    \fc@multiling{numberstring}{F}%
  }%
```

The neuter version of \numberstring:

```
  \def\@numberstringN{%
    \fc@multiling{numberstring}{N}%
  }%
```

The masculine version of \Numberstring:

```
  \def\@NumberstringM{%
    \fc@multiling{Numberstring}{M}%
  }%
```

The feminine version of \Numberstring:

```
  \def\@NumberstringF{%
    \fc@multiling{Numberstring}{F}%
  }%
```

The neuter version of \Numberstring:

```
  \def\@NumberstringN{%
    \fc@multiling{Numberstring}{N}%
  }%
```

The masculine version of \ordinal:

```
\def\@ordinalM{%
  \fc@multiling{ordinal}{M}%
}%
```

The feminine version of \ordinal:

```
\def\@ordinalF{%
  \fc@multiling{ordinal}{F}%
}%
```

The neuter version of \ordinal:

```
\def\@ordinalN{%
  \fc@multiling{ordinal}{N}%
}%
```

The masculine version of \ordinalstring:

```
\def\@ordinalstringM{%
  \fc@multiling{ordinalstring}{M}%
}%
```

The feminine version of \ordinalstring:

```
\def\@ordinalstringF{%
  \fc@multiling{ordinalstring}{F}%
}%
```

The neuter version of \ordinalstring:

```
\def\@ordinalstringN{%
  \fc@multiling{ordinalstring}{N}%
}%
```

The masculine version of \Ordinalstring:

```
\def\@OrdinalstringM{%
  \fc@multiling{Ordinalstring}{M}%
}%
```

The feminine version of \Ordinalstring:

```
\def\@OrdinalstringF{%
  \fc@multiling{Ordinalstring}{F}%
}%
```

The neuter version of \Ordinalstring:

```
\def\@OrdinalstringN{%
  \fc@multiling{Ordinalstring}{N}%
}%
```

Make \fmtord language dependent:

```
\let\fmtord\fc@ord@multiling
}
```

Check to see if babel, polyglossia, mlp, or ngerman packages have been loaded, and if yes set fmtcount in multiling. First we define some \fc@check@for@multiling macro to do such action where #1 is the package name, and #2 is a callback.

```
\def\fc@check@for@multiling#1:#2\@nil{%
  \@ifpackageloaded{#1}{%
    #2\@set@mulitling@fmtcount
  }{}%
}
```

Now we define `\fc@loop@on@multiling@pkg` as an iterator to scan whether any of babel, polyglossia, mlp, or ngerman packages has been loaded, and if so set multilingual mode.

```
\def\fc@loop@on@multiling@pkg#1,{%
  \def\@tempb{#1}%
  \ifx\@tempb\@nnil
```

We have reached the end of the loop, so stop here.

```
    \let\fc@loop@on@multiling@pkg\@empty
  \else
```

Make the `\@ifpackageloaded` test and break the loop if it was positive.

```
    \fc@check@for@multiling#1\@nil
    \iffc@languagemode@detected
      \def\fc@loop@on@multiling@pkg##1\@nil,{}%
    \fi
  \fi
  \fc@loop@on@multiling@pkg
}
```

Now, do the loop itself, we do this at beginning of document not to constrain the order of loading fmtcount and the multilingual package babel, polyglossia, etc.:

```
\AtBeginDocument{%
  \fc@loop@on@multiling@pkg babel:,polyglossia:,ngerman:\FCloadlang{ngerman},\@nil,
```

In the case that no multilingual package (such as babel/polyglossia/ngerman) has been loaded, then we go to multiling if a language has been loaded by package option.

```
   \unless\iffc@languagemode@detected\iffmtcount@language@option
```

If the multilingual mode has not been yet activated, but a language option has been passed to fmtcount, we should go to multilingual mode. However, first of, we do some sanity check, as this may help the end user understand what is wrong: we check that macro `\languagename` is defined, and activate the multilingual mode only then, and otherwise fall back to default legacy mode.

```
      \ifcsundef{languagename}%
      {%
         \PackageWarning{fmtcount}{%
            `\protect\languagename' is undefined, you should use a language package such as bab
             when loading a language via package option. Reverting to default language.
         }%
         \@setdef@ultfmtcount
      }{%
        \@set@mulitling@fmtcount

```

Now, some more checking, having activated multilingual mode after a language option has been passed to fmtcount, we check that the fmtcount language definitions corresponding

to \languagename have been loaded, and otherwise fall \languagename back to the latest fmtcount language definition loaded.

```
        \@FC@iflangloaded{\languagename}{}{%
```

The current \languagename is not a fmtcount language that has been previously loaded. The correction is to have \languagename let to \fc@mainlang. Please note that, as \iffmtcount@language@option is true, we know that fmtcount has loaded some language.

```
            \PackageWarning{fmtcount}{%
               Setting `\protect\languagename' to `\fc@mainlang'.\MessageBreak
               Reason is that `\protect\languagename' was `\languagename',\MessageBreak
               but `\languagename' was not loaded by fmtcount,\MessageBreak
               whereas `\fc@mainlang' was the last language loaded by fmtcount ;
            }%
            \let\languagename\fc@mainlang
         }%
      }%
   \else
       \@setdef@ultfmtcount
   \fi\fi

   \ifcsundef{FBsupR}{\let\fc@textsuperscript\textsuperscript}{\let\fc@textsuperscript\fup}%
}
```

Backwards compatibility:

```
\let\@ordinal=\@ordinalM
\let\@ordinalstring=\@ordinalstringM
\let\@Ordinalstring=\@OrdinalstringM
\let\@numberstring=\@numberstringM
\let\@Numberstring=\@NumberstringM
```